



# COVAL

vacuum managers

## GLOBAL CATALOG

vacuum  
**components**




## ADVANCED VACUUM SOLUTIONS

[www.coval.com](http://www.coval.com)

US4





**COVAL**  
vacuum managers

## VACUUM MANAGERS

### Welcome to the new COVAL catalog!

At COVAL, we set out to provide our clients and users with **vacuum handling** solutions that meet their goals in terms of profitability, productivity, quality, safety, and environmental conservation.

To achieve this, COVAL is rallying its efforts to predict, plan, innovate, and manufacture with one aim in mind: offering the right products and services at the right time. In practical terms, this is what it takes:

- Impeccable knowledge of various industrial sectors.
- Being attentive and available to our clients' teams and users.
- The ability to adapt quickly to evolving needs.
- A rigorous approach to all of COVAL's efforts and endeavors.

To meet our commitments every day, at COVAL we have been developing an organization and a culture geared towards constant innovation, quality, and service for more than 30 years:

- Teams specialized by industry: food processing, aeronautics, robotics, plastic processing, packaging, and more.
- Strong in-house capacity for research and innovation complemented with external resources through public and private partnerships.
- Strong presence thanks to our sales team, foreign subsidiaries, and authorized dealers.

### COVAL is the Vacuum Manager for each and every one of its clients.

We bring together all the skills and know-how to manage the vacuum handling of their parts, products, or packaging.

This catalog presents our products and services. It serves as an introduction to the interactions with our technical and sales teams around your projects.

Michel Cecchin,  
Chairman of COVAL S.A.S.


**COVAL**  
vacuum managers

[www.coval.com](http://www.coval.com)

More  
information







# COVAL

vacuum managers

## COVAL SERVICES

COVAL combines its products with efficient services to assist in defining your needs, selecting your solution, integrating your products, and optimizing your equipment.


### ► ALL COVAL PRODUCTS ONLINE

Just click to access our entire product range, which is regularly updated, and download any of our catalogs.

[www.coval.com](http://www.coval.com)

### ► 3D ONLINE LIBRARY

You have free access to 3D files of all our products in formats compatible with leading CAD software from our website at [www.coval.com](http://www.coval.com)




**3D  
COVAL Data**

You can use this fast, new, reliable service to make it easier to integrate our components directly into your designs.

### ► MOBILE APPLICATION

The **COVAL e-catalogue** application gives you access to all our products from anywhere, allowing you to perform the following actions for each product:



- Download 3D models.
- View the latest up-to-date technical data.
- Download and share technical data sheets.

### ► TECHNICAL PHONE SUPPORT

COVAL provides you technical support to answer all your questions regarding its products, solutions, and services: find a product or spare part, get advice on recommended use, request technical documentation, ask for technical information (how to avoid pressure losses, reduce noise level, save energy, etc.).

### ► COVAL SOLUTIONS SERVICES

To adapt our products to your specific applications, both the COVAL engineering and design department and its development team are dedicated to providing solutions that meet your specifications.

vacuum  
**management**





## QUALITY AND INNOVATION

COVAL applies an ambitious quality and innovation policy to all its product ranges. Our quality relies on a comprehensive approach, which brings together client focus, staff training, and teamwork. All these elements foster a favorable environment and culture for each collaborator to contribute to innovation. This commitment has led to several awards and certifications that reward both the products and their industrial applications.

### ► BROAD INNOVATION NETWORK

At COVAL, we believe that openness to public research centers, universities, and technology clusters is the primary qualification for being able to offer our clients products that make them more competitive. These collaborations complement and strengthen the internal resources of our Research and Innovation Center.

To drive this strategic intent, the Innovation Manager's focus is to develop COVAL interactions with its environment in order to innovate in technical, human, and organizational fields.

### ► ISO 9001 CERTIFICATION: V2015

With this standard, COVAL seeks to achieve the following:

- Satisfy its clients' quality requirements.
- Meet applicable regulatory conditions.
- Improve client satisfaction.
- Constantly optimize performance to achieve these goals.

To do this, COVAL teams focus on clients and rally behind a process of ongoing improvement. Our primary goal is to build a lasting relationship with our clients.



### ► AN EXAMPLE OF INNOVATION: TWIN TECH™, VACUUM INTELLIGENCE AT ITS CORE

At COVAL, innovation focuses on the user. It is our constant dialog with our clients that feeds our technological developments.

The TWIN TECH™ technology, which appeared as early as 2008, is a perfect example of how COVAL views innovation: favoring energy savings, ease-of-use, and compactness.



This technology is available in our main lines of vacuum pumps and allows for the integration of all necessary features in a single, compact and light unit that also improves man-machine communication.

COVAL thus perfectly meets the new expectations of robot manufacturers, system integrators, and users.





## ENERGY SAVINGS

COVAL is committed to making your vacuum handling system energy-efficient. Our goal is to optimize the overall performance of your equipment by operating on the following three principles:

- Analyzing the system to identify the potential for savings.
- Selecting the most appropriate solution.
- Including COVAL energy-saving technologies, such as ASR and ASC, in our products.

### **AIR Saving Regulator** : AIR SAVING REGULATOR

→ **40%** energy savings on average

The AIR SAVING REGULATOR (ASR) regulates the compressed air pressure to 3.5 bar in all circumstances to obtain a perfect mix of efficiency and consumption.

- No more unnecessary consumption of compressed air.
- No external regulator required, thus eliminating the risk of improper adjustment.

The following products feature this technology:

- LEM
- LEMP
- LEMAX
- LEM+
- LEMAX+
- LEMCOM...

### **AIR Saving Control** : AIR SAVING CONTROL

→ **90%** energy savings on average

AIR SAVING CONTROL (ASC) is an intelligent system that stops the consumption of compressed air as soon as the required level of vacuum is reached, thus avoiding any unnecessary consumption and contributing to savings on the equipment's operating costs.

The following products feature this technology:

- LEMAX
- LEMAX+
- LEMCOM...

## ENERGY SAVING APP

Measure the savings online that you can make with a COVAL vacuum handling solution.

The **ENERGY SAVING APP** allows you to measure the savings you can generate with LEMAX, LEMAX+, or LEMCOM vacuum pumps featuring the ASC technology compared with conventional vacuum pumps.


This unique app in the world of vacuum technology is very intuitive to use. Once you've entered the equipment's main characteristics (gripping cycle time, number of cycles, run time, volume to be evacuated), the savings are displayed automatically in euros, air volume, and savings percentage. In most cases, it is quite significant since it peaks at 97% of energy saved, for example with the LEMAX.

It is, therefore, easy to realize that investing in a COVAL pump featuring ASC pays for itself, on average, after less than a year of use.

This COVAL exclusive strengthens our calling as your company's Vacuum Manager and our desire to contribute to improving the energy and production performance of your equipment.

You can access this software from the COVAL website:  
<http://www.coval-international.com/company/our-technologies/>

**Products concerned:** ■ LEMAX ■ LEMAX+ ■ LEMCOM...







## MADE IN EXCELLENCE

For more than 30 years, COVAL has been working every day on offering its clients outstanding products and services. This is not merely a goal, it's a daily commitment that drives each of our teams: sales, engineering and design, production, logistics, innovation, and management.

To foster this spirit of excellence, COVAL constantly invests in the following areas:

- ▶ **MODERNIZING ITS INDUSTRIAL EQUIPMENT** to improve quality and productivity.
- ▶ **TRAINING** to enable each and everyone to update their skills, become more versatile, and advance within the company.
- ▶ **OPEN INNOVATION** to let our clients be the first to benefit from the most advanced technology.
- ▶ **RIGOROUS ORGANIZATION** to guarantee our clients obtain the quality, responsiveness, and flexibility they expect.



## MADE IN FRANCE

COVAL is headquartered in the heart of the Auvergne-Rhône-Alpes region, a particularly powerful economic area in terms of research and industrial production. With their leading network of industrial subcontractors, proximity to university and research centers, and multiple business clusters linked directly to its core activity, COVAL's products and services are an obvious choice to be Made in France.

COVAL USA is the North American subsidiary of COVAL and is located in Raleigh, NC. This location was created to strengthen the global presence of their sales and distribution network and provide its customers with ever improving channels to discover and purchase COVAL products and services.

This subsidiary benefits its customers by offering:

- A nationwide network of authorized COVAL distributors.
- Regional sales representatives who can provide local, hands-on support.
- Easy access to a friendly and knowledgeable technical sales team.
- A fully stocked warehouse to reduce delivery times and improve efficiency.

Let the experienced team at COVAL support your vacuum needs and you will understand why we call ourselves "**vacuum managers**".





# YOU DESERVE MUCH MORE THAN JUST VACUUM

Being able to benefit from high-performance products for the vacuum handling of your workpieces, products, and packages is your main requirement, but that's not enough by itself: you want solutions that are comprehensive, performing, and perfectly suited for your industry.

In order to bring you more than just vacuum, we are committed to a comprehensive development approach:

## ► **SOLUTIONS** that take into account all your concerns:

- The constraints of your process.
- The specific features of your products.
- The safety of operators.
- The energy performance of your equipment.

## ► **KNOW-HOW** that meets your needs:

- A thorough analysis.
- Customized advice.
- Capacity for engineering and innovation.
- High-quality manufacturing and service.
- Ongoing follow-up throughout the entire life cycle of our products.

## ► **PRODUCTS** that you can trust:


- Reduced space requirements for better integration.
- Continuously improved performance.
- Reduced energy consumption.
- Easier communication and interaction with the machine.

## ► **TEAMS** that specialize in **YOUR INDUSTRY**:

At COVAL, technical and sales teams are dedicated to strategic industry sectors: packaging, food processing, plastics, automotive, aeronautics, and robotics.

The experience they've acquired with major brands and manufacturers allows them to provide quick and efficient answers.

Our goal is to be present wherever vacuum handling and automation is useful for the performance of the business.







Being located in France, the world's second largest exporter of food, COVAL enjoys an exclusive relationship with the food processing industry.

Whether this involves handling raw, prepared, or packaged goods, COVAL has continually developed and adapted its products to the food processing industry needs:

- Making production lines more versatile.
- Producing within a safe food environment.
- Increasing productivity while maintaining a high level of quality.
- Reducing production and maintenance costs.

[More information](#)

## Suction Cups with a Firm Grip on Your Products

### ► SILICONE SUCTION CUPS

They are compatible with FDA food standards (FDA 21 CFR 177.2600.) and in conformity with European directives EU 1935/2004 and available in a wide variety of models to adapt perfectly to your products.

- From 1 mm to 88 mm in diameter.
- Round and oblong shapes.
- Flat, 1.5 and 2.5 bellows.
- **Metal-detectable version available upon request.**

→ See chapter 2.



### ► SPECIAL SUCTION CUPS

- FlowPack Suction Cups: **FPC** series.
- Suction cups for bakery applications: **VSD**, **VSE**, and **VSP** series.
- Suction cups for egg-handling: **VSO** series.

→ See chapter 3.



### ► VACUUM PUMPS

COVAL vacuum pumps all have compactness, embedded intelligence, and low energy consumption in common.

- **LEM and LEM+ series** for handling all porous or airtight parts.
- **LEMALX and LEMALX+ series** for handling all airtight or slightly porous parts.
- **LEMCOM series**: a vacuum pump with fieldbus communication.
- **CMS series**: multi-stage vacuum generator.

→ See chapter 8.



### ► VACUUM GRIPPERS


Vacuum grippers are used to grip several products (flow packs, tins, cans, etc.) or packages (palletization) at once.

- **MVG**: fully configurable vacuum gripper.
- **CVG**: vacuum gripper with many possible combinations.

→ See chapter 13.

[More information](#)





## Industry Solutions: **PACKAGING**



**COVAL**  
vacuum managers



Packaging plays an important role in industrial production. Vacuum applications in this field range from grasping small bags to handling large-sized cardboard boxes.

Their extremely various size, shapes, weights, and materials are a result of the many functions they need to fulfill: hold, transport, and store products, but also inform, promote, and facilitate use, etc.

Regardless of the type of packaging, the handling constraints are always the same:

- Safety of goods and operators.
- Handling throughput.
- Versatility.
- Energy savings.

More  
information



## COVAL All Along the Line

### ► SUCTION CUPS

Suction cups meet a wide variety of specifications thanks to the large choice of shapes, diameters, and materials. COVAL offers a complete line of fastening fittings that are suitable for suction cups and compatible with all types of applications.

- Flat and extra-flat suction cups.
- 1.5 and 2.5 bellows.
- Oblong suction cups.
- High-performance suction cups.

→ See chapters 2 and 3.



### ► VACUUM PUMPS

COVAL vacuum pumps all have compactness, embedded intelligence, and low energy consumption in common.

- Micro-ejectors.
- Modular vacuum pumps.
- Smart vacuum pumps.

→ See chapters 6 to 9.



### ► VACUUM GRIPPERS

Vacuum grippers are used to grip several products (flow packs, tins, cans, etc.) or packages (palletization) at once.

- **MVG**: fully configurable vacuum gripper.
- **CVG**: vacuum gripper with many possible combinations.

→ See chapter 13.



More  
information








## Industry Solutions: **AUTOMOTIVE INDUSTRY**



**COVAL**  
vacuum managers



COVAL has been delivering simple, flexible, modular, compact, and energy-efficient vacuum handling and automation solutions to car manufacturers for more than 30 years:

- High-throughput handling of workpieces on stamping press lines.
- Workpiece transport and clamping for gluing and welding at welding stations.
- Handling of windshields or sheet steel parts for assembly.

More  
information



## Integration, Performance and Energy Savings

### ► C SERIES HIGH-PERFORMANCE SUCTION CUPS

These suction cups are available in a wide range of sizes and shapes and have been developed to meet the constraints of the automotive industry:

- Optimal placement of oily steel sheets: anti-slip cleats.
- Preservation of workpieces: nitrile suction cups and polyamide fittings.
- Airtight fastening: o-ring.

Versions made of SITON® are available for handling hot workpieces (plastic workpieces, hot stamping).

→ See page 2/55.



### LEMAX, LEMAX+, AND LEMCOM SERIES SMART VACUUM PUMPS WITH VACUUM CONTROL

- Optimized robot equipment: ultra-compact and lightweight.
- Reduced gripping times: powerful suction flow rate.
- Incoming pressure reduced to 3.5 bar: ASR technology.
- Up to 90% compressed air savings: ASC technology.
- Maintenance free: non-clogging.
- Profinet, EtherNet/IP or CANopen fieldbus for the LEMCOM series.

→ See chapter 8.



**AIR** Saving  
Control







In a growing industry, the ability to reduce production times while preserving a high level of quality is essential. COVAL has worked on the following specific solutions with major manufacturers:

- Gripping parts on laser-trimming machines.
- Referencing and holding aircraft parts during drilling, sanding, riveting, etc.
- Integrating vacuum components in demonstration tools.
- Gripping aircraft parts made of various materials: steel, stainless steel, aluminum, and composite materials.



More  
information



## Dedicated Solutions for your Industry

### ► C SERIES HIGH-PERFORMANCE SUCTION CUPS

- Gripping thin workpieces without deformation.
- Handling or holding in vertical position.
- Optimal positioning and holding: anti-slip cleats.


→ See page 2/55.



### ► VPSC MARK-FREE ULTRA-FLAT SUCTION CUPS

- Gripping raw composite materials.
- No material migration.
- Non-marking on composite parts.

→ See page 3/5.



### ► LEMAX, LEMAX+ AND LEMCOM SERIES VACUUM PUMPS

- Optimized robot equipment: ultra-compact and lightweight.
- Reduced gripping times: powerful suction flow rate.
- Incoming pressure reduced to 3.5 bar: ASR technology.
- Up to 90% compressed air savings: ASR technology.
- Maintenance free: non-clogging.
- Profinet, EtherNet/IP or CANopen fieldbus for the LEMCOM series.

→ See chapter 8.




### ► CONTROL BOX WITH INTEGRATION FUNCTIONS

- Integrated pneumatic or electric vacuum pumps.
- Control and monitoring panel allowing you to manually or automatically select the gripping areas on a structure.
- Indicator light for visual alarm.
- Vacuum sequencing to assist with placement of a curved panel.

→ Upon request.







## Industry Solutions: **PLASTICS**



Hidden behind the generic term “plastics”, you will find materials that are very different in their composition, manufacturing, appearance, and applications.

For more than thirty years, COVAL has been developing vacuum handling solutions that are tailored to the constant technological developments of the processes and materials.

Our vacuum pumps and suction cups are able to handle plastics and composites for industries such as aeronautics, cosmetics, electronics/connectors, health, and transportation.



More  
information



## SITON<sup>®</sup>, A COVAL Exclusive

### ► SITON<sup>®</sup> SUCTION CUPS

SITON<sup>®</sup>, exclusively developed and manufactured by COVAL, is a silicone-free material especially created for handling hot workpieces as they are taken out of molds.

- Non-marking: clear mixture and silicone-free.
- SITON<sup>®</sup> supports peak temperatures up to 320 °F.
- SITON<sup>®</sup> features excellent abrasion resistance.

A wide variety of suction cup models are available in STN (Siton<sup>®</sup> 60 Shore A) in this catalog.

For greater flexibility, some models are available in STN5 (Siton<sup>®</sup> 50 Shore A) upon request.

→ See chapter 2.



## Intelligent Vacuum Pumps

### ► LEMAX, LEMAX+ AND LEMCOM SERIES

Mini-vacuum pumps with ASC are used for handling all airtight or slightly porous plastic parts.


- Ultra-compact and lightweight.
- More than 90% energy savings thanks to ASC technology.
- Silent operation.
- Auto-adjustment corresponding to the material handled.
- Maintenance free: non-clogging.
- Profinet, EtherNet/IP or CANopen fieldbus for the LEMCOM series.

→ See chapter 8.

**AIR**Saving  
Control







**COVAL**  
vacuum managers



## NEW PRODUCTS

Always in touch with the latest market developments, COVAL is driven by constant innovation and regularly introduces new products and solutions that meet specific vacuum handling needs.

► **LEMCOM series**

The first fieldbus-communicating vacuum pump.

► **LEM and LEM+ series**

Mini-vacuum pumps and compact vacuum pumps that feature high flow rates, are intelligent, and come with **ASR** energy-saving technology.

► **LEMAX and LEMAX+ series**

Mini-vacuum pumps and compact vacuum pumps that feature high flow rates, are intelligent, and come with **ASC** energy saving technology.

► **FPC series**

Universal FlowPack Suction Cups.

► **VPSC series**

Ultra-flat, mark-free suction cups for raw composite materials.

► **PSD series**

Mini-vacuum switches with 3-color display.

► **PSK series**

Miniature electronic vacuum switches.

► **MVG series**

Modular vacuum grippers.

These new products are already available today. Feel free to ask your COVAL preferred contact for more information.





## Mini Vacuum Pumps LEMCOM



1<sup>st</sup> mini vacuum pump on industrial fieldbus

**PROFINET**  
**EtherNet/IP™**  
**CANopen®**



**AIR Saving Control**

More information



### The best technology for increasing flexibility and productivity

- Maximum intelligence / minimal bulk.
- One “master” module controls 1 to 15 secondary modules.
- Master module is a fully-integrated pump.
- Remote configuration, monitoring and diagnostics
- Dedicated Coval bus between master and secondary modules.
- Simplified wiring and installation.
- Standard secondary modules (regardless of the type of bus).
- Additional communications port.
- Supported buses: Profinet, EtherNet/IP™, CANopen®...
- IP65 / M8 standard connectors.

### A simple product to utilize

#### LEMCOM master

EtherNet/IP™ **PROFINET**

- On-board 2-Port Ethernet Switch.
- On-board web server.
- Dedicated configuration software.
- M8/RJ45 standard connectors.



#### LEMCOM master

**CANopen®**

- Two CAN ports.
- From 20 to 1000 Kbps.
- Dedicated configuration software.
- Configuration by SDO.
- Adjustable PDO-TX transmission threshold.




#### LEMCOM secondary module

- Universal secondary module, regardless of bus type.



→ See page 8/29.

- For all types of porous or airtight workpieces:







## NEW PRODUCTS



**COVAL**  
vacuum managers

### Compact Vacuum Pumps

## LEM, LEM+



**40%** automatic energy savings

- Suction flow rate from 1.02 to 9.71 SCFM.
- Nozzle diameter: 1, 1.2, 1.4, 2 and 2.5 mm.
- 60 or 85% of maximum vacuum.
- Easy implementation: Plug & Play, multiple choices.
- Compactness: LEM/LEM+ vacuum pumps are the most compact on the market.
- Short response times: Installation close to suction cups.
- Automatic blow-off (LEM+): Automation efficiency due to an automatic blow-off function configurable from 0 to 10 seconds.
- Dust resistant: Non-clogging through-type silencer.
- Safety: Product gripping is maintained even during power failure.

→ See pages 8/3 to 8/14.



#### LEM+


- Nozzle diameter:
- 2 and 2.5 mm.
- Suction flow rate:
- from 4.41 to 9.71 SCFM.



#### LEM

- Nozzle diameter:
- 1, 1.2 and 1.4 mm.
- Suction flow rate:
- from 1.02 to 3.25 SCFM.

- For all types of porous or airtight workpieces:



### Compact Vacuum Pumps

## LEMAX, LEMAX+



**90%** energy savings on airtight parts

- Suction flow rate from 1.02 to 7.06 SCFM.
- Nozzle diameter: 1, 1.2, 1.4, 2 and 2.5 mm.
- 85% of maximum vacuum.
- Easy implementation: Plug & Play, multiple choices.
- Compactness: LEMAX/LEMAX+ vacuum pumps are the most compact on the market.
- Short response times: Installation close to suction cups.
- Automatic blow-off (LEMAX+): Automation efficiency due to an automatic blow-off function configurable from 0 to 10 seconds.
- Dust resistant: Non-clogging through-type silencer.
- Safety: Product gripping is maintained even during power failure.

→ See pages 8/15 to 8/28.



#### LEMAX+


- Nozzle diameter:
- 2 and 2.5 mm.
- Suction flow rate:
- from 4.41 to 7.06 SCFM.



#### LEMAX

- Nozzle diameter:
- 1, 1.2 and 1.4 mm.
- Suction flow rate:
- from 1.02 to 2.47 SCFM.

- For airtight parts:







# NEW PRODUCTS



**COVAL**  
vacuum managers



## FlowPack Suction Cups **FPC**

Focusing on the needs of its customers in the food industry, COVAL has developed a series of particularly innovative silicone cups, dedicated to the high-speed handling of flexible packaging.


Combining great flexibility and food compatibility, the new **FPC** Series suction cups have been specially designed to optimize the handling of packed bags from 100 g to 5 kg. E.g. - FlowPack, DoyPack, etc.

### A Complete Range

Different sizes (round Ø 35 mm 1.5 bellows ; round Ø 60 mm ; elliptical 120 x 100 mm) and two levels of flexibility (35 and 50 Shore) for a suitable solution.

See page 3/6.

More  
information



## Mark-Free, Ultra-Flat Suction Cups **VPSC**

- Gripping raw composite materials.
- No material migration.
- Non-marking on composite parts.

The COVAL **VPSC** suction cup has been developed in partnership with composite materials manufacturers to be able to grip uncured composites without leaving any traces or deformation.



Its ultra-flat design and innovative vacuum feeding system on the entire surface of the suction cup ensure maximum gripping power. The profile of the **VPSC**'s extra-thin lip enables it to fit the part's curve without any constraints.

This suction cup is made of a hydrocarbon-resistant material that guarantees a long lifetime.

It is also available in natural rubber and food grade silicone for a variety of applications.

See page 3/5.

More  
information







## NEW PRODUCTS



**COVAL**  
vacuum managers

### Vacuum Switch with 3-Color Display PSD

The **PSD** series miniature vacuum switch offers great reading comfort thanks to the size of its screen and 3-color display. It features a high-precision electronic vacuum-measuring sensor. Its compact and lightweight design make it easy-to-integrate on all machines. It comes with an M8 connector for easy hookup and is very simple to set up.

#### Measure, control, inform

3 functions in a small format: **30 x 30 x 25 mm** for easy integration on your machines.

See page 11/5.




### Miniature Electronic Vacuum Switches PSK

Thanks to their ultra-compact design and easy installation, **PSK** adjustable miniature vacuum switches can fit into the tightest spaces to be located as close as possible to the suction cups and thus reduce response times.

**PSKs** are recommended for applications that only require a "part present" signal and provide a cost-effective and efficient solution for applications with one vacuum generator per suction cup.


See page 11/3.



### Modular Vacuum Grippers MVG

The **MVG** modular vacuum gripper consists of standard subassemblies and provides a customized vacuum gripper solution for handling parts of various sizes, shapes, and weights.

- Customized dimensions.
- Selection of gripping areas.
- Compact and lightweight.
- Adaptable to products to be handled (choice of gripping interfaces).
- Adaptable to equipment (different types of vacuum generators).
- Universal fastener.
- Integrated functions.
- Easy installation and operation.



See page 13/2.



More  
information








# A TECHNOLOGICAL PARTNER ON A GLOBAL SCALE

Every year, we keep developing our network of partners (subsidiaries, distributors and independent agents) to assist our clients in their quest for local and international markets.



## ► HEADQUARTERS based in FRANCE

Since its creation in 1986, COVAL S.A.S. is established in Montélier in southern France.



## ► 5 SALES SUBSIDIARIES



COVAL Inc.



COVAL  
Iberica



COVAL  
Germany



COVAL  
Italia



COVAL  
China

## ► A broad network:

- 25 authorized **DISTRIBUTORS** in **FRANCE**
- 35 authorized **DISTRIBUTORS** outside **FRANCE**

► Visit the following section on our **WEBSITE**:  
Contact – Sales network,  
to view the latest **UP-TO-DATE LIST**



# Advanced Vacuum Solutions



# Table of Contents

---

<b>General Points About Suction Cups</b>	<b>Chapter 1</b>
<b>Standard Suction Cups</b>	<b>Chapter 2</b>
<b>Special Purpose Suction Cups</b>	<b>Chapter 3</b>
<b>Suction Cup Accessories</b>	<b>Chapter 4</b>
<b>Vacuum Pumps Overview</b>	<b>Chapter 5</b>
<b>Micro Ejectors</b>	<b>Chapter 6</b>
<b>Modular Vacuum Pumps</b>	<b>Chapter 7</b>
<b>Intelligent Vacuum Pumps</b>	<b>Chapter 8</b>
<b>High Flow Vacuum Generators</b>	<b>Chapter 9</b>
<b>Vacuum Pump Accessories</b>	<b>Chapter 10</b>
<b>Vacuum Switches</b>	<b>Chapter 11</b>
<b>Peripheral Devices</b>	<b>Chapter 12</b>
<b>Gripping Solutions</b>	<b>Chapter 13</b>
<b>Alphabetical Index</b>	



# Table of Contents















## INTRODUCTION: Guide to Vacuum Handling

VII to XII













## SUCTION CUPS

### Chapter 1 General Points About Suction Cups

### Chapter 2 Standard Suction Cups


	<b>VP</b> Flat suction cups Ø 8 to 75 mm	<b>2/3</b>		<b>VSAG</b> Suction cups with 1.5 bellows Ø 10 to 150 mm	<b>2/33</b>
	<b>VPG</b> Extra-flat suction cups Ø 2 to 200 mm	<b>2/9</b>		<b>VSAJ</b> Suction cups with 1.5 bellows Ø 15 to 30 mm	<b>2/39</b>
	<b>VPU</b> Flat suction cups Ø 6 à 50 mm	<b>2/17</b>		<b>VS</b> Suction cups with 2.5 bellows Ø 5 to 88 mm	<b>2/43</b>
	<b>VPF</b> Flat suction cups with cleats Ø 15 to 50 mm	<b>2/19</b>		<b>VSG</b> Suction cups with 2.5 bellows Ø 5 and 7 mm	<b>2/49</b>
	<b>VPO</b> Oblong flat suction cups	<b>2/21</b>		<b>VSD</b> Long stroke suction cups	<b>2/51</b>
	<b>VSA</b> Suction cups with 1.5 bellows Ø 5 to 78 mm	<b>2/25</b>		<b>C</b> High-performance suction cups	<b>2/55</b>
	<b>VSAB</b> Suction cups with 1.5 bellows Ø 5 to 50 mm	<b>2/31</b>		<b>VSA-VS BM / VSBM</b> Foam rings	<b>2/59</b>

### Chapter 3 Special Purpose Suction Cups












	<b>VPSC</b> Ultra-flat, Non-Marking Suction Cups	<b>3/5</b>		<b>VSO</b> Suction cups for egg-handling	<b>3/15</b>
	<b>FPC</b> FlowPack Suction Cups	<b>3/6</b>		<b>VBO</b> Suction Cup for Bottle Handling via the Punt	<b>3/16</b>
	<b>MVS</b> Soft Suction Cups for High Speed Applications	<b>3/9</b>		<b>VSBO, VSBO+</b> Suction cups for bottle handling	<b>3/17</b>
	<b>VSAF</b> Suction Cup for Cheese	<b>3/11</b>		<b>VPA</b> Suction cups for paper applications	<b>3/21</b>
	<b>VSAOF</b> Oblong Suction Cup for Cheese	<b>3/12</b>		<b>VPAL</b> Suction cups for labels	<b>3/23</b>
	<b>VSD, VSE, VSP</b> Suction cups for bakery applications	<b>3/13</b>		<b>VPR</b> Suction cups for mailing applications	<b>3/25</b>



# Table of Contents

	<b>VPAG</b> Curved suction cups	<b>3/26</b>		<b>SPL</b> Heavy load suction cups	<b>3/28</b>
	<b>VPYR</b> Radial ball-joint suction cups	<b>3/27</b>		<b>STEEL</b> Steel suction cups	<b>3/29</b>

## Chapter 4 Suction Cup Accessories





	<b>TS11</b> Spring systems	<b>4/3</b>		Miscellaneous gripping	<b>4/8</b>
	<b>TS</b> Spring systems TS1 – TS2 – TS3	<b>4/4</b>		Flow Control Nozzles	<b>4/9</b>
	<b>TS</b> Spring systems TS4 - TS5	<b>4/5</b>		<b>PMG2</b> Mechanical feelers	<b>4/10</b>
	<b>RSC</b> Systems with 4 compensated springs	<b>4/5</b>		<b>IMU</b> Axial ball-joints	<b>4/11</b>
	<b>TSOP - TSOG</b> Anti-rotation spring systems	<b>4/6</b>		<b>CSP</b> Piloted safety valves	<b>4/12</b>
	<b>L</b> Extensions	<b>4/7</b>		<b>BM</b> Foam strips	<b>4/13</b>

## VACUUM PUMPS

### Chapter 5 Vacuum Pumps Overview

General points	<b>5/2</b>	Vacuum pump range	<b>5/6</b>
Choosing a vacuum pump	<b>5/3</b>	Evacuation time and weight of vacuum pumps	<b>5/9</b>
Comparison of vacuum pumps and air amplifiers	<b>5/4</b>		





### Chapter 6 Micro Ejectors

	<b>CIL</b> In-line ejectors	<b>6/2</b>		<b>GVR</b> Heavy-duty in-line ejectors	<b>6/8</b>
	<b>VR</b> Heavy-duty in-line ejectors	<b>6/4</b>		<b>GVRL</b> Heavy-duty in-line ejectors	<b>6/10</b>












# Table of Contents




## Chapter 7 Vacuum Pumps

Overview of vacuum pumps	7/1	 <b>GVEC</b> «Easy Clean» vacuum pumps	7/12
 <b>GVP</b> Vacuum pumps	7/3	 <b>LEMP</b> Mini vacuum pumps with «ASR» (Air Saving Regulator)	7/15
 <b>GEMP</b> Simple vacuum pumps with "ASR" (Air Saving Regulator)	7/9		









## Chapter 8 Intelligent Vacuum Pumps

 <b>LEM</b> Integrated mini-vacuum pumps with "ASR" (Air Saving regulator)	8/3	 <b>LEMCOM</b>  EtherNet/IP  Mini vacuum pumps on industrial fieldbus	8/29
 <b>LEM+</b> Compact high-flow vacuum pumps with "ASR" (Air Saving Regulator)	8/9	 <b>GVMAX V2-2 / V2-2R</b> Self-regulating vacuum pumps	8/39
 <b>LEMAX</b> Integrated mini-vacuum pumps with "ASC" (Air Saving Control)	8/15	 <b>GVMAX</b> Self-regulating vacuum pumps (electric or pneumatic control)	8/44
 <b>LEMAX+</b> Compact high-flow vacuum pumps with "ASC" (Air Saving Control)	8/23		

## Chapter 9 High Flow Vacuum Generators

 <b>CMS</b> Multi-stage vacuum pumps	9/2	 <b>TVM</b> Pipes for air amplifiers	9/7
 <b>M-C</b> Air amplifiers	9/4		










## Chapter 10 Vacuum Pump Accessories

 <b>SIL GV</b> Diffuser-type silencers	10/3	 <b>FVG</b> Mini vacuum filters	10/8
 <b>SIL K--C</b> Through-type silencers	10/3	 <b>FVL12</b> In-line Vacuum filter	10/9
 <b>MS</b> Blow-off devices	10/4	 <b>FVL68</b> In-line Vacuum filter	10/9
 <b>FVI</b> Vacuum filters	10/5	 <b>FSL</b> Liquid separator vacuum filters	10/10
 <b>FVUM, FVUG</b> Vacuum filters	10/7	 <b>CD, CC</b> Screw-type electrical connectors	10/11



# Table of Contents

## Chapter 11 Vacuum Switch Range

	<b>PSK</b> Vacuum Switch	<b>11/3</b>		<b>PSE 100 E</b> Electric Vacuum Switch	<b>11/9</b>
	<b>PSA 100 C</b> Electronic Vacuum Switch With Display	<b>11/4</b>		<b>PSE 100 P</b> Pneumatic Vacuum Switch	<b>11/10</b>
	<b>PSD 100</b> Vacuum Switch With 3-colour Display	<b>11/5</b>		<b>PSE 100 PK</b> Pneumatic Vacuum Switch	<b>11/11</b>
	<b>PSP 100</b> Electronic Vacuum Switch	<b>11/7</b>		<b>VAF 111</b> Needle Vacuum Gauge	<b>11/12</b>
	<b>PSP 100 ANA</b> Electronic Vacuum Switch Analog Output	<b>11/8</b>			

## ACCESSORIES

## Chapter 12 Peripheral Devices

	<b>NVS, NVR, NVA</b> Vacuum Feeders	<b>12/2</b>		<b>REV 38</b> Vacuum Regulator	<b>12/5</b>
	<b>RDV, RCOV, Y</b> Screwed Vacuum Fittings With O-ring	<b>12/3</b>		<b>AG</b> Vacuum Valves, 3 Channels	<b>12/6</b>
	<b>RVM, RVF, RVT - TVR - COV</b> Fittings, Vacuum Tubes, Collars	<b>12/4</b>		<b>PA</b> Angular Jaw Clamps	<b>12/7</b>

## Chapter 13 Gripping Solutions

	<b>MVG</b> Customized Modular Vacuum Grippers	<b>13/2</b>		<b>CSGS</b> Bags/sacks Gripping System	<b>13/18</b>
	<b>CVG</b> Vacuum Grippers	<b>13/10</b>			

## Alphabetical Index

I to III







# Vacuum Handling Guide

---

<b>Vacuum Applications and Measurements</b>	<b>p. VIII</b>
<b>Suction Cup Performance</b>	<b>p. IX</b>
<b>Vacuum Generation Technologies</b>	<b>p. X - XI</b>
<b>The Process of Defining an Installation</b>	<b>p. XII</b>



# Vacuum Handling Guide

## Vacuum Applications and Measurements

### VACUUM HANDLING DEVELOPMENT

Industrial vacuum applied to suction cups is an efficient method for handling objects and materials.

This technique was developed to meet automation needs in the industry with applications in parts assembly, finishing, testing, transfer, packaging, etc....

It is designed particularly for the automobile, wood and plastics industries, as well as all object transformation activities: food, electricals, furniture, etc.

Vacuum handling has become a key production technology, and this document will detail the rules, procedures and components involved.


### MEASURING VACUUM LEVEL

Scientists use absolute pressure, with a scale that starts at perfect vacuum, with atmospheric pressure measuring roughly 1 bar.

For industrial applications, relative pressure is preferred because it marks a clear distinction between vacuum (negative pressure) and positive pressure.

In gripping applications, vacuum is only effective by its difference compared with atmospheric pressure. However, atmospheric pressure varies slightly depending on the altitude of the application site. This is why it is more practical to express vacuum level as a percentage of the atmospheric pressure.

The scale shown on the right illustrates the relationship between pressures expressed in bar and mbar and the vacuum level shown as a percentage of the atmospheric pressure. This relationship is accurate for use at an altitude of 100m. This is the measurement that we will use when discussing suction cups, since this is the most common altitude of industrial sites



### VACUUM UNITS CONVERSION

#### Relative vacuum


%	bar	mbar	Torr (mmHg)	inHg	kPa
0%	0	0	0	0	0
10%	-0.101	-101	-76	-2.98	-10.1
20%	-0.203	-203	-152	-5.99	-20.3
30%	-0.304	-304	-228	-8.97	-30.4
40%	-0.405	-405	-304	-11.96	-40.5
50%	-0.507	-507	-380	-14.97	-50.7
60%	-0.608	-608	-456	-17.95	-60.8
70%	-0.709	-709	-532	-20.93	-70.9
80%	-0.811	-811	-608	-23.94	-81.1
90%	-0.912	-912	-684	-26.93	-91.2
100%	-1.013	-1013	-760	-29.91	-101.3

### RECOMMENDED VACUUM LEVELS

Gripping provides a level of effort that is proportional to the level of the vacuum that generates it (see curves below). For the most efficient operation, a maximum vacuum level is recommended. However, the curves also show that a high level of vacuum:

- has a high energy cost
- takes a long time to establish

This is why the vacuum levels used should be limited, from 30% when a high flow of vacuum needs to be maintained, to 80% in an airtight circuit (no flow required to maintain the vacuum).






# Vacuum Handling Guide

## Suction Cup Performance

### VACUUM HANDLING PHASES



#### 1- Approach

For shock-free contact with the surface to be gripped, and to conform to its shape, the suction cup in this instance has 1.5 bellows.

Chapter 2 outlines a choice of suction cups and fittings to facilitate this phase.

#### 2- Gripping

Vacuum is then applied to the suction cup, which lifts the object pushed by atmospheric pressure.

The suction cup and object then remain bound together throughout the entire process (transfer, packaging, etc).

#### 3- Release

At the end of the suction process, the vacuum is interrupted to release the object.

Most often, an air blow-off will help this process and avoid sticking. This also helps to quickly move to the next cycle.

### VACUUM LEVELS AND SUCTION CUP SIZING

In practice, the majority of surfaces requiring suction are not airtight. If the material is porous or the surface is rough, it is inevitable that air will escape into the vacuum through the material or under the edges of the suction cup. In this situation, a high flow of vacuum must be maintained to compensate for air leaks and to maintain gripping. This can be done economically and efficiently at a low level of vacuum.

Within the recommended vacuum range of 30% to 80%, two distinct zones must be distinguished, depending on the nature of the object to be gripped..

#### 1. Porous materials

The 30 to 55% vacuum zone is both economical and efficient, given the amount of vacuum flow required. The suction cups should be sized appropriately to obtain the required holding force.

#### 2. Airtight surfaces


In this case, the 55 to 80% zone gives excellent results. The holding force is greater (curves opposite), so that smaller suction cups may be used.

Chapter 2 outlines a method for sizing the suction cups, particularly in relation to the chosen vacuum level.

#### 1. Porous materials

Greater vacuum flow must compensate for products and processes that cause air leaks such as cardboard, agglomerated materials, rough wood, irregular surfaces, etc.



The most economic vacuum level is therefore between 30 and 55%.



#### 2. Airtight surfaces

With metal, plastics, glass and any other smooth, airtight surface, the vacuum flow required remains low, or even zero.

The vacuum level can therefore be higher, between 55 and 85%.





# Vacuum Handling Guide

## Vacuum Generation Technologies

### 1- CONTINUOUS VACUUM, USING ROTARY VACUUM PUMPS

#### Rotary Vacuum Pump Principle

The most commonly used type of rotary pump is the vane pump (illustration).

The blades are spun at high speed by the rotor, and the centrifugal force pushes them against the pump housing. The air is displaced and pushed out, creating a vacuum at the inlet.

For low vacuum levels only, turbines (or regenerative blowers) are also used, which operate in a similar manner to vacuum cleaners: a rotor with blades that do not make contact with the housing, causing air to move at high speed.


#### Range of Rotary Vacuum Pumps

To maintain optimum output, rotary pumps must remain within average power levels: from 1 to 10 Kw. The suction capacity generated is much higher than the normal requirements of industrial suction cups.

#### Operation Applications and Practice

Rotary pumps are used where a constant, high level of suction flow rate is required. Vacuum packaging machines are a typical example of this.

However, in the vast domain of vacuum gripping, rotary pumps are only used in rare instances, where an object requires a high level of suction flow rate that needs to be maintained for a long time during the cycle.




#### Rotary Vacuum Pumps

- Constant consumption, continuous generation of vacuum, even for intermittent requirements: not suitable for intermittent vacuum generation requirements.
- Located far from the suction cups.


#### Applications :

- Vacuum sources for various processes such as vacuum packing, etc.
- Clamping maintained throughout the cycle, with high suction flow rate (porous objects etc.)



#### A Typical Application

The example shown below is a digital control manufacturing robot, which uses suction cups to clamp porous parts. Note that the pump, which is bulky, noisy and causes vibrations, must be installed well away from the operational section of the machine. It is connected via a tube, which must have a large diameter (40 to 80 mm) to reduce the loss of vacuum, which can sometimes be dangerous.





# Vacuum Handling Guide


## Vacuum Generation Technologies

### INTERMITTENT VACUUM, USING VENTURI VACUUM PUMPS

#### Venturi Vacuum Pump Principle

Using the "venturi" effect : a nozzle of diameter  $\varnothing$  is supplied with compressed air. The air jet carries along ambient air in its turbulence and then passes through the mixer on its way out. This suction effect of ambient air creates the depression that generates the vacuum.

Unlike rotary vacuum pumps which must turn continuously, venturi vacuum pumps can operate intermittently, only when the suction cups require vacuum.



#### Venturi Vacuum Pumps

- |   |  |
|---|--|
| <ul style="list-style-type: none"><li>• Consumption only when needed, results in low air consumption.</li><li>• Installation very close to the suction cups.</li><li>• Suction flow rate and vacuum level optimized for each application.</li></ul> | <b>Applications :</b> <ul style="list-style-type: none"><li>• All intermittent gripping operations, i.e. which only last for a part of the full cycle of the machine</li></ul> |
|---|--|

#### Venturi Vacuum Pump Ranges

The variations in nozzles and mixers offer an optimal range to meet all needs.

##### ■ Nozzle diameter $\varnothing$

The diameter defines the force generated and therefore the suction capacity:  $\varnothing$  0.5mm for micro suction cups, to  $\varnothing$  3mm with a suction capacity of 15.9 SCFM for several large suction cups.

##### ■ Mixer profile

This profile defines the maximum level of vacuum achieved by the venturi.

Two standard levels offered by COVAL:

- 60% for porous material (30 to 55% vacuum)
- 85% for airtight materials (55 to 80% vacuum)

Max. vacuum ► 2 standard levels:



#### Applications and Practice

Venturi vacuum pumps are used for all normal vacuum gripping applications.

Compact and light, venturis are installed as close as possible to the suction cups: little pressure loss and a minimum volume to purge, resulting in short response times and minimum energy consumption.

The following distinguishes between:

- simple, pneumatically-controlled venturi pumps, which are miniaturized for installation on suction cups.
- complete, electrically-controlled venturi pumps, for installation as near as possible to the suction cups.





# Vacuum Handling Guide

## The Process of Defining an Installation

All vacuum handling systems require a three-stage approach:

1. Defining the appropriate suction cups and attachments for the object to be gripped, the movements required, the type of object (airtight or porous), the holding force required, the cycle rate, the environment, etc.
2. Selecting the appropriate vacuum generator for the suction cups, the type of object (airtight or porous), the required response times, etc.
3. Identifying the additional components required to connect, supply and control the installation.

The 3 steps to follow:

### STEP 1: SUCTION CUPS AND THEIR ATTACHMENTS

COVAL offers a wide range of suction cups, in two main groups: standard and special purpose. Tailored solutions can also be developed according to a set of custom requirements.

Chapter 1 provides a detailed guide on how to choose a suction cup for a given application, among the wide range presented in chapters 2 and 4.



### STEP 2: VACUUM GENERATORS AND THEIR MEANS OF CONTROL

Selecting the perfect vacuum source for the suction cups used guarantees optimal productivity.

COVAL has developed a full range of venturi vacuum pumps using the most advanced technologies: optimized flow rates, low energy consumption, reduced weight and bulk, and silent operation. Numerous integrated functions mean they are easier and more economic to install and use.

Chapter 5 provides a guide starts with a guide to choose and configure a venturi among the many possibilities presented in the catalogue, from vacuum pump chapter 6 to 9.



### STEP 3: AUXILIARY COMPONENTS

Peripheral components are an essential addition to the vacuum network and guarantee reliable installation. The risks related to improper use are increased energy consumption and noise and decreased overall efficiency.

Chapters 4 and 12 present a wide variety of auxiliary components





# Suction Cups

## Chapter 1

<b>Selection Guide</b>	<b>p. 1/2</b>
<b>Suction Cup Assembly Options</b>	<b>p. 1/4</b>
<b>Assembly Reference: "Suction Cup + Fitting"</b>	<b>p. 1/5</b>
<b>The COVAL Range</b>	<b>p. 1/6</b>
<b>Index of Pictograms and Symbols</b>	<b>p. 1/9</b>



# Suction Cups

## Selection Guide

1

A suction cup is a gripper which can be used to handle all sorts of objects of different weights, surfaces, shapes and sizes. For this reason we feel it would be helpful to explain all the parameters to be taken into consideration, in order to choose the right suction cup.

### THE SHAPES

#### Flat Suction Cups

##### ■ Flat suction cups without cleats

Used for handling flat or slightly rounded, rigid, smooth objects. They withstand lateral forces and can be used for vertical handling.



##### ■ Flat suction cups with cleats

Used for handling thin, flexible, deformable objects. They increase resistance to lateral forces and horizontal handling.



#### Suction Cups with Bellows

Used to handle spherical, cylindrical or egg-shaped objects. The effect of the technical characteristics increases with the number of bellows.

They can be used for gripping objects with height differences, for a ball-joint effect, to lift and to grip corners or edges.



### SUCTION CUP FORCE CALCULATION

The force of a suction cup is proportional to its surface under vacuum and also depends on its shape, flexibility, material and especially on the level of vacuum attained inside the suction cup.

#### Theoretical force

$$F(\text{lbf}) = S(\text{cm}^2) \times V(\text{Bar}) / 0.2248^*$$

S = Surface of the suction cup (cm<sup>2</sup>)

V = Vacuum level (bar) (ex: 50% vacuum = -500 mbar = -0.5 bar, for calculation use 0.5)

(\*) coefficient to convert daN (decanewton) to lbf (pound-force)

#### Actual force


As its name implies, this force represents the actual force of the suction cup when in use. In general this is 50% less than the calculated theoretical force.

This difference is explained by the distortion of the suction cup during handling (which reduces the gripping surface), and by the condition of the surface of the object being handled.

#### The safety factor

All holding forces are listed in the data tables for each range of suction cup. These are **actual values at 65% vacuum**, calculated with a safety factor of:

- 2 for horizontal gripping (1),
- 4 for vertical gripping (2).



For applications involving high acceleration, the safety factor will be calculated accordingly.

### SUCTION CUP TECHNICAL DATA

#### Diameters

The force of the suction cup and the product's available gripping surface depend on this parameter. COVAL offers standard suction cups of 1 to 600mm in diameter across the product ranges.



#### Minimum bend radius

This indicates the minimum radius of a product to be reliably gripped by the suction cup.




#### Internal volume

This corresponds to the volume which must be evacuated during a vacuum cycle. It must be accounted for in the total volume of the gripping system and thus in the suction time calculation.



#### Stroke

This corresponds to the compression of the suction cup during the vacuum cycle.





# Suction Cups

## Selection Guide

1

### Parameters to be taken into consideration when choosing a suction cup

Shape of the load	Flat • Rounded • Cylindrical • Egg-shaped • Spherical, etc.
Type of material of the load	Porous • Porous • Deformable • Rigid • Fragile, etc.
Condition of the surface of the load	Smooth • Granular • Ridged • Abrasive, etc
Appearance of the load	Damp • Oily • Dusty • Viscous • Dry, etc
Weight of the load	Heavy • Light, etc.
Temperature of the load	From -40 to 482°F depending on the materials chosen.
Direction of gripping	Horizontal • Vertical • Over corners • Height differences, etc.
Type of grip	Handling • Lifting • Holding • Unfolding ... objects.
Available surface	Depending on the load
Cycle time	Accelerations

### COVAL MATERIALS

To meet the constraints of industrial applications, COVAL has a wide range of both standard and specific materials. COVAL can also study new materials based on specific requirements of your applications.



#### Properties of the materials

Materials	Shore Hardness A	Flexibility	Abrasion resistance	UV & weather resistance	Oil resistance	Heat resistance		Food compatibility	Color
						in °C	in °F		
<b>NBR:</b> Nitrile	60	+	+	—	++	0 to 80	32 to 176	—	Black
<b>SI:</b> Translucent Silicone	50	+++	—	+++	—	-40 to 220	-40 to 428	FDA and EC standard	Translucent
<b>SIB:</b> White Silicone	35	++++	—	+++	—	-40 to 220	-40 to 428	FDA and EC standard	White
<b>SIT5:</b> Translucent Silicone	50	+++	—	+++	—	-40 to 220	-40 to 428	FDA and EC standard	Translucent
<b>NR:</b> Natural Rubber	50	+++	++	—	—	-20 to 70	-4 to 158	+	Grey
<b>STN:</b> Siton®	60	+	++	—	++	0 to 160	32 to 320	—	Blue
<b>STN5:</b> Siton®	50	++	++	—	++	0 to 160	32 to 320	—	Blue

### SITON®

The COVAL laboratory has developed a new material: SITON®. SITON® is a silicone-free material which therefore does not leave a mark and was specially developed for handling hot objects that are waiting to be painted.

■ SITON® can withstand a maximum temperature of 320°F

■ SITON® has good resistance to abrasion.

Example of an application: Removal of plastic parts from injection mold machine.


Standard availability in 60 shore and on request in 50 shore (Part No: STN5) for VSA and VS series.





# Suction Cups

## Suction Cup Fitting Options




1

### Standard Configuration Options

COVAL suction cups offer versatile mounting and fitting options:

**Version C:**  
Barbed fittings.



The suction cup is easily pressed onto the fitting.

The suction cups and their fittings are delivered unassembled.


**Types of use:**

- Lightweight products.
- Horizontal handling.
- For suction cups belonging to groups 1 and 2.

**Advantages :**

- Quickest changeout of suction cups without the need for tools, improving efficiency.
- Fitting can be reused, thus reducing replacement costs.

**Version V :**  
2-piece removable fittings  
(hollow screws and adapter)



The V mounting utilizes a hollow screw passing through the suction cup and connecting to an adaptor on the opposite side, fixing the suction cup in place.

The suction cups and their fittings are delivered unassembled.


**Types of use :**

- Heavy and lightweight products.
- Horizontal, vertical and rotational handling.
- For suction cups belonging to groups 2 and 3.

**Advantages :**

- Excellent mechanical grip of the suction cup.
- Excellent vacuum sealing of the assembly.
- Fitting can be reused, thus reducing replacement costs.

**Version E :**  
Pressed fitting  
(removable).



The fitting is factory pressed onto the suction cup.


**Types of use :**

- Lightweight and heavy products.
- Horizontal, vertical and rotational handling.
- Recommended for handling of porous products.
- For suction cups belonging to group 2.

**Advantages :**

- Excellent mechanical grip of the suction cup.
- Excellent vacuum sealing of the assembly.
- Greater potential vacuum flow rate when handling porous products.

**Version S :**  
Factory-crimped fitting



The fitting is factory-crimped onto the suction cup, ensuring a one-piece assembly.

**Types of use :**

- Heavy and lightweight products.
- Horizontal handling, vertical and rotational.
- Recommended for handling of porous products (when greater flow is required).
- For suction cups belonging to group 3.


**Advantages :**

- Excellent mechanical grip of the suction cup.
- Excellent vacuum sealing of the assembly.
- Greater potential vacuum flow rate when handling porous products.



# Suction Cups

## Configuration Reference "Suction Cup + Fitting"



1

### Referencing

To simplify selection of fittings for standard suction cups, a male or female fitting option can be found in the example table, "**Choice of fittings**".

To demonstrate assembly options, reference the example below, **Standard configurations** (suction cup + fitting) which indicates full part numbers as well as **non-standard configurations**.

Ex :

### Choice of Fittings

Ø	Group	M3-M	M5-M	M6-M	M8-M	M10-M	G1/8"-F	G1/8"-M	10/32-M	G1/4"-F	G1/4"-M	G3/8"-M	G1/2"-M
5	1	■	-	-	-	-	-	-	-	-	-	-	-
11...25	1	-	■	■	-	-	■	■	□	-	-	-	-
26...63	2	-	□	□	□	□	■	■	-	■	■	-	-
78	3	-	-	-	-	□	-	■	-	■	■	□	□

■ Standard configurations (suction cup + fitting)

□ Non-standard mounting configurations

Fitting: M = male F = female

**Standard configurations** (suction cup + fitting) now have a single part number, simplifying your stock management and order fulfillment.

Ex:

Group 3		V			S	
THREAD		G1/8"-M	G1/4"-M	G1/4"-F	G1/4"-M	G1/4"-F
Ø 78 mm	VSA78NBR	VSA78NBRIM18V	VSA78NBRIM14V	VSA78NBRIF14V	VSA78NBRIM14	VSA78NBRIF14
	VSA78NR	VSA78NRIM18V	VSA78NRIM14V	VSA78NRIF14V	VSA78NRIM14	VSA78NRIF14
	VSA78SIT5	VSA78SIT5IM18V	VSA78SIT5IM14V	VSA78SIT5IF14V	VSA78SIT5IM14	VSA78SIT5IF14
	VSA78STN	VSA78STNIM18V	VSA78STNIM14V	VSA78STNIF14V	VSA78STNIM14	VSA78STNIF14


### Note :

For standard configurations (suction cup + fittings), the C and V versions are delivered unassembled.

**Additional mounting configurations** are available. You can find all options on pages "assembly diagrams"

Ex:

### Removable fittings



■ Standard configurations (suction cup + fitting).

□ Non-standard configurations must be ordered in separate part numbers.



# Suction Cups

## The COVAL Range



1















### Standard Suction Cups

Standard suction cups are suitable for all types of applications in various sectors like packaging, plastics, agri-food, sheet-metal working, etc.

These suction cups satisfy very diverse specifications thanks to a wide range of shapes, diameters and materials.

COVAL offers a full range of fittings adapted to suction cups and compatible with all types of applications.

See chapter 2

Flat Suction Cups		
<b>VP</b>		<ul style="list-style-type: none"> <li>■ Ø 8 to 75 mm</li> <li>■ 4 standard materials</li> <li>■ High tensile force and precise gripping and releasing</li> <li>■ High resistance to lateral forces allowing vertical handling</li> <li>■ Full range of fittings and shut-off valves</li> </ul>
<b>VPG</b>		<ul style="list-style-type: none"> <li>■ Extra-flat suction cups</li> <li>■ Ø 2 to 200 mm</li> <li>■ 3 standard materials</li> <li>■ Highly precise gripping and releasing of the load</li> <li>■ High throughput rates</li> </ul>
<b>VPU</b>		<ul style="list-style-type: none"> <li>■ Ø 6 to 50 mm</li> <li>■ 3 standard materials</li> <li>■ Suitable for gripping rigid and flat products</li> </ul>
<b>VPF</b>		<ul style="list-style-type: none"> <li>■ Flat suction cups with cleats</li> <li>■ Ø 15 to 50 mm</li> <li>■ 3 standard materials</li> <li>■ Suitable for gripping rigid and flat products</li> <li>■ Cleats prevent the deformation of the product and provide excellent non-slip properties</li> </ul>
<b>VPO</b>		<ul style="list-style-type: none"> <li>■ Flat oblong suction cups</li> <li>■ From 2x4 mm to 30x90 mm</li> <li>■ 3 standard materials</li> <li>■ Used for handling elongated products such as pens, tubes, bottles, bulbs and flat or cylindrical objects etc.</li> </ul>
Suction Cups with 1.5 Bellows		
<b>VSA</b>		<ul style="list-style-type: none"> <li>■ Ø 5 to 78 mm</li> <li>■ 5 standard materials</li> <li>■ Combines the advantages of flat suction cups with added angle, flexibility and precision</li> <li>■ Used for gripping slightly concave or convex parts</li> <li>■ Full range of fittings</li> </ul>
<b>VSAB</b>		<ul style="list-style-type: none"> <li>■ Ø 5 to 50 mm</li> <li>■ 3 standard materials</li> <li>■ Used for gripping slightly concave or convex parts</li> <li>■ Suitable for gripping products of various heights</li> </ul>
<b>VSAG</b>		<ul style="list-style-type: none"> <li>■ Ø 10 to 150 mm</li> <li>■ 3 standard materials</li> <li>■ Recommended for gripping sensitive products due to the cushioning effect of the bellows</li> <li>■ Used for gripping slightly concave or convex parts</li> </ul>
<b>VSAJ</b>		<ul style="list-style-type: none"> <li>■ Ø 15 to 30 mm</li> <li>■ 2 standard materials</li> <li>■ Used for gripping slightly concave or convex parts</li> <li>■ Suitable for gripping products of various heights</li> </ul>
Suction Cups with 2.5 Bellows		
<b>VS</b>		<ul style="list-style-type: none"> <li>■ Ø 5 to 88 mm</li> <li>■ 4 standard materials</li> <li>■ Recommended for gripping products on different planes (wide deflection) or cylindrical objects gripped at an angle (ball-joint effect).</li> <li>■ Full range of fittings</li> </ul>
<b>VSG</b>		<ul style="list-style-type: none"> <li>■ Ø 5 and 7mm</li> <li>■ 3 standard materials</li> <li>■ Suitable for gripping small products, concave or convex</li> <li>■ Ideal for handling sensitive products</li> </ul>
Long Stroke Suction Cups		
<b>VSD</b>		<ul style="list-style-type: none"> <li>■ Suction cups with 4.5 and 5.5 bellows</li> <li>■ 2 standard materials</li> <li>■ Strongly recommended for handling spherical or cylindrical products requiring a large height adjustment.</li> </ul>
High-performance Suction Cups		
<b>C</b>		<ul style="list-style-type: none"> <li>■ Full range of shapes (flat, bellows, oblongs)</li> <li>■ Ø 35 to 125mm and 25x65mm to 70x140mm</li> <li>■ Integrated M38G, F38G or Square 32 fittings</li> <li>■ Structure and internal cleats</li> <li>■ Textured suction cups for gripping thin sheets</li> <li>■ Non-slip cleats ensure optimum positioning of oily sheet metal</li> <li>■ Extreme resistance to slipping.</li> <li>■ Porous integrated fittings</li> <li>■ Ideal for automated applications</li> </ul>
Suction Cups with Foam Rings		
<b>VSA- VS BM / VSBM</b>		<ul style="list-style-type: none"> <li>■ Foam rings</li> <li>■ Can be adapted to standard suction cups</li> <li>■ 2 standard materials</li> <li>■ Bonded under a suction cup to allow products with an irregular or even-ridged surface to be gripped</li> <li>■ Sawn wood, sheet metal, flat surfaces with bumps or hollows (all types of granular surface)</li> </ul>



# Suction Cups

## The COVAL Range












See chapter 3

1

### Special Purpose Suction Cups

Thanks to a technological mastery and collaboration with its customers in different branches, COVAL supplies solutions for vacuum handling via a wide range of special purpose suction cups.

E.g. handling eggs, flexible bags, raw composite, bottles, paper, cakes, etc.

Ultra-flat, Non-Marking Suction Cups		
<b>VPSC</b>		<ul style="list-style-type: none"> <li>■ Ultra-flat suction cups</li> <li>■ Ø 40 and 80 mm</li> <li>■ 3 materials</li> </ul>
		<ul style="list-style-type: none"> <li>■ Suction cups specially designed not to deform the product being handled.</li> <li>■ Vacuum distributed across the entire surface of the suction cup for an optimal gripping force.</li> <li>■ Extra-thin sealing lip designed to contour to the shape of the product being handled</li> </ul>
FlowPack Suction Cups		
<b>FPC</b>		<ul style="list-style-type: none"> <li>■ Flexible suction cups</li> <li>■ 3 models</li> <li>■ Food-safe materials</li> <li>■ Silicone: FDA and CE standard</li> </ul>
		<ul style="list-style-type: none"> <li>■ Range specially designed for gripping flexible packaging</li> <li>■ Thin and wavy lips mold perfectly to any shape of packaging</li> <li>■ Gripping ability allows for high production rates</li> </ul>
Soft Suction Cups for High Speed Applications		
<b>MVS</b>		<ul style="list-style-type: none"> <li>■ Suction cups with 1.5 and 2.5 bellows</li> <li>■ 9 models</li> <li>■ Silicone: FDA and CE standard</li> </ul>
		<ul style="list-style-type: none"> <li>■ Used to grip delicate objects. Very flexible lip (opening bags, gripping tins and flexible aluminum or plastic bottles, etc.).</li> <li>■ High throughput rate</li> <li>■ Used to grip of flexible products</li> </ul>
Suction Cups for Cheese		
<b>VSAF</b>		<ul style="list-style-type: none"> <li>■ Suction cup with 1.5 bellows</li> <li>■ Ø 50 mm</li> <li>■ Silicone: FDA and CE standard</li> </ul>
		<ul style="list-style-type: none"> <li>■ Suction cup specially designed for gripping fragile foods such as soft cheese</li> <li>■ Accessory: Stainless steel grill prevents deformation of the food</li> </ul>
<b>VSAOF</b>		<ul style="list-style-type: none"> <li>■ Oval suction cup with 1.5 bellows</li> <li>■ Dim. 65x150 mm</li> <li>■ Silicone: FDA and CE standard</li> </ul>
		<ul style="list-style-type: none"> <li>■ Suction cup specially designed for gripping fragile foods such as soft cheese</li> <li>■ Accessory: Stainless steel grill prevents deformation of the food</li> </ul>
Suction Cups for Bakery Applications		
<b>VSD VSE VSP</b>		<ul style="list-style-type: none"> <li>■ Suction cups with 2.5 to 5.5 bellows</li> <li>■ 11 models</li> <li>■ Silicone: FDA and CE standard</li> </ul>
		<ul style="list-style-type: none"> <li>■ Range specially developed for gripping delicate objects such as cakes (buns, biscuits, etc.)</li> <li>■ Specific shapes and shore A hardness depending on the applications</li> <li>■ Resistance to temperature: - 40 °F to 428 °F</li> </ul>
Suction Cups for Egg-handling		
<b>VSO</b>		<ul style="list-style-type: none"> <li>■ Suction cups with 2.5 and 3.5 bellows</li> <li>■ 3 models</li> <li>■ Silicone: FDA and CE standard 1935/2004</li> </ul>
		<ul style="list-style-type: none"> <li>■ Range specially designed to meet constraints involved when handling eggs.</li> <li>■ Very flexible lip</li> <li>■ Different shapes of suction cup</li> </ul>
Suction Cups for Bottle Handling		
<b>VBO</b>		<ul style="list-style-type: none"> <li>■ Suction cup system comprised of a 62mm cup with 2.5 bellows and a silicone gripping disc (COVAL-Flex).</li> </ul>
		<ul style="list-style-type: none"> <li>■ The VBO suction cup system is designed for gripping bottles by the punt on disgorging stations.</li> <li>■ Excellent sealing when gripping different types of bottles.</li> </ul>
<b>VSBO VSBO+</b>		<ul style="list-style-type: none"> <li>■ Suction cups with 4.5 bellows</li> <li>■ 3 models</li> <li>■ High tensile force</li> <li>■ Highly flexible and long stroke</li> </ul>
		<ul style="list-style-type: none"> <li>■ Used to grip 750 ml bottles and Magnums.</li> <li>■ Bottles gripped from the side, vertical and horizontal handling</li> <li>■ Suction cup with stainless steel reinforcement in the bellows</li> <li>■ Available with integrated sensing valve</li> </ul>





# Suction Cups

## The COVAL Range







1


### Special Purpose Suction Cups

See chapter 3



#### Suction Cups for Paper Applications

<b>VPA</b>		<ul style="list-style-type: none"> <li>■ Flat suction cups</li> <li>■ 9 models</li> <li>■ Very flexible lip</li> <li>■ Natural rubber and silicone (FDA and CE standard)</li> </ul>	<ul style="list-style-type: none"> <li>■ Range of suction cups with very flexible lip used to handle very flexible materials</li> <li>■ Very resistant to abrasion (for paper, cardboard)</li> <li>■ Very flexible gripping lip which molds to the shape of the object to be handled</li> </ul>
<b>VPAL</b>		<ul style="list-style-type: none"> <li>■ Extra-flat shape suction cups</li> <li>■ 3 models</li> <li>■ Material: silicone (food compatibility)</li> </ul>	<ul style="list-style-type: none"> <li>■ The VPAL suction cups are especially adapted for gripping and handling IML labels or flexible materials</li> <li>■ Great lip flexibility</li> </ul>
<b>VPR</b>		<ul style="list-style-type: none"> <li>■ Flat suction cups</li> <li>■ 4 models</li> <li>■ Natural rubber</li> </ul>	<ul style="list-style-type: none"> <li>■ Range of suction cups designed to meet the requirements of mailing applications.</li> <li>■ Envelope stuffing, film-wrapping, mailing (picking)</li> <li>■ Very resistant to abrasion</li> </ul>
<b>VPAG</b>		<ul style="list-style-type: none"> <li>■ Curved suction cups</li> <li>■ 2 models</li> <li>■ Natural rubber</li> </ul>	<ul style="list-style-type: none"> <li>■ Thanks to very flexible lips and a curved shape, the VPAG range is adapted to gripping flexible materials such as labels or sheets of paper - or textured objects</li> <li>■ Very resistant to abrasion</li> </ul>

#### Radial Ball-joint Suction Cups

<b>VPYR</b>		<ul style="list-style-type: none"> <li>■ Flat suction cups with ball-joint system</li> <li>■ 4 models (Ø 50 to 100mm)</li> <li>■ Materials: nitrile and silicone</li> </ul>	<ul style="list-style-type: none"> <li>■ The range of ball-joint suction cups is recommended for gripping curved or rotating products which requires a lot of force and mechanical resistance</li> </ul>
-------------	--	---	--

#### "Heavy-load" Suction Cups

<b>SPL</b>		<ul style="list-style-type: none"> <li>■ "Heavy load" flat suction cups</li> <li>■ 5 models (Ø 240 to 600mm)</li> <li>■ Materials: nitrile and silicone</li> </ul>	<ul style="list-style-type: none"> <li>■ SPL suction cups are used to handle heavy loads such as sheet metal or glass panels. They have internal cleats allowing them to handle thin metal sheets without distorting them and for vertical handling (non-slip)</li> </ul>
<b>STEEL</b>		<ul style="list-style-type: none"> <li>■ Flat suction cups with a bonded foam seal</li> <li>■ 9 round models (Ø 150 to 580 mm)</li> <li>■ 9 rectangular models (175x115 to 705x385mm)</li> </ul>	<ul style="list-style-type: none"> <li>■ For horizontal handling of heavy loads (thick sheet metal) or objects with an uneven surface such as concrete slabs, wood, etc.</li> <li>■ Wide choice of dimensions</li> </ul>



# Suction Cups


## Index of Symbols and Pictograms



You will find the symbols and pictograms described below in the "Suction cups" chapters to help you select the range of suction cups best suited to your application.

1

### Industry-specific Applications



#### Metal

For handling rigid, smooth, flat objects (e.g. Sheet metal, glass or plastic panels).

- Heavy loads
- Oily objects
- High throughput
- High acceleration



#### Food-processing


Handling that requires materials which are compatible with food standards, highly flexible lips and suction cup shapes that do not damage fragile products.

- Handling of raw products such as cheese, meat, fish or packaged products.



#### Plastic

For handling plastic objects and requiring resistance to high temperatures, mark-free (e.g. COVAL-developed material, Siton®).



#### Wood

For handling materials with a slightly deformed, rough gripping surface requiring a foam seal to compensate for the unevenness and ensure porousness.



#### Eggs

For handling requiring food compatibility, a very flexible lip and a specific shape of suction cup.

- Gripping eggs



#### Cakes

For handling requiring food compatibility, a very flexible lip and a specific shape of suction cup.

- Gripping buns, biscuits, etc.



#### Bottles

Gripping concave shapes and requiring strong vertical lifting force.


- For handling 750 ml bottles or Magnums



#### Paper/picking

For handling paper, and labels and requiring high resistance to abrasion and a very flexible lip to grip flexible materials.


- Envelope filling, film-wrapping



#### Composite materials

Gripping of raw composite materials.


- No material migration
- No marking of the composite product



#### Bags

Gripping very flexible, deformable materials (plastic or paper).

- e.g. blister pack, bagging, etc.



#### Packaging

For handling wrapped products for packaging, cardboard products. Cardboard shaping, palletization, transfer, Pick & Place.

- Precision
- Abrasion

### Types of Use



Flat surfaces,  
all thicknesses



Flat surfaces,  
thin layers



Rounded  
surfaces



Sheet metal  
(unstacking)



Flexible  
materials



Vertical  
handling



Granular  
surfaces

### Tables

Model or reference	Internal volume	Tensile force	Slipping force	Minimum convex curve radius	Minimum concave curve radius	Weight	See page



# Standard Suction Cups

## Chapter 2

2

### COVAL QUALITY

Standard suction cups are suitable for all types of applications in areas of activity such as packaging, plastics, agri-food, sheet-metal working, etc.

These suction cups satisfy very diverse specifications thanks to a wide range of shapes, diameters and materials.

COVAL offers a full range of fittings adapted to suction cups and compatible with all types of applications.

#### VP



#### Flat Suction Cups Ø 8 to 75 mm

4 standard materials

- Nitrile
- Silicone
- Natural rubber
- Siton®

- High tensile force and precise gripping and releasing
- High resistance to lateral forces enabling vertical handling
- A full range of fittings and shut-off valves

P 2/3

#### VPG



#### Extra-flat Suction Cups Ø 1 to 200 mm

3 standard materials

- Nitrile
- Silicone
- Siton®

- Highly precise gripping and releasing of the load
- High throughput rates

P 2/9

#### VPU



#### Flat Suction Cups Ø 6 to 50 mm

3 standard materials

- Nitrile
- Silicone
- Siton®

- Suitable for gripping smooth, rigid and flat products

P 2/17

#### VPF



#### Flat Suction Cups with Cleats Ø 15 to 50 mm


3 standard materials

- Nitrile
- Silicone
- Siton®

- Suitable for gripping smooth, rigid and flat products
- Cleats prevent the deformation of the product

P 2/19

#### VPO



#### Oblong Flat Suction Cups

3 standard materials

- Nitrile
- Silicone
- Siton®

- Used for handling elongated products such as pens, tubes, bottles, bulbs and flat or cylindrical objects etc.

P 2/21

#### VSA



#### Suction Cups with 1.5 Bellows Ø 5 to 78 mm

5 standard materials

- Nitrile
- Translucent silicone
- 35 shore A white silicone
- Natural rubber
- Siton®

- VSA series suction cups with bellows combine the advantages of flat suction cups with more deflection, flexibility and precision
- Used for gripping slightly concave or convex parts
- Full range of fittings

P 2/25

#### VSAB



#### Suction Cups with 1.5 Bellows Ø 5 to 50 mm

3 standard materials

- Nitrile
- Silicone
- Siton®

- Used for gripping slightly concave or convex parts
- Suitable for gripping products of various heights

P 2/31



# Standard Suction Cups

## Chapter 2

2

### VSAG



#### Suction Cups with 1.5 Bellows Ø 10 to 150 mm

3 standard materials

- Nitrile
- Silicone
- Siton®

- Recommended for gripping products sensitive to the cushioning effect of the bellows
- Used for gripping slightly concave or convex parts

P 2/33

### VSAJ



#### Suction Cups with 1.5 Bellows Ø 15 to 30 mm


2 standard materials

- Nitrile
- Silicone

- Used for gripping slightly concave or convex parts
- Suitable for gripping products of various heights

P 2/39

### VS



#### Suction Cups with 2.5 Bellows Ø 5 to 88 mm

4 standard materials

- Nitrile
- Natural rubber
- Translucent silicone
- Siton®

- VS series suction cups with bellows are recommended for gripping products on different planes (wide deflection) or cylindrical objects gripped at an angle (ball-joint effect).
- Full range of fittings

P 2/43

### VSG



#### Suction Cups with 2.5 Bellows Ø 5 and 7 mm


3 standard materials

- Nitrile
- Silicone
- Siton®

- Suitable for gripping small products, concave or convex
- Ideal for handling sensitive products

P 2/49

### VSD



#### Long Stroke Suction Cups

2 standard materials

- Nitrile
- Silicone

- Strongly recommended for handling spherical or cylindrical products requiring a large height adjustment.

P 2/51

### C



#### High-performance Suction Cups

- Full range of shapes (flat, bellows, oblongs)
- Ø 35 to 125mm and 25x65mm to 70x140mm
- Integrated M3/8G, F38G or Square 32 fittings
- Structure and internal cleats

- Textured suction cups for gripping thin sheet metal
- Non-slip cleats ensure optimum positioning of oily sheet metal
- Extreme resistance to slipping
- Air-tight integrated fittings
- Ideal for automated applications

P 2/55

### VSA-VS BM VSBM



#### Foam Rings

2 standard materials

- Nitrile
- Silicone

- The foam ring is designed for gripping products with an uneven or ridged surface, e.g.
- Sawn wood, sheet metal, flat surfaces with bumps or hollows.
- All granular surfaces to which suction cups cannot adhere correctly and therefore cannot be airtight.
- Foam rings can be adapted to VSA and VS series.

P 2/59



## Flat Suction Cups Ø 8 to 75 mm



VP series flat suction cups are specially recommended for handling flat, rigid, smooth products.


- High tensile force
- High resistance to lateral forces enabling vertical handling.
- High degree of precision

### Materials

**NBR** Nitrile  
**NR** Natural rubber

**SIT5** Translucent silicone  
**STN** Siton®






### Industry-specific applications



### Types of use




### Suction Cup Properties

	Ø (mm)	 (cm³)	 (lbf) <sup>(1)</sup>	 (lbf) <sup>(1)</sup>	 R <sub>min</sub> (mm)	NBR	SIT5	NR	STN
VP 8	7.5	0.04	0.24	0.12	10	VP8NBR	VP8SIT5	-	VP8STN
VP 10	10	0.05	0.36	0.18	13	VP10NBR	VP10SIT5	-	-
VP 15	15	0.18	0.83	0.41	13	VP15NBR	VP15SIT5	-	VP15STN
VP 20	20	0.44	1.38	0.68	20	VP20NBR	VP20SIT5	-	VP20STN
VP 25	25	0.7	2.11	1.06	25	VP25NBR	VP25SIT5	-	VP25STN
VP 26	26	1.5	2.52	1.25	35	VP26NBR	VP26SIT5	-	-
VP 30	30	2.9	3.57	1.79	40	VP30NBR	VP30SIT5	-	VP30STN
VP 35	35	2.7	5.20	2.60	50	VP35NBR	VP35SIT5	-	-
VP 40	40	4	6.01	3.00	50	VP40NBR	VP40SIT5	VP40NR	VP40STN
VP 50	52	7	8.60	4.30	75	VP50NBR	VP50SIT5	-	VP50STN
VP 60	60	7.3	12.99	6.49	100	VP60NBR	VP60SIT5	-	-
VP 75	75	16	22.73	11.36	130	VP75NBR	VP75SIT5	VP75NR	-

(1) Actual force of the suction cup in use with 65% vacuum and including a safety factor of 2 for horizontal handling and a factor of 4 for vertical handling.

### Choice of Fittings

 (Ø)	Group	M5-M	M6-M	M8-M	M10-M	G1/8"-F	G1/8"-M	10/32-M	G1/4"-F	G1/4"-M	G3/8"-M	G1/2"-M
8...25	1	■	■	-	-	■	■	□	-	-	-	-
26...60	2	□	□	□	□	■	■	-	■	■	-	-
75	3	-	-	-	□	-	■	-	■	■	□	□

■ Standard available configurations (suction cup + fitting)  
refer to page 2/4

□ Additional mounting configurations  
see page 2/7

Fitting: M = male

F = female

### Types of Assembly

COVAL suction cups can be assembled in a wide variety of configurations.



**Version C:** Barbed fitting



**Version S:** Factory-crimped fitting



**Version V:** Removable fitting:  
(adapter and hollow screw)



**Version E:** Pressed fitting



Please specify the part n°. e.g. VP40STNIM14C  
Refer to page 2/4

### Accessories

To optimize the use of your suction cups, Coval offers a comprehensive range of accessories (feelers, nozzle fittings, spring extensions, and feeder systems, etc.), see chapters 4 and 12.



## Flat Suction Cups Ø 8 to 75 mm

References "Suction Cup + Fitting"



Group 1					
Ø 8 - 25 mm	THREAD	M5-M	M6-M	G1/8"-M	G1/8"-F
	VP8NBR	VP8NBRIMM5C	VP8NBRIMM6C	VP8NBRIM18C	VP8NBRIF18C
	VP8SIT5	VP8SIT5IMM5C	VP8SIT5IMM6C	VP8SIT5IM18C	VP8SIT5IF18C
	VP8STN	VP8STNIMM5C	VP8STNIMM6C	VP8STNIM18C	VP8STNIF18C
	VP10NBR	VP10NBRIMM5C	VP10NBRIMM6C	VP10NBRIM18C	VP10NBRIF18C
	VP10SIT5	VP10SIT5IMM5C	VP10SIT5IMM6C	VP10SIT5IM18C	VP10SIT5IF18C
	VP15NBR	VP15NBRIMM5C	VP15NBRIMM6C	VP15NBRIM18C	VP15NBRIF18C
	VP15SIT5	VP15SIT5IMM5C	VP15SIT5IMM6C	VP15SIT5IM18C	VP15SIT5IF18C
	VP15STN	VP15STNIMM5C	VP15STNIMM6C	VP15STNIM18C	VP15STNIF18C
	VP20NBR	VP20NBRIMM5C	VP20NBRIMM6C	VP20NBRIM18C	VP20NBRIF18C
	VP20SIT5	VP20SIT5IMM5C	VP20SIT5IMM6C	VP20SIT5IM18C	VP20SIT5IF18C
	VP20STN	VP20STNIMM5C	VP20STNIMM6C	VP20STNIM18C	VP20STNIF18C
	VP25NBR	VP25NBRIMM5C	VP25NBRIMM6C	VP25NBRIM18C	VP25NBRIF18C
	VP25SIT5	VP25SIT5IMM5C	VP25SIT5IMM6C	VP25SIT5IM18C	VP25SIT5IF18C
	VP25STN	VP25STNIMM5C	VP25STNIMM6C	VP25STNIM18C	VP25STNIF18C
	VP25SIT5	VP25SIT5IMM5C	VP25SIT5IMM6C	VP25SIT5IM18C	VP25SIT5IF18C
	VP25STN	VP25STNIMM5C	VP25STNIMM6C	VP25STNIM18C	VP25STNIF18C

Group 2									
Ø 26 - 60 mm	THREAD	G1/4"-M	G1/4"-F	G1/4"-M	G1/4"-F	G1/8"-M	G1/8"-F	G1/4"-M	G1/4"-F
	VP26NBR	VP26NBRIM14C	VP26NBRIF14C	VP26NBRIM14	VP26NBRIF14	VP26NBRIM18V	VP26NBRIF18V	VP26NBRIM14V	VP26NBRIF14V
	VP26SIT5	VP26SIT5IM14C	VP26SIT5IF14C	VP26SIT5IM14	VP26SIT5IF14	VP26SIT5IM18V	VP26SIT5IF18V	VP26SIT5IM14V	VP26SIT5IF14V
	VP30NBR	VP30NBRIM14C	VP30NBRIF14C	VP30NBRIM14	VP30NBRIF14	VP30NBRIM18V	VP30NBRIF18V	VP30NBRIM14V	VP30NBRIF14V
	VP30SIT5	VP30SIT5IM14C	VP30SIT5IF14C	VP30SIT5IM14	VP30SIT5IF14	VP30SIT5IM18V	VP30SIT5IF18V	VP30SIT5IM14V	VP30SIT5IF14V
	VP30STN	VP30STNIM14C	VP30STNIF14C	VP30STNIM14	VP30STNIF14	VP30STNIM18V	VP30STNIF18V	VP30STNIM14V	VP30STNIF14V
	VP35NBR	VP35NBRIM14C	VP35NBRIF14C	VP35NBRIM14	VP35NBRIF14	VP35NBRIM18V	VP35NBRIF18V	VP35NBRIM14V	VP35NBRIF14V
	VP35SIT5	VP35SIT5IM14C	VP35SIT5IF14C	VP35SIT5IM14	VP35SIT5IF14	VP35SIT5IM18V	VP35SIT5IF18V	VP35SIT5IM14V	VP35SIT5IF14V
	VP40NBR	VP40NBRIM14C	VP40NBRIF14C	VP40NBRIM14	VP40NBRIF14	VP40NBRIM18V	VP40NBRIF18V	VP40NBRIM14V	VP40NBRIF14V
	VP40NR	VP40NRIM14C	VP40NRIF14C	VP40NRIM14	VP40NRIF14	VP40NRIM18V	VP40NRIF18V	VP40NRIM14V	VP40NRIF14V
	VP40SIT5	VP40SIT5IM14C	VP40SIT5IF14C	VP40SIT5IM14	VP40SIT5IF14	VP40SIT5IM18V	VP40SIT5IF18V	VP40SIT5IM14V	VP40SIT5IF14V
	VP40STN	VP40STNIM14C	VP40STNIF14C	VP40STNIM14	VP40STNIF14	VP40STNIM18V	VP40STNIF18V	VP40STNIM14V	VP40STNIF14V
	VP50NBR	VP50NBRIM14C	VP50NBRIF14C	VP50NBRIM14	VP50NBRIF14	VP50NBRIM18V	VP50NBRIF18V	VP50NBRIM14V	VP50NBRIF14V
	VP50SIT5	VP50SIT5IM14C	VP50SIT5IF14C	VP50SIT5IM14	VP50SIT5IF14	VP50SIT5IM18V	VP50SIT5IF18V	VP50SIT5IM14V	VP50SIT5IF14V
	VP50STN	VP50STNIM14C	VP50STNIF14C	VP50STNIM14	VP50STNIF14	VP50STNIM18V	VP50STNIF18V	VP50STNIM14V	VP50STNIF14V
	VP60NBR	VP60NBRIM14C	VP60NBRIF14C	VP60NBRIM14	VP60NBRIF14	VP60NBRIM18V	VP60NBRIF18V	VP60NBRIM14V	VP60NBRIF14V
	VP60SIT5	VP60SIT5IM14C	VP60SIT5IF14C	VP60SIT5IM14	VP60SIT5IF14	VP60SIT5IM18V	VP60SIT5IF18V	VP60SIT5IM14V	VP60SIT5IF14V
	VP60SIT5	VP60SIT5IM14C	VP60SIT5IF14C	VP60SIT5IM14	VP60SIT5IF14	VP60SIT5IM18V	VP60SIT5IF18V	VP60SIT5IM14V	VP60SIT5IF14V

Group 3						
Ø 75 mm	THREAD	G1/8"-M	G1/4"-M	G1/4"-F	G1/4"-M	G1/4"-F
	VP75NBR	VP75NBRIM18V	VP75NBRIM14V	VP75NBRIF14V	VP75NBRIM14	VP75NBRIF14
	VP75NR	VP75NRIM18V	VP75NRIM14V	VP75NRIF14V	VP75NRIM14	VP75NRIF14
	VP75SIT5	VP75SIT5IM18V	VP75SIT5IM14V	VP75SIT5IF14V	VP75SIT5IM14	VP75SIT5IF14

Additional mounting configurations are available (see page 2/7).  
For standard configurations (suction cup+fitting), the C and V versions are delivered unassembled.




# VP

## Flat Suction Cups Ø 8 to 75 mm


Dimensions "Suction Cup + Fitting"




### VP 8 - 10 Group 1




### VP 15 - 25 Group 1





### VP 26 - 60 Group 2



### VP 75 Group 3



Group 1		Diagram	ØA	ØD	f <sup>(1)</sup>	H	H1	ØG	G1	ØG2 <sup>(2)</sup>	E 	 (g)
Ø 8 - 25 mm	VP8---IMM5C	1	7.5	-	1.3	10	15	M5-M	4.5	2.5	7	3.5
	VP8---IMM6C	1	7.5	-	1.3	10	15	M6-M	5	3.5	7	3.1
	VP8---IM18C	1	7.5	-	1.3	10	16	G1/8"-M	7.5	3.5	14	4.5
	VP8---IF18C	2	7.5	-	1.3	10	22	G1/8"-F	8	3.5	14	4.4
	VP10---IMM5C	1	10	-	1.5	10.5	15.5	M5-M	4.5	2.5	7	3.6
	VP10---IMM6C	1	10	-	1.5	10.5	15.5	M6-M	5	3.5	7	3.2
	VP10---IM18C	1	10	-	1.5	10.5	16.5	G1/8"-M	7.5	3.5	14	4.6
	VP10---IF18C	2	10	-	1.5	10.5	22.5	G1/8"-F	8	3.5	14	4.5
	VP15---IMM5C	3	15	-	2.25	11	16	M5-M	4.5	2.5	7	3.8
	VP15---IMM6C	3	15	-	2.25	11	16	M6-M	5	3.5	7	3.4
	VP15---IM18C	3	15	-	2.25	11	17	G1/8"-M	7.5	3.5	14	4.8
	VP15---IF18C	4	15	-	2.25	11	23	G1/8"-F	8	3.5	14	4.7
	VP20---IMM5C	3	20	-	3	11.5	17.5	M5-M	4.5	2.5	7	4.2
	VP20---IMM6C	3	20	-	3	11.5	23.5	M6-M	5	3.5	7	3.8
	VP20---IM18C	3	20	-	3	11.5	16.5	G1/8"-M	7.5	3.5	14	5.2
	VP20---IF18C	4	20	-	3	11.5	16.5	G1/8"-F	8	3.5	14	5.1
	VP25---IMM5C	3	25	-	3	12	17	M5-M	4.5	2.5	7	4.6
	VP25---IMM6C	3	25	-	3	12	17	M6-M	5	3.5	7	4.2
	VP25---IM18C	3	25	-	3	12	18	G1/8"-M	7.5	3.5	14	5.6
	VP25---IF18C	4	25	-	3	12	24	G1/8"-F	8	3.5	14	5.5

Note: All dimensions are in mm



(1) f = Deflection of the suction cup. (2) Ø G2 = Ø internal orifice of the fitting.



## Flat Suction Cups Ø 8 to 75 mm

Dimensions "Suction Cup + Fitting"



Group 2		Diagram	ØA	ØD	f <sup>(1)</sup>	H	H1	ØG	G1	ØG2 <sup>(2)</sup>	E 	 (g)
Ø 26 - 60 mm	VP26---IM18V	5	26	-	3	19.5	24	G1/8"-M	6	3.5	13	17.9
	VP26---IF18V	6	26	-	3	19.5	32.5	G1/8"-F	7.5	3.5	13	21.2
	VP26---IM14	5	26	-	3	19.5	23.5	G1/4"-M	11	4.4	17	11.6
	VP26---IM14C	5	26	-	3	19.5	27.5	G1/4"-M	10	7	17	12.5
	VP26---IM14V	5	26	-	3	19.5	24.5	G1/4"-M	8	3.5	17	27.2
	VP26---IF14	6	26	-	3	19.5	34.5	G1/4"-F	10	4.4	17	12.2
	VP26---IF14C	6	26	-	3	19.5	34.5	G1/4"-F	12	6.9	17	11.8
	VP26---IF14V	6	26	-	3	19.5	35.5	G1/4"-F	11	3.5	17	31.8
	VP30---IM18V	5	30	-	2.5	19	23.5	G1/8"-M	6	3.5	13	17.3
	VP30---IF18V	6	30	-	2.5	19	32	G1/8"-F	7.5	3.5	13	21.6
	VP30---IM14	5	30	-	2.5	19	23	G1/4"-M	11	4.4	17	12.0
	VP30---IM14C	5	30	-	2.5	19	27	G1/4"-M	10	7	17	12.9
	VP30---IM14V	5	30	-	2.5	19	24	G1/4"-M	8	3.5	17	27.6
	VP30---IF14	6	30	-	2.5	19	34	G1/4"-F	10	4.4	17	12.6
	VP30---IF14C	6	30	-	2.5	19	34	G1/4"-F	12	6.9	17	12.2
	VP30---IF14V	6	30	-	2.5	19	35	G1/4"-F	11	3.5	17	32.2
	VP35---IM18V	5	35	-	3	20	24.5	G1/8"-M	6	3.5	13	20.1
	VP35---IF18V	6	35	-	3	20	33	G1/8"-F	7.5	3.5	13	23.4
	VP35---IM14	5	35	-	3	20	24	G1/4"-M	11	4.4	17	13.8
	VP35---IM14C	5	35	-	3	20	28	G1/4"-M	10	7	17	14.7
	VP35---IM14V	5	35	-	3	20	25	G1/4"-M	8	3.5	17	29.4
	VP35---IF14	6	35	-	3	20	35	G1/4"-F	10	4.4	17	14.4
	VP35---IF14C	6	35	-	3	20	35	G1/4"-F	12	6.9	17	14.0
	VP35---IF14V	6	35	-	3	20	36	G1/4"-F	11	3.5	17	34.0
	VP40---IM18V	5	40	-	3	20	24.5	G1/8"-M	6	3.5	13	20.6
	VP40---IF18V	6	40	-	3	20	33	G1/8"-F	7.5	3.5	13	23.9
	VP40---IM14	5	40	-	3	20	24	G1/4"-M	11	4.4	17	14.3
	VP40---IM14C	5	40	-	3	20	28	G1/4"-M	10	7	17	15.2
	VP40---IM14V	5	40	-	3	20	25	G1/4"-M	8	3.5	17	29.9
	VP40---IF14	6	40	-	3	20	35	G1/4"-F	10	4.4	17	14.9
	VP40---IF14C	6	40	-	3	20	35	G1/4"-F	12	6.9	17	14.5
	VP40---IF14V	6	40	-	3	20	36	G1/4"-F	11	3.5	17	34.5
	VP50---IM18V	5	52	-	4.5	22	26.5	G1/8"-M	6	3.5	13	26.4
	VP50---IF18V	6	52	-	4.5	22	35	G1/8"-F	7.5	3.5	13	29.7
	VP50---IM14	5	52	-	4.5	22	26	G1/4"-M	11	4.4	17	20.1
	VP50---IM14C	5	52	-	4.5	22	30	G1/4"-M	10	7	17	21.0
	VP50---IM14V	5	52	-	4.5	22	27	G1/4"-M	8	3.5	17	35.7
	VP50---IF14	6	52	-	4.5	22	37	G1/4"-F	10	4.4	17	20.7
	VP50---IF14C	6	52	-	4.5	22	37	G1/4"-F	12	6.9	17	20.3
	VP50---IF14V	6	52	-	4.5	22	38	G1/4"-F	11	3.5	17	40.3
	VP60---IM18V	5	60	-	4.5	22	26.5	G1/8"-M	6	3.5	13	30.1
	VP60---IF18V	6	60	-	4.5	22	35	G1/8"-F	7.5	3.5	13	33.4
	VP60---IM14	5	60	-	4.5	22	26	G1/4"-M	11	4.4	17	23.8
	VP60---IM14C	5	60	-	4.5	22	30	G1/4"-M	10	7	17	24.7
	VP60---IM14V	5	60	-	4.5	22	27	G1/4"-M	8	3.5	17	39.4
	VP60---IF14	6	60	-	4.5	22	37	G1/4"-F	10	4.4	17	24.4
	VP60---IF14C	6	60	-	4.5	22	37	G1/4"-F	12	6.9	17	24.0
	VP60---IF14V	6	60	-	4.5	22	38	G1/4"-F	11	3.5	17	44.0
Group 3												
Ø 75 mm	VP75---IM18V	9	75	23	4.5	32	-	G1/8"-M	8	6	-	58.3
	VP75---IM14	7	75	-	4.5	32	38	G1/4"-M	11	8	21	46.4
	VP75---IM14V	7	75	-	4.5	32	37	G1/4"-M	8	6	17	68.9
	VP75---IF14	8	75	-	4.5	32	47	G1/4"-F	10	8	21	50.3
	VP75---IF14V	8	75	-	4.5	32	51	G1/4"-F	9	6	17	78.5

Note: All dimensions are in mm


(1) f = Deflection of the suction cup. (2) Ø G2 = Ø internal orifice of the fitting.






#### VP 8 - 25 Group 1

Barbed fittings **C**




#### VP 26 - 60 Group 2


Barbed fittings **C**




Pressed fittings **E**



#### Adapters




Removable fittings **V**




#### VP 75 Group 3

Factory-cripped fittings **S**




Removable fittings **V**

#### Adapters



#### Hollow screws



- Configurations (suction cup + fitting) refer to page 2/4
- Non-standard configurations must be ordered in separate part numbers.

Fittings and suction cups dimensions: see page 2/8.



## Flat Suction Cups Ø 8 to 75 mm

### Dimensions




#### Suction Cups

VP 8... 10

VP 15... 25

VP 26... 75




(1) f = Deflection of the suction cup.




	ØA	H	Ød	ØD	f (1)	B	(g)
VP 8	7.5	10	5	9	1.3	7	0.4
VP 10	10	10.5	4.4	9	1.5	7	0.5
VP 15	15	11	4	9	2.25	7	0.7
VP 20	20	11.5	4	10	3	7	1.2
VP 25	25	12	4	10	3	7	1.4
VP 26	26	19.5	8	16	3	13	3.7
VP 30	30	19	8	16	2.5	13	4
VP 35	35	20	8	16	3	13	5.6
VP 40	40	20	8	16	3	13	9
VP 50	52	22	8	18	4.5	13	14
VP 60	60	22	8	18	4.5	13	16
VP 75	75	32	12	23	4.5	20	33

#### Barbed Fittings

Male - IM




Female - IF



	ØA	B	C	ØD	E	Material	(g)
IM 11 A	G1/8"-M	7.5	6	3.5	14	Aluminum	4.1
IMC 14	G1/4"-M	10	8	7	17	Aluminum	8.7
IM 21 (2)	M5-M	4.5	5	2.5	7	Nickel-plated brass	3.1
IM 22 (2)	M6-M	5	5	3.5	7	Nickel-plated brass	2.7
IM 23	10/32-M	4.5	5	2.5	7	Brass	3
IM 24	M5-M	4.5	2.5	2.5	10	Nickel-plated brass	3.2
IF 10 A	G1/8"-F	8	12	3.5	14	Aluminum	4
IFC 14	G1/4"-F	12	15	6.9	17	Aluminum	8


#### Hollow Screws




	ØA	B	C	ØD	Material	(g)
IM 50	M5-M	5	11	2.8	Brass	7.4
IM 60 (2) (3)	M6-M	7	11	3.5	Nickel-plated brass	7.5
IM 68	M8-M	8	11	5.2	Nickel-plated brass	6.4
IM 80	G1/8"-M	8	18	6	Nickel-plated brass	23.7
IM 85	M10x150-M	8	18	6	Nickel-plated brass	23.5

#### Factory-crimped Fittings

Male - IM




Female - IF




	ØA	B	C	ØD	E	Material	(g)
IM 51	G1/4"-M	11	6	4.4	17	Aluminum	11.8
IF 50	G1/4"-F	10	15	8	21	Aluminum	15.7
IM 52	G3/8"-M	11	6	8	21	Aluminum	14

#### Adapters for Hollow Screws

Male - IM



Female - IF



	ØA	B	C	ØD	E	Material	(g)
IM 10 M6F	M10-M	7	3.5	M6-F	13	Brass	5.9
IM 12 F18	G1/2"-M	14	6	G1/8"-F	22	Nickel-plated brass	46.8
IM 14 M6F	G1/4"-M	8	5	M6-F	17	Nickel-plated brass	15.9
IM 14 F18	G1/4"-M	8	5	G1/8"-F	17	Nickel-plated brass	10.6
IM 18 M6F	G1/8"-M	6	4.5	M6-F	13	Nickel-plated brass	6.6
IM 38 F18	G3/8"-M	9	5	G1/8"-F	19	Nickel-plated brass	18.8
IF 14 M6F	G1/4"-F	11	16	M6-F	17	Nickel-plated brass	20.5
IF 18 M6F	G1/8"-F	7.5	13	M6-F	13	Nickel-plated brass	9.9
IF 14 F18	G1/4"-F	9	19	G1/8"-F	17	Nickel-plated brass	20.2

The values represent the average characteristics of our products.


Note: All dimensions are in mm.

(2) Flow restrictor version available: orifice calibrated to reduce leaks when used with a multi-cup gripper (see page 4/9).


(3) Available in stainless steel.

#### Pressed Fitting

Male - IM



Female - IF



	ØA	B	C	ØD	E	Material	(g)
IM 41	G1/4"-M	11	4	4.4	17	Aluminum	7.8
IF 40	G1/4"-F	10	15	4.4	17	Aluminum	8.4



## Extra-flat Suction Cups Ø 2 to 200 mm

The profile of the VPG series extra-flat suction cups provides for accuracy in load gripping and speeds up throughput rates. These suction cups are used for flat surfaces only.

## Materials

**NBR** Nitrile  
**SI** Silicone

**STN** Siton®








Industry-specific applications



Types of use




## Suction Cup Properties

	Ø (mm)	 (cm³)	 (lbf) <sup>(1)</sup>	 (lbf) <sup>(1)</sup>	 R <sub>min</sub> (mm)	NBR	SI	STN
VPG 2	2	0.00073	0.02	0.01	2	VPG2NBR	VPG2SI	-
VPG 3.5	3.5	0.0022	0.06	0.03	8	VPG3.5NBR	VPG3.5SI	-
VPG 5	5	0.005	0.11	0.06	8	VPG5NBR	VPG5SI	VPG5STN
VPG 6	6	0.008	0.16	0.08	8	VPG6NBR	VPG6SI	VPG6STN
VPG 8	8	0.03	0.28	0.14	10	VPG8NBR	VPG8SI	VPG8STN
VPG 10	10	0.07	0.45	0.23	13	VPG10NBR	VPG10SI	VPG10STN
VPG 15	15	0.2	1.06	0.54	13	VPG15NBR	VPG15SI	VPG15STN
VPG 20	20	0.5	1.98	0.99	20	VPG20NBR	VPG20SI	VPG20STN
VPG 25	25	1.1	2.71	1.36	25	VPG25NBR	VPG25SI	VPG25STN
VPG 30	30	1.4	3.69	1.85	40	VPG30NBR	VPG30SI	VPG30STN
VPG 35	35	2.9	5.36	2.68	50	VPG35NBR	VPG35SI	VPG35STN
VPG 40	40	3.8	7.79	3.90	50	VPG40NBR	VPG40SI	VPG40STN
VPG 50	50	5.3	12.18	6.09	75	VPG50NBR	VPG50SI	VPG50STN
VPG 60	60	12	19.97	9.98	100	VPG60NBR	VPG60SI	VPG60STN
VPG 60S	60	12	19.97	9.98	100	VPG60SNBR	VPG60SSI	VPG60SSTN
VPG 80	80	26.9	32.15	16.07	150	VPG80NBR	VPG80SI	VPG80STN
VPG 80S	80	26.9	32.15	16.07	150	VPG80SNBR	VPG80SSI	VPG80SSTN
VPG 95	95	41	45.46	22.73	200	VPG95NBR	VPG95SI	VPG95STN
VPG 95S	95	41	45.46	22.73	200	VPG95SNBR	VPG95SSI	VPG95SSTN
VPG 120	120	141	59.26	29.63	365	VPG120NBR	VPG120SI	VPG120STN
VPG 150	150	230	95.79	47.89	380	VPG150NBR	VPG150SI	VPG150STN
VPG 200	200	384	170.47	85.24	430	VPG200NBR	VPG200SI	VPG200STN

(1) Actual force of the suction cup in use with 65% vacuum and including a safety factor of 2 for horizontal handling and a factor of 4 for vertical handling.

## Choice of Fittings

 (Ø)	M3-M	M5-M	M5-F	M6-M	M8-M	M10-M	M10x125-F	G1/8"-F	G1/8"-M	G1/4"-F	G1/4"-M	G1/2"-F
2, 3.5	■	■	-	-	-	-	-	-	-	-	-	-
5... 10	-	■	■	-	-	-	-	■	■	-	-	-
15, 20	-	■	-	-	-	-	-	■	■	-	-	-
25... 50	-	-	-	■	□	□	-	■	■	■	■	-
60... 95	-	-	-	-	-	-	■	-	-	■	■	-
60S... 95S	-	-	-	-	-	-	-	-	-	■	-	-
120... 200	-	-	-	-	-	-	-	-	-	-	-	■

■ Standard available configurations (suction cup + fitting) see page reference 2/10 □ Additional mounting configurations See pages 2/13 - 2/14

Fitting: M = male F = female

## Types of Assembly

COVAL suction cups can be assembled in a wide variety of configurations.



**Version C:** Barbed fitting



**Version V:** Removable fitting:  
(adaptor and hollow screw)

## Accessories

To optimize the use of your suction cups, Coval offers a comprehensive range of accessories (nozzle fittings, spring extensions, and feeder systems, etc.), see chapters 4 and 12.



Please specify the part n°. e.g. VPG25STNIF18C  
Refer to page 2/10





Ø 2 - 10 mm	THREAD	M3-M	M5-M	M5-F	G1/8"-M	G1/8"-F
	VPG2NBR	VPG2NBRIMM3C	VPG2NBRIMM5C	-	-	-
	VPG2SI	VPG2SIIMM3C	VPG2SIIMM5C	-	-	-
	VPG3.5NBR	VPG3.5NBRIMM3C	VPG3.5NBRIMM5C	-	-	-
	VPG3.5SI	VPG3.5SIIMM3C	VPG3.5SIIMM5C	-	-	-
	VPG5NBR	-	VPG5NBRIMM5C	VPG5NBRIFM5C	VPG5NBRIM18C	VPG5NBRIF18C
	VPG5SI	-	VPG5SIIMM5C	VPG5SIIFM5C	VPG5SIIM18C	VPG5SIIF18C
	VPG5STN	-	VPG5STNIMM5C	VPG5STNIFM5C	VPG5STNIM18C	VPG5STNIF18C
	VPG6NBR	-	VPG6NBRIMM5C	VPG6NBRIFM5C	VPG6NBRIM18C	VPG6NBRIF18C
	VPG6SI	-	VPG6SIIMM5C	VPG6SIIFM5C	VPG6SIIM18C	VPG6SIIF18C
	VPG6STN	-	VPG6STNIMM5C	VPG6STNIFM5C	VPG6STNIM18C	VPG6STNIF18C
	VPG8NBR	-	VPG8NBRIMM5C	VPG8NBRIFM5C	VPG8NBRIM18C	VPG8NBRIF18C
	VPG8SI	-	VPG8SIIMM5C	VPG8SIIFM5C	VPG8SIIM18C	VPG8SIIF18C
	VPG8STN	-	VPG8STNIMM5C	VPG8STNIFM5C	VPG8STNIM18C	VPG8STNIF18C
	VPG10NBR	-	VPG10NBRIMM5C	VPG10NBRIFM5C	VPG10NBRIM18C	VPG10NBRIF18C
	VPG10SI	-	VPG10SIIMM5C	VPG10SIIFM5C	VPG10SIIM18C	VPG10SIIF18C
	VPG10STN	-	VPG10STNIMM5C	VPG10STNIFM5C	VPG10STNIM18C	VPG10STNIF18C

Ø 15 - 20 mm	THREAD	G1/8"-M	G1/8"-F	M5-M	G1/8"-M	G1/8"-F
	VPG15NBR	VPG15NBRIM18C	VPG15NBRIF18C	VPG15NBRIMM5V	VPG15NBRIM18V	VPG15NBRIF18V
	VPG15SI	VPG15SIIM18C	VPG15SIIF18C	VPG15SIIMM5V	VPG15SIIM18V	VPG15SIIF18V
	VPG15STN	VPG15STNIM18C	VPG15STNIF18C	VPG15STNIMM5V	VPG15STNIM18V	VPG15STNIF18V
	VPG20NBR	VPG20NBRIM18C	VPG20NBRIF18C	VPG20NBRIMM5V	VPG20NBRIM18V	VPG20NBRIF18V
	VPG20SI	VPG20SIIM18C	VPG20SIIF18C	VPG20SIIMM5V	VPG20SIIM18V	VPG20SIIF18V
	VPG20STN	VPG20STNIM18C	VPG20STNIF18C	VPG20STNIMM5V	VPG20STNIM18V	VPG20STNIF18V

Ø 25 - 50 mm	THREAD	G1/8"-M	G1/8"-F	M6-M	G1/8"-M	G1/8"-F	G1/4"-M	G1/4"-F
	VPG25NBR	VPG25NBRIM18C	VPG25NBRIF18C	VPG25NBRIMM6V	VPG25NBRIM18V	VPG25NBRIF18V	VPG25NBRIM14V	VPG25NBRIF14V
	VPG25SI	VPG25SIIM18C	VPG25SIIF18C	VPG25SIIMM6V	VPG25SIIM18V	VPG25SIIF18V	VPG25SIIM14V	VPG25SIIF14V
	VPG25STN	VPG25STNIM18C	VPG25STNIF18C	VPG25STNIMM6V	VPG25STNIM18V	VPG25STNIF18V	VPG25STNIM14V	VPG25STNIF14V
	VPG30NBR	VPG30NBRIM18C	VPG30NBRIF18C	VPG30NBRIMM6V	VPG30NBRIM18V	VPG30NBRIF18V	VPG30NBRIM14V	VPG30NBRIF14V
	VPG30SI	VPG30SIIM18C	VPG30SIIF18C	VPG30SIIMM6V	VPG30SIIM18V	VPG30SIIF18V	VPG30SIIM14V	VPG30SIIF14V
	VPG30STN	VPG30STNIM18C	VPG30STNIF18C	VPG30STNIMM6V	VPG30STNIM18V	VPG30STNIF18V	VPG30STNIM14V	VPG30STNIF14V
	VPG35NBR	VPG35NBRIM18C	VPG35NBRIF18C	VPG35NBRIMM6V	VPG35NBRIM18V	VPG35NBRIF18V	VPG35NBRIM14V	VPG35NBRIF14V
	VPG35SI	VPG35SIIM18C	VPG35SIIF18C	VPG35SIIMM6V	VPG35SIIM18V	VPG35SIIF18V	VPG35SIIM14V	VPG35SIIF14V
	VPG35STN	VPG35STNIM18C	VPG35STNIF18C	VPG35STNIMM6V	VPG35STNIM18V	VPG35STNIF18V	VPG35STNIM14V	VPG35STNIF14V
	VPG40NBR	VPG40NBRIM18C	VPG40NBRIF18C	VPG40NBRIMM6V	VPG40NBRIM18V	VPG40NBRIF18V	VPG40NBRIM14V	VPG40NBRIF14V
	VPG40SI	VPG40SIIM18C	VPG40SIIF18C	VPG40SIIMM6V	VPG40SIIM18V	VPG40SIIF18V	VPG40SIIM14V	VPG40SIIF14V
	VPG40STN	VPG40STNIM18C	VPG40STNIF18C	VPG40STNIMM6V	VPG40STNIM18V	VPG40STNIF18V	VPG40STNIM14V	VPG40STNIF14V
	VPG50NBR	VPG50NBRIM18C	VPG50NBRIF18C	VPG50NBRIMM6V	VPG50NBRIM18V	VPG50NBRIF18V	VPG50NBRIM14V	VPG50NBRIF14V
	VPG50SI	VPG50SIIM18C	VPG50SIIF18C	VPG50SIIMM6V	VPG50SIIM18V	VPG50SIIF18V	VPG50SIIM14V	VPG50SIIF14V
	VPG50STN	VPG50STNIM18C	VPG50STNIF18C	VPG50STNIMM6V	VPG50STNIM18V	VPG50STNIF18V	VPG50STNIM14V	VPG50STNIF14V

Ø 60 - 95 mm	THREAD	M10x125-F	G1/4"-F	G1/4"-M	G1/4"-F
	VPG60NBR	VPG60NBR	-	VPG60NBRIM14V	VPG60NBRIF14V
	VPG60SNBR	-	VPG60SNBR	-	-
	VPG60SI	VPG60SI	-	VPG60SIIM14V	VPG60SIIF14V
	VPG60SSI	-	VPG60SSI	-	-
	VPG60STN	VPG60STN	-	VPG60STNIM14V	VPG60STNIF14V
	VPG60SSTN	-	VPG60SSTN	-	-
	VPG80NBR	VPG80NBR	-	VPG80NBRIM14V	VPG80NBRIF14V
	VPG80SNBR	-	VPG80SNBR	-	-
	VPG80SI	VPG80SI	-	VPG80SIIM14V	VPG80SIIF14V
	VPG80SSI	-	VPG80SSI	-	-
	VPG80STN	VPG80STN	-	VPG80STNIM14V	VPG80STNIF14V
	VPG80SSTN	-	VPG80SSTN	-	-
	VPG95NBR	VPG95NBR	-	VPG95NBRIM14V	VPG95NBRIF14V
	VPG95SNBR	-	VPG95SNBR	-	-
	VPG95SI	VPG95SI	-	VPG95SIIM14V	VPG95SIIF14V
	VPG95SSI	-	VPG95SSI	-	-
	VPG95STN	VPG95STN	-	VPG95STNIM14V	VPG95STNIF14V
	VPG95SSTN	-	VPG95SSTN	-	-

Ø 120 - 200 mm	THREAD	G1/2"-F *	G1/2"-F **
	VPG120NBR	VPG120NBRIFS12V	VPG120NBRIF12V
	VPG120SI	VPG120SIIFS12V	VPG120SIIF12V
	VPG120STN	VPG120STNIFS12V	VPG120STNIF12V
	VPG150NBR	VPG150NBRIFS12V	VPG150NBRIF12V
	VPG150SI	VPG150SIIFS12V	VPG150SIIF12V
	VPG150STN	VPG150STNIFS12V	VPG150STNIF12V
	VPG200NBR	VPG200NBRIFS12V	VPG200NBRIF12V
	VPG200SI	VPG200SIIFS12V	VPG200SIIF12V
	VPG200STN	VPG200STNIFS12V	VPG200STNIF12V

\* Configured using fitting n° IFS12120

\*\* Configured using fitting n° IF12120

Non-standard configurations are available (see page 2/13 and 2/14). For standard configurations (suction cup+fitting), the C and V versions are delivered unassembled.




## Extra-flat Suction Cups Ø 2 to 200 mm

Dimensions "Suction Cup + Fitting"



### VPG 2 - 10

### VPG 15 - 50



### VPG 60 - 95

### VPG 120 - 200






		Diagram	ØA	ØD	f <sup>(1)</sup>	H	H1	ØG	G1	ØG2 <sup>(2)</sup>	E	⚖ (g)
Ø 2 - 10 mm	VPG2---IMM3C	1	2	-	0.5	4	6	M3-M	3	1	5	0.21
	VPG2---IMM5C	1	2	-	0.5	4	7.5	M5-M	4.5	1	7	0.91
	VPG3.5---IMM3C	1	3.5	-	0.5	4	6	M3-M	3	1	5	0.22
	VPG3.5---IMM5C	1	3.5	-	0.5	4	7.5	M5-M	4.5	1	7	0.65
	VPG5---IMM5C	1	5	-	0.8	6.5	10	M5-M	4.5	2.2	7	0.86
	VPG5---IFM5C	2	5	-	0.8	6.5	15.5	M5-F	6	2.2	14	1.3
	VPG5---IM18C	1	5	-	0.8	6.5	11.5	G1/8"-M	8	2.2	14	4.1
	VPG5---IF18C	2	5	-	0.8	6.5	21.5	G1/8"-F	9	2.2	14	5.3
	VPG6---IMM5C	1	6	-	0.8	6.5	10	M5-M	4.5	2.2	7	0.9
	VPG6---IFM5C	2	6	-	0.8	6.5	15.5	M5-F	6	2.2	14	1.3
	VPG6---IM18C	1	6	-	0.8	6.5	11.5	G1/8"-M	8	2.2	14	4.1
	VPG6---IF18C	2	6	-	0.8	6.5	21.5	G1/8"-F	9	2.2	14	5.3
	VPG8---IMM5C	1	8	-	1.2	7	10.5	M5-M	4.5	2.2	7	0.9
	VPG8---IFM5C	2	8	-	1.2	7	16	M5-F	6	2.2	14	1.4
	VPG8---IM18C	1	8	-	1.2	7	12	G1/8"-M	8	2.2	14	4.1
	VPG8---IF18C	2	8	-	1.2	7	22	G1/8"-F	9	2.2	14	5.33
Ø 15 - 20 mm	VPG10---IMM5C	1	10	-	1.5	7.5	11	M5-M	4.5	2.2	7	1
	VPG10---IFM5C	2	10	-	1.5	7.5	16.5	M5-F	6	2.2	14	1.5
	VPG10---IM18C	1	10	-	1.5	7.5	12.5	G1/8"-M	8	2.2	14	4.2
	VPG10---IF18C	2	10	-	1.5	7.5	21.5	G1/8"-F	9	2.2	14	5.4
	VPG15---IM18C	4	15	-	1.9	8	13	G1/8"-M	8	2.2	14	4.7
	VPG15---IF18C	5	15	-	1.9	8	23	G1/8"-F	9	2.5	14	5.9
	VPG15---IMM5V	3	15	-	1.9	8	-	M5-M	5	2.5	-	2
	VPG15---IM18V	4	15	-	1.9	8	12.5	G1/8"-M	6	2.5	13	9.3
	VPG15---IF18V	5	15	-	1.9	8	21	G1/8"-F	7.5	2.5	13	12.5
	VPG20---IM18C	4	20	-	2.3	10	15	G1/8"-M	8	3	14	5.6
	VPG20---IF18C	5	20	-	2.3	10	25	G1/8"-F	9	3	14	6.9
	VPG20---IMM5V	3	20	-	2.3	10	-	M5-M	5	2.5	-	3.7
	VPG20---IM18V	4	20	-	2.3	10	14.5	G1/8"-M	6	2.5	13	11
	VPG20---IF18V	5	20	-	2.3	10	23	G1/8"-F	7.5	2.5	13	14.2

Note: All dimensions are in mm.

(1) f = Deflection of the suction cup. (2) Ø G2 = Ø internal orifice of the fitting.





		Diagram	ØA	ØD	f <sup>(1)</sup>	H	H1	ØG	G1	ØG2 <sup>(2)</sup>	E 	 (g)
Ø 25 - 50 mm	VPG25---IM18C	4	25	-	3	14	19	G1/8"-M	8	4	14	6.9
	VPG25---IF18C	5	25	-	3	14	29	G1/8"-F	9	4	14	7.9
	VPG25---IMM6V	3	25	-	3	14	-	M6-M	6	3.5	-	5.5
	VPG25---IM18V	4	25	-	3	14	18.5	G1/8"-M	6	3.5	13	12.1
	VPG25---IF18V	5	25	-	3	14	27	G1/8"-F	7.5	3.5	13	15.4
	VPG25---IM14V	4	25	-	3	14	19	G1/4"-M	8	3.5	17	21.4
	VPG25---IF14V	5	25	-	3	14	30	G1/4"-F	11	3.5	17	26
	VPG30---IM18C	4	30	-	2	12	17	G1/8"-M	8	4	14	7.4
	VPG30---IF18C	5	30	-	2	12	27	G1/8"-F	9	4	14	8.4
	VPG30---IMM6V	3	30	-	2	12	-	M6-M	6	3.5	-	6
	VPG30---IM18V	4	30	-	2	12	16.5	G1/8"-M	6	3.5	13	12.6
	VPG30---IF18V	5	30	-	2	12	25	G1/8"-F	7.5	3.5	13	15.9
	VPG30---IM14V	4	30	-	2	12	17	G1/4"-M	8	3.5	17	21.9
	VPG30---IF14V	5	30	-	2	12	28	G1/4"-F	11	3.5	17	26.5
	VPG35---IM18C	4	35	-	3	14	19	G1/8"-M	8	4	14	9.9
	VPG35---IF18C	5	35	-	3	14	29	G1/8"-F	9	4	14	10.9
	VPG35---IMM6V	3	35	-	3	14	-	M6-M	6	3.5	-	8.5
	VPG35---IM18V	4	35	-	3	14	18.5	G1/8"-M	6	3.5	13	15.1
	VPG35---IF18V	5	35	-	3	14	27	G1/8"-F	7.5	3.5	13	18.4
	VPG35---IM14V	4	35	-	3	14	19	G1/4"-M	8	3.5	17	24.4
	VPG35---IF14V	5	35	-	3	14	30	G1/4"-F	11	3.5	17	29
	VPG40---IM18C	4	40	-	3.5	14	19	G1/8"-M	8	4	14	11.4
	VPG40---IF18C	5	40	-	3.5	14	29	G1/8"-F	9	4	14	12.4
	VPG40---IMM6V	3	40	-	3.5	14	-	M6-M	6	3.5	-	10
	VPG40---IM18V	4	40	-	3.5	14	18.5	G1/8"-M	6	3.5	13	16.6
	VPG40---IF18V	5	40	-	3.5	14	27	G1/8"-F	7.5	3.5	13	19.9
	VPG40---IM14V	4	40	-	3.5	14	19	G1/4"-M	8	3.5	17	25.9
	VPG40---IF14V	5	40	-	3.5	14	30	G1/4"-F	11	3.5	17	30.5
	VPG50---IM18C	4	50	-	4	15	20	G1/8"-M	8	4	14	16
	VPG50---IF18C	5	50	-	4	15	30	G1/8"-F	9	4	14	17.4
	VPG50---IMM6V	3	50	-	4	15	-	M6-M	6	3.5	-	18.6
	VPG50---IM18V	4	50	-	4	15	19.5	G1/8"-M	6	3.5	13	25.2
	VPG50---IF18V	5	50	-	4	15	28	G1/8"-F	7.5	3.5	13	28.5
	VPG50---IM14V	4	50	-	4	15	20	G1/4"-M	8	3.5	17	34.5
	VPG50---IF14V	5	50	-	4	15	31	G1/4"-F	11	3.5	17	39.1
Ø 60 - 95 mm	VPG60---	8	60	38	5	16	-	M10x125-F	-	-	-	25.4
	VPG60---IM14V	6	60	38	5	16	21	G1/4"-M	10	5	17	32.4
	VPG60---IF14V	7	60	38	5	16	33	G1/4"-F	10	5	17	33.7
	VPG60S---	8	60	38	5	16	-	G1/4"-F	-	-	-	25.4
	VPG80---	8	80	53	6	18	-	M10x125-F	-	-	-	53
	VPG80---IM14V	6	80	53	6	18	23	G1/4"-M	10	5	17	60
	VPG80---IF14V	7	80	53	6	18	35	G1/4"-F	10	5	17	61.3
	VPG80S---	8	80	53	6	18	-	G1/4"-F	-	-	-	53
	VPG95---	8	95	68	6	19	-	M10x125-F	-	-	-	93.2
	VPG95---IM14V	6	95	68	6	19	24	G1/4"-M	10	5	17	100.2
	VPG95---IF14V	7	95	68	6	19	36	G1/4"-F	10	5	17	101.5
	VPG95S---	8	95	68	6	19	-	G1/4"-F	-	-	-	93.2
Ø 120 - 200 mm	VPG120---IF12V	10	120	89.5	6	24.5	54.5	G1/2"-F	24	19	48	454.8
	VPG120---IFS12V	9	120	89.5	6	24.5	37.5	G1/2"-F	13	-	-	373.5
	VPG150---IF12V	10	150	105	9	30.5	60.5	G1/2"-F	24	19	48	624.8
	VPG150---IFS12V	9	150	105	9	30.5	43.5	G1/2"-F	13	-	-	543.5
	VPG200---IF12V	10	200	143	12.5	35.5	65.5	G1/2"-F	24	19	48	914.8
	VPG200---IFS12V	9	200	143	12.5	35.5	48.5	G1/2"-F	13	-	-	833.5

Note: All dimensions are in mm.



(1) f = Deflection of the suction cup. (2) Ø G2 = Ø internal orifice of the fitting.







#### VPG 2 - 10

Barbed fittings




#### VPG 15 - 20

Barbed fittings



Removable fittings



Configurations (suction cup + fitting) refer to page 2/10


Fittings and suction cups dimensions: see page 2/15 and 2/16.







#### VPG 25 - 50

Barbed fittings




Removable fittings




#### VPG 60 - 95

Removable fittings



#### VPG 120 - 200

Removable fittings



\*\* Female auxiliary radial output


- Configurations (suction cup + fitting) refer to page 2/10.
- Non-standard configurations must be ordered in separate part numbers.

Fittings and suction cups dimensions: see page 2/15 and 2/16.







#### VPG 2 - 10




#### VPG 15 - 50





#### VPG 60 - 95



#### VPG 120 - 200



(1) 4 holes Ø 9 on Ø 40

 (Ø)	ØA	H	Ød	ØD	f (1)	B	 (g)
VPG 2	2	4	2	4	0.5	2.5	0.03
VPG 3.5	3.5	4	2	4	0.5	2.5	0.04
VPG 5	5	6.5	4	7.5	0.8	4	0.16
VPG 6	6	6.5	4	7.5	0.8	4	0.17
VPG 8	8	7	4	8	1.2	4	0.23
VPG 10	10	7.5	4	8.7	1.5	4	0.3
VPG 15	15	8	4.5	12	1.9	2.5	0.7
VPG 20	20	10	4.5	15	2.3	4.5	1.5
VPG 25	25	14	6	16	3	7	2.8
VPG 30	30	12	6	15	2	7	3.3
VPG 35	35	14	6	20.5	3	7	5.8
VPG 40	40	14	6	23.5	3.5	7	7.3
VPG 50	50	15	8	29	4	7	11.1
VPG 60	60	16	M10x125-F	38	5	-	25.4
VPG 60S	60	16	G1/4"-F	38	5	-	25.4
VPG 80	80	18	M10x125-F	53	6	-	53
VPG 80S	80	18	G1/4"-F	53	6	-	53
VPG 95	95	19	M10x125-F	68	6	-	93.2
VPG 95S	95	19	G1/4"-F	68	6	-	93.2
VPG 120	120	24.5	14.5	89.5	6	-	230
VPG 150	150	30.5	13	105	9	-	400
VPG 200	200	35.5	13	143	12.5	-	690

The values represent the average characteristics of our products.  
Note: All dimensions are in mm.


(1) f = Deflection of the suction cup.






#### Barbed Fittings

##### Male - IM




##### Female - IF



	ØA	B	C	ØD	E ↻	Material	⚖ (g)
<b>IM 3 VPG2</b>	M3-M	3	2	1	5	Aluminum	0.18
<b>IM 5 VPG2</b>	M5-M	4.5	3.5	1	7	Aluminum	0.61
<b>IM 5 VPG5</b>	M5-M	4.5	3.5	2.2	7	Aluminum	0.7
<b>IM 18 VPG5</b>	G1/8"-M	8	5	2.2	14	Aluminum	3.9
<b>IM 18 VPG15</b>	G1/8"-M	8	5	2.2	14	Aluminum	4
<b>IM 18 VPG20</b>	G1/8"-M	8	5	3	14	Aluminum	4.06
<b>IM 18 VPG25</b>	G1/8"-M	8	5	4	14	Aluminum	4.08
<b>IM 18 VPG50</b>	G1/8"-M	8	5	4	14	Aluminum	4.9
<b>IF 5 VPG5</b>	M5-F	6	9	2.2	14	Aluminum	1.2
<b>IF 18 VPG5</b>	G1/8"-F	9	15	2.2	14	Aluminum	5.1
<b>IF 18 VPG15</b>	G1/8"-F	9	15	2.5	14	Aluminum	5.2
<b>IF 18 VPG20</b>	G1/8"-F	9	15	3	14	Aluminum	5.4
<b>IF 18 VPG25</b>	G1/8"-F	9	15	4	14	Aluminum	5.5
<b>IF 18 VPG50</b>	G1/8"-F	9	15	4	14	Aluminum	6.3


#### Hollow Screws




	ØA	B	C	ØD	Material	⚖ (g)
<b>IM 5 M15</b>	M5-M	5	2	2.5	Nickel-plated brass	1.3
<b>IM 5 M20</b>	M5-M	5	4	2.5	Nickel-plated brass	2.2
<b>IM 6 M25</b>	M6-M	6	6	3.5	Nickel-plated brass	2.7
<b>IM 6 M50</b>	M6-M	6	6	3.5	Nickel-plated brass	7.5

#### Adapters for Hollow Screws

##### Male - IM




##### Female - IF




	ØA	B	C	ØD	E ↻	Material	⚖ (g)
<b>IM 10 M6F</b>	M10-M	7	3.5	M6-F	13	Nickel-plated brass	5.9
<b>IM 14 M6F</b>	G1/4"-M	8	5	M6-F	17	Nickel-plated brass	15.9
<b>IM 18 M5F</b>	G1/8"-M	6	4.5	M5-F	13	Nickel-plated brass	7.3
<b>IM 18 M6F</b>	G1/8"-M	6	4.5	M6-F	13	Nickel-plated brass	6.6
<b>IF 14 M6F</b>	G1/4"-F	11	16	M6-F	17	Nickel-plated brass	20.5
<b>IF 18 M5F</b>	G1/8"-F	7.5	13	M5-F	13	Nickel-plated brass	10.5
<b>IF 18 M6F</b>	G1/8"-F	7.5	13	M6-F	13	Nickel-plated brass	9.9

#### Screwed


##### Male - IM




##### Female - IF



##### Female - IF 12120



##### Female - IFS 12120



(\*) 4 M8 holes at 90° on Ø40 (screws provided)

	ØA	B	C	ØD	E ↻	ØF	G	H	Material	⚖ (g)
<b>IM 14 M10M</b>	G1/4"-M	10	5	5	17	M10x125-M	-	-	Aluminum	7
<b>IF 14 M10M</b>	G1/4"-F	10	17	5	17	M10x125-M	-	-	Aluminum	8.3
<b>IF 12120</b>	G1/2"-F	24	30	19	48	G1/8"-F	8.7	60	Aluminum	224.8
<b>IFS 12120</b>	G1/2"-F	13	13	-	-	-	-	65	Aluminum	143.5

Note: All dimensions are in mm.






VPU series suction cups are suitable for gripping flat, smooth and rigid products.

### Materials

**NBR** Nitrile  
**SI** Translucent Silicone

**STN** Siton®

Industry-specific applications



Types of use



### Suction Cup Properties

	Ø (mm)	Volume (cm³)	Force (lbf) (1)	Force (lbf) (1)	R <sub>min</sub> (mm)	NBR	SI	STN
VPU 6	7	0.05	0.21	0.10	5	VPU6NBR	VPU6SI	VPU6STN
VPU 8	9	0.1	0.32	0.16	6	VPU8NBR	VPU8SI	VPU8STN
VPU 10	11	0.018	0.57	0.28	8	VPU10NBR	VPU10SI	VPU10STN
VPU 15	16.5	0.5	0.97	0.49	8	VPU15NBR	VPU15SI	VPU15STN
VPU 20	22	1	1.46	0.73	13	VPU20NBR	VPU20SI	VPU20STN
VPU 30	32	2	2.92	1.46	20	VPU30NBR	VPU30SI	VPU30STN
VPU 40	41	5.5	4.22	2.11	30	VPU40NBR	VPU40SI	VPU40STN
VPU 50	51.4	12	7.47	3.73	35	VPU50NBR	VPU50SI	VPU50STN

(1) Actual force of the suction cup in use with 65% vacuum and including a safety factor of 2 for horizontal handling and a factor of 4 for vertical handling.

### Choice of Fittings

(Ø)	M5-M	G1/8"-M	G1/4"-M
6...15	■	-	-
20...30	-	■	-
40...50	-	-	■

■ Standard available configurations (suction cup + fitting) Fittings: M = Male  
See part n° schedule as below

### Type of Assembly



**Version C: Barbed fitting**

### References - "Section Cup + Fitting"

Ø 6 - 15 mm	THREAD	<b>M5-M</b>	Ø 20 - 30 mm	THREAD	<b>G1/8"-M</b>
	VPU6NBR	VPU6NBRIMM5C		VPU20NBR	VPU20NBRIM18C
	VPU6SI	VPU6SIIMM5C		VPU20SI	VPU20SIIM18C
	VPU6STN	VPU6STNIMM5C		VPU20STN	VPU20STNIM18C
	VPU8NBR	VPU8NBRIMM5C		VPU30NBR	VPU30NBRIM18C
	VPU8SI	VPU8SIIMM5C		VPU30SI	VPU30SIIM18C
	VPU8STN	VPU8STNIMM5C		VPU30STN	VPU30STNIM18C
	VPU10NBR	VPU10NBRIMM5C			
	VPU10SI	VPU10SIIMM5C			
	VPU10STN	VPU10STNIMM5C			
	VPU15NBR	VPU15NBRIMM5C	Ø 40 - 50 mm	THREAD	<b>G1/4"-M</b>
	VPU15SI	VPU15SIIMM5C		VPU40NBR	VPU40NBRIM14C
	VPU15STN	VPU15STNIMM5C		VPU40SI	VPU40SIIM14C
				VPU40STN	VPU40STNIM14C
				VPU50NBR	VPU50NBRIM14C
				VPU50SI	VPU50SIIM14C
				VPU50STN	VPU50STNIM14C

### Accessories

To optimize use of your suction cups, Coval offers a comprehensive range of accessories (sensors, spring extensions, and feeder systems, etc.) see chapters 4 and 12.




Please specify the part n°. e.g. VPU20NBRIM18C  
See part n° table above






#### Suction Cups + Fittings

1 VPU 6 - 15



2 VPU 20 - 30



3 VPU 40 - 50





	Diagram	ØA	f <sup>(1)</sup>	H	H1	ØG	G1	ØG2 <sup>(2)</sup>	E ↺	⚖ (g)
VPU6---IMM5C	1	7	0.3	6.5	10	M5-M	4	1.5	7	1.8
VPU8---IMM5C	1	9	0.5	7	10.5	M5-M	4	1.5	7	1.9
VPU10---IMM5C	1	11	0.5	10.5	15	M5-M	4	2.7	7	1.3
VPU15---IMM5C	1	16.5	1.5	11.5	16	M5-M	4	2.7	7	1.6
VPU20---IM18C	2	22	2.5	8	11.5	G1/8"-M	7	4	14	4.2
VPU30---IM18C	2	32	3.5	9.5	13	G1/8"-M	7	4	14	4.9
VPU40---IM14C	3	41	4.5	13	19	G1/4"-M	9	5	17	11.3
VPU50---IM14C	3	51.4	6	17.5	23.5	G1/4"-M	9	5	21	22

Note: All dimensions are in mm.


(1) f = Deflection of the suction cup. (2) Ø G2 = Ø internal orifice of the fitting.

#### Assembly Diagrams




#### Suction Cups


VPU 6 - 15



VPU 20 - 30



VPU 40 - 50




	ØA	H	Ød	ØD	f <sup>(1)</sup>	B	⚖ (g)
VPU 6	7	6.5	2	5	0.3	3.5	0.12
VPU 8	9	7	2	5	0.5	3.5	0.15
VPU 10	11	10.5	3.8	9	0.5	3	0.51
VPU 15	16.5	11.5	3.8	8.3	1.5	3	0.75
VPU 20	22	8	5	14.5	2.5	4.5	1.2
VPU 30	32	9.5	5	14.5	3.5	4.5	1.9
VPU 40	41	13	6.5	20	4.5	6	5
VPU 50	51.4	17.5	10.5	27	6	8	12

Note: All dimensions are in mm. (1) f = Deflection of the suction cup.

The values represent the average characteristics of our products.

#### Barbed Fittings



	ØA	B	C	ØD	E ↺	Material	⚖ (g)
IMM5P1	M5-M	4	3.5	1.5	7	Brass	1.7
IMM5P2	M5-M	4	4.5	2.7	7	Aluminum	0.8
IM18P3	G1/8"-M	7	3.5	4	14	Aluminum	3
IM14P4	G1/4"-M	9	6	5	17	Aluminum	6.3
IM14P5	G1/4"-M	9	6	5	21	Aluminum	10




## Flat Suction Cups with Cleats Ø 15 to 50 mm



VPF series suction cups are suitable for gripping flat, smooth and rigid products. Cleats prevent the deformation of the product and provide excellent non-slip properties.

Industry-specific applications



Types of use



## Materials

**NBR** Nitrile  
**SIT5** Translucent Silicone

**STN** Siton®

## Suction Cup Properties

	Ø (mm)	(cm³)	(lbf) <sup>(1)</sup>	(lbf) <sup>(1)</sup>	R <sub>min</sub> (mm)	NBR	SI	STN
<b>VPF 15</b>	15.7	0.37	0.81	0.41	13	<b>VPF15NBR</b>	<b>VPF15SI</b>	<b>VPF15STN</b>
<b>VPF 20</b>	22	1.00	1.62	0.81	18	<b>VPF20NBR</b>	<b>VPF20SI</b>	<b>VPF20STN</b>
<b>VPF 25</b>	26.8	1.10	2.11	1.06	22	<b>VPF25NBR</b>	<b>VPF25SI</b>	<b>VPF25STN</b>
<b>VPF 30</b>	32	2.00	2.60	1.30	25	<b>VPF30NBR</b>	<b>VPF30SI</b>	<b>VPF30STN</b>
<b>VPF 40</b>	42.5	1.80	4.06	2.03	52	<b>VPF40NBR</b>	<b>VPF40SI</b>	<b>VPF40STN</b>
<b>VPF 50</b>	53	10.00	7.79	3.90	55	<b>VPF50NBR</b>	<b>VPF50SI</b>	<b>VPF50STN</b>

(1) Actual force of the suction cup in use with 65% vacuum and including a safety factor of 2 for horizontal handling and a factor of 4 for vertical handling.

## Choice of Fittings

(Ø)	M5-M	G1/8"-M	G1/4"-M
<b>15</b>	■	-	-
<b>20 - 30</b>	-	■	-
<b>40 - 50</b>	-	-	■

■ Standard available configurations (suction cup + fitting) Fittings: M = Male refer to n° table above

## Types of Assembly

**C** **Version C: Barbed fitting**

## References "Suction Cup + Fitting"

Ø 15 mm	THREAD	<b>M5-M</b>	Ø 20 - 30 mm	THREAD	<b>G1/8"-M</b>	Ø 40 - 50 mm	THREAD	<b>G1/4"-M</b>
	<b>VPF5NBR</b>	VPF15NBRIMM5C		<b>VPF20NBR</b>	VPF20NBRIM18C		<b>VPF40NBR</b>	VPF40NBRIM14C
	<b>VPF5SI</b>	VPF15SIIMM5C		<b>VPF20SI</b>	VPF20SIIM18C		<b>VPF40SI</b>	VPF40SIIM14C
	<b>VPF15STN</b>	VPF15STNIMM5C		<b>VPF20STN</b>	VPF20STNIM18C		<b>VPF40STN</b>	VPF40STNIM14C
				<b>VPF25NBR</b>	VPF25NBRIM18C		<b>VPF50NBR</b>	VPF50NBRIM14C
				<b>VPF25SI</b>	VPF25SIIM18C		<b>VPF50SI</b>	VPF50SIIM14C
				<b>VPF25STN</b>	VPF25STNIM18C		<b>VPF50STN</b>	VPF50STNIM14C
				<b>VPF30NBR</b>	VPF30NBRIM18C			
				<b>VPF30SI</b>	VPF30SIIM18C			
				<b>VPF30STN</b>	VPF30STNIM18C			

## Accessories

To optimize use of your suction cups, Coval offers a comprehensive range of accessories (sensors, spring extensions, and feeder systems, etc.) see chapters 4 and 12.



Please specify the part n°. e.g. VPF20NBRIM18C  
See part n° table above




## Flat Suction Cups with Cleats Ø 15 to 50 mm

### Assembly Diagrams




#### Suction Cup + Fitting

1 VPF 15



2 VPF 20...30



3 VPF 40...50





	Diagram	ØA	f <sup>(1)</sup>	H	H1	ØG	G1	ØG2 <sup>(2)</sup>	E ↗	⚖ (g)
VPF15---IMM5C	1	15.7	1	11	15.5	M5-M	4	2.7	7	1.5
VPF20---IM18C	2	22	1	8	11.5	G1/8"-M	7	4	14	4.2
VPF25---IM18C	2	26.8	1.3	9	12.5	G1/8"-M	7	4	14	4.7
VPF30---IM18C	2	32	1.8	10	13.5	G1/8"-M	7	4	14	5.2
VPF40---IM14C	3	42.5	1.9	13	19	G1/4"-M	9	5	17	11.9
VPF50---IM14C	3	53	2.4	17.5	23.5	G1/4"-M	9	5	21	22.7

Note: All dimensions are in mm.

(1) f = Deflection of the suction cup. (2) Ø G2 = Ø internal orifice of the fitting.

#### Assembly Diagrams






#### Suction Cups

VPF 15

VPF 20...30

VPF 40...50




	Ø A	H	Ø d	Ø D	f <sup>(1)</sup>	B	⚖ (g)
VPF 15	15.7	11	4	9	1	3	0.7
VPF 20	22	8	5	14.3	1	4.5	1.2
VPF 25	26.8	9	5	14.3	1.3	4.5	1.7
VPF 30	32	10	5	14.3	1.8	4.5	2.2
VPF 40	42.5	13	7	20	1.9	6	5.6
VPF 50	53	17.5	10.5	27	2.4	7.5	12.7

Note: All dimensions are in mm.

(1) f = Deflection of the suction cup.

The values represent the average characteristics of our products.

#### Barbed Male Fitting



	ØA	B	C	ØD	E ↗	Material	⚖ (g)
IMM5P2	M5-M	4	4.5	2.7	7	Aluminum	0.8
IM18P3	G1/8"-M	7	3.5	4	14	Aluminum	3
IM14P4	G1/4"-M	9	6	5	17	Aluminum	6.3
IM14P5	G1/4"-M	9	6	5	21	Aluminum	10



# VPO

## Oblong Flat Suction Cups




The VPO series of flat suction cups is used for handling oblong products, such as pens, tubes and bottles, and flat or cylindrical objects.

Materials

**NBR** Nitrile    **STN** Siton®    **SI** Silicone





Industry-specific applications



Types of use




### Suction Cup Properties

	I x L (mm)	 (cm³)	 (lbf) <sup>(1)</sup>	 R <sub>min</sub> (mm)	NBR	SI	STN
<b>VPO 24</b>	2x4	0.004	0.05	1	<b>VPO24NBR</b>	<b>VPO24SI</b>	<b>VPO24STN</b>
<b>VPO 357</b>	3.5x7	0.019	0.12	3	<b>VPO357NBR</b>	<b>VPO357SI</b>	<b>VPO357STN</b>
<b>VPO 515</b>	5x15	0.036	0.38	4	<b>VPO515NBR</b>	<b>VPO515SI</b>	<b>VPO515STN</b>
<b>VPO 618</b>	6x18	0.058	0.55	4	<b>VPO618NBR</b>	<b>VPO618SI</b>	<b>VPO618STN</b>
<b>VPO 824</b>	8x24	0.138	0.97	8	<b>VPO824NBR</b>	<b>VPO824SI</b>	<b>VPO824STN</b>
<b>VPO 1030</b>	10x30	0.28	1.49	8	<b>VPO1030NBR</b>	<b>VPO1030SI</b>	<b>VPO1030STN</b>
<b>VPO 1545</b>	15x45	0.98	3.43	10	<b>VPO1545NBR</b>	<b>VPO1545SI</b>	<b>VPO1545STN</b>
<b>VPO 2060</b>	20x60	2.3	6.10	20	<b>VPO2060NBR</b>	<b>VPO2060SI</b>	<b>VPO2060STN</b>
<b>VPO 2575</b>	25x75	4.7	9.53	30	<b>VPO2575NBR</b>	<b>VPO2575SI</b>	<b>VPO2575STN</b>
<b>VPO 3090</b>	30x90	8.5	13.72	35	<b>VPO3090NBR</b>	<b>VPO3090SI</b>	<b>VPO3090STN</b>

(1) Actual force of the suction cup with 65% vacuum and a safety factor of 2 included.

### Choice of Fittings

 (Ø)	M3-M	M5-M	M5-F	G1/8"-M	G1/8"-F	G1/4"-M	G1/4"-F
<b>24, 357</b>	■	-	-	-	-	-	-
<b>515, 618</b>	-	■	■	-	-	-	-
<b>824, 1030</b>	-	-	-	■	■	-	-
<b>1545... 3090</b>	-	-	-	-	-	■	■

Collar must be used from 8 x 24 upwards to prevent unintentional rotation when in use.

■ Standard available configurations (suction cup + fitting): refer to n° table above

Fitting: M = male





F = female

### Type of Assembly



Version C: Barbed fitting

### References - "Suction Cup + Fitting"

		
<b>2x4, 3.5x7</b>	THREAD	<b>M3-M</b>
	<b>VPO24NBR</b>	VPO24NBRIMM3C
	<b>VPO24SI</b>	VPO24SIIMM3C
	<b>VPO24STN</b>	VPO24STNIMM3C
	<b>VPO357NBR</b>	VPO357NBRIMM3C
	<b>VPO357SI</b>	VPO357SIIMM3C
	<b>VPO357STN</b>	VPO357STNIMM3C
		
<b>5x15 - 6x18</b>	THREAD	<b>M5-M</b> <b>M5-F</b>
	<b>VPO515NBR</b>	VPO515NBRIMM5C    VPO515NBRIFM5C
	<b>VPO515SI</b>	VPO515SIIMM5C    VPO515SIIFM5C
	<b>VPO515STN</b>	VPO515STNIMM5C    VPO515STNIFM5C
	<b>VPO618NBR</b>	VPO618NBRIMM5C    VPO618NBRIFM5C
	<b>VPO618SI</b>	VPO618SIIMM5C    VPO618SIIFM5C
	<b>VPO618STN</b>	VPO618STNIMM5C    VPO618STNIFM5C
		
<b>8x24 - 10x30</b>	THREAD	<b>G1/8"-M</b> <b>G1/8"-F</b>
	<b>VPO824NBR</b>	VPO824NBRIM18C    VPO824NBRIF18C
	<b>VPO824SI</b>	VPO824SIIM18C    VPO824SIIF18C
	<b>VPO824STN</b>	VPO824STNIM18C    VPO824STNIF18C
	<b>VPO1030NBR</b>	VPO1030NBRIM18C    VPO1030NBRIF18C
	<b>VPO1030SI</b>	VPO1030SIIM18C    VPO1030SIIF18C
	<b>VPO1030STN</b>	VPO1030STNIM18C    VPO1030STNIF18C
		
<b>15x45 - 30x90</b>	THREAD	<b>G1/4"-M</b> <b>G1/4"-F</b>
	<b>VPO1545NBR</b>	VPO1545NBRIM14C    VPO1545NBRIF14C
	<b>VPO1545SI</b>	VPO1545SIIM14C    VPO1545SIIF14C
	<b>VPO1545STN</b>	VPO1545STNIM14C    VPO1545STNIF14C
	<b>VPO2060NBR</b>	VPO2060NBRIM14C    VPO2060NBRIF14C
	<b>VPO2060SI</b>	VPO2060SIIM14C    VPO2060SIIF14C
	<b>VPO2060STN</b>	VPO2060STNIM14C    VPO2060STNIF14C
	<b>VPO2575NBR</b>	VPO2575NBRIM14C    VPO2575NBRIF14C
	<b>VPO2575SI</b>	VPO2575SIIM14C    VPO2575SIIF14C
	<b>VPO2575STN</b>	VPO2575STNIM14C    VPO2575STNIF14C
	<b>VPO3090NBR</b>	VPO3090NBRIM14C    VPO3090NBRIF14C
	<b>VPO3090SI</b>	VPO3090SIIM14C    VPO3090SIIF14C
	<b>VPO3090STN</b>	VPO3090STNIM14C    VPO3090STNIF14C


### Accessories

Anti-rotation spring system, see page 4/6





Please specify the part n°. e.g. VPO618NBRIFM5C  
See part n° table above







#### VPO 2x4 - 3.5x7

1




#### VPO 5x15 - 6x18

2





3




#### VPO 8x24 - 10x30

4





5



#### VPO 15x45 - 20x60 - 25x75 - 30x90

6



7





	Diagram	L	I	f <sup>(1)</sup>	H	H1	ØG	G1	ØG2 <sup>(2)</sup>	E ↘	⚖ (g)
VPO24---IMM3C	1	4	2	0.5	6	8	M3-M	3	1	5	0.4
VPO357---IMM3C	1	7	3.5	0.8	6	8	M3-M	3	1	5	0.3
VPO515---IMM5C	2	15	5	0.7	12	17	M5-M	5	2	8	1.8
VPO515---IFM5C	3	15	5	0.7	12	22	M5-F	8.5	2	8	1.8
VPO618---IMM5C	2	18	6	0.8	12	17	M5-M	5	2	8	1.8
VPO618---IFM5C	3	18	6	0.8	12	22	M5-F	8.5	2	8	1.8
VPO824---IM18C	4	24	8	1	12	17	G1/8"-M	8	3.5	14	6.6
VPO824---IF18C	5	24	8	1	12	25	G1/8"-F	9	3.5	14	7.3
VPO1030---IM18C	4	30	10	1.5	12	17	G1/8"-M	8	3.5	14	6.8
VPO1030---IF18C	5	30	10	1.5	12	25	G1/8"-F	9	3.5	14	7.5
VPO1545---IM14C	6	45	15	2	21	26	G1/4"-M	10	3.5	17	16.5
VPO1545---IF14C	7	45	15	2	21	36	G1/4"-F	12	3.5	17	16.5
VPO2060---IM14C	6	60	20	2.5	21	26	G1/4"-M	10	3.5	17	19.7
VPO2060---IF14C	7	60	20	2.5	21	36	G1/4"-F	12	3.5	17	19.7
VPO2575---IM14C	6	75	25	2.8	21	26	G1/4"-M	10	3.5	17	27.9
VPO2575---IF14C	7	75	25	2.8	21	36	G1/4"-F	12	3.5	17	27.9
VPO3090---IM14C	6	90	30	3.5	21	26	G1/4"-M	10	3.5	17	36.3
VPO3090---IF14C	7	90	30	3.5	21	36	G1/4"-F	12	3.5	17	36.3

Note: All dimensions are in mm.

(1) f = Deflection of the suction cup.



(2) Ø G2 = Ø internal orifice of the fitting.






#### VPO 24 - 357

Barbed fittings





#### VPO 515 - 618

Barbed fittings





#### VPO 824 - 1030

Barbed fittings




#### VPO 1545 - 2060 - 2575 - 3090

Barbed fittings









#### Dimensions Suction Cups


##### VP0 24 - 357




##### VP0 515 - 618





##### VP0 824 - 1030



##### VP0 1545 - 2060 - 2575 - 3090




#### Suction Cups

	L	l	Ø d	H	f (1)	 (g)
VP024	4	2	0.7	6	0.5	0.12
VP0357	7	3.5	1	6	0.8	0.15
VP0515	15	5	1.2	12	0.7	0.51
VP0618	18	6	1.5	12	0.8	0.53
VP0824	24	8	1.5	12	1	1.1
VP01030	30	10	2.5	12	1.5	1.3
VP01545	45	15	3	21	2	4.1
VP02060	60	20	4	21	2.5	7.3
VP02575	75	25	4	21	2.8	15.5
VP03090	90	30	4	21	3.5	23.9


(1) f = Deflection of the suction cup.

#### Barbed Fitting


##### Male - IM





##### Female - IF



##### Collar



	ØA	B	C	ØD	E 	j	Material	 (g)
IM3VP024	M3-M	3	2	1	5	-	Aluminum	0.2
IM5VP0515	M5-M	5	5	2	8	-	Aluminum	1.3
IM18VP0824	G1/8"-M	8	5	3.5	14	-	Aluminum	3.9
IM14VP01545	G1/4"-M	10	5	3.5	17	-	Aluminum	9.7
IF5VP0515	M5-F	8.5	10	2	8	-	Aluminum	1.3
IF18VP0824	G1/8"-F	9	13	3.5	14	-	Aluminum	4.6
IF14VP01545	G1/4"-F	12	15	3.5	17	-	Aluminum	9.7
VP0 COV18	-	-	-	-	-	4	Aluminum	1.6
VP0 COV14	-	-	-	-	-	4	Aluminum	2.7

The values represent the average characteristics of our products.  
Note: All dimensions are in mm.


(1) f = Deflection of the suction cup.






VSA series suction cups with bellows combine the advantages of flat suction cups with increased deflection, flexibility and precision. Used for gripping slightly concave or convex objects.

Industry-specific applications



Types of use








■ Flexibility ■ Precision ■ Deflection  
For delicate gripping requiring a very flexible lip (opening bags, gripping tins and flexible aluminum or plastic bottles, etc.), we recommend using 35 Shore A white silicone, SIB. For larger diameters, see page 3/9, MVS series.

### Materials

<b>NBR</b>	Nitrile	<b>SIT5</b>	Translucent silicone
<b>NR</b>	Natural rubber	<b>SIB</b>	35 shore A white silicone
<b>STN</b>	Siton® 60 ShoreA	<b>STN5</b>	Siton® 50 ShoreA (on request)


### Suction Cup Properties

	Ø (mm)	 (cm³)	 (lbf) <sup>(1)</sup>	 (lbf) <sup>(1)</sup>	 <sub>min</sub> (mm)	NBR	SIT5	SIB	NR	STN <sup>(2)</sup>
VSA 5	5.5	0.04	0.11	0.06	10	VSA5NBR	VSA5SIT5	-	-	VSA5STN
VSA 11	11	0.225	0.39	0.19	10	VSA11NBR	VSA11SIT5	-	-	VSA11STN
VSA 14	13	0.42	0.57	0.28	13	VSA14NBR	VSA14SIT5	-	-	VSA14STN
VSA 16	16	0.75	0.60	0.30	20	VSA16NBR	VSA16SIT5	VSA16SIB	VSA16NR	VSA16STN
VSA 18	18	0.76	0.99	0.50	25	VSA18NBR	VSA18SIT5	VSA18SIB	VSA18NR	VSA18STN
VSA 20	19	1.15	1.25	0.63	30	VSA20NBR	VSA20SIT5	VSA20SIB	VSA20NR	VSA20STN
VSA 22	22	1.4	1.38	0.69	25	VSA22NBR	VSA22SIT5	VSA22SIB	VSA22NR	VSA22STN
VSA 25	24	3.15	1.79	0.89	20	VSA25NBR	VSA25SIT5	VSA25SIB	VSA25NR	VSA25STN
VSA 26	25	3.9	2.44	1.22	30	VSA26NBR	VSA26SIT5	-	VSA26NR	VSA26STN
VSA 33	33	4.75	3.12	1.56	40	VSA33NBR	VSA33SIT5	-	VSA33NR	VSA33STN
VSA 43	43	9.25	4.55	2.27	60	VSA43NBR	VSA43SIT5	-	VSA43NR	VSA43STN
VSA 53	53	26.25	9.58	4.79	75	VSA53NBR	VSA53SIT5	-	VSA53NR	VSA53STN
VSA 63	63	39.0	13.31	6.66	75	VSA63NBR	VSA63SIT5	-	VSA63NR	VSA63STN
VSA 78	78	76.0	24.68	12.34	70	VSA78NBR	VSA78SIT5	-	VSA78NR	VSA78STN

(1) Actual force of the suction cup in use with 65% vacuum and including a safety factor of 2 for horizontal handling and a factor of 4 for vertical handling.

(2) On request, some models are available in STN5 (Siton® 50 shore A)

### Choice of Fittings

 (Ø)	Group	M3-M	M5-M	M6-M	M8-M	M10-M	G1/8"-F	G1/8"-M	10/32-M	G1/4"-F	G1/4"-M	G3/8"-M	G1/2"-M
5	1	■	-	-	-	-	-	-	-	-	-	-	-
11...25	1	-	■	■	-	-	■	■	□	-	-	-	-
26...63	2	-	□	□	□	□	■	■	-	■	■	-	-
78	3	-	-	-	-	□	-	■	-	■	■	□	□

■ Standard available configurations (suction cup + fitting): see page 2/26

□ Additional mounting configurations: see page 2/29 Fitting: M = male F = female

### Types of Assembly

COVAL suction cups can be assembled in a wide variety of configurations.

**C**  **Version C**  
Barbed fitting


**S**  **Version S**  
Factory-crimped fitting

**V**  **Version V**  
Removable fitting:  
(adapter and hollow screw)

**E**  **Version E**  
Pressed fitting

### Textured Surfaces

For handling objects with a granular or textured gripping surface, use VSA suction cups with the VSBM foam strip option (see page 2/59).




### Accessories




To optimize the use of your suction cups, Coval offers a comprehensive range of accessories (nozzle fittings, spring extensions, and feeder systems, etc.), see chapters 4 and 12.



 Please specify the part n°. e.g. VSA78NBRIM14C  
Refer to page 2/26





Group 1		C 				
Ø 5 - 25 mm	THREAD	M3-M	M5-M	M6-M	G1/8"-M	G1/8"-F
	VSA5NBR	VSA5NBRIMM3C	-	-	-	-
	VSA5SIT5	VSA5SIT5IMM3C	-	-	-	-
	VSA5STN	VSA5STNIMM3C	-	-	-	-
	VSA11NBR	-	VSA11NBRIMM5C	VSA11NBRIMM6C	VSA11NBRIM18C	VSA11NBRIF18C
	VSA11NR	-	VSA11NRIMM5C	VSA11NRIMM6C	VSA11NRIM18C	VSA11NRIF18C
	VSA11SIT5	-	VSA11SIT5IMM5C	VSA11SIT5IMM6C	VSA11SIT5IM18C	VSA11SIT5IF18C
	VSA11STN	-	VSA11STNIMM5C	VSA11STNIMM6C	VSA11STNIM18C	VSA11STNIF18C
	VSA14NBR	-	VSA14NBRIMM5C	VSA14NBRIMM6C	VSA14NBRIM18C	VSA14NBRIF18C
	VSA14NR	-	VSA14NRIMM5C	VSA14NRIMM6C	VSA14NRIM18C	VSA14NRIF18C
	VSA14SIT5	-	VSA14SIT5IMM5C	VSA14SIT5IMM6C	VSA14SIT5IM18C	VSA14SIT5IF18C
	VSA14STN	-	VSA14STNIMM5C	VSA14STNIMM6C	VSA14STNIM18C	VSA14STNIF18C
	VSA16NBR	-	VSA16NBRIMM5C	VSA16NBRIMM6C	VSA16NBRIM18C	VSA16NBRIF18C
	VSA16NR	-	VSA16NRIMM5C	VSA16NRIMM6C	VSA16NRIM18C	VSA16NRIF18C
	VSA16SIB	-	VSA16SIBIMM5C	VSA16SIBIMM6C	VSA16SIBIM18C	VSA16SIBIF18C
	VSA16SIT5	-	VSA16SIT5IMM5C	VSA16SIT5IMM6C	VSA16SIT5IM18C	VSA16SIT5IF18C
	VSA16STN	-	VSA16STNIMM5C	VSA16STNIMM6C	VSA16STNIM18C	VSA16STNIF18C
	VSA18NBR	-	VSA18NBRIMM5C	VSA18NBRIMM6C	VSA18NBRIM18C	VSA18NBRIF18C
	VSA18NR	-	VSA18NRIMM5C	VSA18NRIMM6C	VSA18NRIM18C	VSA18NRIF18C
	VSA18SIB	-	VSA18SIBIMM5C	VSA18SIBIMM6C	VSA18SIBIM18C	VSA18SIBIF18C
	VSA18SIT5	-	VSA18SIT5IMM5C	VSA18SIT5IMM6C	VSA18SIT5IM18C	VSA18SIT5IF18C
	VSA18STN	-	VSA18STNIMM5C	VSA18STNIMM6C	VSA18STNIM18C	VSA18STNIF18C
	VSA20NBR	-	VSA20NBRIMM5C	VSA20NBRIMM6C	VSA20NBRIM18C	VSA20NBRIF18C
	VSA20NR	-	VSA20NRIMM5C	VSA20NRIMM6C	VSA20NRIM18C	VSA20NRIF18C
	VSA20SIB	-	VSA20SIBIMM5C	VSA20SIBIMM6C	VSA20SIBIM18C	VSA20SIBIF18C
	VSA20SIT5	-	VSA20SIT5IMM5C	VSA20SIT5IMM6C	VSA20SIT5IM18C	VSA20SIT5IF18C
	VSA20STN	-	VSA20STNIMM5C	VSA20STNIMM6C	VSA20STNIM18C	VSA20STNIF18C
	VSA22NBR	-	VSA22NBRIMM5C	VSA22NBRIMM6C	VSA22NBRIM18C	VSA22NBRIF18C
	VSA22NR	-	VSA22NRIMM5C	VSA22NRIMM6C	VSA22NRIM18C	VSA22NRIF18C
	VSA22SIB	-	VSA22SIBIMM5C	VSA22SIBIMM6C	VSA22SIBIM18C	VSA22SIBIF18C
	VSA22SIT5	-	VSA22SIT5IMM5C	VSA22SIT5IMM6C	VSA22SIT5IM18C	VSA22SIT5IF18C
	VSA22STN	-	VSA22STNIMM5C	VSA22STNIMM6C	VSA22STNIM18C	VSA22STNIF18C
	VSA25NBR	-	VSA25NBRIMM5C	VSA25NBRIMM6C	VSA25NBRIM18C	VSA25NBRIF18C
	VSA25NR	-	VSA25NRIMM5C	VSA25NRIMM6C	VSA25NRIM18C	VSA25NRIF18C
	VSA25SIB	-	VSA25SIBIMM5C	VSA25SIBIMM6C	VSA25SIBIM18C	VSA25SIBIF18C
	VSA25SIT5	-	VSA25SIT5IMM5C	VSA25SIT5IMM6C	VSA25SIT5IM18C	VSA25SIT5IF18C
	VSA25STN	-	VSA25STNIMM5C	VSA25STNIMM6C	VSA25STNIM18C	VSA25STNIF18C

Group 2									
Ø 26 - 63 mm	THREAD	G1/4"-M	G1/4"-F	G1/4"-M	G1/4"-F	G1/8"-M	G1/8"-F	G1/4"-M	G1/4"-F
	VSA26NBR	VSA26NBRIM14C	VSA26NBRIF14C	VSA26NBRIM14	VSA26NBRIF14	VSA26NBRIM18V	VSA26NBRIF18V	VSA26NBRIM14V	VSA26NBRIF14V
	VSA26NR	VSA26NRIM14C	VSA26NRIF14C	VSA26NRIM14	VSA26NRIF14	VSA26NRIM18V	VSA26NRIF18V	VSA26NRIM14V	VSA26NRIF14V
	VSA26SIT5	VSA26SIT5IM14C	VSA26SIT5IF14C	VSA26SIT5IM14	VSA26SIT5IF14	VSA26SIT5IM18V	VSA26SIT5IF18V	VSA26SIT5IM14V	VSA26SIT5IF14V
	VSA26STN	VSA26STNIM14C	VSA26STNIF14C	VSA26STNIM14	VSA26STNIF14	VSA26STNIM18V	VSA26STNIF18V	VSA26STNIM14V	VSA26STNIF14V
	VSA33NBR	VSA33NBRIM14C	VSA33NBRIF14C	VSA33NBRIM14	VSA33NBRIF14	VSA33NBRIM18V	VSA33NBRIF18V	VSA33NBRIM14V	VSA33NBRIF14V
	VSA33NR	VSA33NRIM14C	VSA33NRIF14C	VSA33NRIM14	VSA33NRIF14	VSA33NRIM18V	VSA33NRIF18V	VSA33NRIM14V	VSA33NRIF14V
	VSA33SIT5	VSA33SIT5IM14C	VSA33SIT5IF14C	VSA33SIT5IM14	VSA33SIT5IF14	VSA33SIT5IM18V	VSA33SIT5IF18V	VSA33SIT5IM14V	VSA33SIT5IF14V
	VSA33STN	VSA33STNIM14C	VSA33STNIF14C	VSA33STNIM14	VSA33STNIF14	VSA33STNIM18V	VSA33STNIF18V	VSA33STNIM14V	VSA33STNIF14V
	VSA43NBR	VSA43NBRIM14C	VSA43NBRIF14C	VSA43NBRIM14	VSA43NBRIF14	VSA43NBRIM18V	VSA43NBRIF18V	VSA43NBRIM14V	VSA43NBRIF14V
	VSA43NR	VSA43NRIM14C	VSA43NRIF14C	VSA43NRIM14	VSA43NRIF14	VSA43NRIM18V	VSA43NRIF18V	VSA43NRIM14V	VSA43NRIF14V
	VSA43SIT5	VSA43SIT5IM14C	VSA43SIT5IF14C	VSA43SIT5IM14	VSA43SIT5IF14	VSA43SIT5IM18V	VSA43SIT5IF18V	VSA43SIT5IM14V	VSA43SIT5IF14V
	VSA43STN	VSA43STNIM14C	VSA43STNIF14C	VSA43STNIM14	VSA43STNIF14	VSA43STNIM18V	VSA43STNIF18V	VSA43STNIM14V	VSA43STNIF14V
	VSA53NBR	VSA53NBRIM14C	VSA53NBRIF14C	VSA53NBRIM14	VSA53NBRIF14	VSA53NBRIM18V	VSA53NBRIF18V	VSA53NBRIM14V	VSA53NBRIF14V
	VSA53NR	VSA53NRIM14C	VSA53NRIF14C	VSA53NRIM14	VSA53NRIF14	VSA53NRIM18V	VSA53NRIF18V	VSA53NRIM14V	VSA53NRIF14V
	VSA53SIT5	VSA53SIT5IM14C	VSA53SIT5IF14C	VSA53SIT5IM14	VSA53SIT5IF14	VSA53SIT5IM18V	VSA53SIT5IF18V	VSA53SIT5IM14V	VSA53SIT5IF14V
	VSA53STN	VSA53STNIM14C	VSA53STNIF14C	VSA53STNIM14	VSA53STNIF14	VSA53STNIM18V	VSA53STNIF18V	VSA53STNIM14V	VSA53STNIF14V
	VSA63NBR	VSA63NBRIM14C	VSA63NBRIF14C	VSA63NBRIM14	VSA63NBRIF14	VSA63NBRIM18V	VSA63NBRIF18V	VSA63NBRIM14V	VSA63NBRIF14V
	VSA63NR	VSA63NRIM14C	VSA63NRIF14C	VSA63NRIM14	VSA63NRIF14	VSA63NRIM18V	VSA63NRIF18V	VSA63NRIM14V	VSA63NRIF14V
	VSA63SIT	VSA63SITIM14C	VSA63SITIF14C	VSA63SITIM14	VSA63SITIF14	VSA63SITIM18V	VSA63SITIF18V	VSA63SITIM14V	VSA63SITIF14V
	VSA63STN	VSA63STNIM14C	VSA63STNIF14C	VSA63STNIM14	VSA63STNIF14	VSA63STNIM18V	VSA63STNIF18V	VSA63STNIM14V	VSA63STNIF14V

Group 3		V 			S 		Additional mounting configurations are available (see page 2/29). For standard configurations (suction cup+fitting), the C and V versions are delivered unassembled.
Ø 78 mm	THREAD	G1/8"-M	G1/4"-M	G1/4"-F	G1/4"-M	G1/4"-F	
	VSA78NBR	VSA78NBRIM18V	VSA78NBRIM14V	VSA78NBRIF14V	VSA78NBRIM14	VSA78NBRIF14	
	VSA78NR	VSA78NRIM18V	VSA78NRIM14V	VSA78NRIF14V	VSA78NRIM14	VSA78NRIF14	
	VSA78SIT5	VSA78SIT5IM18V	VSA78SIT5IM14V	VSA78SIT5IF14V	VSA78SIT5IM14	VSA78SIT5IF14	
	VSA78STN	VSA78STNIM18V	VSA78STNIM14V	VSA78STNIF14V	VSA78STNIM14	VSA78STNIF14	




## Suction Cups with 1.5 Bellows Ø 5 to 78 mm



Dimensions - "Suction Cup + Fitting"





### VSA 5 Group 1






### VSA 11 - 25 Group 1





### VSA 26 - 43 Group 2



### VSA 53 - 63 Group 2 / VSA 78 Group 3





Group 1		Diagram	ØA	Øa	ØD	f <sup>(1)</sup>	H	H1	ØG	G1	ØG2 <sup>(2)</sup>	E 	 (g)
Ø 5 - 25 mm	VSA5---IMM3C	1	5.5	6	-	2	11	13	M3-M	3	1.4	5	0.7
	VSA11---IMM5C	2	11	12.2	-	5.5	16	21	M5-M	4.5	2.5	7	4
	VSA11---IMM6C	2	11	12.2	-	5.5	16	21	M6-M	5	3.5	7	3.6
	VSA11---IM18C	2	11	12.2	-	5.5	16	22	G1/8"-M	7.5	3.5	14	5
	VSA11---IF18C	3	11	12.2	-	5.5	16	28	G1/8"-F	8	3.5	14	4.9
	VSA14---IMM5C	2	13	14	-	5	16	21	M5-M	4.5	2.5	7	4.2
	VSA14---IMM6C	2	13	14	-	5	16	21	M6-M	5	3.5	7	3.8
	VSA14---IM18C	2	13	14	-	5	16	22	G1/8"-M	7.5	3.5	14	5.2
	VSA14---IF18C	3	13	14	-	5	16	28	G1/8"-F	8	3.5	14	5.1
	VSA16---IMM5C	2	16	17.3	-	8.5	19	24	M5-M	4.5	2.5	7	4.4
	VSA16---IMM6C	2	16	17.3	-	8.5	19	24	M6-M	5	3.5	7	4
	VSA16---IM18C	2	16	17.3	-	8.5	19	25	G1/8"-M	7.5	3.5	14	5.4
	VSA16---IF18C	3	16	17.3	-	8.5	19	31	G1/8"-F	8	3.5	14	5.3
	VSA18---IMM5C	2	18	18	-	5	16.5	21.5	M5-M	4.5	2.5	7	4.6
	VSA18---IMM6C	2	18	18	-	5	16.5	21.5	M6-M	5	3.5	7	4.2
	VSA18---IM18C	2	18	18	-	5	16.5	22.5	G1/8"-M	7.5	3.5	14	5.6
	VSA18---IF18C	3	18	18	-	5	16.5	28.5	G1/8"-F	8	3.5	14	5.5
	VSA20---IMM5C	2	19	20	-	5	16	21	M5-M	4.5	2.5	7	4.8
	VSA20---IMM6C	2	19	20	-	5	16	21	M6-M	5	3.5	7	5.8
	VSA20---IM18C	2	19	20	-	5	16	22	G1/8"-M	7.5	3.5	14	5.8
	VSA20---IF18C	3	19	20	-	5	16	28	G1/8"-F	8	3.5	14	5.7
	VSA22---IMM5C	2	22	24	-	8	19	24	M5-M	4.5	2.5	7	5.2
	VSA22---IMM6C	2	22	24	-	8	19	24	M6-M	5	3.5	7	4.8
	VSA22---IM18C	2	22	24	-	8	19	25	G1/8"-M	7.5	3.5	14	6.2
	VSA22---IF18C	3	22	24	-	8	19	31	G1/8"-F	8	3.5	14	6.1
	VSA25---IMM5C	2	24	25	-	12	23	28	M5-M	4.5	2.5	7	6
	VSA25---IMM6C	2	24	25	-	12	23	28	M6-M	5	3.5	7	5.8
	VSA25---IM18C	2	24	25	-	12	23	29	G1/8"-M	7.5	3.5	14	7
	VSA25---IF18C	3	24	25	-	12	23	35	G1/8"-F	8	3.5	14	6.9

Note: All dimensions are in mm.

(1) f = Deflection of the suction cup. (2) Ø G2 = Ø internal orifice of the fitting.





Group 2		Diagram	ØA	Øa	ØD	f <sup>(1)</sup>	H	H1	ØG	G1	ØG2 <sup>(2)</sup>	E 	 (g)
Ø 26 - 63 mm	VSA26---IM18V	4	25	30	-	6	25	29.5	G1/8"-M	6	3.5	13	18.7
	VSA26---IF18V	5	25	30	-	6	25	38	G1/8"-F	7.5	3.5	13	22
	VSA26---IM14	4	25	30	-	6	25	29	G1/4"-M	11	4.4	17	12.4
	VSA26---IM14C	4	25	30	-	6	25	33	G1/4"-M	10	7	17	13.3
	VSA26---IM14V	4	25	30	-	6	25	30	G1/4"-M	8	3.5	17	28
	VSA26---IF14	5	25	30	-	6	25	40	G1/4"-F	10	4.4	17	13
	VSA26---IF14C	5	25	30	-	6	25	40	G1/4"-F	12	6.9	17	12.6
	VSA26---IF14V	5	25	30	-	6	25	41	G1/4"-F	11	3.5	17	32.6
	VSA33---IM18V	4	33	36.2	-	11	27.5	32	G1/8"-M	6	3.5	13	21.1
	VSA33---IF18V	5	33	36.2	-	11	27.5	40.5	G1/8"-F	7.5	3.5	13	24.4
	VSA33---IM14	4	33	36.2	-	11	27.5	31.5	G1/4"-M	11	4.4	17	14.8
	VSA33---IM14C	4	33	36.2	-	11	27.5	35.5	G1/4"-M	10	7	17	15.7
	VSA33---IM14V	4	33	36.2	-	11	27.5	32.5	G1/4"-M	8	3.5	17	30.4
	VSA33---IF14	5	33	36.2	-	11	27.5	42.5	G1/4"-F	10	4.4	17	15.4
	VSA33---IF14C	5	33	36.2	-	11	27.5	42.5	G1/4"-F	12	6.9	17	15
	VSA33---IF14V	5	33	36.2	-	11	27.5	43.5	G1/4"-F	11	3.5	17	35
	VSA43---IM18V	4	43	46	-	12.5	28	32.5	G1/8"-M	6	3.5	13	25.9
	VSA43---IF18V	5	43	46	-	12.5	28	41	G1/8"-F	7.5	3.5	13	29.2
	VSA43---IM14	4	43	46	-	12.5	28	32	G1/4"-M	11	4.4	17	19.6
	VSA43---IM14C	4	43	46	-	12.5	28	36	G1/4"-M	10	7	17	20.5
	VSA43---IM14V	4	43	46	-	12.5	28	33	G1/4"-M	8	3.5	17	35.2
	VSA43---IF14	5	43	46	-	12.5	28	43	G1/4"-F	10	4.4	17	20.2
	VSA43---IF14C	5	43	46	-	12.5	28	43	G1/4"-F	12	6.9	17	19.8
	VSA43---IF14V	5	43	46	-	12.5	28	44	G1/4"-F	11	3.5	17	39.8
	VSA53---IM18V	6	53	59	-	15	34	38.5	G1/8"-M	6	3.5	13	35
	VSA53---IF18V	7	53	59	-	15	34	47	G1/8"-F	7.5	3.5	13	38.3
	VSA53---IM14	6	53	59	-	15	34	38	G1/4"-M	11	4.4	17	28.7
	VSA53---IM14C	6	53	59	-	15	34	42	G1/4"-M	10	7	17	29.6
	VSA53---IM14V	6	53	59	-	15	34	39	G1/4"-M	8	3.5	17	44.3
	VSA53---IF14	7	53	59	-	15	34	49	G1/4"-F	10	4.4	17	29.3
	VSA53---IF14C	7	53	59	-	15	34	49	G1/4"-F	12	6.9	17	28.9
	VSA53---IF14V	7	53	59	-	15	34	50	G1/4"-F	11	3.5	17	48.9
	VSA63---IM18V	6	63	67	-	15	34	38.5	G1/8"-M	6	3.5	13	39.1
	VSA63---IF18V	7	63	67	-	15	34	47	G1/8"-F	7.5	3.5	13	42.4
	VSA63---IM14	6	63	67	-	15	34	38	G1/4"-M	11	4.4	17	32.8
	VSA63---IM14C	6	63	67	-	15	34	42	G1/4"-M	10	7	17	33.7
VSA63---IM14V	6	63	67	-	15	34	39	G1/4"-M	8	3.5	17	48.4	
VSA63---IF14	7	63	67	-	15	34	49	G1/4"-F	10	4.4	17	33.4	
VSA63---IF14C	7	63	67	-	15	34	49	G1/4"-F	12	6.9	17	33	
VSA63---IF14V	7	63	67	-	15	34	50	G1/4"-F	11	3.5	17	53	

#### Group 3

Ø 78 mm	VSA78---IM18V	8	78	83	25	14	46.8	-	G1/8"-M	8	6	-	85.4
	VSA78---IM14	6	78	83	-	14	46.8	52.8	G1/4"-M	11	8	21	70.2
	VSA78---IM14V	6	78	83	-	14	46.8	51.8	G1/4"-M	8	6	17	92.7
	VSA78---IF14	7	78	83	-	14	46.8	61.8	G1/4"-F	10	8	21	74.1
	VSA78---IF14V	7	78	83	-	14	46.8	65.8	G1/4"-F	9	6	17	102.3

Note: All dimensions are in mm.

(1) f = Deflection of the suction cup. (2) Ø G2 = Ø internal orifice of the fitting.







2

VSA



#### VSA 5 - 25 Group 1

Barbed fittings




#### VSA 26 - 63 Group 2


Barbed fittings



Pressed fittings




Removable fittings




#### VSA 78 Group 3

Factory-criped fittings



Removable fittings



- Configurations (suction cup + fitting) refer to pages 2/26
- Non-standard configurations must be ordered in separate part numbers.


Fittings and suction cups dimension: see page 2/30.






### Suction Cups


VSA 5



VSA 11 - 25




VSA 26 - 78




### Pressed Fittings

Male - IM




Female - IF




	ØA	B	C	ØD	E	Material	(g)
IM41	G1/4"-M	11	4	4.4	17	Aluminum	7.8
IF40	G1/4"-F	10	15	4.4	17	Aluminum	8.4

### Factory-Crimped Fittings

Male - IM




Female - IF



	ØA	B	C	ØD	E	Material	(g)
IM 51	G1/4"-M	11	6	4.4	17	Aluminum	11.8
IF 50	G1/4"-F	10	15	8	21	Aluminum	15.7
IM 52	G3/8"-M	11	6	8	21	Aluminum	14

### Hollow Screws



	ØA	B	C	ØD	Material	(g)
IM 50	M5-M	5	11	2.8	Brass	7.4
IM 60 (2) (3)	M6-M	7	11	3.5	Nickel-plated brass	7.5
IM 68	M8-M	8	11	5.2	Nickel-plated brass	6.4
IM 80	G1/8"-M	8	18	6	Nickel-plated brass	23.7
IM 85	M10x150-M	8	18	6	Nickel-plated brass	23.5

The values represent the average characteristics of our products.

(2) Flow restrictor version available: orifice calibrated to reduce leaks when used with a multi-cup gripper (see page 4/9)


(3) Available in stainless steel

	Ø A	H	Ø a	Ø d	Ø D	f <sup>(1)</sup>	B	(g)
VSA 5	5.5	11	6	4	7	2	7	0.3
VSA 11	11	16	12.2	4	10	5.5	9	0.9
VSA 14	13	16	14	4	10	5	9	1.1
VSA 16	16	19	17.3	4	10	8.5	9	1.3
VSA 18	18	16.5	18	4	10	5	9	1.5
VSA 20	19	16	20	4	10	5	9	1.7
VSA 22	22	19	24	4	10	8	9	2.1
VSA 25	24	23	25	4	10	12	9	2.9
VSA 26	25	25	30	8	16	6	13	4.6
VSA 33	33	27.5	36.2	8	18	11	13	7
VSA 43	43	28	46	8	18	12.5	13	11.8
VSA 53	53	34	59	8	18	15	13	20.9
VSA 63	63	34	67	8	18	15	13	25
VSA 78	78	46.8	83	12	25	14	20	58.4


(1) f = Deflection of the suction cup.

### Barbed Fittings

Male - IM




Female - IF




	ØA	B	C	ØD	E	Material	(g)
IM 11 A	G1/8"-M	7.5	6	3.5	14	Aluminum	4.1
IMC 14	G1/4"-M	10	8	7	17	Aluminum	8.7
IM20	M3-M	3	2	1.4	5	Aluminum	0.4
IM 21 (2)	M5-M	4.5	5	2.5	7	Nickel-plated brass	3.1
IM 22 (2)	M6-M	5	5	3.5	7	Nickel-plated brass	2.7
IM 23	10/32-M	4.5	5	2.5	7	Brass	3
IM 24	M5-M	4.5	2.5	2.5	10	Nickel-plated brass	3.2
IF 10 A	G1/8"-F	8	12	3.5	14	Aluminum	4
IFC 14	G1/4"-F	12	15	6.9	17	Aluminum	8

### Adapters for Hollow Screws

Male - IM



Female - IF



	ØA	B	C	ØD	E	Material	(g)
IM 10 M6F	M10-M	7	3.5	M6-F	13	Brass	5.9
IM 12 F18	G1/2"-M	14	6	M6-F	22	Nickel-plated brass	46.5
IM 14 M6F	G1/4"-M	8	5	M6-F	17	Nickel-plated brass	15.9
IM 14 F18	G1/4"-M	8	5	G1/8"-F	17	Nickel-plated brass	10.6
IM 18 M6F	G1/8"-M	6	4.5	M6-F	13	Nickel-plated brass	6.6
IM 38 F18	G3/8"-M	9	5	G1/8"-F	19	Nickel-plated brass	18.8
IF 14 M6F	G1/4"-F	11	16	M6-F	17	Nickel-plated brass	20.5
IF 18 M6F	G1/8"-F	7.5	13	M6-F	13	Nickel-plated brass	9.9
IF 14 F18	G1/4"-F	9	19	G1/8"-F	17	Nickel-plated brass	20.2

Note: All dimensions are in mm.






The VSAB series 1.5 bellows suction cups are suitable for gripping slightly concave or convex products. And due to their stroke, VSAB cups are capable of gripping products at varying heights.

Materials

**NBR** Nitrile    **STN** Siton®    **SI** Translucent silicone

Industry-specific applications



Types of use



### Suction Cup Properties

	Ø (mm)	(cm³)	(lbf) (1)	(lbf) (1)	R <sub>min</sub> (mm)	NBR	Si	STN
VSAB 5	5.6	0.05	0.08	0.03	1.5	VSAB5NBR	VSAB5SI	VSAB5STN
VSAB 8	8.8	0.15	0.21	0.10	1.9	VSAB8NBR	VSAB8SI	VSAB8STN
VSAB 10	11	0.48	0.39	0.19	4	VSAB10NBR	VSAB10SI	VSAB10STN
VSAB 15	15.7	1.1	0.68	0.34	5	VSAB15NBR	VSAB15SI	VSAB15STN
VSAB 20	22	2.7	1.14	0.57	10	VSAB20NBR	VSAB20SI	VSAB20STN
VSAB 30	34	10	2.60	1.30	15	VSAB30NBR	VSAB30SI	VSAB30STN
VSAB 40	43	15	4.22	2.11	20	VSAB40NBR	VSAB40SI	VSAB40STN
VSAB 50	53	32	7.14	3.57	30	VSAB50NBR	VSAB50SI	VSAB50STN

(1) Actual force of the suction cup in use with a 65% vacuum and including a safety factor of 2 for horizontal handling and a factor of 4 for vertical handling.

### Choice of Fittings

(Ø)	M5-M	G1/8"-M	G1/4"-M
5...15	■	-	-
20	-	■	-
30...50	-	-	■

### Types of Assembly




**Version C: Barbed fitting**

■ Standard available configurations (suction cup + fitting)    Fitting: M = male  
See part n° table below

### References - "Suction Cup + Fitting"

THREAD	M5-M	THREAD	G1/8"-M	THREAD	G1/4"-M
VSAB5NBR	VSAB5NBRIMM5C	VSAB20NBR	VSAB20NBRIM18C	VSAB30NBR	VSAB30NBRIM14C
VSAB5SI	VSAB5SIIMM5C	VSAB20SI	VSAB20SIIM18C	VSAB30SI	VSAB30SIIM14C
VSAB5STN	VSAB5STNIMM5C	VSAB20STN	VSAB20STNIM18C	VSAB30STN	VSAB30STNIM14C
VSAB8NBR	VSAB8NBRIMM5C			VSAB40NBR	VSAB40NBRIM14C
VSAB8SI	VSAB8SIIMM5C			VSAB40SI	VSAB40SIIM14C
VSAB8STN	VSAB8STNIMM5C			VSAB40STN	VSAB40STNIM14C
VSAB10NBR	VSAB10NBRIMM5C			VSAB50NBR	VSAB50NBRIM14C
VSAB10SI	VSAB10SIIMM5C			VSAB50SI	VSAB50SIIM14C
VSAB10STN	VSAB10STNIMM5C			VSAB50STN	VSAB50STNIM14C
VSAB15NBR	VSAB15NBRIMM5C				
VSAB15SI	VSAB15SIIMM5C				
VSAB15STN	VSAB15STNIMM5C				

### Assembly Diagrams



### Accessories

To optimize use of your suction cups, Coval offers a comprehensive range of accessories (sensors, spring extensions, and feeder systems, etc.) see chapters 4 and 12.



Please specify the part n°. e.g. VSAB30NBRIM14C  
See part n° table above





#### Suction Cup + Fitting

	VSAB 5...15	VSAB 20...30	VSAB 40	VSAB 50						
1										
	Diagrams	ØA	f <sup>(1)</sup>	H	H1	ØG	G1	ØG2 <sup>(2)</sup>	E ↗	(g)
VSAB5---IMM5C	1	5.6	1.5	9.2	12.7	M5-M	4	1.5	7	1.8
VSAB8---IMM5C	1	8.8	3.5	11.9	15.4	M5-M	4	1.5	7	2
VSAB10---IMM5C	1	11	4.5	16.4	20.9	M5-M	4	2.7	7	1.6
VSAB15---IMM5C	1	15.7	6.5	19.8	24.3	M5-M	4	2.7	7	2.1
VSAB20---IM18C	2	22	10	19	22.5	G1/8"-M	7	4	14	5.5
VSAB30---IM14C	2	34	15	26.2	32.2	G1/4"-M	9	5	17	13.2
VSAB40---IM14C	3	43	15	28	34	G1/4"-M	9	5	17	18.9
VSAB50---IM14C	4	53	13	35.3	41.3	G1/4"-M	9	5	21	31.7

#### Suction Cups

VSAB 5...15

VSAB 20...30

VSAB 40

VSAB 50

ØA

H

Øa

Ød

ØD

f <sup>(1)</sup>

B

(g)

VSAB 5

5.6

9.2

6.2

2

4.5

1.5

3.5

0.12

VSAB 8

8.8

11.9

9.6

2

5.5

3.5

3.5

0.27

VSAB 10

11

16.4

12

3.8

9

4.5

5

0.8

VSAB 15

15.7

19.8

17.5

3.8

9

6.5

3

1.3

VSAB 20

22

19

24

5

14.5

10

4.5

2.5

VSAB 30

34

26.2

36

6.5

20

15

6

6.9

VSAB 40

43

28

46

6.5

20

15

6.4

12.6

VSAB 50

53

35.3

58

10.5


27

13

8.5

21.7

#### Barbed Fittings




	ØA	B	C	ØD	E ↗	Material	⚖ (g)
IMM5P1	M5-M	4	3.5	1.5	7	Brass	1.7
IMM5P2	M5-M	4	4.5	2.7	7	Aluminum	0.8
IM18P3	G1/8"-M	7	3.5	4	14	Aluminum	3
IM14P4	G1/4"-M	9	6	5	17	Aluminum	6.3
IM14P5	G1/4"-M	9	6	5	21	Aluminum	10


The values represent the average characteristics of our products.  
Note: All dimensions are in mm.

(1) f = Deflection of the suction cup. (2) Ø G2 = Ø internal orifice of the fitting.






The VSAG series 1.5 bellows suction cups are recommended for gripping concave or convex products as well as sensitive products due to the cushioning effect of the bellows. The bellows also compensate for height variations in product gripping.



Industry-specific applications








Types of use

### Materials


**NBR** Nitrile  
**SI** Translucent silicone  
**STN** Siton®

### Suction Cup Properties

	Ø (mm)	 (cm³)	 (lbf) <sup>(1)</sup>	 (lbf) <sup>(1)</sup>	 R <sub>min</sub> (mm)	NBR	SI	STN
<b>VSAG 10</b>	10.7	0.2	0.41	0.21	4	<b>VSAG10NBR</b>	<b>VSAG10SI</b>	<b>VSAG10STN</b>
<b>VSAG 15</b>	15	0.7	0.57	0.29	6	<b>VSAG15NBR</b>	<b>VSAG15SI</b>	<b>VSAG15STN</b>
<b>VSAG 20B</b>	20	1	1.07	0.54	8	<b>VSAG20BNBR</b>	<b>VSAG20BSI</b>	<b>VSAG20BSTN</b>
<b>VSAG 30</b>	30	4	3.41	1.70	15	<b>VSAG30NBR</b>	<b>VSAG30SI</b>	-
<b>VSAG 40</b>	40	9	5.20	2.60	30	<b>VSAG40NBR</b>	<b>VSAG40SI</b>	-
<b>VSAG 50</b>	50	26	8.60	4.22	40	<b>VSAG50NBR</b>	<b>VSAG50SI</b>	-
<b>VSAG 75</b>	75	76	20.29	10.07	70	<b>VSAG75NBR</b>	<b>VSAG75SI</b>	<b>VSAG75STN</b>
<b>VSAG 110</b>	110	280	43.02	21.11	100	<b>VSAG110NBR</b>	<b>VSAG110SI</b>	<b>VSAG110STN</b>
<b>VSAG 150</b>	150	640	84.91	42.21	130	<b>VSAG150NBR</b>	<b>VSAG150SI</b>	-

(1) Actual force of the suction cup in use with a 65% vacuum and including a safety factor of 2 for horizontal handling and a factor of 4 for vertical handling.

### Choice of Fittings

 (Ø)	M5-F	M5-M	M6-M	M10-M	M10x125F	G1/8"-M	G1/8"-F	G1/4"-M	G1/4"-F	G1/2"-F
<b>10...15</b>	■	■	-	-	-	■	■	-	-	-
<b>20...50</b>	-	-	■	□	-	■	■	■	■	-
<b>75</b>	-	-	-	-	■	-	-	■	■	-
<b>110...150</b>	-	-	-	-	-	-	-	-	-	■

■ Standard available configurations (suction cup + fitting)  
refer to page 2/34

□ Additional mounting configurations  
see page 2/36

Fitting: M = male

F = female

### Types of Assembly

COVAL suction cups can be assembled in a wide variety of configurations:



**Version C**  
Barbed fitting



**Version V**  
Removable fitting  
(adapter and hollow screw)




Please specify the part n°. e.g. VSAG10NBRIM18C  
Refer to page 2/34



### Accessories


To optimize use of your suction cups, Coval offers a comprehensive range of accessories (sensors, spring extensions, and feeder systems, etc.) see chapters 4 and 12.






Ø 10 - 15 mm	THREAD	C 			
		M5-M	M5-F	G1/8"-M	G1/8"-F
	VSAG10NBR	VSAG10NBRIMM5C	VSAG10NBRIFM5C	VSAG10NBRIM18C	VSAG10NBRIF18C
	VSAG10SI	VSAG10SIIMM5C	VSAG10SIIFM5C	VSAG10SIIM18C	VSAG10SIIF18C
	VSAG10STN	VSAG10STNIMM5C	VSAG10STNIFM5C	VSAG10STNIM18C	VSAG10STNIF18C
	VSAG15NBR	VSAG15NBRIMM5C	VSAG15NBRIFM5C	VSAG15NBRIM18C	VSAG15NBRIF18C
	VSAG15SI	VSAG15SIIMM5C	VSAG15SIIFM5C	VSAG15SIIM18C	VSAG15SIIF18C
	VSAG15STN	VSAG15STNIMM5C	VSAG15STNIFM5C	VSAG15STNIM18C	VSAG15STNIF18C

		<b>C</b> 		<b>V</b> 				
Ø 20 - 50 mm	THREAD	G1/8"-M	G1/8"-F	M6-M	G1/8"-M	G1/8"-F	G1/4"-M	G1/4"-F
	<b>VSAG20BNBR</b>	VSAG20BNBRIM18C	VSAG20BNBRIF18C	VSAG20BNBRIMM6V	VSAG20BNBRIM18V	VSAG20BNBRIF18V	VSAG20BNBRIM14V	VSAG20BNBRIF14V
	<b>VSAG20BSI</b>	VSAG20BSIIM18C	VSAG20BSIIF18C	VSAG20BSIIMM6V	VSAG20BSIIM18V	VSAG20BSIIF18V	VSAG20BSIIM14V	VSAG20BSIIF14V
	<b>VSAG20BSTN</b>	VSAG20BSTNIM18C	VSAG20BSTNIF18C	VSAG20BSTNIMM6V	VSAG20BSTNIM18V	VSAG20BSTNIF18V	VSAG20BSTNIM14V	VSAG20BSTNIF14V
	<b>VSAG30NBR</b>	VSAG30NBRIM18C	VSAG30NBRIF18C	VSAG30NBRIMM6V	VSAG30NBRIM18V	VSAG30NBRIF18V	VSAG30NBRIM14V	VSAG30NBRIF14V
	<b>VSAG30SI</b>	VSAG30SIIM18C	VSAG30SIIF18C	VSAG30SIIMM6V	VSAG30SIIM18V	VSAG30SIIF18V	VSAG30SIIM14V	VSAG30SIIF14V
	<b>VSAG40NBR</b>	VSAG40NBRIM18C	VSAG40NBRIF18C	VSAG40NBRIMM6V	VSAG40NBRIM18V	VSAG40NBRIF18V	VSAG40NBRIM14V	VSAG40NBRIF14V
	<b>VSAG40SI</b>	VSAG40SIIM18C	VSAG40SIIF18C	VSAG40SIIMM6V	VSAG40SIIM18V	VSAG40SIIF18V	VSAG40SIIM14V	VSAG40SIIF14V
	<b>VSAG50NBR</b>	VSAG50NBRIM18C	VSAG50NBRIF18C	VSAG50NBRIMM6V	VSAG50NBRIM18V	VSAG50NBRIF18V	VSAG50NBRIM14V	VSAG50NBRIF14V
	<b>VSAG50SI</b>	VSAG50SIIM18C	VSAG50SIIF18C	VSAG50SIIMM6V	VSAG50SIIM18V	VSAG50SIIF18V	VSAG50SIIM14V	VSAG50SIIF14V

		V 		
ø 75 mm	THREAD	M10x125 F	G1/4"-M	G1/4"-F
	VSAG75NBR	VSAG75NBR	VSAG75NBRIM14V	VSAG75NBRIF14V
	VSAG75SI	VSAG75SI	VSAG75SIIM14V	VSAG75SIIF14V
	VSAG75STN	VSAG75STN	VSAG75STNIM14V	VSAG75STNIF14V


Ø 110 - 150 mm		V 	
	THREAD	G1/2"-F *	G1/2"-F **
	VSAG110NBR	VSAG110NBRIFS12V	VSAG110NBRIF12V
	VSAG110SI	VSAG110SIIFS12V	VSAG110SIIF12V
	VSAG110STN	VSAG110STNIFS12V	VSAG110STNIF12V
	VSAG150NBR	VSAG150NBRIFS12V	VSAG150NBRIF12V
	VSAG150SI	VSAG150SIIFS12V	VSAG150SIIF12V

\*Configured using fitting n° IFS12120


\*\* Configured using fitting n° IF12120

Additional mounting configurations are available (see page 2/36).  
For standard configurations (suction cup+fitting), the C and V versions are delivered unassembled.







#### VSAG 10 - 15




#### VSAG 20B - 50





#### VSAG 75



#### VSAG 110 - 150



		Diagrams	ØA	ØD	f <sup>(1)</sup>	H	H1	ØG	G1	ØG2 <sup>(2)</sup>	E 	 (g)
Ø 10 - 15 mm	VSAG10---IMM5C	1	10.7	-	5	13.3	16.8	M5-M	4.5	2.2	7	1.3
	VSAG10---IFM5C	2	10.7	-	5	13.3	22.3	M5-F	6	2.2	14	1.8
	VSAG10---IM18C	1	10.7	-	5	13.3	18.3	G1/8"-M	8	2.2	14	4.5
	VSAG10---IF18C	2	10.7	-	5	13.3	28.3	G1/8"-F	9	2.2	14	5.7
	VSAG15---IMM5C	1	15	-	10	16	19.5	M5-M	4.5	2.2	7	1.6
	VSAG15---IFM5C	2	15	-	10	16	25	M5-F	6	2.2	14	2.1
	VSAG15---IM18C	1	15	-	10	16	21	G1/8"-M	8	2.2	14	4.8
	VSAG15---IF18C	2	15	-	10	16	31	G1/8"-F	9	2.2	14	6
Ø 20B - 40 mm	VSAG20B---IM18C	4	20	-	12	22	27	G1/8"-M	8	4	14	7.1
	VSAG20B---IF18C	5	20	-	12	22	37	G1/8"-F	9	4	14	8.5
	VSAG20B---IMM6V	3	20	15	12	22	-	M6-M	6	3.5	-	5.7
	VSAG20B---IM18V	4	20	-	12	22	26.5	G1/8"-M	6	3.5	13	12.3
	VSAG20B---IF18V	5	20	-	12	22	35	G1/8"-F	7.5	3.5	13	15.6
	VSAG20B---IM14V	4	20	-	12	22	27	G1/4"-M	8	3.5	17	21.6
	VSAG20B---IF14V	5	20	-	12	22	38	G1/4"-F	11	3.5	17	26.2
	VSAG30---IM18C	4	30	-	17	30.5	35.5	G1/8"-M	8	4	14	13.2
	VSAG30---IF18C	5	30	-	17	30.5	45.5	G1/8"-F	9	4	14	14.6
	VSAG30---IMM6V	3	30	20	17	30.5	-	M6-M	6	3.5	-	11.8
	VSAG30---IM18V	4	30	-	17	30.5	35	G1/8"-M	6	3.5	13	18.4
	VSAG30---IF18V	5	30	-	17	30.5	43.5	G1/8"-F	7.5	3.5	13	21.7
	VSAG30---IM14V	4	30	-	17	30.5	35.5	G1/4"-M	8	3.5	17	27.7
	VSAG30---IF14V	5	30	-	17	30.5	46.5	G1/4"-F	11	3.5	17	32.3
	VSAG40---IM18C	4	40	-	15.5	30.5	35.5	G1/8"-M	8	4	14	18.8
	VSAG40---IF18C	5	40	-	15.5	30.5	45.5	G1/8"-F	9	4	14	20.2
	VSAG40---IMM6V	3	40	25	15.5	30.5	-	M6-M	6	3.5	-	17.4
	VSAG40---IM18V	4	40	-	15.5	30.5	35	G1/8"-M	6	3.5	13	24
	VSAG40---IF18V	5	40	-	15.5	30.5	43.5	G1/8"-F	7.5	3.5	13	27.3
	VSAG40---IM14V	4	40	-	15.5	30.5	35.5	G1/4"-M	8	3.5	17	33.3
	VSAG40---IF14V	5	40	-	15.5	30.5	46.5	G1/4"-F	11	3.5	17	37.9
Ø 50 mm	VSAG50---IM18C	4	50	-	20	36.5	41.5	G1/8"-M	8	4	14	27.4
	VSAG50---IF18C	5	50	-	20	36.5	51.5	G1/8"-F	9	4	14	28.8
	VSAG50---IMM6V	3	50	-	20	36.5	-	M6-M	6	3.5	-	30
	VSAG50---IM18V	4	50	-	20	36.5	41	G1/8"-M	6	3.5	13	36.6
	VSAG50---IF18V	5	50	-	20	36.5	49.5	G1/8"-F	7.5	3.5	13	40
	VSAG50---IM14V	4	50	-	20	36.5	41.5	G1/4"-M	8	3.5	17	45.9
	VSAG50---IM14F	5	50	-	20	36.5	52.5	G1/4"-F	11	3.5	17	50.4
Ø 75 - 150 mm	VSAG75---	8	75	50.5	22	43.2	-	M10x125-F	-	-	-	87.6
	VSAG75---IM14V	6	75	50.5	22	43.2	48.2	G1/4"-M	10	5	17	94.6
	VSAG75---IF14V	7	75	50.5	22	43.2	60.2	G1/4"-F	10	5	17	95.9
	VSAG110---IF12V	10	110	85	32.5	55	85	G1/2"-F	24	19	48	488.8
	VSAG110---IFS12V	9	110	85	32.5	55	68	G1/2"-F	13	-	-	407.5
	VSAG150---IF12V	10	150	120	39.5	75.5	105.5	G1/2"-F	24	19	48	911.4
	VSAG150---IFS12V	9	150	120	39.5	75.5	88.5	G1/2"-F	13	-	-	830.1

Note: All dimensions are in mm.


(1) f = Deflection of the suction cup. (2) Ø G2 = Ø internal orifice of the fitting.






#### VSAG 10 - 15

Barbed fittings  




#### VSAG 20B - 50

Barbed fittings  




#### VSAG 20B - 50

Removable fittings  





#### VSAG 75 - 150

Removable fittings  




\* 125 thread

\*\* Female auxiliary radial output


-  Configurations (suction cup + fitting) refer to page 2/34
-  Non-standard configurations must be ordered in separate part numbers.

Fittings and suction cups dimensions: see pages 2/37 and 2/38.







#### VSAG 10 - 15




#### VSAG 20 - 50





#### VSAG 75



#### VSAG 110 - 150



(1) 4 holes Ø 9 on Ø 40

 (Ø)	ØA	H	Øa	Ød	ØD	f <sup>(1)</sup>	B	 (g)
<b>VSAG 10</b>	10.7	13.3	12.5	4	8.5	5	4	0.6
<b>VSAG 15</b>	15	16	17	4	8.5	10	4	0.9
<b>VSAG 20 B</b>	20	22	24	6	15	12	7	3
<b>VSAG 30</b>	30	30.5	36	6	20	17	7	9.1
<b>VSAG 40</b>	40	30.5	46	6	25	15.5	7	14.7
<b>VSAG 50</b>	50	36.5	59.5	7.8	28.5	20	7	22.5
<b>VSAG 75</b>	75	43.2	84	M10 x 125 - F	50.5	22	9	87.6
<b>VSAG 110</b>	110	55	121.5	14	85	32.5	9	264
<b>VSAG 150</b>	150	75.5	166	13	120	39.5	11	686.6


The values represent the average characteristics of our products.  
Note: All dimensions are in mm.

(1) f = Deflection of the suction cup.




## Suction Cups with 1.5 Bellows Ø 10 to 150 mm

### Dimensions - Fittings




#### Barbed fittings

Male - IM




Female - IF



	ØA	B	C	ØD	E	Material	(g)
IM 5 VPG5	M5-M	4.5	3.5	2.2	7	Aluminum	0.7
IM 18 VPG5	G1/8"-M	8	5	2.2	14	Aluminum	3.9
IM 18 VPG25	G1/8"-M	8	5	4	14	Aluminum	4.1
IM 18 VPG50	G1/8"-M	8	5	4	14	Aluminum	4.9
IF 5 VPG5	M5-F	6	9	2.2	14	Aluminum	1.2
IF 18 VPG5	G1/8"-F	9	15	2.2	14	Aluminum	5.1
IF 18 VPG25	G1/8"-F	9	15	4	14	Aluminum	5.5
IF 18 VPG50	G1/8"-F	9	15	4	14	Aluminum	6.3


#### Hollow Screws




	ØA	B	C	ØD	Material	(g)
IM 6 M25	M6-M	6	6	3.5	Nickel-plated brass	2.7
IM 6 M50	M6-M	6	6	3.5	Nickel-plated brass	7.5

#### Adapters for Hollow Screws

Male - IM




Female - IF




	ØA	B	C	ØD	E	Material	(g)
IM 10 M6F	M10-M	7	3.5	M6	13	Nickel-plated brass	5.9
IM 14 M6F	G1/4"-M	8	5	M6-F	17	Nickel-plated brass	15.9
IM 18 M6F	G1/8"-M	6	4.5	M6-F	13	Nickel-plated brass	6.6
IF 14 M6F	G1/4"-F	11	16	M6-F	17	Nickel-plated brass	20.5
IF 18 M6F	G1/8"-F	7.5	13	M6-F	13	Nickel-plated brass	9.9

#### Removable Fittings


Male - IM




Female - IF



Female - IF 12120



Female - IFS 12120




(1) 4 holes Ø 9 on Ø 40


	ØA	B	C	ØD	E	ØF	G	H	Material	(g)
IM 14 M10M	G1/4"-M	10	5	5	17	M10x125-M	-	-	Aluminum	7
IF 14 M10M	G1/4"-F	10	17	5	17	M10x125-M	-	-	Aluminum	8.3
IF 12120	G1/2"-F	24	30	19	48	G1/8"-F	8.7	60	Aluminum	224.8
IFS 12120	G1/2"-F	13	13	-	-	-	-	65	Aluminum	143.5

The values represent the average characteristics of our products.  
Note: All dimensions are in mm.





Industry-specific applications



Types of use








The VSAJ series 1.5 bellows suction cups are recommended to grip slightly convex or concave products. They are also able to compensate for height variations in products being gripped.

### Materials


**NBR** Nitrile  
**SI** Translucent silicone

### Suction Cup Properties

	Ø (mm)	 (cm <sup>3</sup> )	 (lbf) <sup>(1)</sup>	 (lbf) <sup>(1)</sup>	 R <sub>min</sub> (mm)	NBR	SI
<b>VSAJ 15</b>	15	0.5	0.81	0.41	10	<b>VSAJ15NBR</b>	<b>VSAJ15SI</b>
<b>VSAJ 20</b>	20	1.2	1.54	0.76	13	<b>VSAJ20NBR</b>	<b>VSAJ20SI</b>
<b>VSAJ 30</b>	30	3	3.00	1.49	26	<b>VSAJ30NBR</b>	<b>VSAJ30SI</b>

(1) Actual force of the suction cup in use with 65% vacuum and including a safety factor of 2 for horizontal handling and a factor of 4 for vertical handling.

### Choice of Fittings

 (Ø)	M5-M	M6-M	M10-M	G1/8"-F	G1/8"-M	G1/4"-F	G1/4"-M
15...20	■	-	-	■	■	-	-
30	-	■	□	■	■	■	■

■ Standard available configurations (suction cup + fitting)  
refer to page 2/40


□ Additional mounting configurations  
see page 2/41

Fitting: M = male F = female

### Types of Assembly

COVAL suction cups can be assembled in a wide variety of configurations:

**C**  **Version C**  
Barbed fitting

**V**  **Version V**  
Removable fitting  
(adapter and hollow screw)




Please specify the part n°. e.g. VSAJ20NBRIM18C  
Refer to page 2/40





### Accessories

To optimize use of your suction cups, Coval offers a comprehensive range of accessories (spring systems, extensions, feeder systems, etc.) see chapters 4 and 12.






#### References - "Suction Cup + Fitting"

		C 		V 				
Ø 15 - 20 mm	THREAD	G1/8"-M	G1/8"-F	M5-M	G1/8"-M	G1/8"-F		
	VSAJ15NBR	VSAJ15NBRIM18C	VSAJ15NBRIF18C	VSAJ15NBRIMM5V	VSAJ15NBRIM18V	VSAJ15NBRIF18V		
	VSAJ15SI	VSAJ15SIIM18C	VSAJ15SIIF18C	VSAJ15SIIMM5V	VSAJ15SIIM18V	VSAJ15SIIF18V		
	VSAJ20NBR	VSAJ20NBRIM18C	VSAJ20NBRIF18C	VSAJ20NBRIMM5V	VSAJ20NBRIM18V	VSAJ20NBRIF18V		
	VSAJ20SI	VSAJ20SIIM18C	VSAJ20SIIF18C	VSAJ20SIIMM5V	VSAJ20SIIM18V	VSAJ20SIIF18V		
		C 		V 				
Ø 30 mm	THREAD	G1/8"-M	G1/8"-F	M5-M	G1/8"-M	G1/8"-F	G1/4"-M	G1/4"-F
	VSAJ30NBR	VSAJ30NBRIM18C	VSAJ30NBRIF18C	VSAJ30NBRIMM6V	VSAJ30NBRIM18V	VSAJ30NBRIF18V	VSAJ30NBRIM14V	VSAJ30NBRIF14V
	VSAJ30SI	VSAJ30SIIM18C	VSAJ30SIIF18C	VSAJ30SIIMM6V	VSAJ30SIIM18V	VSAJ30SIIF18V	VSAJ30SIIM14V	VSAJ30SIIF14V

#### VSAJ 15 -20

#### VSAJ 30



		Diagrams	ØA	ØD	f <sup>(1)</sup>	H	H1	ØG	G1	ØG2 <sup>(2)</sup>	E	g <sup>(g)</sup>
Ø 15 - 20 mm	VSAJ15---IM18C	1	15	-	3.3	11	16	G1/8"-M	8	2.2	14	4.8
	VSAJ15---IF18C	2	15	-	3.3	11	26	G1/8"-F	9	2.5	14	6
	VSAJ15---IMM5V	3	15	12	3.3	11	-	M5-M	5	2.5	-	3
	VSAJ15---IM18V	1	15	-	3.3	11	15.5	G1/8"-M	6	2.5	13	9.4
	VSAJ15---IF18V	2	15	-	3.3	11	24	G1/8"-F	7.5	2.5	13	12.6
	VSAJ20---IM18C	1	20	-	5.5	13	18	G1/8"-M	8	3	14	5.7
	VSAJ20---IF18C	2	20	-	5.5	13	28	G1/8"-F	9	3	14	7
	VSAJ20---IMM5V	3	20	15	5.5	13	-	M5-M	5	2.5	-	3.8
	VSAJ20---IM18V	1	20	-	5.5	13	17.5	G1/8"-M	6	2.5	13	10.1
	VSAJ20---IF18V	2	20	-	5.5	13	26	G1/8"-F	7.5	2.5	13	14.6
Ø 30 mm	VSAJ30---IM18C	4	30	-	7	17	42	G1/8"-M	8	4	14	9
	VSAJ30---IF18C	5	30	-	7	17	32	G1/8"-F	9	4	14	8.4
	VSAJ30---IMM6V	6	30	20	7	17	-	M6-M	6	3.5	-	7.6
	VSAJ30---IM18V	4	30	-	7	17	21.5	G1/8"-M	6	3.5	13	14.2
	VSAJ30---IF18V	5	30	-	7	17	30	G1/8"-F	7.5	3.5	13	17.5
	VSAJ30---IM14V	4	30	-	7	17	21.5	G1/4"-M	8	3.5	17	20.8
	VSAJ30---IF14V	5	30	-	7	17	33	G1/4"-F	11	3.5	17	28.1

Note: All dimensions are in mm.

(1) f = Deflection of the suction cup.

(2) Ø G2 = Ø internal orifice of the fitting.

Additional mounting configurations are available (see page 2/41). For standard configurations (suction cup+fitting), the C and V versions are delivered unassembled.



# VSAJ


## Suction Cups with 1.5 Bellows Ø 15 to 30 mm

### Assembly Diagrams




#### VSAJ 15 - 20

Barbed fittings **C**




Removable fittings **V**




#### VSAJ 30

Barbed fittings **C**




Removable fittings **V**






## Suction Cups with 1.5 Bellows Ø 15 to 30 mm

### Dimensions




#### Suction Cups


VSAJ 15



VSAJ 20



VSAJ 30




	Ø A	H	Ø a	Ø d	Ø D	f (1)	B	(g)
VSAJ 15	15	11	15.5	4.5	12	3.3	3.5	9
VSAJ 20	20	13	21	4.7	15	5.5	4.5	8.4
VSAJ 30	30	17	30.6	5.8	20	7	7.2	7.6


(1) f = Deflection of the suction cup.

#### Barbed Fittings

Male - IM




Female - IF



	ØA	B	C	ØD	E	Material	(g)
IM 18 VPG15	G1/8"-M	8	5	2.2	14	Aluminum	4
IM 18 VPG20	G1/8"-M	8	5	3	14	Aluminum	4.1
IM 18 VPG25	G1/8"-M	8	5	4	14	Aluminum	4.1
IF 18 VPG15	G1/8"-F	9	15	2.5	14	Aluminum	5.2
IF 18 VPG20	G1/8"-F	9	15	3	14	Aluminum	5.4
IF 18 VPG25	G1/8"-F	9	15	4	14	Aluminum	5.5


#### Hollow Screws




	ØA	B	C	ØD	Material	(g)
IM 5 M15	M5-M	5	2	2.5	Nickel-plated brass	1.3
IM 5 M20	M5-M	5	4	2.5	Nickel-plated brass	2.2
IM 6 M25	M6-M	6	6	3.5	Nickel-plated brass	2.7

#### Adapters for Hollow Screws

Male - IM



Female - IF



	ØA	B	C	ØD	E	Material	(g)
IM 10 M6F	M10-M	7	3.5	M6-F	13	Nickel-plated brass	5.9
IM 14 M6F	G1/4"-M	8	5	M6-F	17	Nickel-plated brass	15.9
IM 18 M5F	G1/8"-M	6	4.5	M5-F	13	Nickel-plated brass	7.3
IM 18 M6F	G1/8"-M	6	4.5	M6-F	13	Nickel-plated brass	6.6
IF 14 M6F	G1/4"-F	11	16	M6-F	17	Nickel-plated brass	20.5
IF 18 M5F	G1/8"-F	7.5	13	M5-F	13	Nickel-plated brass	10.5
IF 18 M6F	G1/8"-F	7.5	13	M6-F	13	Nickel-plated brass	9.9

The values represent the average characteristics of our products.  
Note: All dimensions are in mm.



VS

# Suction Cups with 2.5 Bellows Ø 5 to 88 mm



VS series suction cups with bellows are recommended for gripping products on different planes (wide deflection) where they can replace spring systems, and for gripping spherical or cylindrical objects gripped at an angle (ball-joint effect).


- Large deflection (stroke)
- Flexibility

## Materials

**NBR** Nitrile  
**NR** Natural rubber

**SIT5** Translucent silicone  
**STN** Siton® 60 ShoreA  
**STN5** Siton® 50 ShoreA  
(on request)





## Industry-specific applications



## Types of use




## Suction Cup Properties

	Ø (mm)	 (cm³)	 (lbf) <sup>(1)</sup>	 R <sub>min</sub> (mm)	NBR	SIT5	NR	STN <sup>(2)</sup>
VS 5	5	0.04	0.11	8	VS5NBR	VS5SIT5	-	VS5STN
VS 6	6	0.04	0.11	8	VS6NBR	VS6SIT5	-	-
VS 7	7	0.0425	0.21	8	VS7NBR	VS7SIT5	-	VS7STN
VS 9	9	0.15	0.24	10	VS9NBR	VS9SIT5	VS9NR	VS9STN
VS 12	12	0.54	0.63	13	VS12NBR	VS12SIT5	VS12NR	VS12STN
VS 14	14	0.975	0.67	15	VS14NBR	VS14SIT5	VS14NR	VS14STN
VS 18	17.5	1.35	0.99	20	VS18NBR	VS18SIT5	VS18NR	VS18STN
VS 20	20	2	1.04	30	VS20NBR	VS20SIT5	VS20NR	VS20STN
VS 25	25	5.4	1.46	30	VS25NBR	VS25SIT5	VS25NR	VS25STN
VS 26	25	6.1	2.44	30	VS26NBR	VS26SIT5	VS26NR	VS26STN
VS 32	32	10	2.73	35	VS32NBR	VS32SIT5	VS32NR	VS32STN
VS 42	42	19.5	4.71	75	VS42NBR	VS42SIT5	VS42NR	VS42STN
VS 52	52	36	6.49	75	VS52NBR	VS52SIT5	VS52NR	VS52STN
VS 62	62	72.5	9.25	75	VS62NBR	VS62SIT5	VS62NR	VS62STN
VS 88	88	165	29.87	100	VS88NBR	VS88SIT5	VS88NR	-

(1) Actual force of the suction cup in use with 65% vacuum and including a safety factor of 2 for horizontal handling.

(2) On request, some models are available in STN5 (Siton® 50 ShoreA)

## Choice of Fittings

 (Ø)	Group	M3-M	M5-M	M6-M	M8-M	M10-M	G1/8"-F	G1/8"-M	10/32-M	G1/4"-F	G1/4"-M	G3/8"-M	G1/2"-M
5 - 6	1	■	-	-	-	-	-	-	-	-	-	-	-
7 - 25	1	-	■	■	-	-	■	■	□	-	-	-	-
26 - 62	2	-	□	□	□	□	■	■	-	■	■	-	-
88	3	-	-	-	-	□	-	■	-	■	■	□	□

■ Standard available configurations (suction cup + fitting) refer to page 2/44  
□ Additional mounting configurations see page 2/47

Fitting: M = male F = female

## Types of Assembly

COVAL suction cups can be assembled in a wide variety of configurations.



**Version C**  
Barbed fitting



**Version S**  
Factory-cripped fitting




**Version V**  
Removable fitting:  
(adapter and hollow screw)



**Version E**  
Pressed fitting

## Textured Surfaces

For handling objects with a granular or textured gripping surface, use VS suction cups with the VSBM foam strip option (see page 2/59).



## Accessories

To optimize the use of your suction cups, Coval offers a comprehensive range of accessories (nozzle fittings, spring extensions, and feeder systems, etc.), see chapters 4 and 12.




Please specify the part n°. e.g. VS32SIT5IF14  
Refer to page 2/44








# Suction Cups with 2.5 Bellows Ø 5 to 88 mm

References - "Suction Cup + Fitting"



Group 1		C 				
Ø 5 - 25 mm	THREAD	M3M	M5M	M6M	G1/8"-M	G1/8"-F
	VS5NBR	VS5NBRIMM3C	-	-	-	-
	VS5SIT5	VS5SIT5IMM3C	-	-	-	-
	VS5STN	VS5STNIMM3C	-	-	-	-
	VS6NBR	VS6NBRIMM3C	-	-	-	-
	VS6SIT5	VS6SIT5IMM3C	-	-	-	-
	VS7NBR	-	VS7NBRIMM5C	VS7NBRIMM6C	VS7NBRIM18C	VS7NBRIF18C
	VS7SIT5	-	VS7SIT5IMM5C	VS7SIT5IMM6C	VS7SIT5IM18C	VS7SIT5IF18C
	VS7STN	-	VS7STNIMM5C	VS7STNIMM6C	VS7STNIM18C	VS7STNIF18C
	VS9NBR	-	VS9NBRIMM5C	VS9NBRIMM6C	VS9NBRIM18C	VS9NBRIF18C
	VS9SIT5	-	VS9SIT5IMM5C	VS9SIT5IMM6C	VS9SIT5IM18C	VS9SIT5IF18C
	VS9NR	-	VS9NRIMM5C	VS9NRIMM6C	VS9NRIM18C	VS9NRIF18C
	VS9STN	-	VS9STNIMM5C	VS9STNIMM6C	VS9STNIM18C	VS9STNIF18C
	VS12NBR	-	VS12NBRIMM5C	VS12NBRIMM6C	VS12NBRIM18C	VS12NBRIF18C
	VS12SIT5	-	VS12SIT5IMM5C	VS12SIT5IMM6C	VS12SIT5IM18C	VS12SIT5IF18C
	VS12NR	-	VS12NRIMM5C	VS12NRIMM6C	VS12NRIM18C	VS12NRIF18C
	VS12STN	-	VS12STNIMM5C	VS12STNIMM6C	VS12STNIM18C	VS12STNIF18C
	VS14NBR	-	VS14NBRIMM5C	VS14NBRIMM6C	VS14NBRIM18C	VS14NBRIF18C
	VS14SIT5	-	VS14SIT5IMM5C	VS14SIT5IMM6C	VS14SIT5IM18C	VS14SIT5IF18C
	VS14NR	-	VS14NRIMM5C	VS14NRIMM6C	VS14NRIM18C	VS14NRIF18C
	VS14STN	-	VS14STNIMM5C	VS14STNIMM6C	VS14STNIM18C	VS14STNIF18C
	VS18NBR	-	VS18NBRIMM5C	VS18NBRIMM6C	VS18NBRIM18C	VS18NBRIF18C
	VS18SIT5	-	VS18SIT5IMM5C	VS18SIT5IMM6C	VS18SIT5IM18C	VS18SIT5IF18C
	VS18NR	-	VS18NRIMM5C	VS18NRIMM6C	VS18NRIM18C	VS18NRIF18C
	VS18STN	-	VS18STNIMM5C	VS18STNIMM6C	VS18STNIM18C	VS18STNIF18C
	VS20NBR	-	VS20NBRIMM5C	VS20NBRIMM6C	VS20NBRIM18C	VS20NBRIF18C
	VS20SIT5	-	VS20SIT5IMM5C	VS20SIT5IMM6C	VS20SIT5IM18C	VS20SIT5IF18C
	VS20NR	-	VS20NRIMM5C	VS20NRIMM6C	VS20NRIM18C	VS20NRIF18C
	VS20STN	-	VS20STNIMM5C	VS20STNIMM6C	VS20STNIM18C	VS20STNIF18C
	VS25NBR	-	VS25NBRIMM5C	VS25NBRIMM6C	VS25NBRIM18C	VS25NBRIF18C
	VS25SIT5	-	VS25SIT5IMM5C	VS25SIT5IMM6C	VS25SIT5IM18C	VS25SIT5IF18C
	VS25NR	-	VS25NRIMM5C	VS25NRIMM6C	VS25NRIM18C	VS25NRIF18C
	VS25STN	-	VS25STNIMM5C	VS25STNIMM6C	VS25STNIM18C	VS25STNIF18C

Group 2		C 		E 		V 			
Ø 26 - 62 mm	THREAD	G1/4"-M	G1/4"-F	G1/4"-M	G1/4"-F	G1/8"-M	G1/8"-F	G1/4"-M	G1/4"-F
	VS26NBR	VS26NBRIM14C	VS26NBRIF14C	VS26NBRIM14	VS26NBRIF14	VS26NBRIM18V	VS26NBRIF18V	VS26NBRIM14V	VS26NBRIF14V
	VS26SIT5	VS26SIT5IM14C	VS26SIT5IF14C	VS26SIT5IM14	VS26SIT5IF14	VS26SIT5IM18V	VS26SIT5IF18V	VS26SIT5IM14V	VS26SIT5IF14V
	VS26NR	VS26NRIM14C	VS26NRIF14C	VS26NRIM14	VS26NRIF14	VS26NRIM18V	VS26NRIF18V	VS26NRIM14V	VS26NRIF14V
	VS26STN	VS26STNIM14C	VS26STNIF14C	VS26STNIM14	VS26STNIF14	VS26STNIM18V	VS26STNIF18V	VS26STNIM14V	VS26STNIF14V
	VS32NBR	VS32NBRIM14C	VS32NBRIF14C	VS32NBRIM14	VS32NBRIF14	VS32NBRIM18V	VS32NBRIF18V	VS32NBRIM14V	VS32NBRIF14V
	VS32SIT5	VS32SIT5IM14C	VS32SIT5IF14C	VS32SIT5IM14	VS32SIT5IF14	VS32SIT5IM18V	VS32SIT5IF18V	VS32SIT5IM14V	VS32SIT5IF14V
	VS32NR	VS32NRIM14C	VS32NRIF14C	VS32NRIM14	VS32NRIF14	VS32NRIM18V	VS32NRIF18V	VS32NRIM14V	VS32NRIF14V
	VS32STN	VS32STNIM14C	VS32STNIF14C	VS32STNIM14	VS32STNIF14	VS32STNIM18V	VS32STNIF18V	VS32STNIM14V	VS32STNIF14V
	VS42NBR	VS42NBRIM14C	VS42NBRIF14C	VS42NBRIM14	VS42NBRIF14	VS42NBRIM18V	VS42NBRIF18V	VS42NBRIM14V	VS42NBRIF14V
	VS42SIT5	VS42SIT5IM14C	VS42SIT5IF14C	VS42SIT5IM14	VS42SIT5IF14	VS42SIT5IM18V	VS42SIT5IF18V	VS42SIT5IM14V	VS42SIT5IF14V
	VS42NR	VS42NRIM14C	VS42NRIF14C	VS42NRIM14	VS42NRIF14	VS42NRIM18V	VS42NRIF18V	VS42NRIM14V	VS42NRIF14V
	VS42STN	VS42STNIM14C	VS42STNIF14C	VS42STNIM14	VS42STNIF14	VS42STNIM18V	VS42STNIF18V	VS42STNIM14V	VS42STNIF14V
	VS52NBR	VS52NBRIM14C	VS52NBRIF14C	VS52NBRIM14	VS52NBRIF14	VS52NBRIM18V	VS52NBRIF18V	VS52NBRIM14V	VS52NBRIF14V
	VS52SIT5	VS52SIT5IM14C	VS52SIT5IF14C	VS52SIT5IM14	VS52SIT5IF14	VS52SIT5IM18V	VS52SIT5IF18V	VS52SIT5IM14V	VS52SIT5IF14V
	VS52NR	VS52NRIM14C	VS52NRIF14C	VS52NRIM14	VS52NRIF14	VS52NRIM18V	VS52NRIF18V	VS52NRIM14V	VS52NRIF14V
	VS52STN	VS52STNIM14C	VS52STNIF14C	VS52STNIM14	VS52STNIF14	VS52STNIM18V	VS52STNIF18V	VS52STNIM14V	VS52STNIF14V
	VS62NBR	VS62NBRIM14C	VS62NBRIF14C	VS62NBRIM14	VS62NBRIF14	VS62NBRIM18V	VS62NBRIF18V	VS62NBRIM14V	VS62NBRIF14V
	VS62SIT5	VS62SIT5IM14C	VS62SIT5IF14C	VS62SIT5IM14	VS62SIT5IF14	VS62SIT5IM18V	VS62SIT5IF18V	VS62SIT5IM14V	VS62SIT5IF14V
	VS62NR	VS62NRIM14C	VS62NRIF14C	VS62NRIM14	VS62NRIF14	VS62NRIM18V	VS62NRIF18V	VS62NRIM14V	VS62NRIF14V
	VS62STN	VS62STNIM14C	VS62STNIF14C	VS62STNIM14	VS62STNIF14	VS62STNIM18V	VS62STNIF18V	VS62STNIM14V	VS62STNIF14V

Group 3		V 		S 	
Ø 88 mm	THREAD	G1/8"-M	G1/4"-M	G1/4"-F	G1/4"-M
	VS88NBR	VS88NBRIM18V	VS88NBRIM14V	VS88NBRIF14V	VS88NBRIM14
	VS88SIT5	VS88SIT5IM18V	VS88SIT5IM14V	VS88SIT5IF14V	VS88SIT5IM14
	VS88NR	VS88NRIM18V	VS88NRIM14V	VS88NRIF14V	VS88NRIM14

Additional mounting configurations are available (see page 2/47).  
For standard configurations (suction cup+fitting), the C and V versions are delivered unassembled.



# VS


## Suction Cups with 2.5 Bellows Ø 5 to 88 mm

Dimensions - "Suction Cup + Fitting"




2  
VS


### VS 5 - 9 Group 1




### VS 12 - 25 Group 1



### VS 26 - 62 Group 2



### VS 88 Group 3



Group 1	Diagram	ØA	ØD	f <sup>(1)</sup>	H	H1	ØG	G1	ØG2 <sup>(2)</sup>	E ↗	⚖(g)
Ø 5 - 25 mm	VS5---IMM3C 1	5	-	3	13.5	15.5	M3-M	3	1.4	5	0.7
	VS6---IMM3C 1	6	-	3	13.2	15.2	M3-M	3	1.4	5	0.7
	VS7---IMM5C 1	7	-	3	13.5	18.5	M5-M	4.5	2.5	7	3.5
	VS7---IMM6C 1	7	-	3	13.5	18.5	M6-M	5	3.5	7	3.1
	VS7---IM18C 1	7	-	3	13.5	19.5	G1/8"-M	7.5	3.5	14	4.5
	VS7---IF18C 2	7	-	3	13.5	25.5	G1/8"-F	8	3.5	14	4.4
	VS9---IMM5C 1	9	-	3	15	20	M5-M	4.5	2.5	7	3.7
	VS9---IMM6C 1	9	-	3	15	20	M6-M	5	3.5	7	3.3
	VS9---IM18C 1	9	-	3	15	21	G1/8"-M	7.5	3.5	14	4.8
	VS9---IF18C 2	9	-	3	15	27	G1/8"-F	8	3.5	14	4.6
	VS12---IMM5C 3	12	-	7	21	26	M5-M	4.5	2.5	7	3.2
	VS12---IMM6C 3	12	-	7	21	26	M6-M	5	3.5	7	3.8
	VS12---IM18C 3	12	-	7	21	27	G1/8"-M	7.5	3.5	14	5.2
	VS12---IF18C 4	12	-	7	21	33	G1/8"-F	8	3.5	14	5.1
	VS14---IMM5C 3	14	-	10	23	28	M5-M	4.5	2.5	7	4.6
	VS14---IMM6C 3	14	-	10	23	28	M6-M	5	3.5	7	4.2
	VS14---IM18C 3	14	-	10	23	29	G1/8"-M	7.5	3.5	14	5.6
	VS14---IF18C 4	14	-	10	23	35	G1/8"-F	8	3.5	14	5.5
	VS18---IMM5C 3	17.5	-	10	23	28	M5-M	4.5	2.5	7	5.1
	VS18---IMM6C 3	17.5	-	10	23	28	M6-M	5	3.5	7	4.7
	VS18---IM18C 3	17.5	-	10	23	29	G1/8"-M	7.5	3.5	14	6.1
	VS18---IF18C 4	17.5	-	10	23	35	G1/8"-F	8	3.5	14	6
	VS20---IMM5C 3	20	-	10	23	28	M5-M	4.5	2.5	7	5.5
	VS20---IMM6C 3	20	-	10	23	28	M6-M	5	3.5	7	5.1
	VS20---IM18C 3	20	-	10	23	29	G1/8"-M	7.5	3.5	14	6.5
	VS20---IF18C 4	20	-	10	23	35	G1/8"-F	8	3.5	14	6.4
	VS25---IMM5C 3	25	-	20	34	39	M5-M	4.5	2.5	7	7.4
	VS25---IMM6C 3	25	-	20	34	39	M6-M	5	3.5	7	7
	VS25---IM18C 3	25	-	20	34	40	G1/8"-M	7.5	3.5	14	8.4
	VS25---IF18C 4	25	-	20	34	46	G1/8"-F	8	3.5	14	8.3

Note: All dimensions are in mm.

(1) f = Deflection of the suction cup. (2) Ø G2 = Ø internal orifice of the fitting.





VS

# Suction Cups with 2.5 Bellows Ø 5 to 88 mm

Dimensions - "Suction Cup + Fitting"



Group 2		Diagram	ØA	ØD	f <sup>(1)</sup>	H	H1	ØG	G1	ØG2 <sup>(2)</sup>	E 	 (g)
Ø 26 - 62 mm	VS26---IM18V	5	25	-	11	31	35.5	G1/8"-M	6	3.5	13	20.2
	VS26---IF18V	6	25	-	11	31	44	G1/8"-F	7.5	3.5	13	23.5
	VS26---IM14	5	25	-	11	31	35	G1/4"-M	11	4.4	17	14.1
	VS26---IM14C	5	25	-	11	31	39	G1/4"-M	10	7	17	15
	VS26---IM14V	5	25	-	11	31	36	G1/4"-M	8	3.5	17	29.5
	VS26---IF14	6	25	-	11	31	46	G1/4"-F	10	4.4	17	14.7
	VS26---IF14C	6	25	-	11	31	46	G1/4"-F	12	6.9	17	14.3
	VS26---IF14V	6	25	-	11	31	47	G1/4"-F	11	3.5	17	34.1
	VS32---IM18V	5	32	-	14.5	37.5	42	G1/8"-M	6	3.5	13	22.9
	VS32---IF18V	6	32	-	14.5	37.5	50.5	G1/8"-F	7.5	3.5	13	26.2
	VS32---IM14	5	32	-	14.5	37.5	41.5	G1/4"-M	11	4.4	17	16.8
	VS32---IM14C	5	32	-	14.5	37.5	45.5	G1/4"-M	10	7	17	17.7
	VS32---IM14V	5	32	-	14.5	37.5	42.5	G1/4"-M	8	3.5	17	32.2
	VS32---IF14	6	32	-	14.5	37.5	52.5	G1/4"-F	10	4.4	17	17.4
	VS32---IF14C	6	32	-	14.5	37.5	52.5	G1/4"-F	12	6.9	17	17
	VS32---IF14V	6	32	-	14.5	37.5	53.5	G1/4"-F	11	3.5	17	36.8
	VS42---IM18V	5	42	-	22	46	50.5	G1/8"-M	6	3.5	13	32.1
	VS42---IF18V	6	42	-	22	46	59	G1/8"-F	7.5	3.5	13	35.4
	VS42---IM14	5	42	-	22	46	50	G1/4"-M	11	4.4	17	26
	VS42---IM14C	5	42	-	22	46	54	G1/4"-M	10	7	17	26.2
	VS42---IM14V	5	42	-	22	46	51	G1/4"-M	8	3.5	17	41.4
	VS42---IF14	6	42	-	22	46	61	G1/4"-F	10	4.4	17	26.6
	VS42---IF14C	6	42	-	22	46	61	G1/4"-F	12	6.9	17	26.2
	VS42---IF14V	6	42	-	22	46	62	G1/4"-F	11	3.5	17	46
	VS52---IM18V	5	52	-	27	49	53.5	G1/8"-M	6	3.5	13	38.1
	VS52---IF18V	6	52	-	27	49	62	G1/8"-F	7.5	3.5	13	41.4
	VS52---IM14	5	52	-	27	49	53	G1/4"-M	11	4.4	17	32
	VS52---IM14C	5	52	-	27	49	57	G1/4"-M	10	7	17	32.9
	VS52---IM14V	5	52	-	27	49	54	G1/4"-M	8	3.5	17	47.4
	VS52---IF14	6	52	-	27	49	64	G1/4"-F	10	4.4	17	32.6
	VS52---IF14C	6	52	-	27	49	64	G1/4"-F	12	6.9	17	32.2
	VS52---IF14V	6	52	-	27	49	65	G1/4"-F	11	3.5	17	52
	VS62---IM18V	5	62	-	31	55	59.5	G1/8"-M	6	3.5	13	51
	VS62---IF18V	6	62	-	31	55	68	G1/8"-F	7.5	3.5	13	54.3
	VS62---IM14	5	62	-	31	55	59	G1/4"-M	11	4.4	17	44.9
	VS62---IM14C	5	62	-	31	55	63	G1/4"-M	10	7	17	45.8
VS62---IM14V	5	62	-	31	55	60	G1/4"-M	8	3.5	17	60.3	
VS62---IF14	6	62	-	31	55	70	G1/4"-F	10	4.4	17	45.5	
VS62---IF14C	6	62	-	31	55	70	G1/4"-F	12	6.9	17	45.1	
VS62---IF14V	6	62	-	31	55	71	G1/4"-F	11	3.5	17	65	

## Group 3

Ø 88 mm	VS88---IM18V	9	88	25	48.5	87.5	-	G1/8"-M	8	6	-	142.8
	VS88---IM14	7	88	-	48.5	87.5	93.5	G1/4"-M	11	8	21	153.4
	VS88---IM14V	7	88	-	48.5	87.5	92.5	G1/4"-M	8	6	17	163
	VS88---IF14	8	88	-	48.5	87.5	102.5	G1/4"-F	10	8	21	130.8
	VS88---IF14V	8	88	-	48.5	87.5	106.5	G1/4"-F	9	6	17	134.7

Note: All dimensions are in mm.

(1) f = Deflection of the suction cup.

(2) Ø G2 = Ø internal orifice of the fitting.



# VS

## Suction Cups with 2.5 Bellows Ø 5 to 88 mm


### Assembly Diagrams



2  
VS


#### VS 5 - 25 Group 1

Barbed fittings




#### VS 26 - 62 Group 2


Barbed fittings



Pressed fittings




Adapters



Removable fittings




Hollow screws



#### VS 88 Group 3


Factory-cripped fittings




Removable fittings



Adapters



Hollow screws



- Configurations (suction cup + fitting) refer to page 2/44
- Non-standard configurations must be ordered in separate part numbers.

Fittings and suction cups dimension: see page 2/48.




# Suction Cups with 2.5 Bellows Ø 5 to 88 mm

## Dimensions




### Suction Cups


VS 5 - 25



VS 26 - 62




VS 88



(1) f = Deflection of the suction cup.


### Hollow Screws




	ØA	B	C	ØD	Material	Weight (g)
IM 50	M5-M	5	11	2.8	Nickel-plated brass	7.4
IM 60 <sup>(2) (3)</sup>	M6-M	7	11	3.5	Nickel-plated brass	7.3
IM 68	M8-M	8	11	5.2	Nickel-plated brass	6.5
IM 80	G1/8"-M	8	18	6	Nickel-plated brass	23.8
IM 85	M10x150-M	8	18	6	Nickel-plated brass	23.5

### Factory-Crimped Fittings

Male - IM




Female - IF




	ØA	B	C	ØD	E	Material	Weight (g)
IM 51	G1/4"-M	11	6	8	21	Aluminum	11.8
IF 50	G1/4"-F	10	15	8	21	Aluminum	15.7
IM 52	G3/8"-M	11	6	8	21	Aluminum	14

### Pressed Fittings

Male - IM



Female - IF



	ØA	B	C	ØD	E	Material	Weight (g)
IM 41	G1/4"-M	11	4	4.4	17	Aluminum	7.8
IF 40	G1/4"-F	10	15	4.4	17	Aluminum	8.4

The values represent the average characteristics of our products.


(2) Flow restrictor version available: orifice calibrated to reduce leaks when used with a multi-cup gripper (see page 4/9)

(3) Available in stainless steel


	ØA	H	Ød	ØD	f <sup>(1)</sup>	B	Weight (g)
VS 5	5	13.5	4	7	3	8	0.3
VS 6	6	13.2	4	7	3	7	0.31
VS 7	7	13.5	4.7	9	3	6	0.42
VS 9	9	15	4.4	9	3	7	0.64
VS 12	12	21	4	10	7	9	1.1
VS 14	14	23	4	10	10	9	1.5
VS 18	17.5	23	4	10	10	9	2
VS 20	20	23	4	10	10	9	2.4
VS 25	25	34	4	10	20	9	4.3
VS 26	25	31	8	16	11	13	6.3
VS 32	32	37.5	8	18	14.5	13	9
VS 42	42	46	8	18	22	13	18.2
VS 52	52	49	8	18	27	13	24.2
VS 62	62	55	8	21	31	13	37.1
VS 88	88	87.5	12	25	48.5	20	119

### Barbed Fittings

Male - IM




Female - IF




	ØA	B	C	ØD	E	Material	Weight (g)
IM 11 A	G1/8"-M	7.5	6	3.5	14	Aluminum	4.1
IMC 14	G1/4"-M	10	8	7	17	Aluminum	8.7
IM 21 <sup>(2)</sup>	M5-M	4.5	5	2.5	7	Nickel-plated brass	3.1
IM 22 <sup>(2)</sup>	M6-M	5	5	3.5	7	Nickel-plated brass	2.7
IM 23	10/32-M	4.5	5	2.5	7	Brass	3
IM 24	M5-M	4.5	2.5	2.5	10	Nickel-plated brass	3.2
IF 10 A	G1/8"-F	8	12	3.5	14	Aluminum	4
IFC 14	G1/4"-F	12	15	6.9	17	Aluminum	8

### Adapters for Hollow Screws

Male - IM



Female - IF



	ØA	B	C	ØD	E	Material	Weight (g)
IM 10 M6F	M10-M	7	3.5	M6-F	13	Brass	5.9
IM 12 F18	G1/2"-M	14	6	G1/8"-F	22	Nickel-plated brass	46.8
IM 14 M6F	G1/4"-M	8	5	M6-F	17	Nickel-plated brass	15.9
IM 14 F18	G1/4"-M	8	5	G1/8"-F	17	Nickel-plated brass	10.6
IM 18 M6F	G1/8"-M	6	4.5	M6-F	13	Nickel-plated brass	6.6
IM 38 F18	G3/8"-M	9	5	G1/8"-F	19	Nickel-plated brass	18.8
IF 14 M6F	G1/4"-F	11	16	M6-F	17	Nickel-plated brass	20.5
IF 18 M6F	G1/8"-F	7.5	13	M6-F	13	Nickel-plated brass	9.9
IF 14 F18	G1/4"-F	9	19	G1/8"-F	17	Nickel-plated brass	20.2


Note: All dimensions are in mm.



## Suction Cups with 2.5 Bellows Ø 5 and 7mm



Industry-specific applications



Types of use







The VSG series 2.5 bellows suction cups benefit from very flexible lips allowing the gripping of small concave or convex products. They are ideal for the gripping of sensitive products which require a soft lip.

Materials

**NBR** Nitrile  
**SI** Silicone  
**STN** Siton®

### Suction Cup Properties

	Ø (mm)	 (cm³)	 (lbf) <sup>(1)</sup>	 $R_{min}$ (mm)	NBR	SI	STN
<b>VSG 5</b>	5	0.03	0.08	3.5	<b>VSG5NBR</b>	<b>VSG5SI</b>	<b>VSG5STN</b>
<b>VSG 7</b>	7	0.04	0.23	4	<b>VSG7NBR</b>	<b>VSG7SI</b>	<b>VSG7STN</b>

(1) Actual force of the suction cup in use with 65% vacuum and including a safety factor of 2 for horizontal handling.

### Choice of Fittings


 (Ø)	M5-M	M5-F	G1/8"-M	G1/8"-F
5 - 7	■	■	■	■

■ Standard available configurations (suction cup + fitting) Fitting: M = male  
See part n° table below F = female

### Type of Assembly

**C**  **Version C**  
Barbed fitting

### References - "Suction Cup + Fitting"

					
Ø 5 - 7 mm	THREAD	M5-M	M5-F	G1/8"-M	G1/8"-F
	<b>VSG5NBR</b>	VSG5NBRIMM5C	VSG5NBRIFM5C	VSG5NBRIM18C	VSG5NBRIF18C
	<b>VSG5SI</b>	VSG5SIIMM5C	VSG5SIIFM5C	VSG5SIIM18C	VSG5SIIF18C
	<b>VSG5STN</b>	VSG5STNIMM5C	VSG5STNIFM5C	VSG5STNIM18C	VSG5STNIF18C
	<b>VSG7NBR</b>	VSG7NBRIMM5C	VSG7NBRIFM5C	VSG7NBRIM18C	VSG7NBRIF18C
	<b>VSG7SI</b>	VSG7SIIMM5C	VSG7SIIFM5C	VSG7SIIM18C	VSG7SIIF18C
	<b>VSG7STN</b>	VSG7STNIMM5C	VSG7STNIFM5C	VSG7STNIM18C	VSG7STNIF18C



Please specify the part n°. e.g. **VSG5NBR**  
See part n° table above

### Accessories

To optimize use of your suction cups, Coval offers a comprehensive range of accessories (sensors, spring systems, extensions, feeder systems, etc.) see chapters 4 and 12.



## Suction Cups with 2.5 Bellows Ø 5 and 7mm Dimensions



### Suction Cups + Fittings



VSG 5

2

3


VSG 7

4



	Diagram	ØA	f <sup>(1)</sup>	H	H1	ØG	G1	ØG2 <sup>(2)</sup>	E 	 (g)
VSG5-IMM5C	1	5	3	9.5	13	M5-M	4.5	2.2	7	2.6
VSG5-IFM5C	2	5	3	9.5	18.5	M5-F	6	2.2	14	3.1
VSG5-IM18C	1	5	3	9.5	14.5	G1/8"-M	8	2.2	14	5.8
VSG5-IF18C	2	5	3	9.5	24.5	G1/8"-F	9	2.2	14	7
VSG7-IMM5C	3	7	3	10	13.5	M5-M	4.5	2.2	7	0.9
VSG7-IFM5C	4	7	3	10	19	M5-F	6	2.2	14	1.4
VSG7-IM18C	3	7	3	10	15	G1/8"-M	8	2.2	14	4.1
VSG7-IF18C	4	7	3	10	25	G1/8"-F	9	2.2	14	5.3

(1) f = Deflection of the suction cup. (2) Ø G2 = Ø internal orifice of the fitting.

### Assembly Diagrams



### Suction Cups




	ØA	H	Ød	ØD	f (1)	B	⚖ (g)
VSG 5	5	9.5	4	7.5	3	4	1.9
VSG 7	7	10	4	7.5	3	4	0.24


(1) f = Deflection of the suction cup

### Barbed Fittings

#### Male - IM



#### Female - IF



	ØA	B	C	ØD	E	Material	⚖ (g)
IM 5 VPG 5	M5-M	4.5	3.5	2.2	7	Aluminum	0.7
IF 5 VPG 5	M5-F	6	9	2.2	14	Aluminum	1.2
IM 18 VPG 5	G1/8"-M	8	5	2.2	14	Aluminum	3.9
IF 18 VPG 5	G1/8"-F	9	15	2.2	14	Aluminum	5.1

The values represent the average characteristics of our products.

Note: All dimensions are in mm.



# VSD

## Long Stroke Suction Cups




Long stroke suction cups (3.5 and 4.5 bellows) are specially recommended for handling spherical or cylindrical objects or which require compensation for varying heights.

### Materials

**NBR** Nitrile  
**SIT3** 30 Shore A translucent  
**SIT5** 50 Shore A translucent silicone

### Industry-specific applications



### Types of use



### Suction Cup Properties

	Ø (mm)	Volume (cm³)	Force (lbf) <sup>(1)</sup>	R <sub>min</sub> (mm)	NBR	SIT3	SIT5
<b>VSD 18</b>	17.5	2.5	0.89	20	-	-	<b>VSD18SIT5</b>
<b>VSD 32</b>	32	21.7	2.35	35	<b>VSD32NBR</b>	<b>VSD32SIT3</b>	-

(1) Actual force of the suction cup in use with 65% vacuum and including a safety factor of 2 for horizontal handling.

### Choice of Fittings

	Group	M5-M	M6-M	M8-M	M10-M	G1/8"-F	G1/8"-M	10/32-M	G1/4"-F	G1/4"-M
<b>VSD 18</b>	<b>1</b>	■	■	-	-	■	■	□	-	-
<b>VSD 32</b>	<b>2</b>	□	□	□	□	■	■	-	■	■

■ Standard available configurations (suction cup + fitting)  
 See part n° below

□ Additional mounting configurations  
 see page 2/53

Fitting: M = male

F = female

### Types of Assembly

COVAL suction cups can be assembled in a wide variety of configurations.



**Version C:** Factory-crimped fitting



**Version E:** Pressed fitting



**Version V:** Removable fitting:  
 (adapter and hollow screw)

### References - "Suction Cup + Fitting"

#### Group 1



Ø 18	THREAD	M5-M	M6-M	G1/8"-M	G1/8"-F
<b>VSD18SIT5</b>		VSD18SIT5IMM5C	VSD18SIT5IMM6C	VSD18SIT5IM18C	VSD18SIT5IF18C

#### Group 2



Ø 32	THREAD	G1/4"-M	G1/4"-F	G1/4"-M	G1/4"-F	G1/8"-M	G1/8"-F	G1/4"-M	G1/4"-F
<b>VSD32NBR</b>		VSD32NBRIM14C	VSD32NBRIF14C	VSD32NBRIM14	VSD32NBRIF14	VSD32NBRIM18V	VSD32NBRIF18V	VSD32NBRIM14V	VSD32NBRIF14V
<b>VSD32SIT3</b>		VSD32SIT3IM14C	VSD32SIT3IF14C	VSD32SIT3IM14	VSD32SIT3IF14	VSD32SIT3IM18V	VSD32SIT3IF18V	VSD32SIT3IM14V	VSD32SIT3IF14V



Please specify the part n°. e.g. **VSD18SIT5IMM5C**  
 See part n° table above

### Accessories

To optimize use of your suction cups, Coval offers a comprehensive range of accessories (sensors, spring systems, extensions, feeder systems, etc.) see chapters 4 and 12.







#### VSD 18

#### Group 1

1




2




#### VSD 32

#### Group 2

3



4



2  
VSD

Group 1		Diagram	ØA	f <sup>(1)</sup>	H	H1	ØG	G1	ØG2 <sup>(2)</sup>	E ↗	⚖ (g)
Ø 18 mm	VSD18-IMM5C	1	17.5	18	36	41	M5-M	4.5	2.5	7	6.2
	VSD18-IMM6C	1	17.5	18	36	41	M6-M	5	3.5	7	5.8
	VSD18-IM18C	1	17.5	18	36	42	G1/8"-M	7.5	3.5	14	7.2
	VSD18-IF18C	2	17.5	18	36	48	G1/8"-F	8	3.5	14	7.1

Group 2		Diagram	ØA	f <sup>(1)</sup>	H	H1	G	G1	ØG2 <sup>(2)</sup>	E ↗	⚖ (g)
Ø 32 mm	VSD32-IM18V	3	32	34	65	69,5	G1/8"-M	6	3.5	13	29.2
	VSD32-IF18V	4	32	34	65	78	G1/8"-F	7.5	3.5	13	32.5
	VSD32-IM14	3	32	34	65	69	G1/4"-M	11	4.4	17	22.9
	VSD32-IM14C	3	32	34	65	73	G1/4"-M	10	7	17	23.8
	VSD32-IM14V	3	32	34	65	70	G1/4"-M	8	3.5	17	38.5
	VSD32-IF14	4	32	34	65	80	G1/4"-F	10	4.4	17	23.7
	VSD32-IF14C	4	32	34	65	80	G1/4"-F	12	6.9	17	23.1
	VSD32-IF14V	4	32	34	65	81	G1/4"-F	11	3.5	17	43.5

(1) f = Deflection of the suction cup. (2) Ø G2 = Ø internal orifice of the fitting.

Note: All dimensions are in mm.

Assembly diagrams  
See page 2/53.







#### VSD 18

#### Group 1



Barbed fittings





#### VSD 32

#### Group 2


Barbed fittings




Pressed fittings



Removable fittings









#### Suction Cups

VSD 18



VSD 32



	ØA	f <sup>(1)</sup>	H	Ød	ØD	B	(g)
VSD 18	17.5	18	36	4	10	9	3.1
VSD 32	32	34	65	8	18	13	15.1


(1) f = Deflection of the suction cup.

2


VSD

#### Barbed Fittings

Male - IM




Female - IF



	ØA	B	C	ØD	E	Material	(g)
IM 11 A	G1/8"-M	7.5	6	3.5	14	Aluminum	4.1
IMC 14	G1/4"-M	10	8	7	17	Aluminum	8.7
IM 21 <sup>(2)</sup>	M5-M	4.5	5	2.5	7	Nickel-plated brass	3.1
IM 22 <sup>(2)</sup>	M6-M	5	5	3.5	7	Nickel-plated brass	2.7
IM 23	10/32-M	4.5	5	2.5	7	Brass	3.0
IM 24	M5-M	4.5	2.5	2.5	10	Nickel-plated brass	3.2
IF 10 A	G1/8"-F	8	12	3.5	14	Aluminum	4.0
IFC 14	G1/4"-F	12	15	6.9	17	Aluminum	8.0


#### Hollow Screws




	ØA	B	C	ØD	Material	(g)
IM 50	M5-M	5	11	2.8	Brass	7.4
IM 60 <sup>(2) (3)</sup>	M6-M	7	11	3.5	Nickel-plated brass	7.5
IM 68	M8-M	8	11	5.2	Nickel-plated brass	6.4

#### Pressed Fittings

Male - IM




Female - IF




	ØA	B	C	ØD	E	Material	(g)
IM 41	G1/4"-M	11	4	4.4	17	Aluminum	7.8
IF 40	G1/4"-F	10	15	4.4	17	Aluminum	8.6

#### Adapters for Hollow Screws

Male - IM



Female - IF



	ØA	B	C	ØD	E	Material	(g)
IM 10 M6F	M10-M	7	3.5	M6-F	13	Brass	5.9
IM 14 M6F	G1/4"-M	8	5	M6-F	17	Nickel-plated brass	15.9
IM 18 M6F	G1/8"-M	6	4.5	M6-F	13	Nickel-plated brass	6.6
IF 14 M6F	G1/4"-F	11	16	M6-F	17	Nickel-plated brass	20.5
IF 18 M6F	G1/8"-F	7.5	13	M6-F	13	Nickel-plated brass	9.9

The values represent the average characteristics of our products.

Note: All dimensions are in mm.

(2) Flow restrictor version available: orifice calibrated to reduce leaks when used with a multi-cup gripper (see page 4/9).

(3) Available in stainless steel.



# C


## High-performance Suction Cups



The **C series** high-performance suction cup range has been designed to meet the requirements of the automotive sector. The improved characteristics of the **C series** range optimizes production tools in all branches of activity.

- A full range of shapes and diameters to meet every requirement.
- Non-slip cleats ensure optimum positioning of oily metal sheets.
- Textured suction cups for gripping thin sheets without deforming them.
- Ideal for automated applications.
- Specifically for use in the fields of stamping and welding.

Industry-specific applications



Types of use



### Characteristics

- Extreme resistance to slipping.
- Gripping of thin metal sheets without deforming them, thanks to the central cleats.
- Elastomer and glass-fibre reinforced plastic design to avoid any risk of damaging costly equipment and to facilitate recycling.
- Double tightening: 2 wrenches of 22 mm and 1 hex key of 6 mm or 8 mm.
- Air-tight fittings using:
  - O-rings on 3/8G male cylindrical suction cups 32 square suction cups,- sealing on all oblong 3/8 male suction cups.
- Traceability.

### Materials

The **C series** vacuum cups are made of a nitrile elastomer and the fittings (M38G/ F38G) are polyamide reinforced with fiberglass.

These materials guarantee the vacuum cups' long life, strong oil resistance and heat tolerance of up to 212°F.

This approach helps to avoid any risk of damaging costly equipment and facilitates recycling of vacuum cups.

Suction cups: **NBR** - Nitrile 55 Shore A (high resistance to oils), grey color.

Fitting: **PA** - Polyamide PA 6.6 ensuring reduced weight (3/8G / F38G Male or Female fitting).

**AL** - Aluminum (F38GA / C32 fitting).

O-ring: **NBR** - Nitrile blue  
Other fittings available on request.

More information



### Range

The **C Series** high performance vacuum cups are available in a full range of shapes, dimensions and connections in order to meet all your needs in the most appropriate way.

#### Models

**CFC** flat suction cup



**CBC** suction cup with 1.5 bellows



**COFC** flat oblong suction cup



**COBC** oblong suction cup with 1.5 bellows



#### Fittings

**M38G** male fitting G3/8"



**F38G** female fitting G3/8"



**F38GA** aluminum female fitting G3/8"



**C32** square coupling 32 mm



#### Accessories

To optimize use of your suction cups, Coval offers a comprehensive range of accessories (3/8G extensions, feeders and special couplings for 100% air-tight vacuum networks,) see chapters 4 and 12.



Please specify the part n°. e.g. **CBC85M38G**  
Refer to page 2/56



# C

## High-performance Suction Cups

### References - Suction Cups



#### CFC Flat Suction Cup



##### Fittings

	M38G	F38G	F38GA	C32
<b>CFC35</b>	CFC35M38G	CFC35F38G	CFC35F38GA	CFC35C32
<b>CFC50</b>	CFC50M38G	CFC50F38G	CFC50F38GA	CFC50C32
<b>CFC75</b>	CFC75M38G	CFC75F38G	CFC75F38GA	CFC75C32
<b>CFC100</b>	CFC100M38G	CFC100F38G	CFC100F38GA	CFC100C32
<b>CFC125</b>	CFC125M38G	CFC125F38G	CFC125F38GA	CFC125C32

2



#### CBC Suction Cup with 1.5 Bellows



##### Fittings

	M38G	F38G	F38GA	C32
<b>CBC22</b>	CBC22M38G	CBC22F38G	CBC22F38GA	CBC22C32
<b>CBC30<sup>(1)</sup></b>	CBC30M38G	CBC30F38G	CBC30F38GA	CBC30C32
<b>CBC45</b>	CBC45M38G	CBC45F38G	CBC45F38GA	CBC45C32
<b>CBC60</b>	CBC60M38G	CBC60F38G	CBC60F38GA	CBC60C32
<b>CBC85</b>	CBC85M38G	CBC85F38G	CBC85F38GA	CBC85C32
<b>CBC115</b>	CBC115M38G	CBC115F38G	CBC115F38GA	CBC115C32

#### COFC Flat Oblong Suction Cup



##### Fittings

	M38G	F38G	F38GA	C32
<b>COFC2565</b>	COFC2565M38G	COFC2565F38G	COFC2565F38GA	COFC2565C32
<b>COFC3080</b>	COFC3080M38G	COFC3080F38G	COFC3080F38GA	COFC3080C32
<b>COFC4080</b>	COFC4080M38G	COFC4080F38G	COFC4080F38GA	COFC4080C32
<b>COFC50100</b>	COFC50100M38G	COFC50100F38G	COFC50100F38GA	COFC50100C32

#### COBC Oblong Suction Cup with 1.5 Bellows



##### Fittings

	M38G	F38G	F38GA	C32
<b>COBC3065</b>	COBC3065M38G	COBC3065F38G	COBC3065F38GA	COBC3065C32
<b>COBC4080</b>	COBC4080M38G	COBC4080F38G	COBC4080F38GA	COBC4080C32
<b>COBC55110</b>	COBC55110M38G	COBC55110F38G	COBC55110F38GA	COBC55110C32
<b>COBC70140</b>	COBC70140M38G	COBC70140F38G	COBC70140F38GA	COBC70140C32

#### (1) CBC 30 M38G SP624

In order to meet the specific needs of end-of-arm tooling users in Stamping, COVAL has designed a Ø 30 mm suction cup, with an extra-large Ø 9.5 mm air-flow, thus removing pressure drops in the vacuum network of the gripper's power supply.








# High-performance Suction Cups

## Suction Cup Properties





### CFC Flat Suction Cup





		ØA at rest	ØA gripping						Ø bore	tightening
				(cm <sup>3</sup> )	(lbf) <sup>(1)</sup>	(lbf) <sup>(1)</sup>	R <sub>min</sub>	R <sub>min</sub>		
CFC 35		37	38.5	2.46	11.24	11.24	58	50	6.3	w 22 + hk 6
CFC 50		51	54	8.37	22.48	22.48	66	52	6.3	w 22 + hk 6
CFC 75		76	80	25.03	44.96	38.22	100	58	6.3	w 22 + hk 6
CFC 100		101	105.7	57.61	78.68	60.70	120	90	6.3	w 22 + hk 6
CFC 125		127	132	119.7	123.64	107.90	160	115	6.3	w 22 + hk 8

		H1	f <sup>(3)</sup>	G1	G1'	ØD	(g)			
							F38G	F38GA	M38G	C32
CFC 35		25	3	10	12.6	37	14	25.7	18	36.2
CFC 50		30	5.5	10	12.6	38	25	34.9	29	47.2
CFC 75		33	8	10	12.6	41	40	48.9	45	62.2
CFC 100		38	10	10	12.6	41	67	75.3	72	89.2
CFC 125		44	14	10	12.6	55	119	146	124	141.2





### CBC Suction Cup with 1.5 Bellows



		ØA at rest	ØA gripping						Ø bore	tightening
				(cm <sup>3</sup> )	(lbf) <sup>(1)</sup>	(lbf) <sup>(1)</sup>	R <sub>min</sub>	R <sub>min</sub>		
CBC 22		21.5	22	1.6	3.82	3.82	25	30	6.3	w 22 + hk 6
CBC 30 <sup>(2)</sup>		32	34	5	8.99	8.99	30	32	6.3	w 22 + hk 6
CBC 45		47	48.7	11.47	15.74	20.23	36	45	6.3	w 22 + hk 6
CBC 60		62	64.5	25.31	31.47	29.22	44	62	6.3	w 22 + hk 6
CBC 85		85	88	66.54	51.70	53.95	65	115	6.3	w 22 + hk 6
CBC 115		115	119	141.47	94.42	87.67	84	140	6.3	w 22 + hk 8

		H1	f <sup>(3)</sup>	G1	G1'	ØD	(g)			
							F38G	F38GA	M38G	C32
CBC 22		32	6	10	12.6	37	10	23	14	32.2
CBC 30 <sup>(2)</sup>		31	8	10	12.6	37	14	26.3	19	36.2
CBC 45		36	11	10	12.6	37	22	31.5	26	44.2
CBC 60		41	14	10	12.6	39	32	42	37	54.2
CBC 85		51	22	10	12.6	41	64	71.2	69	86.2
CBC 115		53	24	10	12.6	55	103	131.1	107	125.2



(1) Force measured at 65% on dry, smooth, flat sheet metal, without safety factor.

(2) A specific model of the CBC 30 is available with M 3/8G fitting and 9.5mm diameter bore: **CBC30 M38G SP624**. (3) f: deflection of the suction cup. Note: All dimensions are in mm.




# C







## High-performance Suction Cups


### Suction Cup Properties






#### COFC Flat Oblong Suction Cup




		I x L	I x L	 (cm <sup>3</sup> )	 (lbf) <sup>(1)</sup>	 (lbf) <sup>(1)</sup>	 R <sub>min</sub>	 R <sub>min</sub>	Ø bore	tightening
COFC 2565		25x65	26.8x67	3.78	15.74	15.74	25	25	6	hk 6
COFC 3080		30x80	31.5x82	6.08	24.73	20.23	40	32	6	hk 6
COFC 4080		40x80	42x82	11.03	31.47	26.98	60	40	6	hk 6
COFC 50100		50x100	52.5x102.5	22.25	51.70	53.95	70	50	6	hk 6




		H1	H	G1	G1'	f <sup>(2)</sup>	 (g)			
							F38G	F38GA	M38G	C32
COFC 2565		31.5	12.5	8	10	3	24	35	17	35
COFC 3080		32	13	8	10	3	29	45	22	40
COFC 4080		34	15	8	10	4.5	30	45.5	23	41
COFC 50100		35	16	8	10	6	43	72.7	36	54



F38G/F38GA Female fitting G3/8"










M38G Male fitting G3/8"






C32 Square coupling 32


#### COBC Oblong Suction Cup with 1.5 Bellows




		I x L at rest	I x L gripping	 (cm <sup>3</sup> )	 (lbf) <sup>(1)</sup>	 (lbf) <sup>(1)</sup>	 R <sub>min</sub>	 R <sub>min</sub>	Ø bore	tightening
COBC 3065		31x65	32.3x67	9.98	13.49	13.49	25	30	6	hk 6
COBC 4080		40x80	41.5x82	19.44	24.73	26.98	38	37	6	hk 6
COBC 55110		55x110	57x112.5	49.25	38.22	42.71	58	57	6	hk 6
COBC 70140		70x140	72x143	93.57	67.44	67.44	72	68	6	hk 6




		H1	H	G1	G1'	f <sup>(2)</sup>	 (g)			
							F38G	F38GA	M38G	C32
COBC 3065		39	20	8	10	7	31	45.5	25	43
COBC 4080		41	22	8	10	9	37	53.1	31	49
COBC 55110		48	29	8	10	13	68	95.1	62	80
COBC 70140		49	30	8	10	16	103	121.4	97	115



F38G/F38GA Female fitting G3/8"



M38G Male fitting G3/8"



C32 Square coupling 32

The values represent the average characteristics of our products.

(1) Force measured at 65% on dry, smooth, flat sheet metal without safety factor.

(2) f = deflection of the suction cup.

Note: All dimensions are in mm.




# VSA-VS BM

## Suction Cups with Foam Ring Seals



Industry-specific applications



Types of use



The VSA and VS series suction cups equipped with VSBM foam rings are suitable for gripping products with rough surfaces. For example...

- sawn wood, sheet metal, flat surfaces with holes.
- Any rough surfaces for which the suction cups' lips do not seal properly.

Materials







**NBR** Nitrile      **SIT5** Translucent silicone      **SI** Silicone

### Specifications

Some suction cup models are available with a foam ring:

- **VSA series:** Standard 1.5 bellows suction cups, Ø 20 to 78 mm in nitrile (NBR) or in transparent silicone (SIT5).
- **VS series:** Standard 2.5 bellows suction cups, Ø 20 to 78 mm in nitrile (NBR) or in transparent silicone (SIT5).
- Foam ring in nitrile for nitrile suction cups (good resistance to oil).
- Foam ring in silicone (SI) for transparent suction cups (SIT5) and silicone glue. (Resistant up to 320°F and leaves no marks on gripped products. Do not use for gripping of products before painting or lacquering.)
- Assembling: foam rings are factory-bonded onto suction cup lips.


### Suction Cup Properties

	Ø (mm)	 (cm³)		 (lbf) <sup>(1)</sup>	NBR	SIT5 / SI		Ø (mm)	 (cm³)		 (lbf) <sup>(1)</sup>	NBR	SIT5 / SI
		NBR	SIT5 / SI						NBR	SIT5 / SI			
VSA 20	20	-	1.3	1.26	-	VSA20SIT5BM	VS 20	20	-	2.2	1.03	-	VS20SIT5BM
VSA 25	25	-	3.4	1.37	-	VSA25SIT5BM	VS 25	25	-	5.7	1.46	-	VS25SIT5BM
VSA 26	26	-	4.2	2.43	-	VSA26SIT5BM	VS 26	26	-	6.4	2.43	-	VS26SIT5BM
VSA 33	33	6.7	5.3	3.12	VSA33NBRBM	VSA33SIT5BM	VS 32	32	11.9	10.6	2.72	VS32NBRBM	VS32SIT5BM
VSA 43	43	12.3	10.8	4.54	VSA43NBRBM	VSA43SIT5BM	VS 42	42	22.6	21.1	4.70	VS42NBRBM	VS42SIT5BM
VSA 53	53	34.8	30.5	9.58	VSA53NBRBM	VSA53SIT5BM	VS 52	52	44.6	40.3	6.50	VS52NBRBM	VS52SIT5BM
VSA 63	63	52.9	45.9	13.31	VSA63NBRBM	VSA63SIT5BM	VS 62	62	86.4	79.4	9.26	VS62NBRBM	VS62SIT5BM
VSA 78	78	102.4	87.5	24.68	VSA78NBRBM	VSA78SIT5BM	VS 88	88	201.3	181.1	29.88	VS88NBRBM	VS88SIT5BM


(1) Actual force of the suction cup in use with a 65% vacuum and including a safety factor of 2 for horizontal handling.

### Dimensions

VSA-BM 20-78



VS-BM 20-88



	ØA	Øa	Ød	ØD	B	NBR					⬆ (g)	SIT5 / SI					⬆ (g)
						ØA1	C	H	f <sup>(2)</sup>			ØA1	C	H	f <sup>(2)</sup>		
<b>VSA 20 ... BM</b>	20	20	4	10	9	-	-	-	-	-	10	2	18	6.0	1.9		
<b>VSA 25 ... BM</b>	25	25	4	10	9	-	-	-	-	-	13	2	25	13.0	3.3		
<b>VSA 26 ... BM</b>	25	30	8	16	13	-	-	-	-	-	13	2	27	7.0	5		
<b>VSA 33 ... BM</b>	32	36.2	8	18	13	22	5	32.5	13.5	7.3	19	2	29.5	12.0	7.5		
<b>VSA 43 ... BM</b>	42	46	8	18	13	28	5	33	15.0	12.5	20	5	33	15.0	14		
<b>VSA 53 ... BM</b>	53	59	8	18	13	33	10	44	20.0	23.6	33	5	39	17.5	23.7		
<b>VSA 63 ... BM</b>	62	67	8	18	13	42	10	44	20.0	27.8	42	5	39	17.5	28.4		
<b>VSA 78 ... BM</b>	78	83	12	25	20	58	10	56.8	19.0	62.1	54	5	51.8	16.5	63.6		
<b>VS 20 ... BM</b>	20	-	4	10	9	-	-	-	-	-	10	2	25	11.0	2.6		
<b>VS 25 ... BM</b>	25	-	4	10	9	-	-	-	-	-	13	2	36	21.0	4.6		
<b>VS 26 ... BM</b>	25	-	8	16	13	-	-	-	-	-	13	2	33	12.0	6.6		
<b>VS 32 ... BM</b>	32	-	8	18	13	22	5	42.5	17.0	9.3	19	2	39.5	15.5	9.5		
<b>VS 42 ... BM</b>	42	-	8	18	13	28	5	51	24.5	18.9	20	5	51	24.5	20.4		
<b>VS 52 ... BM</b>	53	-	8	18	13	33	10	59	32.0	26.9	33	5	54	29.5	27		
<b>VS 62 ... BM</b>	62	-	8	21	13	42	10	65	36.0	37.1	42	5	60	33.5	40.5		
<b>VS 88 ... BM</b>	88	-	12	25	20	68	10	97.5	53.5	123.6	64	5	92.5	51.0	125.4		

(2) f = Deflection of the suction cup.

Note: All dimensions are in mm.

The values represent the average characteristics of our products.



Please specify the part n°. e.g. **VS42NBRBM**  
See part n° table above

**Selection of fittings:** please refer to fittings which are available in the suction cup series. **VSA series:** page 2/25, **VS series:** page 2/43.



# VSBM


## Foam Rings



The foam ring is designed for gripping products with an uneven or ridged surface, e.g.

- Sawn wood, sheet metal, flat surfaces with bumps or hollows.
- All granular surfaces to which suction cups cannot adhere correctly and therefore cannot be airtight.

Industry-specific applications



Types of use





Materials

**NBR** Nitrile      **SIT5** Translucent silicone      **SI** Silicone


### Operating Characteristics of the Materials

- **Nitrile (NBR - Black)**  
5 or 10mm thick, depending on the diameters of the suction cups.  
Good resistance to oil.  
The nitrile foam strip can only be bonded to nitrile suction cups.
- **Silicone (SI - White)**  
2 or 5 mm thick, depending on the diameters of the suction cups.  
Heat-resistant up to 320°F, does not leave marks on products handled.  
Do not use the silicone foam strip for gripping products before painting or lacquering.  
The silicone foam strip can only be bonded onto silicone suction cups (bonding is guaranteed if it is carried out in the factory).
- **Mounting**  
The foam rings are mounted by bonding. In all cases, this should be performed in our factory as we have the adhesives adapted to the materials. It is essential that bonding of silicone be carried out in the COVAL factory.

### Foam Ring Characteristics

NBR						SI					
Part Nr.	ØA	ØA1	C	f <sup>(1)</sup>	 (g)	Part Nr.	ØA	ØA1	C	f <sup>(1)</sup>	 (g)
VSBM32	32	22	5	2.5	0.3	VSBM20SI	20	10	2	1.0	0.2
VSBM42	42	28	5	2.5	0.7	VSBM25SI	25	13	2	1.0	0.4
VSBM53	53	33	10	5.0	2.7	VSBM32SI	32	19	2	1.0	0.5
VSBM62	62	42	10	5.0	2.8	VSBM42SI	42	20	5	2.5	2.2
VSBM78	78	58	10	5.0	3.7	VSBM53SI	53	33	5	2.5	2.8
VSBM88	88	68	10	5.0	4.6	VSBM62SI	62	42	5	2.5	3.4
						VSBM78SI	88	64	5	2.5	5.2
						VSBM88SI	88	64	5	2.5	6.4

Note: Suction cups with bellows are preferable when foam rings are required, as the slope of the lips is better suited to this type of grip. Please consult us for other models based on quantities.



Please specify the part n°. e.g. VSBM32SI  
See part n° table above

The values represent the average characteristics of our products.

(1) f = Deflection of the suction cup.

Note: All dimensions are in mm.



# Special Purpose Suction Cups

## Chapter 3

### Special Purpose Suction Cups

Thanks to its technological strength and collaboration with its customers in different industries, COVAL supplies a varied range of special purpose suction cups. E.g. handling eggs, CDs, bottles, paper, cakes, sheet metal at high speed, etc.

#### VPSC



#### Ultra-flat, Non-Marking Suction Cups

- Ultra flat suction cups
- Ø 40 and 80 mm
- 2 materials
- Suction cup specially designed not to deform the gripped product.
- Vacuum distributed across the entire surface of the suction cup for optimal gripping force.
- Extra-thin sealing lip designed to contour to the shape of the product being handled

P 3/5

#### FPC



#### FlowPack Suction Cups

- Flexible suction cups
- 3 models
- Food-safe materials
- Silicone: FDA and CE standard
- Range specially designed for gripping flexible packaging
- Thin and wavy lips mold perfectly to any shape of packaging
- Gripping ability allows for high production rates

P 3/6

#### MVS



#### Soft Suction Cups for High Speed Applications

- Suction cups with 1.5 and 2.5 bellows
- 9 models
- Silicone: FDA and CE standard
- Used to grip delicate objects. Very flexible lip (opening bags, gripping tins and flexible aluminum or plastic bottles, etc.).
- High throughput rate
- Used to grip of flexible products

P 3/9

#### VSAF



#### Suction Cup for Cheese

- Suction cup with 1.5 bellows
- Ø 50 mm
- Silicone: FDA and CE standard
- Suction cup specially designed for gripping fragile foods such as soft cheese
- Accessory: Stainless steel grill prevents deformation of the food

P 3/11

#### VSAOF



#### Oblong Suction Cup for Cheese

- Oval suction cup with 1.5 bellows
- Dim. 65x150 mm
- Silicone: FDA and CE standard
- Suction cup specially designed for gripping fragile foods such as soft cheese
- Accessory: Stainless steel grill prevents deformation of the food

P 3/12

#### VSD VSE VSP



#### Suction Cups For Bakery Applications

- Suction cups with 2.5 to 5.5 bellows
- 11 models
- Silicone: FDA and CE standard
- Range specially developed for gripping delicate objects such as cakes (buns, biscuits, etc.)
- Specific shapes and shore A hardness depending on the applications
- Resistance to temperature: - 40 °F to 428 °F

P 3/13



# Special Purpose Suction Cups

## Chapter 3

### VSO



#### Suction Cups for Egg-Handling

- Suction cups with 2.5 and 3.5 bellows
- 3 models
- Silicone: FDA and CE standard 1935/2004
- Range specially designed to meet constraints involved when handling eggs.
- Very flexible lip
- Different shapes of suction cup

P 3/15

3

### VBO



#### Suction Cup for Bottle Handling via the Punt

- Suction cup system comprised of a 62mm cup with 2.5 bellows and a silicone gripping disc (COVAL-Flex).
- The VBO suction cup system is designed for gripping bottles by the punt on disgorging stations.
- Excellent sealing when gripping different types of bottles.

P 3/16

### VSBO VSBO+



#### Suction Cups for Bottle Handling

- Suction cups with 4.5 bellows
- 3 models
- High tensile force
- Highly flexible and long stroke
- Used to grip 750 ml bottles and Magnums.
- Bottles gripped from the side, vertical and horizontal handling
- Suction cup with stainless steel reinforcement in the bellows
- Available with integrated sensing valve

P 3/17

### VPA




#### Suction Cups for Paper Applications

- Flat suction cups
- 9 models
- Very flexible lip
- Materials: natural rubber and silicone (food compatibility)
- Range of suction cups with very flexible lip used to handle very flexible materials
- Very resistant to abrasion (for paper, cardboard)
- Very flexible gripping lip which molds to the shape of the object to be handled

P 3/21

### VPAL



#### Suction Cups for Labels

- Extra-flat shape suction cups
- 3 models
- Material: silicone (food compatibility)
- The VPAL suction cups are especially adapted for gripping and handling IML labels or flexible materials
- Great lip flexibility

P 3/23

### VPR



#### Suction Cups for Mailing Applications

- Flat suction cups
- 4 models
- Material: natural rubber
- Range of suction cups designed to meet the requirements of mailing applications
- Envelope stuffing, film-wrapping, mailing (picking)
- Very resistant to abrasion

P 3/25



# Special Purpose Suction Cups

## Chapter 3

3

### VPAG



#### Rounded Suction Cups

- Curved suction cups
- 2 models
- Material: natural rubber
- Thanks to very flexible lips and a curved shape, the VPAG range is adapted to gripping flexible materials such as labels or sheets of paper - or textured objects
- Very resistant to abrasion

P 3/26

### VPYR




#### Radial Ball-joint Suction Cups

- Flat suction cups with axial ball-joint system
- 4 models (Ø50 to 100mm)
- Materials: nitrile and silicone
- The range of ball-joint suction cups is recommended for gripping curved or rotating products which requires a lot of force and mechanical resistance

P 3/27

### SPL



#### Heavy Load Suction Cups

- "Heavy load" flat suction cups
- 5 models (Ø240 to 600mm)
- Materials: nitrile and silicone
- SPL suction cups are used to handle heavy loads such as sheet metal or glass panels. They have internal cleats allowing them to handle thin metal sheets without distorting them and for vertical handling (non-slip)

P 3/28

### Steel



#### Steel Suction Cups

- Flat suction cups with a bonded foam seal
- 9 round models (Ø 150 to 580 mm)
- 9 rectangular models (175x115 to 705x385mm)
- For horizontal handling of heavy loads (thick sheet metal) or objects with an uneven surface such as concrete slabs, wood, etc.
- Wide choice of dimensions

P 3/29



# Special Purpose Suction Cups


## Chapter 3

---





Industry-specific applications



Types of use



More information



Developed through partnerships with the composite material industry, the VPSC suction cups are dedicated to the handling of raw composite. Their ultra-flat profile and innovative system of vacuum distribution across the surface of the cups provide optimized gripping with no mark and no deformation. The extra thin sealing lip contours to the product shape without restriction.

The specific characteristics of these suction cups enable its use in other fields such as cheese handling or other fragile, easily deformed products.

The VPSC cups are available in two materials to meet all the applications:

- Polyurethane (PU), high resistance to hydrocarbons and high durability.
- Silicone (SIBL5), food compliance. FDA and CE 1935/2004 standards.

The VPSC suction cups are equipped with a G1/4" female pressed aluminum fitting.

### Materials

**PU** Polyurethane 60 Shore A

**SIBL5** Blue Silicone 50 Shore A


### Suction Cup Characteristics

	Ø (mm)	cm <sup>3</sup>	(lbf) <sup>(1)</sup>	(lbf) <sup>(1)</sup>	PU	SIBL5
<b>VPSC 40</b>	40	5.6	6.07	3.37	<b>VPSC40PUIF14</b>	<b>VPSC40SIBL5IF14</b>
<b>VPSC 80</b>	80	11.2	20.82	10.41	<b>VPSC80PUIF14</b>	<b>VPSC80SIBL5IF14</b>

(1) Actual force of the suction cup in use with 65% vacuum and including a safety factor of 2 for horizontal handling and a factor of 4 for vertical handling.

When used on deformable materials, the indicated forces may require more consideration. Please contact us, particularly for composite applications.

### Suction Cup Dimensions



	Ø A	Ø D	f <sup>(2)</sup>	H	H1	Ø G	E	(g)
<b>VPSC 40</b>	40	21	1.5	21.8	33.8	G1/4"-F	17	16
<b>VPSC 80</b>	80	22	4	23.8	35.8	G1/4"-F	17	26

(2) f = Deflection of the suction cup.



Specify the part number e.g.: VPSC80PUIF14  
Please refer to the characteristics table above

The values represent the average characteristics of our products.  
Note: All dimensions are in mm



# FPC

## FlowPack Suction Cups



Combining great flexibility and food compatibility, the new FPC Series suction cups have been specially designed to optimize the handling of packed bags from 100 g to 5 kg. E.g. - FlowPack, DoyPack, etc.

- Its gripping ability allows for high production rates.
- No interruption in the packaging line due to faulty gripping.
- Suction cup made of silicone, a material that is recommended for its temperature resistance and food safety (FDA and CE 1935/2004).
- Energy Savings: the airtightness of FPC Series suction cups avoids the need for an oversized vacuum generator.

Different forms and dimensions for a suitable solution.


- Round Ø 35 1.5 bellows, Round Ø 60 mm or elliptical 120 x 100 mm.

### Applications

The FPC series suction cups are dedicated to the handling of flexible packaging such as FlowPack, Doypack, etc. :

- FlowPack < 0.5 kg: suction cup Ø 35 mm, FPC351.5.
- FlowPack < 1.5kg: suction cup Ø 60 mm, FPC60.
- FlowPack ≤ 5 kg: elliptical suction cup 120x100 mm, FPC120100.

Industry-specific applications



Types of use



More information



Materials

Suction cups: **SIBL3** Blue silicone 35 Shore A  
**SIBL5** Blue silicone 50 Shore A

Fittings: Plastic POM-C and PETP

Flat seal: Silicone

Screw: Stainless steel


FPC suction cups are compatible with FDA food standards (FDA 21 CFR 177.2600.) and meet the European regulation (EC) 1935/2004.

3  
FPC




### Innovations

The shape of the lip has been designed to match the deformation of flexible packaging and ensure the best possible seal during positioning; which, as an additional advantage, allows for a reduction in power of the vacuum generator. The FPC suction cups are also equipped with cleats that stiffen the lip and reinforce the clamping effect.

- 1 Thin and wavy flower-shaped lips that perfectly mold to the packaging, whatever the shape.
- 2 Internal cleats that allow for optimized vacuum while preventing any crushing and also strengthen the hold on the product being handled.
- 3 Fittings featuring a lateral vacuum distributor that prevent any loss in efficiency when the product is held.
- 4 Materials: Food-grade silicone and plastic insert meets FDA and CE standards.



### Suction Cup characteristics

	Dim. (mm)	 (cm <sup>3</sup> )	 (lbf) <sup>(1)</sup>	SIBL3	SIBL5
				Part number suction sup + fitting	Part number suction sup + fitting
FPC351.5...IF14PC	Ø 35	7.2	1.12	FPC351.5SIBL3IF14PC	FPC351.5SIBL5IF14PC
FPC60...IF38PC	Ø 60	24.5	3.37	FPC60SIBL3IF38PC	FPC60SIBL5IF38PC
FPC120100...IF38P1V	120x100	167	11.24	FPC120100SIBL3IF38P1V	FPC120100SIBL5IF38P1V

(1) Force measured at 65% vacuum, without safety factor.

### Range

FPC351.5...IF14PC

Round Ø 35 mm 1.5 bellows



FPC60...IF38PC

Round Ø 60 mm



FPC120100...IF38P1V

Elliptical 120 x 100 mm








Specify the part number e.g.: FPC60SIBL3IF38PC  
Please refer to the characteristics table above





#### Suction Cup + fitting



	Ø A	Ø D	L	I	f <sup>(1)</sup>	H	H1	Ø G	E	 (g)
<b>FPC351.5...IF14PC</b>	35	23	-	-	10	29	36	G1/4"-F	19	9.9
<b>FPC60...IF38PC</b>	60	40	-	-	10	26	33	G3/8"-F	26	21.5
<b>FPC120100...IF38P1V</b>	-	-	120	100	15	32.5	42.5	G3/8"-F	-	92.1

(1) f = Deflection of the suction cup

#### Mounting Configurations

##### FPC351.5 / FPC60

Via connection:


- FPC351.5 : G1/4"-F
- FPC60 : G3/8"-F



##### FPC120100

From below:

2 M5x20 screws(not included)



From above:

2 M6x16 screws(not included)



The values represent the average characteristics of our products.  
Note: All dimensions are in mm



## FlowPack Suction Cups

### Part Configurations



#### FPC351.5

Ø 35 mm 1.5 bellows

##### COMPLETE PART CONFIGURATION

SUCTION CUP

+

UPPER G1/4"-F FITTING

+

LOWER PLATE:

Hardness 35 Shore

**FPC351.5SIBL3IF14PC**

Hardness 50 Shore

**FPC351.5SIBL5IF14PC**



##### INDIVIDUAL PART REFERENCE

UPPER G1/4"-F FITTING ONLY:  
**IF14PFPC35**

SUCTION CUP ONLY:  
Hardness 35 Shore  
**FPC351.5SIBL3**  
Hardness 50 Shore  
**FPC351.5SIBL5**

LOWER PLATE ONLY  
**IL1PFPC35**

#### FPC60

Ø 60 mm

##### COMPLETE PART CONFIGURATION

SUCTION CUP

+


G3/8"-F FITTING:

Hardness 35 Shore

**FPC60SIBL3IF38PC**

Hardness 50 Shore

**FPC60SIBL5IF38PC**



##### INDIVIDUAL PART REFERENCE

G3/8"-F FITTING ONLY:  
**IF38PFPC60**

SUCTION CUP ONLY:  
Hardness 35 Shore  
**FPC60SIBL3**  
Hardness 50 Shore  
**FPC60SIBL5**

#### FPC120100

Elliptical 120 x 100 mm

##### COMPLETE PART CONFIGURATION

SUCTION CUP

+

LOWER PLATE

+

UPPER PLATE G3/8"-F

+


FLAT SEAL:

Hardness 35 Shore

**FPC120100SIBL3IF38P1V**

Hardness 50 Shore

**FPC120100SIBL5IF38P1V**



##### INDIVIDUAL PART REFERENCE

UPPER PLATE G3/8"-F + FLAT SEAL:  
**IF38PFPC120**

SUCTION CUP ONLY:  
Hardness 35 Shore  
**FPC120100SIBL3**  
Hardness 50 Shore  
**FPC120100SIBL5**

LOWER PLATE + 2 STAINLESS SCREWS M4x16:  
**IL1PFPC120**






COVAL has designed a range of high performance cups in order to meet demanding industry requirements for gripping soft or flexible products at high speeds.

- Soft, thin sealing lip and optional cleats provide a perfect grip during high work rates for all types of flexible shapes and materials.
- Food-grade silicone meets FDA and CE 1935/2004 standards.
- Available in 1.5 and 2.5 bellows.
- Available in Ø 20-40 mm.

### Applications

This flexibility allows for high speed gripping of all types of materials and foods: FlowPack, DoyPack, thermoformed food trays, raw materials (sausage, fresh fish, cookies, chocolates)...Speeds of 120 or more grip and release cycles per minute.

Industry-specific applications



Types of use



More information






### Materials

**SIB** 35 Shore A white silicone

**SIT5** 50 Shore A Translucent silicone

### Suction Cup Characteristics

	Ø (mm)	 (cm³)	 (lbf) <sup>(1)</sup>	SIB	SIT5	Fittings		
				Reference	Reference	G1/8"-M	G1/4"-M	G1/4"-F
<b>MVS202.5</b>	20	4	0.70	<b>MVS202.5SIB</b>	<b>MVS202.5SIT5</b>	IM18SP1251	-	-
<b>MVS202.5...C</b>	20	4	0.74	<b>MVS202.5SIBC</b>	<b>MVS202.5SIT5C</b>	IM18SP1251	-	-
<b>MVS301.5</b>	30	7	1.75	<b>MVS301.5SIB</b>	<b>MVS301.5SIT5</b>	-	IM51SP143	IF50SP143
<b>MVS301.5...C</b>	30	7	2.27	<b>MVS301.5SIBC</b>	<b>MVS301.5SIT5C</b>	-	IM51SP143	IF50SP143
<b>MVS302.5</b>	30	11.2	1.71	<b>MVS302.5SIB</b>	<b>MVS302.5SIT5</b>	-	IM51SP143	IF50SP143
<b>MVS302.5...G</b>	30	11.2	1.71	<b>MVS302.5SIBG</b>	<b>MVS302.5SIT5G</b>	-	IM51SP143	IF50SP143
<b>MVS302.5...C</b>	30	11.2	1.91	<b>MVS302.5SIBC</b>	<b>MVS302.5SIT5C</b>	-	IM51SP143	IF50SP143
<b>MVS401.5...C</b>	40	7.3	2.85	<b>MVS401.5SIBC</b>	<b>MVS401.5SIT5C</b>	-	IM51SP143	IF50SP143
<b>MVS402.5...C</b>	40	13	1.84	<b>MVS402.5SIBC</b>	<b>MVS402.5SIT5C</b>	-	IM51SP143	IF50SP143

(1) Actual holding force of the suction cup at a vacuum of 65% on flat and smooth surface and safety factor of 2 included.

**MVS302.5**



**MVS302.5C**



**MVS302.5G**



For applications requiring suction cups with a smaller diameter, we recommend the VSA series in the SIB version, see page 2/25.

Note: Nozzle fitting IM5MVS see page 4/9.

### Accessories

To optimize the use of your suction cups, Coval offers a comprehensive range of accessories (nozzle fittings, spring extensions, and feeder systems, etc.), see chapters 4 and 12.






Specify the part number e.g.: **MVS302.5SIBC**  
Please refer to the characteristics table above





#### Suction Cups




	Ø A	H	Ø d	Ø D	f <sup>(2)</sup>	B	 (g)
MVS202.5	20	31	8	13	10	13	2.3
MVS202.5...C	20	31	8	13	10	13	3
MVS301.5	30	35	11	18	10	19.5	5.9
MVS301.5...C	30	35	11	18	9	19.5	6.5
MVS302.5	30	46	11	18	17.5	19.5	7.4
MVS302.5...G	30	46	11	18	17.5	19.5	6.8
MVS302.5...C	30	46	11	18	15.5	19.5	8.2
MVS401.5...C	40	37.5	11	18	7	21.5	8.7
MVS402.5...C	40	48	11	18	15.5	21.5	10.5


(2) f = Deflection of the suction cup.



#### Barbed Fittings

##### Male fittings



##### Female fittings



	ØA	B	C	ØD	E 	Materials	 (g)
IM 18 SP1251	G1/8"-M	8	5	4.8	14	POM-C	2.5
IM 51 SP143	G1/4"-M	11	6	8	21	Aluminum	10.5
IF 50 SP143	G1/4"-F	10	15	8	21	Aluminum	14.4

The values represent the average characteristics of our products.  
Note: All dimensions are in mm




## Suction cup with 1.5 bellow Specifically designed for cheese

To meet the requirements of applications for handling soft and fragile food products such as soft cheese, COVAL has developed a 1.5 bellow suction cup made of food-grade silicone that can be fitted with a stainless steel grid, which prevents deforming the food product.

- Suction cup made of 50 Shore A blue silicone that complies with food standards (FDA and CE 1935/2004).
- 1.5 bellow
- Ø 50 mm

### Materials

**SIBL5** 50 Shore A blue silicone






Industry-specific applications



Types of use




### Suction Cup Characteristics

	Ø (mm)	 (cm <sup>3</sup> )	 (lbf) <sup>(1)</sup>
<b>VSAF50SIBL5</b>	50	24.1	4.27


(1) Actual force of suction cup in use with 20% vacuum and including a safety factor of 2.



### Dimensions



### Accessory

Stainless steel grid 50 mm  
in diameter for suction cup VSAF50:  
Part no.: 80002171  
Weight: 18 g



	Ø A	H	Ø d	Ø D	B	f <sup>(2)</sup>	 (g)
<b>VSAF50SIBL5</b>	50	54	15	26	24	11	28

(2) f = Deflection of suction cup.



**Specify the part number: VSAF50SIBL5  
+ stainless steel grid Part no. 80002171**

The values represent the average characteristics of our products.  
Note: All dimensions are in mm



## Oblong suction cup with 1.5 bellow Specifically designed for cheese

To meet the requirements of applications for handling soft and fragile food products such as soft cheese, COVAL has developed a 1.5 bellow oblong suction cup made of food-grade silicone that can be fitted with a stainless steel grid, which prevents deforming the food product.

- Suction cup made of 50 Shore A blue silicone that complies with food standards (FDA and CE 1935/2004).
- 1.5 bellow
- Dimensions: 65 x 150 mm

### Materials

**SIBL5** 50 Shore A blue silicone



Industry-specific applications






Types of use



3


VSAOF

### Suction Cup Characteristics

	Dim. (mm)	 (cm <sup>3</sup> )	 (lbf) <sup>(1)</sup>
<b>VSAOF65150SIBL5</b>	65x150	298	11.58



(1) Actual force of suction cup in use with 20% vacuum and including a safety factor of 2.

### Dimensions



### Accessory

Stainless steel grid for suction cup  
VSAOF65150:  
Part no.: 80002470  
Weight: 80 g

	L	I	L'	I	Ø d	f <sup>(2)</sup>	 (g)
<b>VSAOF65150SIBL5</b>	149.8	64.8	164	79	22	26	124

(2) f = Deflection of suction cup.




**Specify the part number: VSAOF65150SIBL5  
+ stainless steel grid Part no. 80002470**

The values represent the average characteristics of our products.  
Note: All dimensions are in mm



# VSD, VSE, VSP

## Suction Cups for Bakery Applications



Suction cups specially developed for gripping delicate objects such as cakes (buns, biscuits, etc.). Specific shape and shore hardness options are available depending on the application. Food-grade silicone (FDA and CE 1935/2004) allows the suction cups to be used at temperatures between -40 °F to 428 °F.

Industry-specific applications



Types of use



Materials

**Si** Silicone

**Si3** 30 Shore A silicone

**Si5** 50 Shore A silicone

**SIT3** 30 Shore A translucent silicone

**SIT5** 50 Shore A translucent silicone


**SIT6** 60 Shore A translucent silicone

### Suction Cup Characteristics

	dim. (mm)	f <sup>(1)</sup>	maximum vacuum (%)	shore hardness	(g)	Fittings		
						M5-M	G1/8"-F	G1/8"-M
<b>VSD 25 SI</b>	Ø 25	24	90	30	6.5	-	-	-
<b>VSD 38 SI5</b>	Ø 38	21	20	50	6.3	-	-	-
<b>VSE 35 SI3</b>	Ø 35	26	20	30	8.8	-	-	-
<b>VSE 35 SI</b>	Ø 35	26	30	50	8.8	-	-	-
<b>VSE 39 SI</b>	Ø 39	28	30	50	11.5	-	-	-
<b>VSP 14 SI3</b>	Ø 14	9	70	30 <sup>(2)</sup>	0.9	IM21SP139	IF10ASP139	IM11ASP139
<b>VSP 14 SIT6</b>	Ø 14	9	90	60	0.9	IM21SP139	IF10ASP139	IM11ASP139
<b>VSP 2258 SIT5</b>	22 x 58	8	20	50	12.5	-	-	-
<b>VSP 2747 SIT3</b>	27 x 47	26	15	30	9.8	-	-	-
<b>VSP 3856 SIT5</b>	38 x 56	28	15	50	11.8	-	-	-
<b>VSP 7623 SIT5</b>	23 x 76	14	15	50	13.5	-	-	-

(1) f = Deflection of the suction cup. (2) Non-toxic red silicone

### Suction Cup Dimensions



The values represent the average characteristics of our products.  
Note: All dimensions are in mm

### Accessories

To optimize the use of your suction cups, Coval offers a comprehensive range of accessories (nozzle fittings, spring extensions, and feeder systems, etc.), see chapters 4 and 12.




**Specify the part number e.g.: VSP14SIT6**  
**Please refer to the characteristics table above**




# VSD, VSE, VSP

## Suction Cups for Bakery Applications




### Barbed Fittings

Male - IM



Female - IF



	ØA	B	C	ØD	E	Material	(g)
<b>IM 11 ASP 139</b>	G1/8"-M	7.5	6	3.5	14	Aluminum	4.3
<b>IM 21 SP 139</b>	M5-M	4.5	5	2.5	7	Aluminum	2.8
<b>IF 10 ASP 139</b>	G1/8"-F	8	12	3.5	14	Nickel-plated brass	4.3



## Suction Cups for Egg-handling



Industry-specific applications



Types of use



The VSO range of suction cups has been specially designed to meet the constraints involved when handling eggs.

- Very flexible lip
- Different shapes of suction cup
- Food-grade silicone meets FDA and CE 1935/2004 standards.


Materials

**SI** 35 Shore A red silicone

**SIT3** 35 Shore A translucent silicone

**SIT6** 60 Shore A translucent silicone


### Suction Cup Characteristics

	Ø (mm)	cm <sup>3</sup>	(lbf) <sup>(1)</sup>	SI	SIT3	SIT6
<b>VSO 30</b>	30	40	0.24	<b>VS030SI</b>	-	-
<b>VSO 33</b>	33	13	0.24	-	-	<b>VS033SIT6</b>
<b>VSO 36</b>	36	34	0.24	-	<b>VS036SIT3</b>	-


(1) at 30% vacuum with a safety factor of 2 included.

### Suction Cup Dimensions


VSO 30 SI




VSO 33 SIT6



VSO 36 SIT3



	Ø A	H	Ø a	Ø d	Ø D	B	(g)
<b>VSO 30</b>	30	74	-	4.5	12.6	12.5	17
<b>VSO 33</b>	33	46	-	4.5	12.5	14	7.3
<b>VSO 36</b>	36	75	41	5.3	16.4	9.2	16.36



Specify the part number e.g.: **VSO 30 SI**  
Please refer to the characteristics table above

The values represent the average characteristics of our products.  
Note: All dimensions are in mm



## Suction Cup for Bottle Handling via the Punt

Developed in partnership with manufacturers in the wine sector, the VBO suction cup system is designed for gripping bottles by the punt on disgorging stations.

Its modular design allows for a high degree of flexibility in positioning the whole assembly when gripping the base, as well as excellent sealing when gripping different types of bottles

The VBO suction cup system consists of:

- A 2.5 bellows suction cup, Ø62 mm in Nitrile with 31 mm stroke, ensuring a high degree of flexibility in positioning on the bottle base (swivel effect, deflection).
- An aluminium fitting threaded G1/4" -Male allowing the assembly to be mounted on the tool.
- Aluminium top and bottom coupler plates for joining the suction cup to the gripping disc.
- A silicone gripping disc (COVAL-Flex) ensures the tightness of the grip on various punts.

### Materials

**Suction Cup:** NBR - Nitrile

**Fitting and Couplers:** Aluminum

**Gripping Disc:** SI - Silicone



Industry-specific application




Types of use






3

VBO




### Suction Cup Characteristics

	Ø (mm)	 (cm <sup>3</sup> )	 (N) <sup>(1)</sup>
VBO60D85A2.5X62NBRM14C0	85	72.5	-

Force to be determined depending on application

### Suction Cup Dimensions



	Ø A	C	f <sup>(2)</sup>	H	H1	Ø G	G1	E 	K	 (g)
VBO60D85A2.5X62NBRM14C0	85	6	31	65	69	G1/4"-M	11	Hexa 17	M14-F	130

(2) f = Deflection of the suction cup.



Please specify part n°  
**VBO60D85A2.5X62NBRM14C0**  
See table of properties above.

The values represent the average characteristics of our products.  
Note: All dimensions are in mm.



# VSBO, VSBO+ Bottle Suction Cups



Designed for gripping 750 ml bottles, the VSBO suction cups range has grown with the development of the VSBO+, a specially created suction cup for gripping bottles at high frequency.

For the gripping of Magnum bottles, we have designed the Magnum suction cup VSBO 50105 with a lip shape and surface suited for the weight and the diameter of the bottle.

- The VSBO and VSBO+ are made for handling bottles from the side during vertical or horizontal gripping.
- The VSBO+ is equipped with anti-slip cleats to ensure the gripping of 750 ml bottles at high frequency and in humid environments.
- F2 mounting options: the VSBO Series includes 2 M6 threads allowing the suction cups to be mounted internally with 2 M5 screws or externally with 2 M6 screws.
- To increase lifting force while maintaining a large stroke and flexibility, the VSBO and VSBO+ suction cups are equipped with stainless steel upper inserts (a), and 4 stainless steel reinforcements (b) inside the bellows and with a lower reinforcement (c) available either in stainless steel or polypropylene.


Industry-specific applications



Types of use



More information



## Materials

### Suction cups

**NBR** Nitrile

**NR** Natural rubber

### Reinforcements

**Version D5** ■ Upper stainless steel insert (a), the 4 internal stainless steel reinforcements (b) and the lower reinforcement in stainless steel (c).

**Version D5P** ■ Upper stainless steel insert (a), the 4 internal stainless steel reinforcements (b) and the lower reinforcement in polypropylene (c).

## Suction Cup Characteristics VSBO

						NBR		NR	
						D5	D5P	D5	D5P
						<b>VSBO4095NBRD5</b>	<b>VSBO4095NBRD5P</b>	<b>VSBO4095NRD5</b>	<b>VSBO4095NRD5P</b>

(1) Force measured at 65% on dry and smooth bottle without safety factor.

(2) f = Deflection of the suction cup.

### Mounting holes:

The VSBO suction cup center to center distance is 45 mm.

### Suction cup replacement without insert and reinforcements

**NBR** (Nitrile): Part No **VSBO4095NBR**

**NR** (Natural rubber): Part No **VSBO4095NR**



## Suction Cup Characteristics VSBO+

						NBR		NR	
						D5	D5P	D5	D5P
						<b>VSBO4095CNBRD5</b>	<b>VSBO4095CNBRD5P</b>	<b>VSBO4095CNRD5</b>	<b>VSBO4095CNRD5P</b>

(1) Force measured at 65% on dry and smooth bottle without safety factor.

(2) f = Deflection of the suction cup.

### Mounting holes:

The VSBO+ suction cup has 2 center to center distances: 30 or 45 mm.

It includes an integrated seal to simplify the mounting.

### Suction cup replacement without insert and reinforcements:

**NBR** (Nitrile): Part No **VSBO4095CNBR**

**NR** (Natural rubber): Part No **VSBO4095CNR**

The values represent the average characteristics of our products.



### Options:

- Sensing valve (see page 3/19)
- Magnum bottle suction cup VSBO50105 (see page 3/18)



Specify the part number e.g.: **VSBO4095CNBRD5**  
Please refer to the characteristics table above




# VSBO, VSBO+ Bottle Suction Cups




## Suction Cup Dimensions

**VSBO (VSBO4095)**



**VSBO+ (VSBO4095C)**



## Suction Cups for Gripping Magnum Bottles

For the gripping of Magnum bottles, we have designed the Magnum suction cup **VSBO 50105 D5** with a lip shape and surface suited for the weight and the diameter of the bottle.

The **VSBO50105D5** includes:

- Suction cup with 4 bellows in nitrile, VSBO4095NBR
- One stainless steel upper insert
- A lower stainless steel reinforcement
- A 50 x 105 mm nitrile lip
- 4 stainless steel internal reinforcement

Materials

**Suction cups**

**NBR** Nitrile

**Insert and reinforcements**

**Upper insert**

stainless steel

**4 internals reinforcements**

stainless steel

## Suction Cup Characteristics

	 (cm <sup>3</sup> )	 (lbf) <sup>(1)</sup>	 (lbf) <sup>(1)</sup>	 f <sup>(2)</sup> (mm)	 (g)	<b>NBR</b>
<b>VSBO50105</b>	142.5	55.08	18.66	2.5 + 34	202	<b>VSBO50105D5</b>

(1) Force measured at 65% on dry and smooth bottle without safety factor.


(2) f = Deflection of the suction cup.

**Note:** The **VSBO4095** cups may be converted to a Magnum cup **VSBO50105D5** using the kit, **VP050105M**. This includes the lip (50 x 105 mm) in nitrile (NBR) with reinforcement for mounting below the cup.

## Spare parts:

- 4 bellows suction cup in nitrile (NBR) without insert and reinforcement, part number: VSBO4095NBR or VSBO4095CNBR
- Sealing lip with dimensions 50 x 105 mm in nitrile (NBR), part number: VPB050105NBR

## Dimensions



Specify the part number e.g.: **VSBO50105D5**  
Please refer to the characteristics table above



# VSBO, VSBO+

## Suction Cups for Bottle Handling with Sensing Valve (V4 version)



Designed for gripping 750 ml bottles, the VSBO and VSBO+ suction cups are available with a new sensing valve (V4 version) ensuring an airtight vacuum network if a bottle is missing. This new technology gives a greater sensitivity in opening the valve and placing the suction cup under vacuum once contact is made with bottle.

The VSBO suction cups with sensing valve include one upper HDPE insert (a), 3 stainless steel reinforcements (b) in the bellows and an HDPE trigger plate (c) to increase the traction force while offering a large stroke and flexibility for box filling and emptying applications.


Industry-specific applications



Types of use



Sensing valve



### Materials

Suction cup	Insert and reinforcements	Sensing valve
NBR Nitrile	Upper insert 3 internals reinforcements	Pin Cone O-ring Trigger plate Reinforcements Spring
	Stainless steel Stainless steel	Nylon Aluminum Nitrile POM Stainless steel Stainless steel

### Advantages of the V4 Sensing Valve

The sensing valve opens when pressure is exerted on the suction cup by a lower reinforcement called the «trigger plate».

- Valve adjustment underneath the suction cup
- Elimination of residual vacuum on release
- Immediate vacuum action from the first pressure
- No vacuum loss in the event a bottle is absent

### Vacuum switch connection

The VSBO and VSBO+ suction cups with sensing valve V4 have a Ø 5 mm connection enabling a vacuum switch or blow-off.

### Mounting:

The VSBO suction cups (VSBO4095..) and VSBO+ suction cups (VSBO4095C..) have a 45mm center to center mounting distance. The VSBO+ suction cups (VSBO4095C..) include an integrated seal to simplify the mounting.

### Characteristics

	(cm³)	(lbf) <sup>(1)</sup>	(lbf) <sup>(1)</sup>	f <sup>(2)</sup> (mm)	(g)
VSBO	112.5	35.52	18.66	22	118
VSBO+	112.5	35.52	18.66	22	118

(1) Force measured at 65% on dry and smooth bottle without safety factor.  
(2) f = Deflection of the suction cup.

### Suction Cup Part Numbers

	Mounting distance 45mm, NBR Material	Mounting distance 45mm, NR Material
VSBO	VSBO4095NBRCH445	VSBO4095NRCH445
VSBO+	VSBO4095CNBRCH445	VSBO4095CNRCH445

The values represent the average characteristics of our products.

### Replacement cup without valve, fitting and reinforcements

#### ■ VSBO series

NBR (nitrile): Part No VSBO4095NBR

NR (Natural rubber): Part No VSBO4095NR

#### ■ Serie VSBO+

NBR (nitrile): Part No VSBO4095CNBR

NR (Natural rubber): Part No VSBO4095CNR



Specify the part number e.g.:  
**VSBO4095CNBRCH445**  
Please refer part number table above




# VSBO, VSBO+

## Suction Cups for Bottle Handling with Sensing Valve (V4 version)




### Dimensions





VSBO (VSB04095)



VSBO+ (VSB04095C)



pre-stress adjusting screw (0 to 5 mm)



Ø 5 vacuum-switch connector  
available in 45mm version

3

VSBO, VSBO+



## Suction Cups for Paper Applications

The VPA series is a range of suction cups with a very flexible lip used to handle highly flexible materials. These suction cups are specially designed for gripping in applications such as label placement, plastic films and printing. They are mainly produced in natural rubber (NR) to provide resistance to abrasion caused by paper and cardboard or in silicone (SIT5) for food compatibility (FDA and CE 1935/2004).

### Materials

<b>NBR</b>	Nitrile	<b>NR</b>	Natural rubber
<b>SIT5</b>	Translucent silicone	<b>STN</b>	Siton®



### Industry-specific applications



### Types of use




### Suction Cup Characteristics


	Ø (mm)	(lbf) <sup>(1)</sup>	NBR	SIT5	NR	STN
<b>VPA 15</b>	15	0.65	-	<b>VPA15SIT5</b>	<b>VPA15NR</b>	-
<b>VPA 20</b>	20	0.97	-	<b>VPA20SIT5</b>	<b>VPA20NR</b>	-
<b>VPA 25</b>	25	1.46	-	<b>VPA25SIT5</b>	<b>VPA25NR</b>	-
<b>VPA 26</b>	26	1.46	-	-	<b>VPA26NR</b>	<b>VPA26STN</b>
<b>VPA 30</b>	30	2.11	<b>VPA30NBR</b>	<b>VPA30SIT5</b>	<b>VPA30NR</b>	<b>VPA30STN</b>
<b>VPA 35 A</b>	35	2.76	-	-	<b>VPA35ANR</b>	-
<b>VPA 40</b>	40	4.71	-	<b>VPA40SIT5</b>	<b>VPA40NR</b>	-
<b>VPA 25000</b>	25.5	1.62	-	<b>VPA25000SIT5</b>	<b>VPA25000NR</b>	-
<b>VPA 25001</b>	25.5	1.62	-	<b>VPA25001SIT5</b>	<b>VPA25001NR</b>	-

(1) Actual force of the suction cup with 65% vacuum and a safety factor of 2 included.


VPA 15...40



VPA 25000



VPA 25001



### Suction Cup Dimensions

	ØA	H	Ød	ØD	f <sup>(2)</sup>	B
<b>VPA 15</b>	15	9.8	5	9	0.8	7
<b>VPA 20</b>	20	10.3	5	10	1.3	7
<b>VPA 25</b>	25	10.8	5	10	1.8	7
<b>VPA 26</b>	26	21.5	6	14	1.9	13.5
<b>VPA 30</b>	30	23	11	15	2.5	16
<b>VPA 35 A</b>	35	23	11	15	2.5	16
<b>VPA 40</b>	40	20	8	16	2	15
<b>VPA 25000</b>	25.5	20	5.8	11	3	15.8
<b>VPA 25001</b>	25.5	9.5	5.8	16	3	5.1

(2) f = Deflection of the suction cup.

The values represent the average characteristics of our products.  
Note: All dimensions are in mm

### Accessories

To optimize the use of your suction cups, Coval offers a comprehensive range of accessories (nozzle fittings, spring extensions, and feeder systems, etc.), see chapters 4 and 12.



**Specify the part number e.g.: VPA20NR**  
**Please refer to the characteristics table above**







### Choice of Fittings

	Male fittings				Female fittings	
	G1/8"-M	G1/4"-M	M5-M	M6-M	G1/8"-F	G1/4"-F
VPA 15	IM11A	-	IM21	IM22	IF10A	-
VPA 20	IM11A	-	IM21	IM22	IF10A	-
VPA 25	IM11A	-	IM21	IM22	IF10A	-
VPA 26	-	-	-	-	-	-
VPA 30	-	IM51SP143	IM5VPA30	-	-	IF50SP143
VPA 35 A	-	IM51SP143	IM5VPA30	-	-	IF50SP143
VPA 40	-	IM41SP477	-	-	-	IF40SP477
VPA 25000	-	-	-	-	-	-
VPA 25001	IM11ASP082	-	-	-	IF10ASP082	-


Male fittings  
VPA 15...25




Female fittings  
VPA 15...25



Male fittings  
VPA 30...40



Female fittings  
VPA 30...40



### Barbed Fittings

Model	ØA	B	C	ØD	E	Materials	(g)
IM 11 A	G1/8"-M	7.5	6	3.5	14	Aluminum	4.1
IM 11 A SP082	G1/8"-M	7.5	6	3.5	14	Aluminum	4.1
IM 21 <sup>(1)</sup>	M5-M	4.5	5	2.5	7	Nickel-plated brass	3.1
IM 22 <sup>(1)</sup>	M6-M	5	5	3.5	7	Nickel-plated brass	2.7
IM 41 SP477	G1/4"-M	11	4	44	17	Aluminum	7.5
IM 51 SP143	G1/4"-M	11	6	8	21	Aluminum	10.5
IM 5 VPA30	M5-M	5	3	2.5	13	Aluminum	5.7
IF 10 A	G1/8"-F	8	12	3.5	14	Aluminum	4
IF 10 A SP082	G1/8"-F	8	12	3.5	14	Aluminum	4
IF 50 SP143	G1/4"-F	10	15	8	21	Aluminum	14.4
IF 40 SP477	G1/4"-F	10	15	4.4	17	Aluminum	8

(1) Flow control nozzle available: orifice calibrated to reduce the leakage in case of use of a multi-cup gripper (refer to page 4/9)




## Suction Cups for Labels

Thanks to their extra-flat shape and great lip flexibility, the VPAL suction cups are especially adapted for gripping and handling IML labels or flexible materials. They are made of silicone to meet food compatibility standards (FDA and CE 1935/2004).

### Materials

**SIBL5** Blue Silicone 50 Shore



### Industry-specific applications





### Types of use



3


VPAL

### Suction Cup Characteristics


	Ø (mm)	 (lbf) <sup>(1)</sup>	SIBL5
<b>VPAL 10</b>	10	0.65	<b>VPAL10SIBL5</b>
<b>VPAL 15</b>	15.5	0.97	<b>VPAL15SIBL5</b>
<b>VPAL 20</b>	20	1.46	<b>VPAL20SIBL5</b>

(1) Actual force of the suction cup with 65% vacuum and a safety factor of 2 included.


**VPAL10**




**VPAL15**



**VPAL20**



### Suction Cup Dimensions

	ØA	H	Ød	ØD	f <sup>(2)</sup>	B
<b>VPAL 10</b>	10	7.5	4	8.5	1.5	4
<b>VPAL 15</b>	15.5	7.5	4	8.5	1.5	4
<b>VPAL 20</b>	20	9.9	4	9	1.4	4

(2) f = Deflection of the suction cup.

The values represent the average characteristics of our products.  
Note: All dimensions are in mm

### Accessories

To optimize the use of your suction cups, Coval offers a comprehensive range of accessories (nozzle fittings, spring extensions, and feeder systems, etc.), see chapters 4 and 12.




**Specify the part number e.g.: VPAL15SIBL5**  
**Please refer to the characteristics table above**



# VPAL


## Suction Cups for Labels




### Choice of Fittings

	Male fittings		Female fittings	
	G1/8"-M	M5-M	G1/8"-F	M5-F
VPAL 10	IM18VPG5	IM5VPG5	IF18VPG5	IF5VPG5
VPAL 15	IM18VPG5	IM5VPG5	IF18VPG5	IF5VPG5
VPAL 20	IM18VPG5	IM5VPG5	IF18VPG5	IF5VPG5

Male fittings  
VPAL 10...20



Female fittings  
VPAL 10...20




### Barbed Fittings

Model	ØA	B	C	ØD	E	Materials	Weight (g)
IM 5 VPG 5	M5-M	4.5	3.5	2.2	7	Aluminum	0.7
IM 18 VPG 5	G1/8"-M	8	5	2.2	14	Aluminum	3.9
IF 5 VPG 5	M5-F	6	9	2.2	14	Aluminum	1.2
IF 18 VPG 5	G1/8"-M	9	15	2.2	14	Aluminum	5.1





Industry-specific applications



Types of use



The COVAL range of mailing application suction cups is designed to meet the requirements of the mailing industry. The improved characteristics mean you can optimize production equipment in your branch, such as:

- Envelope stuffing
- Film wrapping
- Envelope insertion
- Mailing (picking).


Material

**NR** Natural rubber


### Advantages

- Longer life expectancy
- Optimized for high throughput rates
- Excellent resistance to abrasion and slipping
- 100% compatible with machines currently on the market


### Suction Cup Characteristics

	ØA	H	Ød	Ød1	ØD	B	Color	NR
<b>VPR 001</b>	24.4	15	5.9	7.8	13.8	8	green	<b>VPR001NR</b>
<b>VPR 002</b>	25.7	14.5	5.9	7.8	14	9	brown	<b>VPR002NR</b>
<b>VPR 003</b>	20	14.2	5.7	4	13.8	6	red	<b>VPR003NR</b>
<b>VPR 004</b>	20	14.2	5.7	5	14.8	6	black	<b>VPR004NR</b>

VPR 001 - 002



VPR 003 - 004




The values represent the average characteristics of our products.  
Note: All dimensions are in mm



**Specify the part number e.g.: VPR003NR**  
**Please refer to the characteristics table above**



## Rounded Suction Cups




Thanks to very flexible lips, the VPAG range is suitable for gripping flexible materials such as labels or sheets of paper as well as textured objects. Their shape allows them to be used for unstacking.

### Materials

**NR** Natural rubber

### Industry-specific applications







### Types of use



### Suction Cup Characteristics


	NR	Fittings	
		G1/8"-M	G1/8"-F
VPAG 25	VPAG25NR	IM11ASP082	IF10ASP082
VPAG 3536	VPAG3536NR	-	-

### Suction Cup Dimensions




### Barbed Fittings

#### Male - IM



#### Female - IF



	ØA	B	C	ØD	E	Materials	(g)
IM 11 A SP082	G1/8"-M	7.5	6	3.5	14	Aluminum	4.1
IF 10 A SP082	G1/8"-F	8	12	3.5	14	Aluminum	4.0

The values represent the average characteristics of our products.  
Note: All dimensions are in mm



**Specify the part number e.g.: VPAG3536NR**  
**Please refer to the characteristics table above.**

### Accessories

To optimize the use of your suction cups, Coval offers a comprehensive range of accessories (nozzle fittings, spring extensions, and feeder systems, etc.), see chapters 4 and 12.





VPYR series ball-joints are recommended for gripping rounded or rotating products. They are also recommended for gripping requiring high mechanical resistance and force.

Industry-specific applications

Materials

**Suction cups**

**NBR** Nitrile

**Si** Silicone






**Ball-joint**

Nickel-plated brass and zinc-plated steel

Types of use





### Suction Cup Characteristics

	 (lbf) <sup>(1)</sup>	 $R_{min}$	$\varnothing A$	B	C	D	E 	E1 	f <sup>(2)</sup>	NBR	Si	 (g)
<b>VPYR 50</b>	14.61	41	50	60	12	42	19	-	4	<b>VPYR50NBR</b>	<b>VPYR50SI</b>	117
<b>VPYR 60</b>	21.06	70	60	93	16	58	21	19	5	<b>VPYR60NBR</b>	<b>VPYR60SI</b>	352
<b>VPYR 80</b>	37.34	100	80	95	18	60	21	19	6	<b>VPYR80NBR</b>	<b>VPYR80SI</b>	444
<b>VPYR 100</b>	58.45	150	100	95	18	60	21	19	6	<b>VPYR100NBR</b>	<b>VPYR100SI</b>	568

(1) Actual force of the suction cup with 65% vacuum and a safety factor of 2 included.

(2) f = Deflection of the suction cup.



### Replacement suction cup

If the suction cup becomes worn, the VPR suction cup can be ordered alone, specifying the diameter ( $\varnothing A$ ) and material of the suction cup. Example VPR 50 NBR.

The values represent the average characteristics of our products.

Note: All dimensions are in mm



**Specify the part number e.g.: VPYR50NBR**  
Please refer to the characteristics table above.

### Accessories

Possibility of telescopic spring-mounting on request.





SPL suction cups are used to handle heavy loads such as sheet metal or glass panels. They have internal cleats allowing them to handle thin sheet metal without distorting them and for vertical handling (non-slip).

SPL suction cups are delivered without holes for fittings or you can choose from our range of standard models or specific models on request.

### Materials

**NBR** Nitrile  
**Si** Silicone






Industry-specific applications



Types of use



### Suction Cup Characteristics

		 (cm <sup>3</sup> )	 (lbf) <sup>(1)</sup>	 (lbf) <sup>(1)</sup>	Ø A	H	Ø D	f <sup>(2)</sup>	NBR	Si	Fittings <sup>(3)</sup>	 (kg)
<b>SPL 240</b>		510	292	146	240	28	200	14	<b>SPL240NBR</b>	<b>SPL240SI</b>	Steel	2.2
<b>SPL 340</b>		720	617	308	340	32	300	15	<b>SPL340NBR</b>	<b>SPL340SI</b>	Steel	5.5
<b>SPL 400</b>		850	812	406	400	46	300	25	<b>SPL400NBR</b>	<b>SPL400SI</b>	Steel	7.6
<b>SPL 500</b>		1050	1299	649	500	46	400	25	<b>SPL500NBR</b>	-	Steel	12
<b>SPL 600</b>		1300	1786	893	600	46	500	25	<b>SPL600NBR</b>	-	Steel	18

(1) Actual force of the suction cup in use with 65% vacuum and including a safety factor of 2 for horizontal handling and a factor of 4 for vertical handling.

(2) f = Deflection of the suction cup.


(3) Thickness of the steel fitting: 8 mm

### Standard internal threads


The threads given below are for mounting on the COVAL spring systems (not supplied with the suction cup).

RSC1: specify **G38 RS1** in the order number






RSC2: specify **G38 RS2** in the order number



### Internal Thread

		TS5 + IFA 12120	RSC1 <sup>(1)</sup>	RSC2 <sup>(1)</sup>
<b>SPL 240</b>		■	■	-
<b>SPL 340</b>		■	■	■
<b>SPL 400</b>		-	-	■

(1) A G3/8" internal thread is available for connection to the vacuum system.



The values represent the average characteristics of our products.  
Note: All dimensions are in mm

### Accessories

Suction cups from the SPL series can be mounted on RSC series spring systems. SPL 240 suction cups can be mounted on the IFA 12 120 fitting and the TS560 spring system. See page 4/5.



**For all orders, please specify the part number from characteristics table and any required threadings**  
**E.g.: SPL240NBRG38RS1**



# STEEL


## Steel Suction Cups with Bonded Seal With Bonded Seal

For horizontal handling of heavy loads (very thick sheet metal) or objects with an uneven surface such as concrete slabs or wood, etc.


Advantage: wide selection of shapes and sizes.

Materials

**Body** Painted steel  
**Foam seal** Nitrile



Industry-specific applications







Types of use





3

STEEL

### Suction Cup Characteristics


Round suction cups				Rectangular suction cups							
	Ø A	H	 (lbf) <sup>(1)</sup>		L	I	H	M1/M2	Rac. <sup>(2)</sup>	 (lbf) <sup>(1)</sup>	Type of seal
<b>5020</b>	150	25	70	<b>6020</b>	175	115	25	40	G1/4"-F	75	BM 2020 SPTR
<b>5028</b>	170	25	97	<b>6028</b>	215	115	25	45	G1/4"-F	96	BM 2020 SPTR
<b>5035</b>	190	25	128	<b>6035</b>	225	125	25	50	G1/4"-F	115	BM 2020 SPTR
<b>5050</b>	210	25	166	<b>6050</b>	250	150	25	60	G1/4"-F	169	BM 2020 SPTR
<b>5085</b>	260	25	278	<b>6085</b>	305	180	25	70	G1/4"-F	271	BM 2020 SPTR
<b>5150</b>	350	35	482	<b>6150</b>	410	250	35	80	G3/8"-F	485	BM 3030 SPTR
<b>5240</b>	420	35	744	<b>6240</b>	480	310	35	100	G3/8"-F	768	BM 3030 SPTR
<b>5330</b>	500	35	1111	<b>6330</b>	575	330	35	120	G3/8"-F	1016	BM 3030 SPTR
<b>5500</b>	580	35	1550	<b>6500</b>	705	385	35	140	G3/8"-F	1531	BM 3030 SPTR

(1) Force measured at 65% vacuum including a factor of 2.




### Fittings

#### ■ 5000 An ring fitting



#### ■ 5000 Ch cap fitting



The values represent the average characteristics of our products.  
Note: All dimensions are in mm



**For all orders, please specify:**  
**Round suction cup: Model + Fitting model.**  
**E.g.: 5050 5000 An**

### Option

Spring system mounting, see page 4/5.



# Suction Cup Accessories

## Chapter 4

---



# Suction Cup Accessories

## Chapter 4

4

### TS11



#### Level Compensators

- Stroke available from 7 to 40 mm
- Protected internal spring
- The TS 11 series spring systems are recommended for horizontal handling of objects located on different levels. The spring function also ensures the gripping points are applied on the same plane when gripping using multiple suction cups.

P<sub>4/3</sub>

### TS



#### Level Compensators TS1 – TS2 – TS3

- 4 models
- 5 to 70 mm stroke available
- TS Series spring systems are recommended for horizontal handling of parts at different levels. The spring function also ensures the gripping points are applied on the same plane when gripping using multiple suction cups.

P<sub>4/4</sub>

### TS




#### Level Compensators TS4 - TS5

- 3 models available
- Stroke 40 mm and 60 mm
- Available connections to suction cups: G3/8"-M and G1/2"-M
- TS Series spring systems are recommended for horizontal handling of parts at different levels. The spring function also ensures the gripping points are applied on the same plane when gripping using multiple suction cups.

P<sub>4/5</sub>

### RSC



#### Multi-Compensator Systems

- 2 models
- 30 mm stroke + 10° ball-joint effect
- Possibility of mounting on square tube with fitting system
- The system of 4 compensated springs is particularly recommended for horizontal handling requiring large diameter suction cups. The springs compensate for different levels between the suction cups (ball-joint effect).

P<sub>4/5</sub>

### TSOP TSOG



#### Anti-Rotation Level Compensators

- 8 models
- Anti-rotation
- 7 to 50 mm stroke available
- Protected spring
- The TSOP and TSOG series anti-rotation spring systems are used for horizontal handling of objects at different levels. The anti-rotation function ensures that objects are always gripped in the same position.

P<sub>4/6</sub>

### L



#### Mounting Extensions

- 4 ranges (G1/4"-M, G1/8"-M, G3/8"-M and G3/8"-F)
- 3 possible strokes
- The L series extensions are used for gripping on various levels using the same installation plate. These extensions are adjustable to different heights.

P<sub>4/7</sub>



# Suction Cup Accessories

## Chapter 4

### Flow Control Fittings



#### Groups 1 and 2

- 13 models
- (Hollow screw or hollow shaft fitting)

- These fittings are designed for installations requiring a large number of suction cups connected to the same vacuum source, particularly for situations where parts may be missing in the layer to be handled. Using flow-controlled fittings reduces the loss of flow and therefore optimizes the size of the vacuum generator.

P<sub>4/9</sub>

### PMG2



#### Mechanical Feelers

- Mechanical feelers
- 5 models
- For VP series Ø30 to 60 mm suction cups

- The PMG2 series mechanical feelers are mounted on VP series diameter 30 to 60 mm flat suction cups in all types of material. The feeler is activated by the object to be handled, causing it to open and free the route for the vacuum.

P<sub>4/10</sub>

### IMU



#### Axial Ball-Joints

- Ball-joint fitting
- 4 models

- IMU series ball-joints are recommended for gripping rounded products.
- When installed on a flat suction cup, they provide greater force than a bellows suction cup.

P<sub>4/11</sub>

### CSP




#### Piloted Safety Valves

- Vacuum check-valve
- Directly mounted on the suction cup
- Release by blow-off

- The CSP series safety valve is a useful safety device in the event of loss of vacuum or emergency shut-off as it maintains the vacuum in the suction cup. Release is obtained by connecting the ancillary coupling to the pressure supply.

P<sub>4/12</sub>

### BM



#### Foam Seals

- Foam strip (airtight cells)
- 12 models
- 3 types of material (Nitrile, Silicone and Natural rubber)

- The foam strip is designed for gripping products with an uneven or ridged surface: sawn wood, metal sheets, flat surfaces with bumps or hollows.
- All granular surfaces to which suction cups cannot adhere correctly and therefore cannot be airtight.

P<sub>4/13</sub>

4



# TS 11

## Level Compensators



The TS 11 series compensated spring systems are recommended for horizontal handling of objects at different levels. The spring function also ensures that the gripping points are applied on the same plane when gripping with multiple suction cups.


■ Protected spring.

Materials

**Spring** Stainless steel

**Tubing** Zinc-plated steel

**Slider** Brass



### Characteristics

References	A	F1	F2	C	D	L	1	2	Fres (lbf/in)	Frep (lbf)	(g)
TS11 7	M5-F	M5-F	G1/8"-M	7	19	43	7	14	3.88	0.29	20
TS11 10	M5-F	M5-F	G1/8"-M	10	22	49	7	14	2.57	0.40	22
TS11 20	M5-F	M5-F	G1/8"-M	20	39	76	7	14	1.37	0.38	33
TS11 40	M5-F	M5-F	G1/8"-M	40	64	121	7	14	0.74	0.36	50


Note: All dimensions are in mm

C = Stroke

Fres = Spring force

Frep = Force at rest

### TS11



### Suction cup mounting

The TS 11 series spring system can be fitted on all suction cups in group 1 (VP, VSA, VS Ø 5 to 25 mm) for IM21 and on suction cups in series VPG 5 to 20.



Please specify the part n° e.g.: TS1140  
See part n° table above.






TS series compensated spring systems are recommended for horizontal handling of parts at different levels. The spring function also ensures that the gripping parts are applied on the same plane when gripping with multiple suction cups.

### Materials

**Spring** Stainless steel  
**Tubing** Zinc-plated steel  
**Slider** Brass




### Characteristics


Models	TS1				TS2				TS3				TS1.20 LG
Stroke	05	10	20	30	10	30	50	70	10	30	50	70	20
L	29	39	59	79	48	88	128	168	48	88	128	168	59
Spring force (lbf/in)	2.06	0.86	0.40	0.26	5.14	1.14	0.66	0.46	5.14	1.14	0.66	0.46	0.40
Force at rest (lbf)	0.22	0.38	0.33	0.45	1.82	0.94	1.01	1.01	1.15	0.94	1.01	1.01	0.33

Note: All dimensions are in mm


### TS1




### TS2



### TS3



### TS1.20 LG



Please specify the part n° e.g.:  
**Model + Spring stroke + Fitting**  
 e.g.: TS350C46

1: Model	2: Spring stroke	3: Fittings (for TS series)
TS1	05 - 10 - 20 - 30 (TS1)	D46 (Straight 4 x 6 - TS1, TS2, TS3)
TS2	10 - 30 - 50 - 70 (TS2, TS3)	D68 (Straight 6 x 8 - TS2, TS3)
TS3		C46 (Elbow 4 x 6 - TS1, TS2, TS3)
		C68 (Elbow 6 x 8 - TS2, TS3)
		T46 <sup>1</sup> (T-shape 4 x 6 - TS1)
		N <sup>2</sup> (Without fitting)

(1) versions T46 and T68 on request for TS2 and TS3.

(2) For TS1 model, vacuum connection M5-F and for models TS2 and TS3 vacuum connection G1/8"-M.

### Advantage of the TS120LG

The adjustment height is twice that of the standard TS1 spring system and its spring is protected.







# TSOP - TSOG

## Anti-Rotation Level Compensators



The TSOP and TSOG series spring systems are anti-rotation spring systems. They are used for horizontal handling of parts at different levels. The anti-rotation function ensures that objects are always gripped in the same position

The TSOP range is designed for applications requiring very precise handling.

- The hexagonal rod prevents the suction cup from rotating.
- Protected spring.

### Characteristics - TSOP

References	A	F1	F2	C	D	L	1	2	Fres (lbf/in)	Frep (lbf)	(g)
TSOP 107	M5-F	M5-F	G1/8"-M	7	18	42	7	14	3.88	0.29	20
TSOP 110	M5-F	M5-F	G1/8"-M	10	22	49	7	14	2.57	0.40	22
TSOP 120	M5-F	M5-F	G1/8"-M	20	39	73.5	7	14	1.37	0.38	33
TSOP 140	M5-F	M5-F	G1/8"-M	40	64	118.5	7	14	0.74	0.36	50

Note: All dimensions are in mm

C = Stroke

Fres = Spring force


Frep = Force at rest

Materials

**Spring** Stainless steel

**Tubing** Anodized aluminum

**Slider** Nickel-plated steel



### Characteristics - TSOG

References	A	F1	F2	C	B	D	E	G	L	1	2	3	Fres (lbf/in)	Frep (lbf)	(g)
TSOG2 20F	G1/8"-F	G1/8"-F	M16x1-M	20	20	38.5	7	9	100	12	19	12	1.44	0.82	35
TSOG2 35F	G1/8"-F	G1/8"-F	M16x1-M	35	20	58.5	7	9	135	12	19	12	0.78	0.97	45
TSOG3 25F	G1/4"-F	G1/4"-F	M20x1.5-M	25	23	50	10	10	113	16	24	16	1.47	0.99	65
TSOG3 50F	G1/4"-F	G1/4"-F	M20x1.5-M	50	23	82.5	10	10	170.5	16	24	16	0.74	1.00	90
TSOG4 40F	G3/8"-F	G3/8"-F	M25x1.5-M	40	33	71	11	11	159	22	32	22	1.31	1.37	170
TSOG4 80F	G3/8"-F	G3/8"-F	M25x1.5-M	80	33	121	11	11	249	22	32	22	0.68	1.35	235

Note: All dimensions are in mm

C = Stroke

Fres = Spring force


Frep = Force at rest

Materials

**Spring** Stainless steel

**Tubing** Anodized aluminum

**Slider** Anodized aluminum




Please specify the part e.g.: TSOG350F  
See part n° table above.



# L

## Mounting Extensions



The L series extensions are used for gripping on various levels using the same installation plate. These extensions are adjustable to different heights.


This system is especially useful for 2.5 bellows type suction cups, as height adjustment is made easier by the deflection of the suction cup.

Spring systems should be chosen, instead, for flat suction cups with low deflection.

### Materials

**Threaded rod and nut** Brass

**Screwed vacuum fitting** Nickel-plated brass



4

### Characteristics



Models	A <sup>(1)</sup>			B	C	h		Ød	ØL	D	P
G1/8"-M	22	42	52	25	19	3	14	6	G1/8"-M	-	-
G1/4"-M	19	49	69	29	24	4	19	9	G1/4"-M	-	-
G3/8"-F	19	49	69	20.5	19.5	4	23	-	G3/8"-F	19	22
G3/8"-M	19	49	69	20.5	19.5	4	23	10	G3/8"-M	-	-

(1) Other lengths available on request for a minimum quantity of 10 pieces.

### G1/4"-M - G1/8"-M


Straight

Elbow




### G3/8"-F

Straight or elbow 6x8



### G3/8"-M

Straight or elbow 6x8



Note: All dimensions are in mm



Please specify the part:

Model + Thread + Adjustable stroke + Fitting + Suction cup fitting  
e.g.: L1449C68F

1: Model	2: Thread	3: Adjustable stroke	4: Fittings	5: Suction cup fitting G3/8" version	
L	18 G1/8"	22 - 42 - 52	G1/8"	D46 Straight 4 x 6	F Female
	14 G1/4"	19 - 49 - 69	G1/4"	D68 Straight 6 x 8	M Male
	38 G3/8"		G3/8"	C46 Elbow 4 x 6	
				C68 Elbow 6 x 8	
				N Without fitting	

G3/8" extensions are compatible with the High Performance C series range of suction cups (see page 2/55).




# Miscellaneous Gripping

## Principle


In many cases when using a multi-suction cup installation, some of the cups will not be covered by the product(s) to be handled. This leads to a high risk of reduced grip from the covered suction cups, or may even prevent them gripping at all.

## Examples


- Gripping of panels, sheet metal, etc. in a wide variety of sizes by a vacuum lifter equipped with suction cups.



- Uncertain position of the object(s).



- Gripping several objects at one time, some of which may be missing.



## Solutions

- Independent ejector

Mounting an ejector for each suction cup guarantees the installation will operate perfectly even if one or more suction cups are not covered.

COVAL responds to this problem by offering the CIL, VR, GVR, and GVRL Series ejectors.

For further information, see chapter 6.

- Flow control fittings

Flow control fittings are incorporated as part of the suction cup mounting, thus reducing leakage in that cup with no part present during the vacuum cycle.

This technical solution is particularly suitable for vacuum grippers with a large number of suction cups.

To determine the diameter of the nozzle, COVAL has developed a specific CAD.

- Mechanical feelers

See following pages. COVAL offers four solutions depending on the application, with their advantages and drawbacks.



# Flow Control Fittings

## Groups 1 and 2




These fittings are designed for installations with a large number of suction cups connected to the same vacuum generator (vacuum gripper technology), particularly in cases where there may be objects missing from the layer of objects to be handled. Using flow-controlled fittings reduces the loss of flow and therefore optimizes the size of the vacuum generator.


**Caution, do not use this type of fitting for applications in a dusty environment.**

### Characteristics

References	ØA	ØD	B	C
IM5 MVSD1.1	M5-M	1.1	8	5
IM21 SP058	M5-M	0.45	4.5	5
IM21 SP094	M5-M	0.6	4.5	5
IM60 SP335	M6-M	0.6	7	11
IM60 SP387	M6-M	1.2	7	11
IM60 SP461	M6-M	0.9	7	11
IM60 SP483	M6-M	1	7	11
IM60 SP510	M6-M	1.7	7	11
IM60 SP511	M6-M	2.5	7	11
IMCM5 D0.6	M5-M	0.6	8	5
IMCM5 SP691	M5-M	1.1	8	5
IMCM5 SP701	M5-M	1.5	8	5



### Maximum suction per nozzle diameter



Please specify the part e.g.: IM60SP387  
See part n° table above.

Note: All dimensions are in mm



# PMG2

## Mechanical Feelers

The PMG2 series mechanical feelers are mounted on VP series diameter 30 to 60 mm flat suction cups in all types of material (group 2 suction cups).

The mechanical feeler blocks the path from the vacuum source to the suction cup.


The feeler is actuated by the object, causing it to open and free the path for the vacuum.

### Materials

**Body** Nickel-plated brass

**Spring** Stainless steel

**Feeler** Delrin and brass



### Advantages


- Simple to install and operate.
- Very efficient air-tightness for non-covered suction cups.
- Little risk of marking delicate objects, as the feeler has a rounded surface.

### Mounting

The feelers are mounted by press fitting. It is preferable to allow us to assemble the feeler onto the suction cup.

### Characteristics

	VP 30	VP 35	VP 40	VP 50	VP 60
d (mm)	3.9	2.9	2.9	0.9	0.9
H (mm)	19	20	20	22	22



### Leakage rate

No leakage if all the suction cups are correctly placed. This represents substantial savings in power with regard to the vacuum source: pneumatic ejector or electric vacuum pumps.




Please specify the part: PMG2

### Accessories

Mounting on spring or ball-joint systems (see chapter 4).



## Axial Ball-Joints



IMU series ball-joints are recommended for gripping rounded or rotating products.

When installed on a flat suction cup, they provide greater force than a bellows suction cup.

The vacuum connection is axial and sealing is ensured by a special seal always in contact with the spherical articulation.

The suction pad installed over the axial ball joint is free to rotate on its axis around 360° and can incline up to 15°

The ball joints are manufactured entirely in copper except the spherical joint made in stainless steel.

### Materials


**Ball-joint** Zinc-plated steel and brass


**Seal** Nitrile (NBR)

4

IMU

### Characteristics

References	G	G1	C2	C	E ↺	E1 ↺	H	 (g)
<b>IMU 18</b>	G1/8"-F	G1/8"-M	8	8.5	11	18	43	40
<b>IMU 14</b>	G1/4"-F	G1/4"-M	8	10	15	18	44.6	56
<b>IMU 38</b>	G3/8"-F	G3/8"-M	13	13	26	28	63.3	206
<b>IMU 12</b>	G1/2"-F	G1/2"-M	15	17	26	28	72.3	232



Please specify the part e.g.: IMU14  
See part n° table above.

Note: All dimensions are in mm





The CSP series safety valve is a useful safety device. In the event of loss of vacuum or emergency stop it maintains the vacuum in the suction cup. Release is obtained by connecting the ancillary coupling to the pressure supply.

### Materials


**Valve** Nitrile (NBR)

**Body** Anodized aluminum

**Filter** Stainless steel screen 200  $\mu$


### Characteristics

Reference	G	ØD	F	L	J	H
CSP 14	G1/4"-M	4	25	33	12.8	21



### Mounting

- One safety valve per suction cup.
- Blow-off pressure, minimum 5 bar.




Please specify the part e.g.: CSP14  
See part n° table above.

Note: All dimensions are in mm



# BM Foam Strips



Industry-specific applications



## Nitrile foam strip: 10m roll


### Mounting

Mounting with contact adhesive or flush-mounted at a depth adapted to the height and potential flush-mounting of the seal subject to the vacuum: 50% to 70% of the new height.

References	A	B
BM 1510	15	10
BM 1010	10	10
BM 1515	15	15
BM 2020	20	20
BM 3030	30	30

### Support


- All supports, particularly steel, aluminum, etc.
- Closed cells.
- Tube of neoprene adhesive (120 ml):  
Part No. 095.99.006.



## Nitrile beveled foam strip: 10m roll

- The beveling facilitates gripping of products with uneven surfaces.
- Closed cells.
- Contact adhesive reference: BOSTIK 1400 (Neoprene adhesive).


References	A	B
BM 2020 SPTR	20	20
BM 3020 SPTR	20	30
BM 3030 SPTR	30	30



## Silicone foam strip

- Heat resistant: 320°F.
- Do not use on parts before painting.
- Closed cells.
- Contact adhesive reference: LOCTITE 5366 (silicone adhesive).


References	A	B
BM 210 SI	10	2
BM 513 SI	13	5
BM SI 3030	30	30



## Natural rubber foam strips: Length 1m

- Flush-mounting.
- Use with turbine (strong suction) for gripping products with very uneven surfaces, such as slabs of washed gravel.
- Open cells.
- Contact adhesive reference: BOSTIK 1400 (Neoprene adhesive)

Reference	A	B
BMS 3025	30	25



Please specify the part e.g.: BM1510  
See part n° table above.

Note: All dimensions are in mm



# Vacuum Pumps Overview

## Chapter 5


<b>General Points</b>	<b>p. 5/2</b>
<b>Choosing a Vacuum Pump</b>	<b>p. 5/3</b>
<b>Comparison of Vacuum Pumps and Air Amplifiers</b>	<b>p. 5/4</b>
<b>Vacuum Pump Range</b>	<b>p. 5/6</b>
<b>Evacuation Time and Weight of Vacuum Pumps</b>	<b>p. 5/9</b>



# Vacuum Pumps Overview


## General Points

### What is vacuum?



### HOW A VENTURI WORKS

The COVAL vacuum pump works on the Venturi principle. The filtered, non-lubricated compressed air in **A** is blown through nozzle **D** and speeds up. It then goes into mixer **E** and finally escapes through silencer **B**. The vacuum is caused by the pressure drop in the chamber around nozzle **D**. The air sucked in **C** follows the same route to end up in silencer **B**.



### PRESSURE UNIT CONVERSION

Units	Bar 10 N/cm <sup>2</sup> = 100 kPa	Atm kp/cm <sup>2</sup>	Torr mm of Hg
Bar = 10 N/cm <sup>2</sup> = 100 kPa	1	0.986923	750.0617
Atm = kp/cm <sup>2</sup>	1.01325	1	760
Torr = mm of Hg	0.0013332	0.001316	1

### CONVERSION ACCORDING TO THE PERCENTAGE OF VACUUM

%	Bar (10 N/cm <sup>2</sup> = 100 kPa)	Atm (kp/cm <sup>2</sup> )	mm of water column
10%	-0.101	-0.103	1000
20%	-0.203	-0.207	2000
30%	-0.304	-0.310	3000
40%	-0.405	-0.413	4000
50%	-0.507	-0.517	5000
60%	-0.608	-0.620	6000
70%	-0.709	-0.723	7000
80%	-0.811	-0.827	8000
90%	-0.912	-0.930	9000




# Vacuum Pumps Overview

## Choosing a Vacuum Pump

The role of the vacuum pump is to generate a vacuum relative to a specific capacity. For vacuum handling, this capacity generally consists of:

- the internal volume of the suction cups to be evacuated,
- the volume of the network (piping).



### GRIPPING AIRTIGHT AND POROUS OBJECTS

#### Airtight objects

Only the volume of the cups and vacuum network needs to be considered. The choice of vacuum pump will correspond directly to the evacuation time required by the application. By nature of the product, it is ideal and more efficient to select pumps with a maximum vacuum level of 85% or more.

#### Porous objects

In this case, it is not possible to fully evacuate the vacuum system. The leakage rate from the suction cup network must be considered as well as the volume. A vacuum pump equipped to handle this application will be one whose flow is significantly greater than that of the leakage in the system, thus allowing vacuum pressure to build. For these products, it is preferable to choose a pump with high flow rates and a reduced maximum vacuum level of 50-60%.

5

### CALCULATING THE LEAKAGE RATE

First, choose a suction cup with a diameter compatible with the object to be gripped.

Second, equip a vacuum pump (with known characteristics) with a pressure gauge and a vacuum gauge. Then supply the pump with optimal pressure (e.g. 5 bar).

Finally, apply the suction cup to the surface to be tested.

#### Three possible cases may arise:

- The vacuum gauge indicates the maximum vacuum achieved for this type of pump: the object is airtight.
- The vacuum gauge does not measure any vacuum: choose a more efficient vacuum pump as the leakage rate is higher than the maximum vacuum pump flow.
- The vacuum gauge displays a vacuum value, e.g. -300 mb (30% vacuum), refer to the vacuum pump curve. Read the flow corresponding to -300 mb (e.g. 2.65 SCFM).

For example, the leakage rate at -300mb is measured at 2.65 SCFM for the suction cup used.

Using this data, calculate the forces to be applied to handle the object:

At -300mb the theoretical force of the suction cup is:

**$F(\text{lbf}) = S(\text{cm}^2) \times 0.3 / 0.2248^*$**  with:

**S** = surface of the suction cup in  $\text{cm}^2$ .

(-300 mbar = -0.3 bar, for calculation use 0.3).

(\*) coefficient to convert daN (decanewton) to lbf (pound-force)

To grip the object safely, (factor of 2 for horizontal gripping and 4 for vertical gripping), one must account for the varying characteristics of the vacuum pumps.

### THINGS TO REMEMBER

"An installation must breathe properly".

The throughput for a machine includes:

- gripping time,
- transfer time,
- release time.

Efficient vacuum handling will ensure a proper release of the object in addition to the grip, as the release is often a difficult point to resolve. Some steps to consider.

- Install vacuum pump as close as possible to the suction cups,
- Choose suction cups with the smallest possible internal volume,
- Identify suitable sizes of piping and fittings to limit pressure losses.



# Vacuum Pumps Overview

## Comparison of Vacuum Pumps and Air Amplifiers

### AIR AMPLIFIER

Optimal usage zone: 0 to 12% vacuum.

Maximum usage range: 0 to 15% vacuum.

#### ■ Applications:

##### **TRANSPORT - DRYING - DEGASSING**

Handling very porous, lightweight products: carpet, textiles, foam, etc...

Transporting small objects: granules, grains of coffee, rice, paperclips, etc...

Smoke extraction, degassing.



## 5

### TYPES OF VACUUM PUMPS

#### ■ Version 60% vacuum

Optimal usage zone: 30 to 55% vacuum.

Use of vacuum pumps optimized at 60% maximum vacuum implies high suction flow to account for the drop in vacuum pressure.

#### ■ Version 85 % vacuum

Optimal usage zone: 55 to 80% vacuum.

The importance of a vacuum pump which can create an 85% vacuum is to generate high vacuum and therefore a high force/surface ratio.

#### ■ Applications:

##### **HANDLING - SUCTION - EMPTYING - DOSING**

Handling porous, semi-porous and airtight products.

High-speed pick and place.

Air and/or liquid dosing.



### COMMENTS

The optimal use zones recommended as follows are the most adapted to the different types of technology. However they are in no way restrictive or limiting.

The notes are valid for both COVAL product groups: air amplifiers and vacuum pumps and also apply to all products using the same technology.

### NOTE


The following curves have been established using COVAL equipment: M 10 C air amplifier, LEM60X14 and LEM90X14 vacuum pumps.

The values given are values for identical compressed air consumption and optimal characteristics of each of the vacuum generation procedures.



# Vacuum Pumps Overview

## Comparison of Vacuum Pumps and Air Amplifiers





# Vacuum Pumps Overview

## Vacuum Pump Range

5

### Micro/Mini-Ejectors

#### CIL



- 2 sizes
- 3 nozzle Ø: 0.5 ; 0.7 ; 0.9 mm
- Suction flow rate: 0.25 to 0.80 SCFM
- Optimum supply pressure: 5 bar
- Weight between 7 and 13g
- Push fitting

- In-line connection
- Easily integrated
- No clogging
- Installation very close to the suction cups
- Very flexible installation
- Adaptable to all industries

#### VR



- 3 models
- Nozzle Ø: 0.5 ; 0.7 ; 0.9 ; 1 ; 1.2 ; 1.4mm
- Suction flow rate: 0.25 to 2.26 SCFM
- Optimum supply pressure: 5 bar
- Weight between 20 and 45 g
- Silencer option

- Wide range
- Very compact
- Installed directly on the suction cups
- Excellent mechanical resistance
- Reduced gripping time
- Blow-off option
- Extended suction flow rate range
- Silent operation
- Adaptable to all industries

#### GVR



- 2 models
- Nozzle Ø: 0.9 ; 1 ; 1.2 ; 1.4 mm
- Suction flow rate: 0.74 to 2.26 SCFM
- Optimum supply pressure: 5 bar
- Weight 45 g
- Integrated silencer

- Very compact
- Installed directly on the suction cups
- Excellent mechanical resistance
- No clogging
- Reduced gripping time
- Blow-off option
- Extended suction flow rate range
- Silent operation
- Adaptable to all industries

#### GVRL10



- Nozzle Ø: 1 mm
- Suction flow rate: 1.02 SCFM
- Optimum supply pressure: 3.5 bar
- Weight 28 g
- Silencer option

- Ultra compact and lightweight
- Easily integrated with grippers
- Excellent mechanical resistance
- Dust resistant
- Direct connection onto suction cups
- Ideal for high-speed robotics

### Vacuum Pumps

#### GVP



- Simple vacuum pumps
- Nozzle Ø: 1.2 ; 1.5 ; 2 ; 2.5 ; 3 mm
- Suction flow rate: 1.59 to 15.9 SCFM
- Optimum supply pressure: 4 bar
- Integrated silencer

- Modular design with interchangeable options
- Compact
- Optimized performance for handling all types of objects
- Silent operation
- No clogging
- Adaptable to all industries

#### GEMP



- Simple energy-saving vacuum pumps
- Nozzle Ø: 1.2 ; 1.5 ; 2 ; 2.5 ; 3 mm
- 2 vacuum levels: 60% and 85%
- Suction flow rate: 2.54 to 13.6 SCFM
- Integrated supply pressure regulator (ASR)
- Integrated silencer

- Very compact and light-weight
- Exceptional energy savings thanks to automatic pressure regulation at 4 bar
- Optimized performance for handling all types of objects
- Silent operation
- No clogging

#### GVEC



- "Easy Clean" Vacuum Pumps
- Nozzle Ø: 1.5 ; 2.5 ; 3 mm
- Suction flow rate: 3.35 to 11.65 SCFM
- Optimum supply pressure: 4 bar
- Materials resistant to corrosion and compatible with food-processing sector

- Very compact and light-weight
- Ideal for applications needs frequent cleaning
- Use in washing or splashing zones
- No clogging

#### LEMP



- Mini-Vacuum Pumps with ASR (Air Saving Regulator)
- Nozzle Ø: 1 ; 1.2 ; 1.4 mm
- 2 vacuum levels: 60% and 85%
- Suction flow rate: 1.02 to 3.25 SCFM
- Integrated supply pressure regulator (ASR)
- With or without vacuum switch
- Stand-alone or island module
- Integrated silencer

- For airtight and porous objects
- Ultra compact and lightweight
- Energy savings in all networks > 4 bar
- Reduced installation time
- Adaptable to all industries



# Vacuum Pumps Overview

## Vacuum Pump Range

### Intelligent Vacuum Pumps

#### LEM



- Integrated mini-vacuum pump with ASR (Air Saving Regulator)
- Nozzle Ø: 1; 1.2; 1.4
- 2 vacuum levels: 60% and 85%
- Suction flow rate up to 3.25 SCFM
- Integrated pressure regulator (ASR)
- All required functions integrated internally
- M8 connections
- Stand-alone or island module

- For airtight and porous objects
- Ultra compact and lightweight
- Control panel for monitoring and adjustment
- Energy savings in all networks > 4 bars
- Reduced wiring
- Reduced installation time
- Adaptable to all industries

#### LEM+



- Compact, high-flow vacuum pumps with ASR (Air Saving Regulator)
- Nozzle Ø: 2; 2.5 mm
- 2 vacuum levels: 60% and 85%
- Suction flow rate up to 9.71 SCFM
- Integrated pressure regulator (ASR)
- All required functions integrated internally
- M12 connections

- For airtight and porous objects
- Compact and lightweight
- Control panel for monitoring and adjustment
- Energy savings in all networks > 4 bars
- Reduced wiring
- Reduced installation time
- Adaptable to all industries

#### LEMAX



- Integrated mini-vacuum pump with ASC (Air Saving Control)
- Nozzle Ø: 1; 1.2; 1.4
- Vacuum level: 85%
- Suction flow rate up to 2.47 SCFM
- Integrated pressure regulator (ASR)
- Integrated vacuum regulation (ASC)
- All required functions integrated internally
- M8 connections
- Stand-alone or island module

- For airtight and slightly porous objects
- Ultra compact and lightweight
- Control panel for monitoring and adjustment
- ASC = 75 to 99% energy savings
- Reduced wiring
- Reduced installation time
- Adaptable to all industries

#### LEMAX+



- Compact, high-flow vacuum pumps with ASC (Air Saving Control)
- Nozzle Ø: 2; 2.5 mm
- Vacuum level: 85%
- Suction flow rate up to 7.06 SCFM
- Integrated pressure regulator (ASR)
- Integrated vacuum regulation (ASC)
- All required functions integrated internally
- M12 connections

- For airtight and slightly porous objects
- Compact and lightweight
- Control panel for monitoring and adjustment
- ASC = 75 to 90% energy savings
- Reduced wiring
- Reduced installation time
- Adaptable to all industries

#### LEMCOM



- Mini-vacuum pumps with fieldbus communication
- Nozzle Ø: 1; 1.2; 1.4
- 2 vacuum levels: 60 and 85%
- Suction flow rate up to 3.25 SCFM
- Integrated pressure regulator (ASR)
- Integrated vacuum regulation (ASC)
- Fieldbus: Profinet, EtherNet/IP™, CANopen®...
- M8 connections
- Stand-alone or island module

- For airtight and slightly porous objects
- Ultra compact and lightweight
- Settings and diagnosis by remote monitoring.
- ASC = 75 to 99% energy savings
- Reduced wiring
- Reduced installation time
- Adaptable to all industries



# Vacuum Pumps Overview

## Vacuum Pump Range

5

### Intelligent Vacuum Pumps

#### GVMAX V2-2 / V2-V2R



- Self-regulating vacuum pumps (electric vacuum and blow-off control)
- Separate inlets and outlets
- M12 connections
- Nozzle Ø: 2.5 mm
- Maximum vacuum level 85%
- Suction flow rate up to 7.06 SCFM
- Integrated vacuum check-valve
- Vacuum regulation function

- Compact and light
- Ideal for retaining air-tight objects in the automotive, plastics and sheet metal industries
- Energy saved by automatic vacuum regulation
- Safety guaranteed in case of power failure
- Optimal performances
- Silent operation
- No clogging

#### GVMAX



- Self-regulating vacuum pumps (electric or pneumatic vacuum control and blow-off)
- Two versions: electric or pneumatic
- Nozzle Ø: 2.5 mm
- Three levels of vacuum: 50%, 75% and 85%
- Vacuum regulation function
- Integrated vacuum solenoid valves and blow-off
- 2 integrated check valves for pneumatic version and 1 for electric version
- Integrated vacuum switch to adjust the vacuum threshold and hysteresis

- Compact and light
- Ideal for retaining air-tight objects in the automotive, plastics and sheet metal industries
- Energy saved by the vacuum regulation function
- Safety guaranteed in case of power failure
- Optimal performances
- Silent operation
- No clogging

### High Flow Vacuum Generators

#### CMS



- Multi-stage technology
- 2 vacuum flow rates: 31.8 and 63.6 SCFM
- Possibility to include a control valve for control of vacuum and release (M12 connectors)
- Optional vacuum gauge

- For applications requiring a high suction flow rate
- Emptying of large tanks
- Handling porous materia
- Remotely generate vacuum for chambers in MVG and CVG Series

#### M--C



- Operating principle based on the COANDA effect
- Bore diameter (Ø): 6, 10, 20, 30, 40 mm
- Flow rate: between 7.06 and 177 SCFM depending on the supply pressure (between 1.5 and 6 bar)
- Body material: aluminum

- Recommended for gripping light-weight, porous products: foam, carpet, cakes, leather, etc.
- Transport of powdery materials: powders, granules, etc.
- Transporting small, light-weight objects: paper clips, rice, coffee, etc.
- Smoke evacuation, depressurizing chambers



# Vacuum Pumps Overview

## Evacuation Time

### Evacuation time in seconds per liter

% vacuum	10 %	20 %	30 %	40 %	50 %	60 %	70 %	80 %	85 %
VR05	0.92	1.96	3.18	4.63	6.38	8.79	12.17	18.96	27.39
CIL05	0.92	1.96	3.18	4.63	6.38	8.79	12.17	18.96	27.39
VR07	0.46	0.98	1.58	2.28	3.13	4.27	5.8	8.55	11.01
CIL07	0.46	0.98	1.58	2.28	3.13	4.27	5.8	8.55	11.01
VR09	0.31	0.65	1.05	1.52	2.09	2.85	3.87	5.7	7.34
CIL09	0.31	0.65	1.05	1.52	2.09	2.85	3.87	5.7	7.34
VR10	0.24	0.51	0.82	1.18	1.62	2.21	3.01	4.43	5.71
GVR09S	0.31	0.65	1.05	1.52	2.09	2.85	3.88	5.7	7.34
GVR10	-	-	-	-	-	2.04	2.8	4.09	-
GVR10	0.24	0.51	0.82	1.18	1.62	2.21	3.01	4.43	5.71
VR12	0.14	0.3	0.49	0.71	0.97	1.33	1.81	2.66	3.42
GVR12	0.14	0.3	0.49	0.71	0.97	1.33	1.81	2.66	3.42
VR14	0.1	0.21	0.34	0.5	0.68	0.93	1.27	1.85	2.44
GVR14	0.1	0.21	0.34	0.5	0.68	0.93	1.27	1.85	2.44
GVP12N	0.14	0.3	0.49	0.71	0.97	1.33	1.81	2.66	3.42
GVP15N	0.09	0.20	0.32	0.46	0.63	0.85	1.16	1.71	2.20
GVP20N	0.06	0.12	0.19	0.28	0.38	0.52	0.71	1.04	2.13
GVP25N, GVMAXv2-2, GVMAXN	0.03	0.07	0.11	0.16	0.22	0.30	0.41	0.60	0.77
GVP30N	0.02	0.05	0.08	0.12	0.17	0.23	0.31	0.45	0.58

% vacuum	10 %	20 %	30 %	40 %	50 %	60 %	70 %
GVP12T	0.1	0.22	0.37	0.55	0.78	1.16	1.92
GVP15T, GVEC15T	0.07	0.15	0.24	0.36	0.52	0.77	1.27
GVP20T	0.04	0.09	0.14	0.22	0.31	0.46	0.76
GVP25T, GVEC25T, GVMAXT	0.03	0.06	0.1	0.14	0.21	0.3	0.5
GVP30T, GVEC30T	0.02	0.04	0.07	0.1	0.15	0.22	0.37

% vacuum	10 %	20 %	30 %	35 %	40 %	45 %
GVP12X	0.05	0.11	0.22	0.33	0.62	0.62
GVP15X	0.04	0.09	0.15	0.2	0.27	0.39
GVP20X	0.03	0.06	0.11	0.15	0.19	0.28
GVP25X, GVMAXX	0.02	0.04	0.08	0.1	0.14	0.19
GVP30X	0.01	0.03	0.06	0.08	0.11	0.15

% vacuum	10 %	20 %	30 %	40 %	50 %	60 %	70 %	80 %	85 %
GEMP60x12	0.09	0.2	0.35	0.55	0.9	-	-	-	-
GEMP60x15	0.06	0.14	0.23	0.36	0.59	-	-	-	-
GEMP60x20	0.04	0.08	0.13	0.21	0.34	-	-	-	-
GEMP60x25	0.03	0.05	0.09	0.14	0.24	-	-	-	-
GEMP60x30	0.01	0.04	0.07	0.10	0.17	-	-	-	-
GEMP90x12	0.13	0.27	0.44	0.64	0.88	1.19	1.62	2.37	3.12
GEMP90x15	0.09	0.18	0.29	0.42	0.58	0.79	1.08	1.59	2.08
GEMP90x20	0.05	0.11	0.18	0.25	0.35	0.46	0.65	0.95	1.25
GEMP90x25	0.03	0.07	0.11	0.16	0.22	0.3	0.41	0.59	0.78
GEMP90x30	0.03	0.06	0.09	0.13	0.18	0.24	0.33	0.48	0.64

5



# Vacuum Pumps Overview

## Evacuation Time and Weight of Vacuum Pumps

### Evacuation time in seconds per liter (cont.)

% vacuum	30 %	35 %	40 %	45 %	50 %	55 %
LEM/LEMP60X10	0.66	0.83	1.04	1.31	1.70	2.35
LEM/LEMP60X12	0.41	0.52	0.66	0.83	1.07	1.49
LEM/LEMP60X14	0.27	0.34	0.43	0.54	0.70	0.97
LEM60X20	-	0.16	-	0.27	-	0.42
LEM60X25	-	0.11	-	0.18	-	0.31

% vacuum	55 %	60 %	65 %	70 %	75 %	80 %
LEM/LEMP/LEMAX90X10	1.76	2.04	2.38	2.80	3.33	4.09
LEM/LEMP/LEMAX90X12	1.13	1.31	1.53	1.80	2.15	2.64
LEM/LEMP/LEMAX90X14	0.73	0.85	0.99	1.16	1.38	1.70
LEM/LEMAX90X20	0.38	-	0.55	-	0.80	-
LEM/LEMAX90X25	0.26	-	0.35	-	0.50	-

### Weight of micro/mini-ejectors in grams

Model	Nozzle size (mm)							
	0.5	0.7	0.9	1.0	1.2	1.4	1.5	2.0
CIL (Size 1)	7	9	-	-	-	-	-	-
CIL (Size 2)	-	-	13	-	-	-	-	-
VR	20.7	20.5	20.2	45.4	45.4	45.4	-	-
GVR	20.7	20.5	20.2	45.4	45.4	45.4	-	-
GVRL	-	-	-	28	-	-	-	-

### Weight of vacuum pumps in grams

Model	Nozzle size (mm)				
	1.2	1.5	2.0	2.5	3.0
GVEC	-	33	-	139	159
GVP	100	110	160	180	265
GVMAXE1	-	-	-	510	-
GVMAXP1	-	-	-	440	-
GVMAXV2/V2R	-	-	-	550	-
GEMP	maximum weight 265				

Model	Nozzle size (mm)				
	1.0	1.2	1.4	2.0	2.5
LEMP	90 to 110 g, depending on the model.			-	-
LEM	90 to 120 g, depending on the model.			-	-
LEM+	-	-	-	410 to 460 g, depending on the model.	
LEMAX	100 to 130 g, depending on the model.			-	-
LEMAX+	-	-	-	410 to 460 g, depending on the model.	
LEMCOM	150g			-	-



# Micro Ejectors

## Chapter 6

### CIL



#### In-line Ejectors

- 2 sizes
- 3 nozzle Ø: 0.5 ; 0.7 ; 0.9 mm
- Suction flow rate: 0.25 to 0.8 SCFM
- Optimum supply pressure: 5 bar
- Weight between 7 and 13g
- Push fitting
- In-line connection
- Easily integrated
- No clogging
- Installation very close to the suction cups
- Very flexible installation
- Adaptable to all industries

**P** 6/2

### VR



#### Heavy-duty in-Line Ejectors

- 2 models
- Nozzle Ø: 0.5 ; 0.7 ; 0.9 ; 1 ; 1.2 ; 1.4 mm
- Suction flow rate: 0.25 to 2.26 SCFM
- Optimum supply pressure: 5 bar
- Weight between 20 and 45 g
- Silencer option
- Wide range
- Very compact
- Direct installation on suction cups
- Excellent mechanical resistance
- Reduced gripping time
- Blow-off option
- Extended suction flow rate range
- Silent operation
- Adaptable to all industries

**P** 6/4

### GVR



#### Heavy-duty in-Line Ejectors

- 2 models
- Nozzle Ø: 0.9 ; 1 ; 1.2 ; 1.4 mm
- Suction flow rate: 0.74 to 2.26 SCFM
- Optimum supply pressure: 5 bar
- Weight: 45 g
- Integrated silencer
- Very compact
- Direct installation on suction cups
- Excellent mechanical resistance
- No clogging
- Reduced gripping time
- Blow-off option
- Extended suction flow rate range
- Silent operation
- Adaptable to all industries

**P** 6/8

**6**

### GVRL



#### Ultra Light in-Line Ejector for High Speeds

- Nozzle Ø: 1 mm
- Suction flow rate: 1.02 SCFM
- Optimum supply pressure: 3.5 bar
- Weight 28 g
- Silencer option
- Ultra compact and light weight
- Easily integrated onto grippers
- Excellent mechanical resistance
- Dust resistant
- Direct installation on suction cups
- Ideal for high speed robotics

**P** 6/10



# CIL

## In-line Ejectors


Due to their lightweight and compact design (only 7 to 13 g depending on the version), the "just plug it in" CIL ejectors can be easily integrated into the compressed air network and very close to the suction cups, even in the most inaccessible parts of the machine.

### Use

COVAL advises using CIL in-line ejectors for handling electronic components and other lightweight objects, feed systems, "Pick and Place" applications and separating systems for machining sheet metal or plastics.



### Industry-specific applications



### Advantages

- Simple, efficient connection  
Push fittings, M12 male or M14 male thread.
- Improved reliability due to no moving mechanical parts.
- Silent operation  
Nozzle-mixer combination resulting from new COVAL fluidics.
- Optimized performance  
CILs are available in 3 nozzle diameters (0.5, 0.7 and 0.9 mm), max. vacuum 85%.  
Size 1 (M12): 0.5 and 0.7 nozzles  
Size 2 (M14): 0.9 nozzle

### Characteristics

References	Ø nozzle	Air consumed (SCFM)	Maximum vacuum (%)	Air drawn in (SCFM)	At air pressure (bar)
CIL 190X05R	0.5	0.34	85	0.25	5
CIL 190X07R	0.7	0.65	85	0.48	5
CIL 290X09R	0.9	1.08	85	0.80	5

Note: All dimensions are in mm

### Evacuation Time in Seconds per Liter

% vacuum	10 %	20 %	30 %	40 %	50 %	60 %	70 %	80 %	85 %
CIL 190X05R	0.92	1.96	3.18	4.63	6.38	8.79	12.17	18.96	27.39
CIL 190X07R	0.46	0.98	1.58	2.28	3.13	4.27	5.8	8.55	11.01
CIL 290X09R	0.31	0.65	1.05	1.52	2.09	2.85	3.87	5.7	7.34

### Specifications

Supply	non-lubricated filtered air, 5 microns (ISO standard 8573-1:2010 [4:5:4])
Optimum operating pressure	5 bar
Weight	7 to 13 g, depending on the model
Materials	PA6.6 15 % FV – 2017A
Operating temperature	32 to 140°F

### Flexible Installation

#### Push fitting

Removable axial mounting directly on the pipe using push fittings.

Available in two sizes

- For calibrated pipe 2.7 x 4 mm (size 1)
- For calibrated pipe 4 x 6 mm (size 2)





#### Integrated fitting

M12 (size 1) or M14 (size 2) incorporated male thread allows the CIL in-line module to be fitted easily and securely.



#### Manifold mounting

M12 (size 1) or M14 (size 2) incorporated male thread allows several CIL in-line vacuum modules to be integrated into a machined block to feed several suction cups simply and economically from a single source of compressed air.



Delivered with a zinc-plated steel fastening nut.




Please specify the part n°. e.g. CIL190X05R  
See Characteristics table above






#### Dimensions

##### Size 1



##### Size 2







Note: All dimensions are in mm

#### Advantages

- Adaptable to all industries
- In-line connection
- Installation very close to the suction cups
- No clogging
- Very flexible installation
- Silent operation

#### Data Curves





# VR 05, 07, 09

## Heavy-duty In-line Ejectors


The main advantage of the VR series in-line ejectors is that they can be mounted directly on the suction cup, which simplifies plumbing.

By integrating the ejector on the suction cup, we obtain a localized vacuum and, therefore, the possibility of obtaining multiple independent grips, even in the absence of objects.

It is also possible to supply vacuum to two or more suction cups using a G1/8" or G1/4" T-shaped fitting.



Industry-specific applications



### Advantages

- Wide range
- Adaptable to all industries
- Lightweight and compact
- Reduced gripping time
- Direct installation on suction cups
- Excellent mechanical resistance
- Blow-off option
- Extended range of suction flow rates
- No clogging
- Silent operation

### Characteristics

Model	Ø Nozzle	Air consumed (SCFM)	Maximum vacuum (%)	Air drawn in (SCFM)	At air pressure (bar)
VR 05	0.5	0.42	87	0.25	5
VR 07	0.7	0.74	90	0.49	5
VR 09	0.9	1.27	90	0.74	5

Note: All dimensions are in mm

### Evacuation Time in Seconds per Liter

% vacuum	10 %	20 %	30 %	40 %	50 %	60 %	70 %	80 %	85 %
VR05	0.92	1.96	3.18	4.63	6.38	8.79	12.17	18.96	27.39
VR07	0.46	0.98	1.58	2.28	3.13	4.27	5.8	8.55	11.01
VR09	0.31	0.65	1.05	1.52	2.09	2.85	3.87	5.7	7.34

### Specifications

Supply	Non-lubricated filtered air, pressure 2 to 6 bar
Optimum operating pressure	5 bar
Weight	20 g
Material	2017A - Cu Zn
Temperature	32 to 176 °F.



**When ordering, please specify:**  
**Model + Nozzle diameter + Vacuum outlet**  
e.g.: VR07M6

1: Model	2: Ø Nozzle	3: Vacuum outlet
VR	05 Ø 0.5 mm	M6 M6 Female
	07 Ø 0.7 mm	M18 G1/8" Male
	09 Ø 0.9 mm	M14 G1/4" Male
		F18 G1/8" Female
		F14 G1/4" Female

### Additional Information

#### Mounting on spring systems


- Spring system, series TS3, available strokes: 10, 30, 50, 70mm, page 4/4.
- TSOP-TSOG series anti-rotation spring system, page 4/6.
- Ball-joint systems, IMU series, page 4/11.

#### Customized on request

- Alternate material option: stainless steel or plastic, based on specifications.
- Special characteristics such as suction flow rate or vacuum level.
- On request for the F18 model, M5 ancillary vacuum fitting for connection of a vacuum switch.

#### New function

- Silencer option: (ref. SILGV10M5F)
- Vacuum or blow-off switch, on request.








## Dimensions and Data Curves







## Dimensions

- (1) G1/4"-F C.A. inlet, depth 10 mm
- (2) M6-F vacuum outlet, depth 6 mm
- (3) Example of suction cup
- (4) Silencer
- (5) G1/8"-F vacuum outlet, depth 7.5 mm
- (6) G1/4"-F vacuum outlet, depth 10 mm
- (7) Compressed air
- (8) Exhaust
- (9) Hexagonal nut, 14 across flats
- (10) Hexagonal nut, 19 across flats



Note: All dimensions are in mm

## Data Curves





# VR 10, 12, 14

## Ejector Fittings




Based on the same principle as the VR 05, 07, 09, the main advantage of the VR 10, 12, 14 series is that they can be mounted directly on larger suction cups due their optimum technical characteristics.

The aluminum design guarantees:

- Excellent mechanical resistance
- Lightweight
- Ideal for miscellaneous gripping.

Industry-specific applications



### Advantages

- Wide range
- Adaptable to all industries
- Lightweight and compact
- Reduced gripping time
- Direct installation on suction cups
- Excellent mechanical resistance
- Blow-off option
- Extended range of suction flow rates
- No clogging
- Silent operation

### Characteristics

Model	Ø nozzle	Air consumed (SCFM)	Maximum vacuum (%)	Air drawn in (SCFM)	At air pressure (bar)
VR 10	1	1.55	90	0.95	5
VR 12	1.2	2.37	90	1.59	5
VR 14	1.4	3.81	90	2.26	5

Note: All dimensions are in mm

### Evacuation Time in Seconds per Liter

% vacuum	10 %	20 %	30 %	40 %	50 %	60 %	70 %	80 %	85 %
VR 10	0.24	0.51	0.82	1.18	1.62	2.21	3.01	4.43	5.71
VR 12	0.14	0.3	0.49	0.71	0.97	1.33	1.81	2.66	3.42
VR 14	0.1	0.21	0.34	0.5	0.68	0.93	1.27	1.85	2.44

### Specifications

Supply	Non-lubricated filtered air, pressure 2 to 6 bar
Optimum operating pressure	5 bar
Weight	50 g
Material	2017A - Cu Zn
Temperature	32 to 176 °F.



When ordering, please specify:

Model + Nozzle diameter + Vacuum outlet + Silencer  
e.g.: VR12M14S

1: Model	2: Ø Nozzle	3: Vacuum outlet	4: Silencer
VR	10 Ø 1 mm 12 Ø 1.2 mm 14 Ø 1.4 mm	M14 G1/4" Male	S SILGV 10 K SILK 18 C <sup>(1)</sup>

(1) SILK 18 C through-type silencer dimensions, see page 10/3.

### Additional Information

#### As standard


- New functions: vacuum switch or blow-off switch with or without silencer (SILGV 10).

#### Optional

- MS2M5 or MS4M5 blow-off valves with no-return valve on vacuum (see page 10/4).

#### Special

- Coval offers the product best adapted to your needs based on your specifications, and advises you according to your applications (material, shape, special technical characteristics).






# VR 10, 12, 14

## Ejector Fittings


### Dimensions and Data Curves



#### Dimensions







#### VR + MS4M5 version



- (1) Blow-off or vacuum switch
- (2) Silencer
- (3) Vacuum
- (4) Hexagonal nut, 19 across flats
- (5) Push fitting, external Ø 6

#### Data Curves



Note: All dimensions are in mm



# GVR 09, 10, 12, 14


## Micro Ejectors



The GVR range is designed for an industrial environment:

- Compact
- Lightweight
- Optimized technical characteristics
- Pollution-resistant with its through-type silencer (SILK 18C)
- Easily integrated onto vacuum gripper
- Pass-through mounting using M10 screws (GVR09)

Industry-specific applications



### Advantages

- Adaptable to all industries
- Lightweight and compact
- Reduced gripping time
- Direct installation on suction cups
- Excellent mechanical resistance
- Blow-off option
- No clogging
- Silent operation

### Characteristics

Models	Ø nozzle	Air consumed (SCFM)	Maximum vacuum (%)	Air drawn in (SCFM)	At air pressure (bar)
GVR 09	0.9	1.27	85	0.74	5
GVR 10	1	1.55	85	0.95	5
GVR 12	1.2	2.37	85	1.59	5
GVR 14	1.4	3.81	85	2.26	5

Note: All dimensions are in mm

### Evacuation Time in Seconds per Liter

% vacuum	10 %	20 %	30 %	40 %	50 %	60 %	70 %	80 %	85 %
GVR 09	0.31	0.65	1.05	1.52	2.09	2.85	3.87	5.7	7.34
GVR 10	0.24	0.51	0.82	1.18	1.62	2.21	3.01	4.43	5.71
GVR 12	0.14	0.3	0.49	0.71	0.97	1.33	1.81	2.66	3.42
GVR 14	0.1	0.21	0.34	0.5	0.68	0.93	1.27	1.85	2.44

### Specifications

Supply	Non-lubricated filtered air, pressure 2 to 6 bar
Optimum operating pressure	5 bar
Weight	40 g
Material	2017A - Cu Zn
Temperature	32 to 176 °F.



When ordering, please specify:  
Model + Nozzle diameter + Silencer  
e.g.: GVR12K

1: Model	2: Ø nozzle	3: Silencer
GVR	09 Ø 0.9 mm 10 Ø 1 mm 12 Ø 1.2 mm 14 Ø 1.4 mm	- Without S SILGV 10 K SILK 18 C <sup>(1)</sup>

(1) SILK 18 C through-type silencer dimensions, see page 10/3.


### Additional Information

#### As standard

- Vacuum switch or blow-off switch with SILGV 10. SILK18C silencer (through-type) on request.

#### Optional

- MS2M5 or MS4M5 blow-off valves with non-return valve on vacuum (see page 10/4).





# GVR 09, 10, 12, 14


## Micro Ejectors

### Dimensions and Data Curves




#### Dimensions


##### GVR 10, 12, 14 + MS4M5



##### GVR 10, 12, 14







##### GVR 09



- (1) Vacuum G1/4"-F
- (2) Silencer
- (3) M5-F plug for vacuum switch
- (4) Push fitting, outside Ø 6

#### Data Curves



Note: All dimensions are in mm



# GVRL 10

## Ultra Light In-line Ejector for High Speeds




Due to its ultra light and compact nature, the GVRL ejector can be easily integrated onto automated, high-speed grippers. Its tough aluminum design is reliable and allows the GVRL to be mounted directly to the suction cup.

- Compact
- Lightweight
- Easy integration on grippers
- Excellent mechanical resistance
- Dust resistant
- Directly mounted onto suction cups
- Ideal for high-speed robotics (Flex-picker)

### Connections

- Compressed air supply: G1/8"-Female
- Vacuum: G1/4"-Female
- Silencer: G1/4"-Female
- Vacuum switch plug available G1/8"-Female (supplied with stopper)

### Industry-specific applications



### Characteristics

References	Ø nozzle	Air consumed (SCFM)	Maximum vacuum (%)	Air drawn in (SCFM)	At air pressure (bar)
GVRL 10	1	1.55	85	1.02	3.5


Note: All dimensions are in mm

### Evacuation Time in Seconds per Liter

% vacuum	55%	60%	65%	70%	75%	80%
GVRL 10	1.76	2.04	2.38	2.8	3.33	4.09

### Specifications

Supply	Non-lubricated filtered air, pressure 2 to 8 bar
Optimum operating pressure	3.5 bar
Noise level	70 dB maxi at 3.5 bar (without silencer)
Weight	28 g
Material	Laiton, Aluminium
Temperature	32 to 140 °F.



Please specify the part n°. e.g. GVRL10  
See part n° table above




# GVRL 10

## Ultra Light In-line Ejector for High Speeds

### Dimensions and Data Curves



#### Dimensions







- (1) C.A. G1/8"-F
- (2) Vacuum outlet, G1/4"-F
- (3) Silencer G1/4"-F, depth 4mm
- (4) Vacuum switch plug G1/8"-F (supplied with stopper)

#### Options:

- Through-type silencer SILK14C

#### Data Curves




Note: All dimensions are in mm




# Overview of Vacuum Pumps

## VACUUM PUMPS - CHAPTER 7



■: Standard or integrated □: Option

Functions	Model	GVP	GEMP	GVEC	LEMP	LEM	LEM+	LEMAX	LEMAX+	LEMCOM	GVMAX--V2	GVMAX
Compressed air control (Suction)						■	■	■	■	■	■	■
Blow-off control						■	■	■	■	■	■	■
Integrated pressure regulator (ASR) <small>AIR Saving Regulator</small>			■		■	■	■	■	■	■		
Powerful blow-off							■		■			
Electronic vacuum switch with display		□	□		□	■	■	■	■		■	■
Electronic vacuum switch		□	□							■		
Vacuum switch with electrical contact		□	□									
Vacuum check-valve		□				□		■	■	■	■	■
Electric control						■	■	■	■	■	■	■
Pneumatic control												■
Twin Tech (Integration & Intelligence) <small>twin tech</small>						■	■	■	■	■		
ASC (Air saving Control) <small>AIR Saving Control</small>								■	■	■		
Automatic vacuum regulation								■	■	■	■	■
M8 connections					■	■		■		■		
M12 connections							■		■		■	
Island Assembly Available					■	■		■		■		
Field bus EtherNet/IP™ / PROFIBUS / CANopen®										■		



## INTELLIGENT VACUUM PUMPS - CHAPTER 8

### Energy Savings

COVAL is committed to making your vacuum handling system energy-efficient.

Our goal is to optimize the overall performance of your equipment by operating on the following three principles:

- Analyzing the system to identify the potential for savings.
- Selecting the most appropriate solution.
- Including COVAL energy-saving technologies, such as ASR and ASC, in our products.



#### ASR (Air Saving Regulator)

A «venturi pressure regulator» that guarantees optimized operation at 3.5 bar.

Ideal for gripping of porous products or rough surfaces.

**Advantage:** Up to 40 % energy savings.



#### ASC (Air Saving Control)

A vacuum regulation system that auto-adjusts to the product being handled.

Ideal for gripping airtight products.


**Advantage:** Up to 90 % energy savings.



# Vacuum Pumps

## Chapter 7

### GVP




#### Vacuum Pumps

- Nozzle Ø: 1.2 ; 1.5 ; 2 ; 2.5 ; 3 mm
- Suction flow rate: 1.59 to 15.9 SCFM
- Optimum supply pressure: 4 bar
- Integrated silencer
- Modular design with interchangeable options
- Compact
- Optimized performance for handling all types of objects
- Silent operation
- No clogging
- Adaptable to all industries

P 7/3

### GEMP



#### Simple Vacuum Pumps with ASR (Air Saving Regulator)

- Nozzle Ø: 1.2 ; 1.5 ; 2 ; 2.5 ; 3 mm
- 2 vacuum levels: 60% and 85%
- Suction flow rate: 2.54 to 13.6 SCFM
- Integrated supply pressure regulator (ASR)
- Integrated silencer
- Very compact and light-weight
- Exceptional energy savings thanks to automatic pressure regulation at 4 bar
- Optimized performance for handling all types of objects
- Silent operation
- No clogging

P 7/9

### GVEC



#### “Easy Clean” Vacuum Pumps

- Nozzle Ø: 1.5 ; 2.5 ; 3 mm
- Suction flow rate: 3.35 to 11.65 SCFM
- Optimum supply pressure: 4 bar
- Materials resistant to corrosion and compatible with food-processing sector
- Very compact and light-weight
- Ideal for applications needing frequent cleaning
- Use in washing or splashing zones
- No clogging

P 7/12

### LEMP



#### Mini-Vacuum Pumps with ASR (Air Saving Regulator)


- Nozzle Ø: 1 ; 1.2 ; 1.4 mm
- 2 vacuum levels: 60% and 85%
- Suction flow rate: 1.02 to 3.25 SCFM
- Integrated supply pressure regulator (ASR)
- With or without vacuum switch
- Stand-alone or island module
- Integrated silencer
- For airtight and porous objects
- Ultra compact and lightweight
- Energy savings in all networks > 4 bar
- Reduced installation time
- Adaptable to all industries

P 7/15



# GVP

## Vacuum Pumps




The GVP series vacuum pumps are the simplest in the range. They exist in 5 levels of power (suction rate) and 3 different levels of maximum vacuum:

- Version X (50% vacuum for very porous products).
- Version T (75% vacuum for porous products).
- Version N (85% vacuum for air-tight products).

For the same nozzle diameter, the suction flow rate increases proportionally to the decrease in the maximum vacuum level.

In addition to suction pads, they can also be used for dosing liquid, spraying and tank depressurization.

Industry-specific applications



### Characteristics

Model	Ø Nozzle (mm)	Air consumed (SCFM)	Max. vacuum (%)			Air drawn in (SCFM)			At air pressure (bar)
			X	T	N	X	T	N	
GVP 12	1.2	2.37	40	75	85	5.30	2.22	1.59	4
GVP 15	1.5	3.53	50	75	85	6.36	3.35	2.47	4
GVP 20	2	6.36	50	75	85	8.83	5.65	4.41	4
GVP 25	2.5	9.53	50	75	85	12.71	8.48	7.06	4
GVP 30	3	14.13	50	75	85	15.90	11.65	9.36	4

As standard, versions N and T are delivered with silencer S and version X with silencer K. Only exception, the GVP 30 is fitted with silencer K.

### Advantages


- Adaptable to all industries
- Optimized performance for handling all types of objects
- Options
- Light and compact
- Silent operation
- No clogging thanks to the through type silencer

### Evacuation Time in Seconds per Liter

% vacuum	10 %			20 %			30 %			40 %			50 %			60 %			70 %			80 %			85 %		
versions	X	T	N	X	T	N	X	T	N	X	T	N	X	T	N	X	T	N	X	T	N	X	T	N	X	T	N
GVP12	0.05	0.10	0.14	0.11	0.22	0.30	0.22	0.37	0.49	0.62	0.55	0.71	-	0.78	0.97	-	1.16	1.33	-	1.92	1.81	-	-	2.66	-	-	3.42
GVP15	0.04	0.07	0.09	0.09	0.15	0.20	0.15	0.24	0.32	0.27	0.36	0.46	-	0.52	0.63	-	0.77	0.85	-	1.27	1.16	-	-	1.71	-	-	2.20
GVP20	0.03	0.04	0.06	0.06	0.09	0.12	0.11	0.14	0.19	0.19	0.22	0.28	-	0.31	0.38	-	0.46	0.52	-	0.76	0.71	-	-	1.04	-	-	2.13
GVP25	0.02	0.03	0.03	0.04	0.06	0.07	0.08	0.10	0.11	0.14	0.14	0.16	-	0.21	0.22	-	0.30	0.30	-	0.50	0.41	-	-	0.60	-	-	0.77
GVP30	0.01	0.02	0.02	0.03	0.04	0.05	0.06	0.07	0.08	0.11	0.10	0.12	-	0.15	0.17	-	0.22	0.23	-	0.37	0.31	-	-	0.45	-	-	0.58

### Specifications

Supply	Non-lubricated filtered air, pressure 2 to 6 bar
Optimum pressure	4 bar
Weight	100 to 265g
Material	POM - 2017A – Cu Zn
Temperature	32 to 176 °F



For all orders, please specify:  
Model + Nozzle Ø + % vacuum + Silencer + C.A. fitting  
e.g.: GVP30NK14

1: Model	2: Nozzle diameter		3: % vacuum		4: Silencer		5: C.A. fitting
GVP	12	1.2 mm	X	50 % vacuum	-	Without silencer	14 G1/4" Female
	15	1.5 mm	T	75 % vacuum	S <sup>(1)</sup>	Diffuser	
	20	2 mm	N	85 % vacuum	K	Through-type	
	25	2.5 mm					
	30	3 mm					



(1) no silencer for nozzle Ø 30.



# GVP

## Vacuum Pumps

### Dimensions



Models	L1		L2			D		D1	
	X	N/T	S(N/T)	K(N/T)	K(X)	X	N/T	X	N/T
GVP12	76	81	46	68	121	30	20	G1/2 "-F	G1/4 "-F
GVP15	76	91	46	68	121	30	20	G1/2 "-F	G1/4 "-F
GVP20	76	76	62	121	121	30	30	G1/2 "-F	G1/2 "-F
GVP25	76	76	62	121	121	30	30	G1/2 "-F	G1/2 "-F
GVP30	148	148	-	121	121	30	30	G 1/2 "-F	G1/2 "-F

- (1) Vacuum switch option mounting zone
- (2) 4 bar compressed air supply
- (3) Exhaust
- (4) Silencer model S or K
- (5) G1/4"-F
- (6) Vacuum G1/2"-F

Note: all dimensions are in mm


#### Options

- Vacuum switches see page 7/6 and 7/7.
- Other options see pages 7/7 and 7/8.
- Silencer see page 10/3.


#### Curves

See page 7/5.









#### Vacuum Generated - Supply pressure 4 bar






#### Air Consumed - Supply pressure 4 bar



#### Suction Flow Rate/Vacuum Curves - Supply pressure 4 bar



#### Suction Flow Rate Generated - Supply pressure 4 bar






## Customer-mounted Vacuum Pump Options

### Electronic Vacuum Switch with Display

#### GVO PSA 100 C option

(See exact characteristics page 11/4)



Delivered with M8 cable (2 meters)

(1) M8 connector


Our top-of-the-range electronic vacuum switch, the PSA 100C has an LED display showing the vacuum value in different units. It also has two separate outputs with independently regulated hysteresis, NO or NC

- PNP as standard
- M8 connector.
- Connection cable, see page 10/11.

### Electronic Vacuum Switch

#### GVO PSP 100 C (M5), PSP 100 L (M5) option

(See characteristics page 11/7)



Delivered with M8 cable (2 meters)

(1) M8 4 pole connector


The vacuum data collected is always very reliable even with a large number of suction pads, thanks to the precision of the PSP 100. It has one output with hysteresis adjustment.

- PNP as standard
- M8 connector.
- Connection cable, see page 10/11.


### Vacuum Switch with Electrical Signal

#### GVO PSE 100 E or EC option

(See characteristics page 11/9)



GVO PSE 100 E with cable (length 2 metres)



GVO PSE 100 EC with M12 connector (delivered without connection cable)

(1) M12 male connector

The PSE 100 E or EC vacuum switch indicates the level of vacuum in the suction pad circuit. For a small number of suction pads (5 to 10 maximum). This indication is enough to prove an object is gripped. Hysteresis (125mbar) must also be taken into account according to the use of the vacuum switch data.

Check that the vacuum pump supply pressure generates a level of pressure equal to the threshold setting.


For connection cable, see page 10/11.



## Customer-mounted Vacuum Pump Options

### Vacuum Switch with Pneumatic Signal


**GVO PSE 100 P NO or NC option** (see characteristics page 11/10)



For use in fully pneumatic applications or explosive environments. The vacuum switch enables a pressure data message to be given when a vacuum threshold is reached.

### Vacuum Gauge


**GVO VAF 111 40 option** (See characteristics page 11/12)



The vacuum gauge displays the level of vacuum in the suction pad circuit. This option makes it simple to keep the status of the vacuum circuit under constant surveillance.

### Plug to Shut off Vacuum Data

**GVOB Option**



(1) Plug

This plug option makes it possible to shut off the vacuum signal to avoid affecting operation of the vacuum pump if a GVO option is removed.




## Factory-mounted Vacuum Pump Options

### GVO AL and GVO AL NPT option (for GVP vacuum pump)

Body and flange G1/4"-F Gas in aluminum (on request).

■ Note: It is no longer possible to mount vacuum gauge options.



**L1** = L1 GVP (plastic) - 1mm

**D1** = D1 (GVP N, T and X)

**D2** = G1/4"-F  
1/4 NPT (on request)

**(1)** Exhaust

**(2)** G1/2"-F


**(3)** Vacuum

### GVO P Option

With G1/2"-F protective extension.


The G1/2"-F extension is recommended for double valve models or with pneumatic vacuum switch to protect components during mounting or installation.

The extension is fitted with a 400 micron stainless steel filtration grid as standard.






## Simple Vacuum Pump with ASR



The GEMP series vacuum pumps are the simplest in the energy-saving range. They automatically regulate the supply pressure to an optimal 4 bar thanks to an integrated pressure regulator (ASR). Energy savings are achieved regardless of the pressure in the compressed air network and without penalizing other applications which require more than 4 bar. GEMP pumps therefore reduce both energy consumption and the noise level.

Industry-specific applications



### Characteristics

Models	Ø Nozzle (mm)	Air consumed (SCFM)	Maximum vacuum (%)	Air drawn in (SCFM)	At air pressure (bar)
GEMP60x12	1.2	2.30	60	2.54	4
GEMP60x15	1.5	3.43	60	3.88	4
GEMP60x20	2.0	6.32	60	6.67	4
GEMP60x25	2.5	9.18	60	9.71	4
GEMP60x30	3.0	13.60	60	13.60	4
GEMP90x12	1.2	2.30	85	1.77	4
GEMP90x15	1.5	3.43	85	2.65	4
GEMP90x20	2.0	6.32	85	4.41	4
GEMP90x25	2.5	9.18	85	7.06	4
GEMP90x30	3.0	13.60	85	8.65	4

### Advantages

- Modular design with interchangeable options
- Compact and light
- Exceptional energy savings
- Optimized performance for all types of applications
- Silent operation
- No clogging

### Evacuation Time in Seconds per Liter

% vacuum	10	20	30	40	50	60	70	80	85
GEMP60x12	0.09	0.2	0.35	0.55	0.9	-	-	-	-
GEMP60x15	0.06	0.14	0.23	0.36	0.59	-	-	-	-
GEMP60x20	0.04	0.08	0.13	0.21	0.34	-	-	-	-
GEMP60x25	0.03	0.05	0.09	0.14	0.24	-	-	-	-
GEMP60x30	0.01	0.04	0.07	0.10	0.17	-	-	-	-
GEMP90x12	0.13	0.27	0.44	0.64	0.88	1.19	1.62	2.37	3.12
GEMP90x15	0.09	0.18	0.29	0.42	0.58	0.79	1.08	1.59	2.08
GEMP90x20	0.05	0.11	0.18	0.25	0.35	0.46	0.65	0.95	1.25
GEMP90x25	0.03	0.07	0.11	0.16	0.22	0.3	0.41	0.59	0.78
GEMP90x30	0.03	0.06	0.09	0.13	0.18	0.24	0.33	0.48	0.64

### Specifications

Supply	Non-lubricated filtered air, 2 to 8 bar
Optimum pressure	4 bar
Weight	100 to 265g
Material	POM - 2017A - Cu Zn - PA6 15 % FV
Operating temperature	32 to 176 °F

### Vacuum Switch Characteristics


See pages 7/10.





For all orders, please specify:  
Model + % vacuum + X + Ø Nozzle + Vacuum switch.  
e.g.: GEMP90X12VA

1: Model	2: % vacuum	X	4: Nozzle diameter	5: Vacuum switch
GEMP	60 90	max. 60% vacuum. (porous objects) max. 85% vacuum (air-tight objects)	X	12 1.2 mm 15 1.5 mm 20 2 mm 25 2.5 mm 30 3 mm
				VA electronic display VB electronic VC with electrical contact VO without vacuum switch






#### 1 - Modules with Electronic Indexable Vacuum Switch GEMP-----VA or GEMP-----VB




##### Vacuum switch with display, 2 outputs, GEMP-----VA

- compatible fluids: non-corrosive gas, dry, non-lubricated air.
- measuring range: -1 ... 0 bar
- hysteresis: configurable.
- maximum excess pressure: 3 bar.
- repetitivity: +/- 1% of the range.
- output thresholds: 2 x NO / NC.
- switching power: 125 mA transistor PNP
- threshold status display: 2 x LEDs.
- display unit: bar.
- Electrical connection: M8 (4 pins).
- supply voltage: 12 - 24 VDC ± 10%.
- current draw: < 60 mA.
- protection level: IP40.
- working temperature: 32 to 122 °F



##### Electronic vacuum switch, 1 output, GEMP-----VB


- compatible fluids: non-corrosive gas, dry, non-lubricated air.
- measuring range: -1 ... 0 bar
- hysteresis: configurable from 0 to 30%.
- maximum excess pressure: 3 bar.
- repetitivity: +/- 1% of the range.
- output thresholds: 1 x NO.
- switching power: 125 mA transistor PNP
- threshold status display: 1 x LED.
- electrical connection: M8 (4 poles).
- supply voltage: 18 - 30 VDC (regulated).
- current draw: < 20 mA.
- protection level: IP50.
- working temperature: 32 to 122 °F



#### 2 - Modules with Electrical Contact Vacuum Switch GEMP-----VC


##### Contact vacuum switch, GEMP-----VC

- compatible fluids: non-corrosive gas, dry, non-lubricated air.
- measuring range: -350 to -850 mb.
- hysteresis: 125 mb.
- maximum overpressure: 2 bar.
- repetitivity: 3% of the range.
- breaking capacity: 1 x NO, 1 x NC.
- switching power: 3 A (breaker)
- electrical connection: M12 (4 poles).
- supply voltage: up to 125 V.
- protection level: IP40.
- working temperature: 14 to 122° F.
- number of operations: 5 million cycles.
- maximum throughput: 30 cycles per minute.



#### 3 - Modules without Vacuum Switch GEMP-----V0


This model without vacuum switch must be accompanied by an independent vacuum switch on the vacuum circuit or a vacuum gauge for manually-controlled vacuum capacity.




##### Note:

Screw-on electrical connectors, straight and angled M8 and M12 shown p. 10/11.






#### Dimensions




- (1) silencer for nozzles Ø 1.2 or 1.5 mm (GEMP--X12--, GEMP--X15--)
- (2) silencer for nozzles Ø 2 - 2.5 or 3 mm (GEMP--X20--, GEMP--X25--, GEMP--X30--)
- (3) fittings Ø 4.2 mm
- (4) G1/4"-F pressure fitting: pressure at 4 bar
- (5) G1/2"-F vacuum fitting

#### Performance Curves



- 1 - GEMP60X30
- 2 - GEMP60X25
- 3 - GEMP60X20
- 4 - GEMP60X15
- 5 - GEMP60X12



- 1 - GEMP90X30
- 2 - GEMP90X25
- 3 - GEMP90X20
- 4 - GEMP90X15
- 5 - GEMP90X12

Note: all dimensions are in mm





Industry-specific applications



The GVEC series “Easy Clean” vacuum pumps have been designed to meet the needs of vacuum handling applications in industries whose production requires frequent cleaning, particularly in the food-processing sector.

### Characteristics

Model	Ø Nozzle (mm)	Air consumed (SCFM)	Max. vacuum (%)	Air drawn in (SCFM)	At air pressure (bar)
GVEC15T18	1.5	3.53	75	3.35	4
GVEC25T14	2.5	9.53	75	8.48	4
GVEC30T14	3	14.13	75	11.65	4

### Advantages


- Plastic and stainless steel materials: meet the requirements of splash zones, are resistant to cleaning agents and corrosion.
- Compact and light design: installation as close as possible to suction cups to improve the evacuation times and production rate.
- Easy disassembly: quick and precise cleaning.

### Evacuation Time in Seconds per Liter

% vacuum	10 %	20 %	30 %	40 %	50 %	60 %	70 %
GVEC15T18	0.07	0.15	0.24	0.36	0.52	0.77	1.27
GVEC25T14	0.03	0.06	0.10	0.14	0.21	0.30	0.50
GVEC30T14	0.02	0.04	0.07	0.10	0.15	0.22	0.37

### Specifications

Supply	Non-lubricated filtered air, pressure 2 to 6 bar	
Optimum pressure	4 bar	
Weight	GVEC15T18	33 g
	GVEC25T14	139 g
	GVEC30T14	159 g
Material	Body and mixer	POM-C
	Nozzle	316L Stainless Steel
	Seal	EPDM
Operating temperature	From 32 to 122°F	
Cleaning temperature	max. 212°F	




Specify the part number e.g.: GVEC25T14  
Please refer to the characteristics table above






#### Dimensions

##### GVEC15T18



##### GVEC25T14 / GVEC 30T14



7

GVEC

Models	L1	D	(1)	D1 (2)	(3)
GVEC15T18	54.6	16	G1/8"-F	G1/4"-F	G1/4"-F
GVEC25T14	120.9	28	G1/4"-F	G1/2"-F	G1/2"-F
GVEC30T14	144.9	28	G1/4"-F	G1/2"-F	G1/2"-F


- (1) Pressure fitting
- (2) Exhaust
- (3) Vacuum fitting

Note: all dimensions are in mm







#### Vacuum Generated - Supply pressure 4 bar




#### Air Consumed - Supply pressure 4 bar



#### Suction Flow Rate/Vacuum Curves - Supply pressure 4 bar



#### Suction Flow Rate Generated - Supply pressure 4 bar






## Mini-Vacuum Pumps with ASR (Air Saving Regulator)



AIR Saving Regulator

Industry-specific applications



For all objects, porous or airtight


### Advantages

- Simplified installation and use thanks to the Plug & Play system
- Unmatched compactness: Installation close to suction cups  
→ short response times and energy savings.
- No clogging, thanks to the through-type silencer.
- A LEMP for every need: optional vacuum switch.
- Installation: standalone or island assembly.

### Compact Integration


The illustrations below demonstrate the functions integrated in the mini-module, and their respective roles in operation.  
The result of this COVAL innovation is:

- **A mini module** ( $\approx 110$  g) that is easy to install close to the suction cups, reducing the volume to be evacuated → increased speed and energy savings.
- **A complete module** (including integrated pressure regulator and clog-free silencer), therefore not requiring any additional function or connection.



### Integrated functions

- 1 3.5 bar Pressure regulator
- 2 3.5 bar optimized Venturi
- 3 Clog-free silencer
- 4 Electronic vacuum switch



Combined "venturi regulator" **ASR**: pressure regulator  
1 feeds venturi 2 with 3.5 bar, the optimized pressure  
for its operation.

→ **No more unnecessary consumption of  
compressed air.**

AIR Saving Regulator

**40%** Energy savings

AIR Saving Regulator


### (ASR): Air Saving Regulator

The LEMP vacuum pumps, which integrate an **ASR** "venturi regulator" combination, maintain ideals that COVAL values greatly: reducing both compressed air consumption and noise generation.

Regardless of pressure supplied by the compressed air network, the integrated regulator feeds the venturi at **3.5 bar** pressure, optimal for its operation.

- No more unnecessary energy consumption.
- No external regulator required and thus the risk of inadvertent misadjustment is eliminated.

Compared to pressures found in most compressed air networks (5-7 bar), the graph opposite demonstrates an achieved economy of 40% on average.





## Mini-Vacuum Pumps with ASR

Optional Vacuum Switch/Stand-alone and Island Modules


AIR Saving  
Regulator



### Version with Integrated Vacuum Switch

The front dialogue panel shown below displays the real-time vacuum level and lets the operator set the threshold level which triggers the "object gripped" signal allowing operations to continue.

This communications panel is particularly visual and intuitive. It makes it easy to monitor production.



### Stand-alone or Island Modules?

Stand-alone modules are suitable for the most common applications; one module controls one or more suction cups which all operate according to the same sequence.


When several suction cups are operating according to different sequences, multiple modules are required, which can be:

- several stand-alone modules,
- an island of these modules with an internal common pressure unit.


The diagrams below help in the selection:

- Stand-alone modules are complete, with the integrated pressure regulator (ASR, see p 7/15)
- in an island, the integrated regulator is absent: to maintain the advantage of economical and silent operation, it is recommended to reduce the pressure of the island's common pressure unit to 4 bar.

#### 4.5 to 7 bar network pressure



#### network pressure 4 bar



P optimal = 4 bar  
(operation at 4-7 bar)



island of 3 modules  
supplying suction cups





### LEMP: Versatile Series for all Applications

The opposite page demonstrates the versatility of this series. In addition to a very wide range of complete, stand-alone, or island vacuum pumps, there are the option of with or without vacuum switch.

### Select Vacuum Level and Nozzle Diameter

#### ■ Airtight products handling: glass, plastic, coated wood, metal sheet...


Because vacuum leaks are limited, the vacuum level to be used may be high: between 50 to 80%, to be generated by a 85% max. vacuum level venturi.

Taking into account the volume to be emptied and the response time to do so, the chart below is a guide towards the most economical nozzle and gives the air suction flow.


#### ■ Porous products handling: cardboard, raw wood, pastries...

Significant porosity and/or surface vacuum leaks are to be expected. For handling, a vacuum level between 30 to 55% is the best compromise, to be generated by a 60% max. vacuum level venturi.


The chart below is a first indication towards the most economical nozzle ID, to be completed by a product leak flow measurement.




**Porous materials:**  
cardboard, unfinished  
wood, pastries, etc.



force generated by the  
vacuum



**Airtight materials:**  
glass, plastic, sheet  
metal, finished wood



#### Porous Objects ▶ Maximum Vacuum Level: 60%

Time to create vacuum (seconds) for a volume of 1 liter

vacuum achieved	30%	35%	40%	45%	50%	55%	Air consumed (SCFM)	Air drawn in (SCFM)
ø nozzle								
1.0 mm	0.66	0.83	1.04	1.31	1.70	2.35	1.55	1.34
1.2 mm	0.41	0.52	0.66	0.83	1.07	1.49	2.30	2.54
1.4 mm	0.27	0.34	0.43	0.54	0.70	0.97	3.18	3.25

#### Airtight Objects ▶ Maximum Vacuum Level: 85%

Time to create vacuum (seconds) for a volume of 1 liter

vacuum achieved	55%	60%	65%	70%	75%	80%	Air consumed (SCFM)	Air drawn in (SCFM)
ø nozzle								
1.0 mm	1.76	2.04	2.38	2.80	3.33	4.09	1.55	1.02
1.2 mm	1.13	1.31	1.53	1.80	2.15	2.64	2.30	1.59
1.4 mm	0.73	0.85	0.99	1.16	1.38	1.70	3.18	2.47

### Select with or without Vacuum Switch

For common applications, the vacuum switch is needed, with the dialogue face for digital display and adjustment → see p. 7/16. However, some applications may just require a simple operation, without an "object gripped" return signal. The simplified version may then be chosen, with no vacuum switch, display, or adjustment.





Part numbers for an island assembly or components in an island

Part numbers for stand-alone units

**LEMP 60 X 12 VA**

VACUUM LEVEL	
60% max. vacuum → porous objects	<b>60</b>
85% max. vacuum → airtight objects	<b>90</b>

NOZZLE DIAMETER	
ø 1 mm nozzle	<b>10</b>
ø 1.2 mm nozzle	<b>12</b>
ø 1.4 mm nozzle	<b>14</b>

VACUUM SWITCH	
■ Electronic vacuum switch with digital display and adjustment	
■ No vacuum switch and no adjustment	

**B3**

**B2**

**B3**

**B4**

#### ISLAND ASSEMBLIES



LEMP--X---**B2**  
island assembly  
with 2 identical  
modules.



LEMP--X---**B3**  
island assembly  
with 3 identical  
modules.

If the planned island contains different module types, it must be ordered as separate components in order to then be assembled on site according to the arrangement suitable to the application.

#### COMPONENTS FOR THE ISLAND TO BE ASSEMBLED

**B**



LEMP-X---**B**  
Module that can be grouped  
(complete with integrated  
grouping screw)



Set of ends for a complete  
group, with grouping screw  
and common pressure unit  
plug.  
**Part No.: LEMSETA**

#### EXAMPLE COMPOSITE PART NUMBER FOR AN ISLAND ASSEMBLY:

##### ■ LEMP60X14VAB3

LEMP island assembly, containing 3 x 60% max. vacuum modules, Ø1.4 mm nozzle and vacuum switch.

#### ORDER EXAMPLE FOR AN ISLAND TO BE ASSEMBLED:

##### ■ LEMP60X10VAB

##### ■ LEMP90X12VAB

##### ■ LEMP60X14VAB

##### ■ LEMSETA

3 LEMP modules for a group, of different types.

Set of ends for island.

#### REFERENCE EXAMPLE COMPOSED OF A STAND-ALONE MODULE:

##### ■ LEMP60X12VA

Stand-alone LEMP Module, 60% max. vacuum, Ø1.2 mm nozzle and vacuum switch.










#### Stand-alone Modules



Side mounting



Front mounting





For front mounting, order the necessary kit, in addition to the module:

Front mounting kit:  
1 plate + 4 screws

**Part No.: LEMFIXA**



Mounting on DIN rail




A module can be clipped onto a DIN rail.

For this purpose, the module must first be equipped with an individual DIN installation plate, ordered separately:


DIN rail mounting kit:  
1 plate/clip + 4 screws

**Part No.: LEMFIXB**

#### Islands




#### Front mounting



2 optional holes for 1 Ø 4mm connecting screw, at each end of the island

#### Mounting on DIN rail



DIN rail mounting kit:  
2 clips + 2 screws

**Part No.: LEMFIXC**





#### Overall Characteristics

- Supply: non-lubricated air filtered to 5 microns according to standard ISO 8573-1:2010 [4:5:4].
- Operating pressure: 4.5 to 7 bar.
- Mini dynamic pressure:
  - stand-alone module:  $P = 4.5$  bar.
  - island modules: 4 bar.
- Maximum vacuum: 60% or 85% depending on model (see page 7/17).
- Suction rate: 1.02 to 3.25 SCFM depending on model (see page 7/17).
- Air consumption: 1.55 to 3.18 SCFM depending on model (see page 7/17).
- Electrical protection level: IP 65.
- Weight: 90 to 110 g, depending on model.
- Operating temperature: 50 to 140 °F.
- Materials: PA 6-6 15 %FV, brass, aluminium, NBR.

#### Integrated Vacuum-switch Characteristics


- Measuring range: -1 to 0 bar.
- Precision:  $\pm 1.5\%$  of the range.
- Hysteresis: adjustable from 0% to 100%.
- Output threshold: 1 x T.O.R. in NO.
- Analog output: 1 V DC to 5 V DC on the measuring range.
- Switching power: 125 mA, PNP.
- Threshold status display: 1 green LED.
- Supply voltage 24V DC (regulated  $\pm 10\%$ ).
- Current draw: < 20 mA.
- Protection: against polarity inversions.

#### Integrated-silencer Characteristics

- Noise level: approximately 68 dBA.
- Clog-free silencer.


#### Electrical Connections

##### MODULES WITH VACUUM-SWITCH FUNCTION




#### M8 Connector Characteristics


Models	Connectors	No. of pins	Orientation	Cable length
CDM8	M8	4	Straight	2 m
CDM8N	M8	4	Straight	0.5 m
CCM8	M8	4	Elbow	2 m



- 1: Brown
- 2: White
- 3: Blue
- 4: Black




#### Characteristics and Connecting an Island



##### Maximum number of modules in an island:

- $\varnothing 1.4$  mm nozzle  $\rightarrow$  5 modules
- $\varnothing 1.2$  mm nozzle  $\rightarrow$  7 modules
- $\varnothing 1$  mm nozzle  $\rightarrow$  9 modules

#### Suction Flow Rate / Vacuum Curves



- 1 - LEMP60X10
- 2 - LEMP60X12
- 3 - LEMP60X14

- 1 - LEMP90X10
- 2 - LEMP90X12
- 3 - LEMP90X14



# Intelligent Vacuum Pumps

## Chapter 8

### Ultra-Compact series

#### LEM



#### Integrated Mini-vacuum Pumps with ASR (Air Saving regulator)

- Nozzle Ø: 1; 1.2; 1.4 mm
- 2 vacuum levels: 60% and 85%
- Suction flow rate up to 3.25 SCFM
- Integrated pressure regulator (ASR)
- All required functions integrated internally
- M8 connections
- Stand-alone or island module
- For airtight and porous objects
- Ultra compact and lightweight
- Control panel for monitoring and adjustment
- Energy savings in all networks > 4 bars
- Reduced wiring
- Reduced installation time
- Adaptable to all industries

P 8/3

#### LEM+



#### Compact High-flow Vacuum Pumps with ASR (Air Saving Regulator)

- Nozzle Ø: 2; 2.5 mm
- 2 vacuum levels: 60% and 85%
- Suction flow rate up to 9.71 SCFM
- Integrated pressure regulator (ASR)
- All required functions integrated internally
- M12 connections
- For airtight and porous objects
- Compact and lightweight
- Control panel for monitoring and adjustment
- Energy savings in all networks > 4 bars
- Reduced wiring
- Reduced installation time
- Adaptable to all industries

P 8/9

#### LEM MAX



#### Integrated Mini-vacuum Pumps with ASC (Air Saving Control)

- Nozzle Ø: 1; 1.2; 1.4 mm
- Vacuum levels: 85%
- Suction flow rate up to 2.47 SCFM
- Integrated pressure regulator (ASR)
- Integrated vacuum regulation (ASC)
- All required functions integrated internally
- M8 connections
- Stand-alone or island module
- For airtight and porous objects
- Ultra compact and lightweight
- Control panel for monitoring and adjustment
- ASC = 75 to 99% energy savings
- Reduced wiring
- Reduced installation time
- Adaptable to all industries

P 8/15

#### LEM MAX+



#### Compact High-flow Vacuum Pumps with ASC (Air Saving Control)

- Nozzle Ø: 2; 2.5 mm
- Vacuum levels: 85%
- Suction flow rate up to 7.06 SCFM
- Integrated pressure regulator (ASR)
- Integrated vacuum regulation (ASC)
- All required functions integrated internally
- M12 connections
- For airtight and porous objects
- Compact and lightweight
- Control panel for monitoring and adjustment
- ASC = 75 to 90% energy savings
- Reduced wiring
- Reduced installation time
- Adaptable to all industries

P 8/23

#### LEM COM



#### Mini-vacuum Pump Communicating via Industrial Field Bus

- Nozzle Ø: 1; 1.2; 1.4 mm
- 2 vacuum levels: 60 and 85%
- Suction flow rate up to 3.25 SCFM
- Integrated pressure regulator (ASR)
- Integrated vacuum regulation (ASC)
- Field bus: Profinet, Ethernet/IP™, CANopen®...
- M8 connections
- Stand-alone or island module
- For airtight and porous objects
- Ultra compact and lightweight
- Settings and diagnosis by remote monitoring.
- ASC = 75 to 99% energy savings
- Reduced wiring
- Reduced installation time
- Adaptable to all industries

P 8/29




# Intelligent Vacuum Pumps

## Chapter 8

### The GVMAX series vacuum pumps

#### GVMAX V2-2 / V2-2R



#### Self-regulating Vacuum Pumps

- Electric vacuum and blow-off controls
- Nozzle Ø: 2.5 mm
- Maximum vacuum level 90%
- Vacuum regulation function
- Integrated vacuum solenoid valves and blow-off
- Integrated vacuum check-valve
- Compact and lightweight
- Ideal for retaining airtight objects in the automotive, plastics and sheet metal industries
- Energy savings thanks to the vacuum regulation function
- Safety guaranteed in case of power failure
- Optimized performance for handling all types of objects
- Silent operation
- No clogging

**P** 8/39

#### GVMAX



#### Self-regulating Vacuum Pumps (electric or pneumatic control)

- Nozzle Ø: 2.5 mm
- Three vacuum levels: 50%, 75% and 90%
- Vacuum regulation function
- Integrated vacuum solenoid valves and blow-off
- 2 integrated non-return valves for pneumatic version and 1 for electric version
- Integrated vacuum switch to adjust the vacuum threshold and hysteresis
- Integrated silencer
- Compact and lightweight
- Ideal for retaining airtight objects in the automotive, plastics and sheet metal industries
- Energy saved by the vacuum regulation function
- Safety guaranteed in case of power failure
- Optimized performance for handling all types of objects
- Silent operation
- No clogging


**P** 8/44



## Integrated Mini-Vacuum Pumps with ASR (Air Saving Regulator)



Industry-specific applications



For all objects, porous or airtight

More information




### Advantages

- "All-in-one" solution, no more peripherals to be added.
- Simplified installation and use thanks to the Plug & Play system
- Unmatched compactness: Installation close to suction cups → short response times and energy savings.
- No clogging, thanks to the through-type silencer.
- A LEM for every need: a wide range, with many options.
- Smart dialogue → user friendly at all stages: initial settings, operation, maintenance.

### Compact Integration


The illustrations below demonstrate the 8 functions integrated in the mini-module, and their respective roles in operation.  
The result of this COVAL innovation is:

- **A mini module** ( $\cong 120$  g) that is easy to install close to the suction cups, reducing the volume to be evacuated → increased speed and energy savings.
- **A complete module** (including integrated pressure regulator and clog-free silencer), therefore not requiring any additional function or connection.



### Integrated functions

- 1 3.5 bar Pressure regulator
- 2 Solenoid valve "vacuum"
- 3 3.5 bar optimized Venturi
- 4 Clog-free silencer
- 5 Electronic vacuum switch
- 6 Integrated electronics
- 7 Solenoid valve "blow-off"
- 8 Blow-off flow adjustment



Combined "venturi regulator" **ASR**: pressure regulator 1 feeds venturi 3 with 3.5 bar, the optimized pressure for its operation.

→ **No more unnecessary consumption of compressed air.**



**40%** Energy savings




### (ASR): Air Saving Regulator

The LEM vacuum pumps, which integrate an **ASR** "venturi regulator" combination, maintain ideals that COVAL values greatly: reducing both compressed air consumption and noise generation.

Regardless of pressure supplied by the compressed air network, the integrated regulator feeds the venturi at **3.5 bar** pressure, optimal for its operation.

- No more unnecessary energy consumption.
- No external regulator required and thus the risk of inadvertent misadjustment is eliminated.

Compared to pressures found in most compressed air networks (5-7 bar), the graph opposite demonstrates an achieved economy of 40% on average.






## Integrated Mini-Vacuum Pumps with ASR Smart Dialogue / Stand-alone and Island Modules



### Smart Dialogue

The front dialogue panel shown below displays the real-time vacuum level and lets the operator set the threshold level which triggers the "object gripped" signal allowing operations to continue.

This communications panel is particularly visual and intuitive. It makes it easy to monitor production by viewing each of the phases of the cycle: vacuum, blow-off, and rest.



### Stand-alone or Island Modules?

Stand-alone modules are suitable for the most common applications; one module controls one or more suction cups which all operate according to the same sequence.


When several suction cups are operating according to different sequences, multiple modules are required, which can be:

- several stand-alone modules,
- an island of these modules with an internal common pressure unit.


The diagrams below help in the selection:

- Stand-alone modules are complete, with the integrated pressure regulator (ASR, see p 8/3)
- in an island, the integrated regulator is absent: to maintain the advantage of economical and silent operation, it is recommended to reduce the pressure of the island's common pressure unit to 4 bar.

#### 4.5 to 7 bar network pressure



#### network pressure 4 bar



island of 3 modules supplying suction cups according to different sequences



## Integrated Mini-Vacuum Pumps with ASR Selection Guide



### LEM: Versatile Series for all Applications

The opposite page demonstrates the versatility of this series. In addition to a very wide range of complete, stand-alone, or island vacuum pumps, there are the options of no blow-off and/or no vacuum switch, and for specific applications.


### Select Vacuum Level and Nozzle Diameter

The introductory guide in this catalog shows that for porous objects, a 30-55 % vacuum is economical and effective. This is obtained with a 60 % maximum vacuum pump.



The table below helps to select the nozzle diameter which generates enough vacuumed air flow to respond in the time required by the application, based on a measurement of the material's leakage rate.

On the contrary, with an airtight material, the vacuum used is 55 % to 80 %, obtained by a 85 % max. vacuum pump.


- For standard cases, with its integrated blow-off, the LEMAX series is preferable, as it is more economical due to its ASC (Air Saving Control) function (see p. 8/15).
- For special cases, the LEM series contains versions without blow-off and versions without a vacuum switch. The table below helps to select the nozzle diameter required for the application.



force generated by the vacuum



Airtight materials:  
glass, plastic, sheet  
metal, finished wood



#### Porous Objects ► Maximum Vacuum Level: 60%

Time to create vacuum (seconds) for a volume of 1 liter

vacuum achieved	30%	35%	40%	45%	50%	55%	Air consumed (SCFM)	Air drawn in (SCFM)
ø nozzle								
1.0 mm	0.66	0.83	1.04	1.31	1.70	2.35	1.55	1.34
1.2 mm	0.41	0.52	0.66	0.83	1.07	1.49	2.30	2.54
1.4 mm	0.27	0.34	0.43	0.54	0.70	0.97	3.18	3.25

#### Airtight Objects ► Maximum Vacuum Level: 85%



Time to create vacuum (seconds) for a volume of 1 liter

vacuum achieved	55%	60%	65%	70%	75%	80%	Air consumed (SCFM)	Air drawn in (SCFM)
ø nozzle								
1.0 mm	1.76	2.04	2.38	2.80	3.33	4.09	1.55	1.02
1.2 mm	1.13	1.31	1.53	1.80	2.15	2.64	2.30	1.59
1.4 mm	0.73	0.85	0.99	1.16	1.38	1.70	3.18	2.47

### Select Vacuum Controlled by NC or NO Solenoid Valve

Vacuum controlled by a NC (Normally Closed) solenoid valve remains the simplest standard option to use. In the event of an electricity shutoff, the vacuum is interrupted and the object is released.

Select vacuum controlled by NO (Normally Open) solenoid valve if the application requires holding the object in the event of an electricity shut-off. In this case, make sure to control the NO solenoid valve with the inverse signal of the "vacuum" signal, which is noted as "vacuum".



### Select with or without Integrated Blow-off

Many applications require integrated blow-off. However, for some applications not requiring blow-off, a simplified version without blow-off is offered.

### Select with or without Vacuum Switch

For common applications, the vacuum switch is needed, with the dialogue face for digital display and adjustment → see page 8/4. However, some applications may just require a simple operation, without an "object gripped" return signal. The simplified version may then be chosen, with no vacuum switch, display, or adjustment.



## Integrated Mini-Vacuum Pumps with ASR Configuring a Vacuum Pump



Part numbers for an island assembly or components in an island

Part numbers for stand-alone units

**LEM 60 X 12 S VA B3**

VACUUM LEVEL	
60% max. vacuum → porous objects	<b>60</b>
85% max. vacuum → airtight objects	<b>90</b>

NOZZLE DIAMETER	
ø 1 mm nozzle	<b>10</b>
ø 1.2 mm nozzle	<b>12</b>
ø 1.4 mm nozzle	<b>14</b>

VACUUM SWITCH	
<b>VA</b> ■ Electronic vacuum switch with digital display and adjustment	
<b>VO</b> ■ No vacuum switch and no adjustment	

### ISLAND ASSEMBLIES

<b>B2</b>		LEM--X----- <b>B2</b> island assembly with 2 identical modules.
<b>B3</b>		LEM--X----- <b>B3</b> island assembly with 3 identical modules.
<b>B4</b>	...	

If the planned island contains different module types, it must be ordered as separate components in order to then be assembled on site according to the arrangement suitable to the application.

### COMPONENTS FOR THE ISLAND TO BE ASSEMBLED

<b>B</b>		LEM-X----- <b>B</b> Module that can be grouped (complete with integrated grouping screw)
		Set of ends for a complete group, with grouping screw and common pressure unit plug. <b>Part No.: LEMSETA</b>

### COMPOSITION OF THE MODULE

<b>S</b>	<ul style="list-style-type: none"> <li>■ Vacuum controlled by NC solenoid valve → if the electricity is shut off, the vacuum is interrupted.</li> <li>■ Blow-off controlled by a specific signal</li> </ul>	
<b>V</b>	<ul style="list-style-type: none"> <li>■ Vacuum controlled by NO solenoid valve → vacuum is maintained if electricity is shut off</li> <li>■ Blow-off controlled by a specific signal</li> </ul>	
<b>R</b>	<ul style="list-style-type: none"> <li>■ Vacuum controlled by NC solenoid valve</li> <li>■ No blow-off</li> </ul>	
<b>U</b>	<ul style="list-style-type: none"> <li>■ Vacuum controlled by NO solenoid valve</li> <li>■ No blow-off</li> </ul>	

### Additional options: On specific request:

- Modules with enhanced blow-off by integrated isolation valve.
- Modules with non-return valve will maintain vacuum in the event of loss of pneumatic and/or electrical power, during the grip cycle.

### EXAMPLE COMPOSITE PART NUMBER FOR AN ISLAND ASSEMBLY:

#### ■ LEM60X14SVAB3

LEM island assembly, containing 3 x 60% max. vacuum modules, ø 1.4 mm nozzle, controlled by NC solenoid valve, blow-off and vacuum switch

### ORDER EXAMPLE FOR AN ISLAND TO BE ASSEMBLED:

- LEM60X10VVAB
  - LEM90X12SVAB
  - LEM60X14SVAB
  - LEMSETA
- 3 LEM modules for a group, of different types.  
Set of ends for island.

### REFERENCE EXAMPLE COMPOSED OF A STAND-ALONE MODULE:

#### ■ LEM60X12SVA

Stand-alone LEM Module, 60% max. vacuum, ø 1.2 mm nozzle, vacuum controlled by NC solenoid valve, blow-off and vacuum switch.



## Integrated Mini-Vacuum Pumps with ASR




### Dimensions / Mounting options





#### Stand-alone Modules



Side mounting



Front mounting





For front mounting, order the necessary kit, in addition to the module:

Front mounting kit:  
1 plate + 4 screws

**Part No.: LEMFIXA**



Mounting on DIN rail




A module can be clipped onto a DIN rail.

For this purpose, the module must first be equipped with an individual DIN installation plate, ordered separately:


DIN rail mounting kit:  
1 plate/clip + 4 screws

**Part No.: LEMFIXB**


#### Islands



#### Front mounting



#### Mounting on DIN rail



DIN rail mounting kit:  
2 clips + 2 screws

**Part No.: LEMFIXC**



## Integrated Mini-Vacuum Pumps with ASR

### Characteristics / Assembling an Island



#### Overall Characteristics

- Supply: non-lubricated air filtered to 5 microns according to standard ISO 8573-1:2010 [4:5:4].
- Operating pressure: 4.5 to 7 bar.
- Mini dynamic pressure:
  - stand-alone module: P = 4.5 bar.
  - island modules: 4 bar.
- Blow-off: adjustable flow:
  - stand-alone version: P = 3.5 bar.
  - island version: P network.
- Maximum vacuum: 60% or 85% depending on model (see page 8/5).
- Suction rate: 1.02 to 3.25 SCFM depending on model (see page 8/5).
- Air consumption: 1.55 to 3.18 SCFM depending on model (see page 8/5).
- Electrical protection level: IP 65.
- Control voltage: 24 V DC (regulated  $\pm 10\%$ ).
- Current draw: 30 mA (0.7 W) vacuum or blow-off.
- Max. operating frequency: 4 Hz.
- Endurance: 30 million cycles.
- Weight: 90 to 120 g, depending on model.
- Operating temperature: 50 to 140 °F.
- Materials: PA 6-6 15 %FV, brass, aluminium, NBR.

#### Integrated Vacuum-switch Characteristics


- Measuring range: -1 to 0 bar.
- Precision:  $\pm 1.5\%$  of the range.
- Hysteresis: adjustable from 0% to 100%.
- Output threshold: 1 x T.O.R. in NO.
- Analog output: 1 V DC to 5 V DC on the measuring range.
- Switching power: 125 mA, PNP.
- Threshold status display: 1 green LED.
- Supply voltage 24V DC (regulated  $\pm 10\%$ ).
- Current draw: < 20 mA.
- Protection: against polarity inversions.

#### Integrated-silencer Characteristics

- Noise level: approximately 68 dBA.
- Clog-free silencer.


#### Electrical Connections

##### MODULES WITHOUT VACUUM-SWITCH FUNCTION



Note: straight and angled M8 connectors shown (p. 10/11).


##### MODULES WITH VACUUM-SWITCH FUNCTION



#### Characteristics and Connecting an Island

island of 4 modules

set of ends for the island.




island of 3 modules



#### Maximum number of modules in an island:

- $\varnothing 1.4$  mm nozzle  $\rightarrow$  5 modules
- $\varnothing 1.2$  mm nozzle  $\rightarrow$  7 modules
- $\varnothing 1$  mm nozzle  $\rightarrow$  9 modules

#### Suction Flow Rate / Vacuum Curves



- 1 - LEM60X10
- 2 - LEM60X12
- 3 - LEM60X14

- 1 - LEM90X10
- 2 - LEM90X12
- 3 - LEM90X14

#### Note:

In the same island, it is possible to combine LEM series modules and LEMAX series modules.



# LEM+

## Compact, High Flow Vacuum Pumps


### General Information

**LEM+ Series**, compact, high flow vacuum pumps, integrate **ASR** (Air Saving Regulator) technology that allows up to 40% of energy savings. They are designed for gripping porous products or those with a rough surface.

For gripping airtight or semi-airtight products, it is recommended to use the **LEM+ Series** (see page 8/23).



Industry-specific applications



More information



### Advantages

- Easy implementation: Plug & Play, multiple choices, every type of application.
- Maximum automatic energy savings:
  - ASR**: 40% savings for porous products.
- Compactness: LEM+ vacuum pumps are the most compact on the market.
- Short response times: Possible installation very close to vacuum pads.
- Automatic blow-off: Reduced PLC I/O requirement thanks to the automatic blow-off function (blow-off time configurable from 0 to 10s).
- Dust resistant: Non-clogging through-type silencer.
- Safety: Product gripping is maintained even during power failure.



### Configurations



- 60 or 85% of maximum vacuum.
- NC or NO, depending on safety.
- Combined **ASR** "venturi regulator".
- With or without visual display.
- With or without vacuum sensor.
- With or without controlled blow-off or automatic blow-off function.
- Powerful blow-off as option.
- Versions with 1 or 2 M12 connectors.
- Suction flow rate (SCFM):

max. vacuum nozzle Ø	60%	85%
2.0 mm	6.67	4.41
2.5 mm	9.71	7.06

### Integration

The **LEM+** compact modules integrate all the functions of "industrial vacuum" including simple, efficient, economical compressed air and are adapted for every application:

- 1 3.5 bar pressure regulator
- 2 "Vacuum" solenoid valve
- 3 3.5 bar optimised venturi
- 4 Optimized silencer
- 5 Electronic vacuum sensor
- 6 Integrated electronics
- 7 "Blow-off" solenoid valve
- 8 Blow-off flow rate regulator



**40%** energy savings  
(on average, see p.8/10).

Combined "venturi regulator" **ASR**: pressure regulator 1 feeds venturi 3 with 3.5 bar, optimal for its operation.

→ No more unnecessary consumption of compressed air.



# LEM+

## Compact, High Flow Vacuum Pumps Energy Savings & Intelligence




### (ASR): Air Saving Regulator

The LEM+ vacuum pumps, which integrate an **ASR** "venturi regulator" combination, maintain ideals that COVAL values greatly: reducing both compressed air consumption and noise generation. Regardless of pressure supplied by the compressed air network, the integrated regulator feeds the venturi at **3.5 bar** pressure, optimal for its operation.

- ➔ No more unnecessary energy consumption.
- ➔ No external regulator required and thus the risk of inadvertent misadjustment is eliminated.

Compared to pressures found in most compressed air networks (5-7 bar), the graph opposite demonstrates an achieved economy of 40% on average.



More information



### Intelligence

The front communication face panel allows access and programming of all operations: Various types of monitoring, threshold settings, pump configuration, diagnostics, etc. This front face panel can be locked to prevent an inadvertent misadjustment.

Built-in intelligence, as well as standard factory settings, optimize the implementation, operation, monitoring and maintenance.


➔ **Simplified & Protected Installation and Operation.**

Due to the high visibility display of the **LEM+** modules, all useful information can be seen at a single glance: vacuum level, product gripped, thresholds reached, energy saving mode activated, etc.


The actual vacuum level is shown with direct reading (selection of different display units), and with "bar graph".

Configuration help messages (multilingual: in French, English, Italian, Spanish, German) are also provided.

➔ **Clear & Complete Communication at Each Stage.**



L1 "Product Gripped" visualisation and setting: (vacuum threshold, hysteresis)



Displaying:  
- Vacuum level  
- Setting values

Keypad lock

ⓘ: Automatic blow-off function activated.

Display units:  
%, mbar, inHg.

Display shows data in many languages / bar graphs





### LEM+: Versatile Series for all Applications

The opposite page demonstrates the versatility of this series. In addition to a very wide range of complete vacuum pumps, there are the options of no blow-off and/or no vacuum switch, and for specific applications.

### Select Vacuum Level and Nozzle Diameter

The introductory guide in this catalog shows that for porous objects, a 30-55% vacuum is economical and effective. This is obtained with a 60% maximum vacuum pump.



The table below helps to select the nozzle diameter which generates enough vacuumed air flow to respond in the time required by the application, based on a measurement of the material's leakage rate.

On the contrary, with an air-tight material, the vacuum used is 55% to 80%, obtained by a 85% max. vacuum pump.


For standard cases, with its integrated blow-off the **LEM+** series is preferable, and more economical due to its **ASC** (Air Saving Control) function → see p. 8/23.

For special cases, the **LEM+** series contains versions without blow-off and versions without a vacuum switch. The table below helps to select the nozzle diameter required for the application.

**Porous materials:**  
cardboard, unfinished wood,  
pastries, etc.



**Airtight materials:**  
glass, plastic, sheet metal,  
finished wood



#### Porous Objects ▶ Maximum Vacuum Level: 60%



Time to create vacuum (seconds) for a volume of 1 liter				Air consumed (SCFM)	Air drawn in (SCFM)
vacuum achieved	35 %	45 %	55 %		
Ø nozzle					
2.0 mm	0.16	0.27	0.42	6.32	6.67
2.5 mm	0.11	0.18	0.31	9.18	9.71

#### Airtight Objects ▶ Maximum Vacuum Level: 85%

Time to create vacuum (seconds) for a volume of 1 liter				Air consumed (SCFM)	Air drawn in (SCFM)
vacuum achieved	55 %	65 %	75 %		
Ø nozzle					
2.0 mm	0.38	0.55	0.80	6.32 *	4.41
2.5 mm	0.26	0.35	0.50	9.18 *	7.06

\* To save compressed air, choose **LEM+** → **ASC** reduces the air consumption by 90%

### Suction Flow Rate / Vacuum Curves







	<b>LEM</b>	<b>60</b>	<b>X</b>	<b>25</b>	<b>S</b>		<b>VA</b>	<b>C15</b>		<b>P</b>	<b>G1</b>	<b>F</b>
--	------------	-----------	----------	-----------	----------	--	-----------	------------	--	----------	-----------	----------

VACUUM LEVEL	
60 % max. vacuum is optimal for porous materials	<b>60</b>
85 % max. vacuum is optimal for air-tight products	<b>90</b>

NOZZLE DIAMETER	
2 mm nozzle Ø	<b>20</b>
2.5 mm nozzle Ø	<b>25</b>

MODULE COMPOSITION	
<b>NC Vacuum Pump Without Blow-Off</b>  LEM__X__RV_C__PG1 ▪ Single command signal. ▪ <b>NC</b> vacuum command valve.	<b>R</b>
<b>NC Vacuum Pump With Blow-Off</b>  LEM__X__SV_C__PG1 ▪ 2 command signals. ▪ <b>NC</b> vacuum command valve. ▪ Blow-off configured on site, at choice: - Blow-off controlled by specific signal; - Automatic blow-off function (blow-off time configurable from 0 to 10s), only with VA option (advantage: reduced PLC I/O requirement). ▪ Adjustable blow-off flow rate.	<b>S</b>
<b>NO Vacuum Pump With Blow-Off</b>  LEM__X__VV_C__PG1 ▪ 2 command signals. ▪ <b>NO</b> vacuum command valve. ▪ Blow-off controlled by external signal. ▪ Adjustable blow-off flow rate.	<b>V</b>

VACUUM SENSOR DIALOGUE		CONNECTORS	
Vacuum pump without vac. sensor	<b>V0</b> <b>C14</b>	one M12 connector 4 pins (C14)	
LEM__X__VOC14PG1		 ▪ Simplified LEM+ without settings and dialogue. ▪ Automatic operation until maximum vacuum level.	
Vacuum pump with vacuum sensor & dialogue	<b>VA</b> <b>C15</b>	one M12 connector 5 pins (C15)	
LEM__X__VAC15PG1		 ▪ Electronic vacuum sensor (VA). ▪ "Gripped product" switching output 24V DC / NO. ▪ Front face panel and full dialogue.	
Vacuum pump with vacuum sensor & dialogue	<b>VA</b> <b>C24</b>	two M12 connectors 4 pins (C24)	
LEM__X__VAC24PG1		 ▪ Electronic vacuum sensor (VA). ▪ Stand alone I/O. ▪ "Gripped product" switching output 24V DC / NO. ▪ 1 auxiliary output: "Vacuum level" signal analogic 1 to 5V DC. ▪ Front face panel with full dialogue.	

POWERFUL BLOW-OFF	
Without	
With	<b>F</b>

The powerful blow-off option allows you to release the product quickly. Isolation valve **F** directs the entire blow-off flow to the vacuum pad. The option is only available with LEM+ modules equipped with a blow-off regulation: Version LEM\_\_X\_\_SV... and LEM\_\_X\_\_VV...  
 NB: If option **F** is selected, no blow-off flow rate setting is available.

**EXAMPLE OF COMPLETE PART NUMBER: LEM60X25SVAC15PG1** LEM+ vacuum pump, 60% maximum vacuum, 2.5 mm nozzle Ø, controlled by a NC (Normally Closed) solenoid valve with vacuum sensor and dialogue, connection by 1 M12 5-pin connector.







#### Side Mounting



▪ Version: one M12 connector

▪ Version: two M12 connectors



Mounting from side is the simplest to implement: Two Ø 5 mm through screws or bolts with large washers.

#### Mounting from Front





For mounting from front, in addition to the module, you need to order an additional kit:

Mounting from front kit:  
1 plate + 4 screws

**Part No.: LEMFIX2A**

#### Mounting on DIN rail



For a static mounting (for example, in a cabinet), a module can be clipped onto a DIN rail. For this purpose, the module must first be equipped with an individual plate for fixing onto a DIN rail, to be ordered separately:

Kit for mounting on DIN rail:  
1 plate / clip + 4 screws

**Part No.: LEMFIX2B**





#### Specifications

##### COMMON SPECIFICATIONS

- Supply: Non-lubricated air 5 microns filtered, according to ISO 8573-1:2010 [4:5:4].
- Operating pressure: 4.5 to 7 bar.
- Blow-off: Adjustable flow rate.
- Powerful blow-off (option F) P = 3.5 bar without flow rate control.
- Maximum vacuum: 60% or 85% depending on model.
- Suction flow rate: From 4.41 to 9.71 SCFM, depending on model.
- Air consumption: From 6.32 to 9.18 SCFM, depending on model.
- Integrated non-clogging silencer.
- Sound level: From 72 to 75 dBA.
- Display status:
  - of the vacuum control on the front panel: Green LED.
  - of the blow-off control on the front panel: Orange LED.
- Electric protection grade: IP 65.
- Maximum operating frequency: 4 Hz.
- Response time for opening / closing: 20/30 ms.
- Service life: 30 million cycles.
- Weight: From 410 to 460 g, depending on model.
- Operating temperature: From 50 to 122°F.
- Materials: PA 6-6 15% FG, brass, aluminum, NBR, HNBR, PU.

##### Electrical Controls

- Control voltage: 24V DC ( $\pm 10\%$  regulated).
- Current consumption: 30 mA (0.7W) by vacuum or blow-off solenoid valve.

##### VA MODEL SPECIAL SPECIFICATIONS

###### Displays

- Display status of the threshold on the front panel: Green or red LED.
- Black and white LCD display, 7 matrix, symbols, vacuum reading area.
- Displaying the vacuum level and bar graph.
- Displaying number of cycles (vacuum cycles counter).
- Indication of exceeding service life (> 30 million cycles).

###### Settings

- Using membrane keypad and pull down menu.
- Language selection: FR, ENG, DE, IT or ES.
- Blow-off type selection: controlled or automatic (blow-off time configurable from 0 to 10s).
- Measurement unit selection (% , mbar, inHg).
- Manual, electrical, monostable commands.
- If the application requires, specific setting of thresholds and hysteresis that are different from the initial factory settings: L1 = 65%, h1 = 10%.

###### Vacuum Sensor

- Power supply voltage: 24V DC ( $\pm 10\%$  regulated).
- Current consumption: Standby: <25mA / max. 60 mA.
- Measurement range: 0 to 99% of vacuum, 0 to -999 mbar, 0 to -29.9 inHg.
- Measurement accuracy:  $\pm 1.5\%$  of range, temperature compensated.

###### "Gripped Product" Output Signal

- 24V DC, switching output / NO, switching capacity: 125 mA PNP.


###### Auxiliary output (C24 model only, 2 x M12 4 pins)

- "Vacuum level" signal, analogic 1 to 5V DC of measuring range.


#### Electrical Connections

##### 1- For Vacuum Pumps of Model R (vacuum control NC valve)


- C14:** 1 M12 4-pin connector



- C15:** 1 M12 5-pin connector




- C24:** 2 M12-4 pin connector




##### 2- For Vacuum Pumps of Model S (vacuum control NC valve, blow-off control NC valve)


- C14:** 1 M12 4-pin connector



- C15:** 1 M12 5-pin connector




- C24:** 2 M12-4 pin connector




\* externally controlled blow-off or automatic blow-off function > economy of an automaton outlet.

##### 3- For Vacuum Pumps of Model V (vacuum control NO valve, blow-off control NC valve)


- C14:** 1 M12 4-pin connector



- C15:** 1 M12 5-pin connector



- C24:** 2 M12-4 pin connector



**M12 Electrical Connectors:** see page 10/11.



## Integrated Mini Vacuum Pumps with "ASC" (Air Saving Control)



Industry-specific applications



For all objects, airtight or not very porous

More  
information



### Advantages

- Energy savings of 75 to 99% (depending on application) thanks to automatic **ASC** (Air Saving Control) operation.
- "All-in-one" solution, no more peripherals to be added.
- Simplified installation and use thanks to the Plug & Play system.
- Unmatched compactness: Installation close to suction cups → short response times and energy savings.
- No clogging, thanks to the through-type silencer.
- Controlled or timed blow-off.
- Gripping safety in the event of electricity shut-off.
- Smart communication → Easier experience at all stages: initial settings, production, maintenance.

### Compact Integration


The illustrations below demonstrate the 9 functions integrated in the mini-module, and their respective roles in operation.

The result of this COVAL performance is:

- A **mini module** ( $\approx 130$  g) that is easy to install close to the suction cups, reducing the volume to be evacuated → increased speed and energy savings.
- A **complete module**, therefore not requiring any additional function or connections.


The **LEMAX** compact modules integrate all the functions of "industrial vacuum" including simple, efficient, economical compressed air usage and are adapted for every application:

- 1 3.5 bar pressure regulator
- 2 Solenoid valve "vacuum"
- 3 3.5 bar optimized Venturi
- 4 Through-type silencer
- 5 Electronic vacuum switch
- 6 Integrated electronics
- 7 Solenoid valve "blow-off"
- 8 Blow-off flow adjustment
- 9 Check valve on vacuum



Combination of non-return 9 and advanced electronics 6 ensures the **ASC's** automatic performance.

→ Once desired vacuum level is reached, the **LEMAX** no longer consumes air when gripping the product.




**90%** energy savings  
(on average, see p.8/16).

### Smart Communication

The adjacent illustration presents the display panel which enables:

- Initial settings
- Any adjustments
- Production monitoring
- Maintenance

In particular, the no "**ASC**" alert, (see next page), helps to start maintenance operations in order to return to "**ASC**" operation, which is especially energy-saving.








### AIR Saving Control

### "Air Saving Control" Cycle



As illustrated above, the LEMAX module automatically executes the "ASC" cycle, thus saving the maximum amount of energy, based on the following 3 phases.

#### 1- Gripping the object

The "vacuum" solenoid ② starts the cycle by supplying the venturi ③ which generates the vacuum to quickly pick up the object with the suction cup → short-term consumption.

#### 2- Operations on the object held by vacuum


The vacuum level is constantly monitored by the vacuum switch ④. When it reaches the L1 threshold (65%), the "gripped object" signal is generated, which allows the planned operations (transfer, machining, etc.). When the vacuum reaches threshold L2 (75%), the supply to the venturi via the solenoid valve ② is cut off → consumption is halted. The object remains held by the retained vacuum thanks to the closed valve ⑤. Micro-leaks will generally cause the vacuum level to fall slowly. Each time it falls below 65%, vacuum generation is briefly resumed until it reaches threshold L2 (75%).

#### 3- Releasing the object

At the end of operations, blow-off is ordered. The "blow-off" solenoid valve ⑦ generates a stream of air which closes the isolation valve ⑥, blows on the object to release it quickly.

### Smart Adaptation

The illustration below shows the adaptation capacities of the LEMAX module. "ASC" operation is automatic for any object that is airtight enough (cycle 1). If a leak occurs (cycle 2), due to a rough object or to suction-cup wear, the module automatically detects the anomaly, ends the cycle without "ASC" in order to continue production and reports the event for possible maintenance. Production continues. Once everything is returned to normal (cycle 3), "ASC" operation is automatically resumed.



#### 1- Gripping + Transfer (Ø 1.4 mm nozzle, 0.2 l of vacuum)

Phase	Duration	Air consumption		
		"ASC" off	"ASC" on	
Gripping	0.28 s	0.014 ft³	0.014 ft³	Energy savings achieved
Transfer	1.20 s	0.063 ft³	0	
Release	0.14 s	0.007 ft³	0.007 ft³	
		0.084 ft³	0.021 ft³	75 %

#### 2- Clamping + Operations (Ø 1.4 mm nozzle, 0.4 l of vacuum)

Phase	Duration	Air consumption		
		"ASC" off	"ASC" on	
Clamping	0.55 s	0.028 ft³	0.028 ft³	Energy savings achieved
Operations	60 s	3.178 ft³	0	
Release	0.14 s	0.007 ft³	0.007 ft³	
		3.213 ft³	0.035 ft³	99 %

### Resulting savings

Energy savings from "ASC" are major, as the two examples opposite above:

- 75% savings for transferring an object after gripping.
- 99% savings for holding an object during a 1 minute operation.

The investment generally pays for itself in just a few months.

### "ASC": AN ADVANTAGE WITHOUT LIMITATIONS

Saving energy has become essential. With LEMAX, thanks to "ASC", energy is automatically saved without interfering with established operations:

- 1- No specific adjustment:** The initial setting (L1 = 65%, L2 = 75%) is suitable for most applications.
- 2- Production regardless of what happens:** Operation is always ensured, if necessary without "ASC", if the leakage level is too high.
- 3- Guided maintenance:** Clear display of the need for maintenance to return to auto-regulated "ASC" operation.



## Integrated Mini Vacuum Pumps with "ASC" Selection Guide



### Stand-alone or Island Modules?

Stand-alone modules are suitable for the most common applications: one module controls one or more suction cups which all operate according to the same sequence.


When several suction cups are operating according to different sequences, multiple modules are required, which can be:

- several autonomous modules;
- a group of these modules with an internal common pressure unit.

The illustrations opposite guide the selection:

- stand-alone modules are coupled with integrated pressure regulators (see "ASR" p. 8/3)
- in an island, the integrated regulator is removed: to maintain the advantage of economical and silent operation, it is recommended to reduce the island's common pressure supply pressure to 4 bar.

Network pressure:  
4.5 to 7 bar



### Power Determined by the Venturi Nozzle Diameter

The table shows the power levels generated by each of the nozzle diameters available: when the module is operating with "ASC" off, a larger nozzle draws and consumes more compressed air.

On the other hand, during "ASC" operation, a large nozzle quickly reaches the vacuum threshold generating power shut-off.

In conclusion:


- A large nozzle enables quicker gripping without consuming more during "ASC" operation.
- A small nozzle consumes less only when operating continues without "ASC".

#### Selecting the Nozzle Diameter

Ø nozzle	Venturi characteristics during "ASC off" operation.		"ASC" operation - gripping at 65% vacuum - vacuum shutoff at 75% Time for a volume of 1l		
	air drawn in (SCFM)	air consumed (SCFM)	grip time (s) (65% vacuum)	time (s) up to 75% vacuum	air consumed (ft³)
1.4 mm	2.47	3.18	0.99	1.38	0.077
1.2 mm	1.59	2.30	1.53	2.15	0.077
1.0 mm	1.02	1.55	2.38	3.33	0.077



### Suction Flow Rate / Vacuum Curves



- 1 - LEMAX90X10
- 2 - LEMAX90X12
- 3 - LEMAX90X14

### Select Vacuum Controlled by NC or NO Solenoid Valve


Vacuum controlled by a NC (Normally Closed) solenoid valve remains the simplest standard option to use. In the event of an electricity shutoff, the vacuum is interrupted and the object is released. On the contrary, with vacuum control by NO (Normally Open) solenoid valve, the vacuum continues to be generated in the event of an electrical shutoff: positive object-holding security.

The diagrams opposite show that both versions are controlled by the same "vacuum" signal  $\bar{v}$ :


The opposite  $\bar{v}$  required for control of the NO solenoid valve is automatically obtained internally by the control electronics.

Note, however, that the NO version requires blow-off controlled by a specific signal: automatic, timed blow-off can only be configured in the NC version.

#### NC solenoid valve



#### NO solenoid valve





## Integrated Mini Vacuum Pumps with "ASC" Configuring a Vacuum Pump



Part numbers for an island assembly or components in an island

Part numbers for stand-alone units

<b>LEMAX</b>	<b>90</b>	<b>X</b>	<b>14</b>	<b>S</b>	<b>-</b>	<b>B3</b>
--------------	-----------	----------	-----------	----------	----------	-----------

<b>VACUUM LEVEL</b>	<b>CONNECTORS</b>	<b>ISLAND ASSEMBLIES</b>
<p>maximum 85% vacuum optimum for airtight objects</p> <p><b>90</b></p>	<p><b>-</b></p> <p>Vacuum Pump with 2 M8 4-pin Connectors LEMAX90X...</p> <ul style="list-style-type: none"> <li>Discrete I/O.</li> <li>"Gripped product" switching output 24V DC / NO.</li> <li>1 configurable auxiliary output:                     <ul style="list-style-type: none"> <li>either "Vacuum level" signal analogic 1 to 5V DC.</li> <li>or "Without ASC" signal +5V DC switching output NO.</li> </ul> </li> </ul>	<p><b>B2</b> LEMAX90X...<b>B2</b> island assembly with 2 identical modules.</p> <p><b>B3</b> LEMAX90X...<b>B3</b> island assembly with 3 identical modules.</p> <p><b>B4</b> ...</p>

<b>NOZZLE DIAMETER</b>	
Ø 1.4 mm nozzle	<b>14</b>
Ø 1.2 mm nozzle	<b>12</b>
Ø 1 mm nozzle	<b>10</b>

<b>COMPOSITION OF THE MODULE</b>	
<p><b>Vacuum pump controlled by a Normally Closed (NC) solenoid valve</b></p> <p>LEMAL90X...<b>S</b>...</p> <ul style="list-style-type: none"> <li>In the event of an electrical shut-off, vacuum is no longer generated.</li> <li>Optional configured blow-off:                     <ul style="list-style-type: none"> <li>by specific signal,</li> <li>automatic, timed 0 to 9.9 sec. (→ a single control signal vacuum and blow-off).</li> </ul> </li> </ul>	<b>S</b>
<p><b>Vacuum pump controlled by a Normally Open (NO) solenoid valve</b></p> <p>LEMAL90X...<b>V</b>...</p> <ul style="list-style-type: none"> <li>In the event of an electrical shut-off, the vacuum continues to be generated: gripped object held → positive security.</li> <li>Blow-off controlled by a specific signal.</li> </ul>	<b>V</b>

<b>C14</b>	<b>B</b>
<p>Vacuum Pump with 1 M8 4-pin Connector LEMAL90X...<b>SC14</b> (<b>S</b> version only)</p> <ul style="list-style-type: none"> <li>"Gripped product" switching output 24V DC / NO.</li> <li>Automatic blow-off, timed 0 to 9.9 sec.</li> </ul>	<p>LEMAL...<b>B</b> Module that can be grouped (complete with integrated grouping screw).</p> <p>Set of ends for a complete island, with grouping screw and common pressure unit plug.</p> <p><b>PART NO.: LEMSETA</b></p>

If the planned island contains different module types, it must be ordered as separate components in order to then be assembled on site according to the arrangement suitable to the application. (see p. 8/20)

Input/Output switching type can be set to PNP/NPN

**REFERENCE EXAMPLE COMPOSED OF A STAND-ALONE MODULE:**

■ **LEMAL90X14S**

LEMAL, mini vacuum pump, 85% max. vacuum, 1.4 mm nozzle, controlled by a NC (Normally Closed) solenoid valve.

**EXAMPLE COMPOSITE PART NUMBER FOR AN ISLAND ASSEMBLY:**

■ **LEMAL90X14SB3**

LEMAL group assembly, containing 3 x 85% max. vacuum modules, Ø 1.4 mm nozzle, controlled by NC (Normally Closed) solenoid valve.

**ORDER EXAMPLE FOR AN ISLAND TO BE ASSEMBLED:**

■ **LEMAL90X14VB**

■ **LEMAL90X12SB**

■ **LEMAL90X10VB**

■ **LEMSETA**

3 LEMAL modules for an island, of different types.

Set of ends for island.






## Integrated Mini Vacuum Pumps with "ASC" Dimensions, Mounting Options





### Stand-alone Modules



Side mounting



Front mounting



For front mounting, order the necessary kit, in addition to the module:

Front mounting kit:  
1 plate + 4 screws



**Part No.: LEMFIXA**

8

LEMAX



Mounting on DIN rail



A module can be clipped onto a DIN rail.

For this purpose, the module must first be equipped with an individual DIN installation plate, ordered separately:

DIN rail mounting kit:  
1 plate/clip + 4 screws




**Part No.: LEMFIXB**



## Integrated Mini Vacuum Pumps with "ASC" Dimensions, Mounting Options




### Islands




**Part No.: LEMFIXC**

### Assembling and Connecting an Island



island of 3 modules



### Maximum number of modules in an island:

- Ø 1.4 mm nozzle → 5 modules
- Ø 1.2 mm nozzle → 7 modules
- Ø 1 mm nozzle → 9 modules

### Note:

In a single island, it is possible to combine LEMAX series modules and LEM series modules (see p. 8/3).







## Integrated Mini Vacuum Pumps with "ASC" Characteristics / Assembling a Group



### For NC Vacuum Pumps with 2 M8 4-pin connectors, model LEMAX90X..S..

#### configurable auxiliary output




- "vacuum level" signal analog, 1 to 5 VDC  
↓ OR (configuration)
- ASC off signal +5 V TOR in NO





### For NO Vacuum Pumps with 2 M8 4-pin connectors, model LEMAX90X..V..

#### configurable auxiliary output

- "vacuum level" signal analog, 1 to 5 VDC  
↓ OR (configuration)
- ASC off signal +5 V TOR in NO



### For NC Vacuum Pumps with 1 M8 4-pin connector, model LEMAX90X..SC14



**M8 Electrical Connectors:** see page 10/11.



## Integrated Mini Vacuum Pumps with "ASC" Characteristics / Assembling a Group



### Overall Characteristics

- Supply: non-lubricated air filtered to 5 microns according to standard ISO 8573-1:2010 [4:5:4].
- Operating pressure: 4.5 to 7 bar.
- Mini dynamic pressure:
  - stand-alone version: P = 4.5 bar.
  - island version: P = 4 bar.
- Blow-off: adjustable flow:
  - stand-alone version: P = 3.5 bar.
  - island version: P network
- Maximum vacuum: 85 %
- Suction rate: 1.02 to 2.47 SCFM.
- Air consumption: 1.55 to 3.18 SCFM during "ASC" off operation
- Integrated clog-free silencer.
- Noise level: approximately 68 dBA "ASC" off. 0 dBA with "ASC".
- Electrical protection level: IP 65.
- Max. operating frequency: 4 Hz.

- Endurance: 30 million cycles.
- Weight: 130 g.
- Operating temperature: 50 to 140 °F.
- Materials: PA 6-6 15%FV, brass, aluminium, NBR.

### Electrical controls

- Control voltage: 24 V DC (regulated  $\pm 10\%$ ), PNP or NPN.
- Current draw: 30 mA (0.7 W) vacuum or blow-off.

### Integrated electronics

- Power supply 24 V; current draw: <57mA.
- Measuring range: 0 to 99% vacuum.
- Measuring precision:  $\pm 1.5\%$  of the range, compensated in temperature.
- Display: 3 digits, 7 segments.

### Service Characteristics

#### "Object gripped" output signal

- 24 VDC, switching output / NO, switching power: 125 mA PNP or NPN.

#### Configurable auxiliary output, choose either of the following

(not available for version LEMAX90X\_**SC14**):

- "vacuum level" signal, analog 1 to 5 VDC of the measuring range.
- "ASC" off signal, +5 V switching output / NO.

#### Input/Output switching type

- can be set to PNP (by default) or NPN.

#### Displays

- Scrolling display: 3 digits, 7 segments.
- Flashing if "ASC" off for maintenance.
- Status indicators: "Vacuum," green LED, "blow-off," red LED.
- "Object gripped" indicator: Green LED on front panel.

#### Configurations

- By mechanical keys and drop-down menu (see page 8/15).
- Measurement unit selection (% , mbar, inHg)..
- Choice of blow-off type:
  - LEMAX90X\_**S** version: controlled by a specific signal or automatic and adjustable from 0 to 9.9 s.
  - LEMAX90X\_**V** version: controlled by a specific signal.
  - LEMAX90X\_**SC14** version: automatic and adjustable from 0 to 9.9 s.

#### Settings

- Display of the number of cycles (vacuum cycle counter).
- If the application so requires, specific adjustment of thresholds and hysteresis different to original factory settings (L1=65% h1=10%, L2=75%, h2=10%).

#### Autoreactivity

- Constant monitoring of leakage rate: abandon or automatic return to "ASC" operation.



# LEM MAX+

## Compact, High Flow Vacuum Pumps


### General Information

**LEM MAX+ Series**, compact, high flow vacuum pumps, integrate ASC (Air Saving Control) technology that allows up to 90% of energy savings. They are specifically designed for gripping airtight or semi-airtight products.

For gripping porous products or those with a rough surface, it is recommended to use the **LEM+ Series** (see page 8/9).



Industry-specific applications



More information



#### Advantages

- Easy implementation: Plug & Play, multiple choices, every type of application.
- Maximum automatic energy savings:
  - AIR Saving Control ASC**: 90% savings for airtight products.
- Compactness: **LEM MAX+** vacuum pumps are the most compact on the market.
- Short response times: Possible installation very close to vacuum pads.
- Automatic blow-off: Reduced PLC I/O requirement thanks to the automatic blow-off function (blow-off time configurable from 0 to 10s).
- Dust resistant: Non-clogging through-type silencer.
- Safety: Product gripping is maintained even during power failure.

#### Configurations



- 85% of maximum vacuum.
- NC or NO, depending on safety.
- ASC advanced electronics.
- High visibility display.
- Integrated vacuum sensor.
- Vacuum non-return valve.
- Combined **ASR** "venturi regulator".
- External blow-off signal or automatic blow-off function.
- Powerful blow-off as option.
- Versions with 1 or 2 M12 connectors.
- Suction flow rate (SCFM):

max. vacuum	85%
nozzle Ø	
2.0 mm	4.41
2.5 mm	7.06

#### Integration

The **LEM MAX+** compact modules integrate all the functions of "industrial vacuum" including simple, efficient, economical compressed air usage and are adapted for every application:

- 1 3.5 bar pressure regulator
- 2 "Vacuum" solenoid valve
- 3 3.5 bar optimised venturi
- 4 Optimized silencer
- 5 Electronic vacuum sensor
- 6 Integrated electronics
- 7 "Blow-off" solenoid valve
- 8 Blow-off flow rate regulator
- 9 Powerful blow-off valve
- 10 Vacuum non-return valve



Schematic representation

Combination of non-return **10** and advanced electronics **6** ensures the ASC's automatic management.

→ Once vacuum is established, the pump does not continue to consume air to hold the product.



**90%** energy savings  
(on average, see p.8/24).




# LEMAX+

## Compact, High Flow Vacuum Pumps

### Energy Saving & Auto-adjustment



#### AIR Saving Control "Air Saving Control" Cycle



As illustrated in the above figure, the LEMAX module automatically executes the "ASC", cycle, thus saving the maximum amount of energy, based on the following 3 phases.

#### 1- Gripping the object

The "vacuum" solenoid ② starts the cycle by supplying the venturi ③ which generates the vacuum to quickly pick up the object with the suction cup → short-term consumption.

#### 2- Operations on the object held by vacuum

The vacuum level is constantly monitored by the vacuum switch ⑤. When it reaches the L1 threshold (65%), the "grippled object" signal is generated, which allows the planned operations (transfer, machining, etc.). When the vacuum reaches threshold L2 (75%), the supply to the venturi via the solenoid valve ② is cut off → consumption is halted. The object remains held by the vacuum maintained thanks to the closed valve ⑩. Micro-leaks will generally cause the vacuum level to fall slowly. Each time it falls below 65%, vacuum generation is briefly resumed until it reaches threshold L2 (75%).


#### 3- Releasing the object

At the end of operations, blow-off is ordered. The "blow-off" solenoid valve ⑦ generates a stream of air which closes the isolation valve ⑨, and, via flow regulation ⑧, blows on the object to release it quickly.

#### Smart Adaptation

The illustration below shows the adaptation capacities of the LEMAX module. "ASC" operation is automatic for any object that is air-tight enough (cycle 1).

If a leak occurs (cycle 2), due to a rough object or to suction-pad wear, the module automatically detects the anomaly, ends the cycle without "ASC" in order to continue production and reports the event for possible maintenance. Production continues. Once everything is returned to normal (cycle 3), "ASC" operation is automatically resumed.



#### 1- Gripping + transfer (2 mm nozzle Ø, emptying 0.2 l)

Phase	Duration	Air consumption		
		without "ASC"	with "ASC"	
Gripping	0.16 s	0.016 ft <sup>3</sup>	0.016 ft <sup>3</sup>	achieved economy
Transfer	1.20 s	0.106 ft <sup>3</sup>	0	
Release	0.14 s	0.010 ft <sup>3</sup>	0.010 ft <sup>3</sup>	
		0.132 ft <sup>3</sup>	0.027 ft <sup>3</sup>	→ 80 %

#### 2- Clamping + operations (2 mm nozzle Ø, emptying 0.4 l)

Phase	Duration	Air consumption		
		without "ASC"	with "ASC"	
Clamping	0.32 s	0.032 ft <sup>3</sup>	0.032 ft <sup>3</sup>	achieved economy
Operations	60 s	6.32 ft <sup>3</sup>	0	
Release	0.14 s	0.010 ft <sup>3</sup>	0.010 ft <sup>3</sup>	
		6.36 ft <sup>3</sup>	0.042 ft <sup>3</sup>	→ 99 %

#### Resulting Savings

Energy savings from "ASC" are major, as the two examples above show:

- 80 % savings for transferring an object after gripping.
- 99 % savings for holding an object during a 1 minute operation.

The investment generally pays for itself in just a few months.

#### "ASC": AN ADVANTAGE WITHOUT LIMITATIONS

Saving energy has become essential. With LEMCOM, thanks to ASC, energy is automatically saved without interfering with established operations:

##### 1- No specific adjustment

The initial setting (L1 = 65%, L2 = 75%) is suitable for most applications.

##### 2- Production regardless of what happens

Operation is always ensured, if necessary without "ASC", if the leakage level is too high.

##### 3- Guided maintenance

Clear display of the need for maintenance to return to auto-regulated "ASC" operation.



Specially designed by COVAL, the LEMAX+ vacuum pumps integrate the ASR (regulator-venturi) combination which greatly reduces the compressed air consumption and noise level. See page 8/10.



# LEM MAX+

## Compact, High Flow Vacuum Pumps

### Intelligence & Selection Guide



#### Intelligence

The front communication face panel allows access and programming of all operations: Various types of monitoring, threshold settings, pump configuration, diagnostics, etc. This front face panel can be locked to prevent an inadvertent misadjustment.

Built-in intelligence, as well as standard factory settings, optimize the implementation, operation, monitoring and maintenance.


#### → Simplified & Protected Installation and Operation.

Due to the high visibility display of the **LEM MAX+** modules, all useful information can be seen at a single glance: vacuum level, product gripped, thresholds reached, energy saving mode activated, etc.


The actual vacuum level is shown with direct reading (selection of different display units), and with "bar graph".

Configuration help messages (multilingual: in French, English, Italian, Spanish, German) are also provided.

#### → Clear & Complete Communication at Each Stage.



L1 "Product Gripped" visualisation and setting: (vacuum threshold, hysteresis)  
 "ASC" monitoring  
 L2 "ASC Threshold" visualisation and setting: (vacuum threshold, hysteresis)



Display shows data in many languages / bar graphs

8

LEM MAX+

#### Power Determined by the Venturi Nozzle Diameter


The table shows the power levels generated by each of the nozzle diameters available: when the module is operating "ASC" off, a larger nozzle draws and consumes more compressed air.

On the other hand, during "ASC" operation, a large nozzle quickly reaches the vacuum threshold generating power shut-off.


In conclusion:

- A large nozzle enables quicker gripping without consuming more during "ASC" operation.
- A small nozzle does not consume less when operating with "ASC" off.

nozzle Ø	Nozzle Diameter Selection				
	Venturi Specifications While Working Without "ASC"		Evacuation of 1L Volume. "ASC" Operation:		
	Vacuum flow (SCFM)	Consumed Air (SCFM)	Gripping Time (65% Vacuum) (s)	Time Until 75% Vacuum (s)	Consumed Air (ft³)
2.0 mm	4.41	6.32	0.55	0.80	0.077
2.5 mm	7.06	9.18	0.35	0.50	0.077









#### Suction Flow Rate / Vacuum Curves







	<b>LEMAX</b>	<b>90</b>	<b>X</b>	<b>25</b>	<b>S</b>	<b>C24</b>	<b>P*</b>	<b>G1</b>	<b>F</b>	<b>S</b>
<b>VACUUM LEVEL</b>						<b>CONNECTORS</b>		<b>POWERFUL BLOW-OFF</b>		
85% max. vacuum is optimal for airtight products		<b>90</b>				<b>C15</b> Vacuum Pump with 1 M12 5-pin Connector LEMAX90X__C15PG1		Without		
								<b>F</b> With		
								The powerful blow-off option allows you to release the product quickly.		
										
								Isolation valve <b>F</b> directs the entire blow-off flow to the vacuum pad.		
								NB: If option <b>F</b> is selected, no blow-off flow rate setting is available.		
<b>MODULE COMPOSITION</b>				<b>S</b>		<b>C24</b> Vacuum Pump with 2 M12 4-pin Connectors LEMAX90X__C24PG1				
<b>NC Vacuum Pump With Blow-Off</b>										
		LEMAX__X__SV_C__PG1								
		<ul style="list-style-type: none"><li>2 command signals.</li><li><b>NC</b> vacuum command valve.</li><li>Blow-off configured on site, at choice:<ul style="list-style-type: none"><li>Blow-off controlled by specific signal;</li><li>Automatic blow-off function (blow-off time configurable from 0 to 10s.). Advantage: reduced PLC I/O requirement.</li></ul></li><li>Adjustable blow-off flow rate.</li></ul>								
<b>NO Vacuum Pump With Blow-Off</b>				<b>V</b>						
		LEMAX__X__VV_C__PG1								
		<ul style="list-style-type: none"><li>2 command signals.</li><li><b>NO</b> vacuum command valve.</li><li>Blow-off controlled by external signal.</li><li>Adjustable blow-off flow rate.</li></ul>								
<b>Safety in Case of Power Failure</b>										
This version is suitable for applications where product gripping safety must be ensured in the event of an untimely power failure, and this even in the case of leakage (failsafe).										
This version does not include automatic blow-off function that enables control of the module with a single"vacuum and blow-off" signal.										
		</								



# LEMAX+

## Compact, High Flow Vacuum Pumps



### Dimensions, Mounting Options



#### Side Mounting



▪ Version: one M12 connector

▪ Version: two M12 connectors



Mounting from side is the simplest to implement: Two Ø 5 mm through screws or bolts with large washers.

#### Mounting from Front





For mounting from front, in addition to the module, you need to order an additional kit:

Mounting from front kit:  
1 plate + 4 screws

**Part No.: LEMFIX2A**

#### Mounting on DIN rail



For a static mounting (for example, in a cabinet), a module can be clipped onto a DIN rail. For this purpose, the module must first be equipped with an individual plate for fixing onto a DIN rail, to be ordered separately:

Kit for mounting on DIN rail:  
1 plate / clip + 4 screws

**Part No.: LEMFIX2B**





#### Specifications

- Supply: Non-lubricated air 5 microns filtered, according to standard ISO 8573-1:2010 [4:5:4].
- Operating pressure: 4.5 to 7 bar.
- Blow-off: Adjustable flow rate.
- Powerful blow-off (option F) P = 3.5 bar without flow rate control.
- Maximum vacuum: 85%.
- Suction flow rate: From 4.41 to 7.06 SCFM, depending on model.
- Air consumption: From 6.32 to 9.18 SCFM, depending on model (when operating "without ASC").
- Integrated non-clogging silencer.
- Sound level: From 72 to 75 dBA "without ASC". 0 dBA with ASC available.
- Display status:
  - of the vacuum control on the front panel: Green LED.
  - of the blow-off control on the front panel: Orange LED.
- Electric protection grade: IP 65.
- Maximum operating frequency: 4 Hz.
- Response time for opening / closing: 20/30 ms.
- Service life: 30 million cycles.
- Weight: From 410 to 460 g, depending on model.
- Operating temperature: From 50 to 122°F.
- Materials: PA 6-6 15% FG, brass, aluminum, NBR, HNBR, PU.

#### Electrical Controls

- Control voltage: 24V DC ( $\pm 10\%$  regulated).
- Current consumption: 30 mA (0.7W) by vacuum or blow-off solenoid valve.

#### Displays

- Display status of the threshold on the front panel: Green or red LED.
- Black and white LCD display, 7 matrix, symbols, vacuum reading area.
- Displaying the vacuum level and bar graph.
- Displaying number of cycles (vacuum cycles counter).
- Indication of exceeding service life (> 30 million cycles).

#### Settings

- Using membrane keypad and pull down menu.
- Language selection: FR, ENG, DE, IT or ES.
- Blow-off type selection: controlled or automatic (blow-off time configurable from 0 to 10s).
- Measurement unit selection (% , mbar, inHg).
- Manual, electrical, monostable commands.
- If the application requires, specific setting of thresholds and hysteresis that are different from the initial factory settings: L1 = 65%, h1 = 10%).

#### Vacuum Sensor

- Power supply voltage: 24V DC ( $\pm 10\%$  regulated).
- Current consumption: Standby: <25mA / max. 60 mA.
- Measurement range: 0 to 99% of vacuum, 0 to -999 mbar, 0 to -29.9 inHg.
- Measurement accuracy:  $\pm 1.5\%$  of range, temperature compensated.

#### "Gripped Product" Output Signal

- 24V DC, switching output / NO, switching capacity: 125 mA PNP.

#### Configurable auxiliary output

- (C24 model only, 2 x M12 4 pins)
- either "Vacuum level" signal, analogic 1 to 5V DC of measuring range.
- or "without ASC" signal +5V DC NO switching output.


#### ASC: Regulation & Self-Adaptation

- Continuous monitoring of the leakage level: Back-off or automatic return to operation with ASC.



#### Electrical Connections

##### 1- For Vacuum Pumps of Model S (vacuum control NC valve, blow-off control NC valve)

- C15:** 1 M12 5-pin connector



- C24:** 2 M12-4 pin connector




#### Configurable auxiliary output

- "Vacuum level" signal analogic 1 to 5 V DC
- OR
- "Without ASC" signal +5V DC switching output NO



\* externally controlled blow-off or automatic blow-off function > economy of an automaton outlet.

##### 2- For Vacuum Pumps of Model V (vacuum control NO valve, blow-off control NC valve)

- C15:** 1 M12 5-pin connector



- C24:** 2 M12-4 pin connector



#### Configurable auxiliary output

- "Vacuum level" signal analogic 1 to 5 V DC
- OR
- "Without ASC" signal +5V DC switching output NO

**M12 Electrical Connectors:** see page 10/11.



## 1st Mini Vacuum Pump on Industrial Fieldbus General Points

In a world where everything is connected, COVAL is innovating once more by unveiling the LEMCOM series: the first vacuum pump on fieldbus.


The LEMCOM establishes a verified remote communication between the operator and the vacuum pump, with three possible fieldbus choices, EtherNet/IP, PROFINET and CANopen. This allows the operator to receive real-time information and more importantly respond at all times to configure, diagnose and maintain the operation.

### Compact Integration: The COVAL Technique

The illustrations demonstrate the COVAL advantage: all necessary functions are integrated into a complete and self-governing mini-module.

#### INTEGRATED FUNCTIONS:

- ❶ Pressure regulator 3.5 bar
- ❷ "Vacuum" solenoid valve
- ❸ 3.5 bar optimized venturi
- ❹ Optimized silencer
- ❺ Vacuum non-return valve
- ❻ Vacuum sensor
- ❼ Integrated electronics: management of "vacuum" functions and communication
- ❽ "Blow-off" solenoid valve
- ❾ Blow-off flow regulator





PROFI  
NET  
EtherNet/IP  
CANopen



PROFI  
NET

EtherNet/IP CANopen

Industry-specific applications




More  
information

### Easy Integration with Existing Industrial Network

LECOM is the first vacuum pump which seamlessly integrates with the field network without the use of gateways or other specific interfaces.

The LEMCOM "master" modules enable the continuity of a fieldbus through their two integrated communication ports. Tested and certified by ODVA (EtherNet/IP), PI (PROFINET) and by CiA (CANopen), LEMCOM is connected very easily to the PLC (EDS file, RSLogix 5000 Add-On Instructions, GSDML file).

Based on a "master/secondary" structure where the "master" is a fully-integrated pump, the LEMCOM design enables the supply and control of 1 to 16 vacuum pumps while requiring only 2 connecting cables.



### Advantages

- **Easy implementation:** Plug & Play, custom configuration for every type of application.
- **Maximum automatic energy savings:**
  - ASR: 40% savings for porous products.
  - ASC: 90% savings for airtight products.
- **Compactness:** LEMCOM vacuum pumps are the most compact on the market.
- **Short response times:** Installed in close proximity to vacuum cups.

- **Dust resistant:** Non-clogging through-type silencer.
- **Safety:** Product gripping is maintained even during power failure.
- **Supported buses:** EtherNet/IP, PROFINET and CANopen.
- **Wiring simplified:** 2 cables are capable of managing 1 to 16 modules.
- Settings and diagnosis via **remote monitoring**.
- Nearly unlimited arrangements (stand-alone modules, island assemblies or remote modules), see page 8/32.

→ An essential innovation for intelligent vacuum gripping.





### 2 Vacuum Levels to Match Precise Application Needs

#### VERSION 60 (Max. 60% vacuum)

To enable a high rate of vacuum flow and compensate for leakage when gripping porous materials.

Suction flow rate (SCFM):

max. vacuum Nozzle Ø	60%
1.0 mm	1.34
1.2 mm	2.54
1.4 mm	3.25



#### VERSION 90 (Max. 85% vacuum)

To enable a high vacuum level and thus increase the holding force for gripping airtight materials.

Suction flow rate (SCFM):

max. vacuum Nozzle Ø	85%
1.0 mm	1.02
1.2 mm	1.59
1.4 mm	2.47



	Porous Materials, Rough Surfaces				Airtight & Semi-Porous Materials				
	Cardboard	Food	Wood	Paper	Plastic	Metal	Glass	Composites	Concrete/Stone
LEMCOM 60	●	●	●	●	●	●	●	●	●
LEMCOM 90					■	■	■	■	■

● Air Saving Regulator

→ 40% of energy savings on average.

■ Air Saving Control

→ 90% of energy savings on average.


### Integrated Energy-saving Technologies

#### AIRSaving Regulator

40% energy savings  
(on average, see below).

Combined "venturi regulator"  
ASR: pressure regulator ①  
feeds venturi ③ with 3.5 bar,  
the optimized pressure for  
operation.

→ No more unnecessary  
consumption of compressed  
air.




#### AIRSaving Control

90% energy savings  
(on average, see p.8/31)

Combination of non-return  
valve ⑤ and advanced  
electronics ⑦ ensures ASC's  
automatic performance.

→ Once vacuum is  
established, the pump no  
longer consumes air to hold  
the product.



#### AIRSaving Regulator

#### (ASR): Air Saving Regulator


LECOM series vacuum pumps, which integrate an ASR "venturi regulator" combination, maintain ideals that COVAL values greatly: reducing both compressed air consumption and noise generation.

Regardless of pressure supplied by the compressed air network, the integrated regulator feeds the venturi at 3.5 bar pressure, optimal for its operation.

→ No more unnecessary energy consumption.

→ No external regulator required, thus eliminating the risk of improper adjustment.

Compared to pressures found in most compressed air networks (5-7 bar), the graph opposite demonstrates an achieved economy of 40% on average.








PROFIBUS  
ETHERNET/IP

EtherNet/IP CANopen



### AIR Saving Control

### "Air Saving Control" Cycle



As illustrated above, the LEMCOM module automatically executes the "ASC" cycle, thus saving the maximum amount of energy, based on the following 3 phases.

#### 1- Gripping the object

The "vacuum" solenoid ② starts the cycle by supplying the venturi ③ which generates the vacuum to quickly pick up the object with the suction cup → short-term consumption.

#### 2- Operations on the object held by vacuum

The vacuum level is constantly monitored by the vacuum switch ⑤. When it reaches the L1 threshold (65%), the "gripped object" signal is generated, which allows the planned operations (transfer, machining, etc.). When the vacuum reaches threshold L2 (75%), the supply to the venturi via the solenoid valve ② is cut off → consumption is halted. The object remains held by the retained vacuum thanks to the closed valve ⑤. Micro-leaks will generally cause the vacuum level to fall slowly. Each time it falls below 65%, vacuum generation is briefly resumed until it reaches threshold L2 (75%).

#### 3- Releasing the object

At the end of operations, blow-off is ordered. The "blow-off" solenoid valve ⑥ generates a stream of air which closes the isolation valve ⑤, blows on the object to release it quickly.


### Smart Adaptation

The illustration above shows the adaptation capability of the LEMCOM module. "ASC" operation is automatic for any object that is airtight or generally nonporous (cycle1).

If a leak occurs (cycle 2), due to a rough object or suction cup wear:

1/ the module automatically detects the anomaly, 2/ ends the cycle without "ASC" in order to continue production and 3/ reports the event for possible maintenance. Production continues and once everything is returned to normal (cycle 3), "ASC" operation is automatically resumed.

More information



#### 1- Gripping + Transfer (1.4 mm nozzle Ø, emptying 0.2 l)

Phase	Duration	Air consumption		Energy savings achieved
		without "ASC"	with "ASC"	
Gripping	0.28 s	0.014 ft <sup>3</sup>	0.014 ft <sup>3</sup>	75 %
Transfer	1.20 s	0.063 ft <sup>3</sup>	0	
Release	0.14 s	0.007 ft <sup>3</sup>	0.007 ft <sup>3</sup>	
		0.084 ft <sup>3</sup>	0.021 ft <sup>3</sup>	

#### 2- Clamping + Operations (1.4 mm nozzle Ø, emptying 0.4 l)

Phase	Duration	Air consumption		Energy savings achieved
		without "ASC"	with "ASC"	
Clamping	0.55 s	0.028 ft <sup>3</sup>	0.028 ft <sup>3</sup>	99 %
Operations	60 s	3.178 ft <sup>3</sup>	0	
Release	0.14 s	0.007 ft <sup>3</sup>	0.007 ft <sup>3</sup>	
		3.213 ft <sup>3</sup>	0.035 ft <sup>3</sup>	

### Resulting Savings

Energy savings from "ASC" are significant, as the two examples opposite show:

- 75% savings for transferring an object after gripping.
- 99% savings for holding an object during a 1 minute operation.

The product often pays for itself in just a few months.

### "ASC": AN ADVANTAGE WITHOUT LIMITATIONS

Saving energy has become essential. With LEMCOM, thanks to ASC, energy is saved automatically without interfering with established practices:

#### 1- No specific adjustment

The default setting (L1 = 65%, L2 = 75%) is suitable for most applications.

#### 2- Production regardless of conditions

Performance is guaranteed. When necessary, without "ASC", if the leakage level is too high.

#### 3- Guided maintenance

Clear display of the need for maintenance in order to return to autoregulated "ASC" operation.

With LEMCOM, all settings are remotely configurable, and diagnosis is made easier.





PROFI  
NET

EtherNet/IP CANopen



### Individual or Island Modules?

Stand-alone modules are suitable for the most common applications: one module controls one or more suction cups, all of which operate according to the same sequence.

When several suction cups are operating according to different sequences, multiple modules are required, which can be:

- several autonomous modules, OR
- a group of these modules with an internally shared pressure supply


The illustrations shown here guide the selection:

- autonomous modules are coupled with integrated pressure regulators (ASR)
- in a group, the integrated regulator is eliminated: to maintain the advantage of economical and silent operation, it is recommended to reduce the group's common pressure supply to 4 bar.


The maximum number of modules in an island depends on the power of the modules that must be active simultaneously:

- 5 modules maximum for nozzle 1.4 mm ID.
- 7 modules maximum for nozzle 1.2 mm ID.
- 9 modules maximum for nozzle 1 mm ID.


Network: 4.5 to 7 bar



common pressure supplied to units Optimal pressure: 4 bar



P optimal = 4 bar  
(operation at 4-7 bar)




island of 3 modules  
supplying suction cups  
according to different  
sequences or operations

### Vacuum Control by NC or NO Solenoid Valve


Vacuum control by NC (Normally Closed) solenoid valve is the most common: in the event of an electrical shut-off, vacuum is no longer generated. On the other hand, with a NO (Normally Open) solenoid valve, vacuum continues to be generated in the event of an electrical shut-off, providing positive object-gripped security.

The diagrams opposite show that both versions are controlled by the same "vacuum" signal  $\bar{v}$ : The opposite  $\bar{v}$  required for control of the NO solenoid valve is automatically obtained internally by the control electronics.

■ NC solenoid valve




■ NO solenoid valve




### Communications Panel


LEMCOM master  
PROFI EtherNet/IP



LEMCOM master  
CANopen



LEMCOM secondary module








PROFI  
NET

EtherNet/IP CANopen

#### Multitude of Innovations

- Maximum intelligence / minimal bulk.
- One "master" module controls up to 15 secondary modules.
- Master module is a fully-integrated pump.
- Remote configuration, monitoring and diagnostics.
- Dedicated Coval bus between master and secondary modules.
- Simplified wiring and installation.
- Standard secondary modules (regardless of the type of bus).
- Additional communications port.
- Supported buses: EtherNet/IP™ / PROFINET / CANopen®.
- IP 65 / M8 standard connectors.

PROFI  
NET  
EtherNet/IP  
CANopen



up to  
**16**  
modules

#### A Simple Product to Utilize

##### LEMCOM master

EtherNet/IP PROFI  
NET

- On-board 2-Port Ethernet Switch.
- On-board web server.
- Dedicated configuration software.
- M8/RJ45 standard connectors.



##### LEMCOM master

CANopen

- Two CAN ports.
- From 20 to 1000 Kbps.
- Dedicated configuration software.
- Configuration by SDO.
- Adjustable PDO-TX transmission threshold.



##### LEMCOM secondary module

- Universal secondary module, whatever the type of bus used.



#### Settings, Diagnosis and Process Data



##### CONFIGURABLE SETTINGS

- "Product Gripped" and vacuum regulation (ASC) thresholds.
- Automatic blow-off.
- State of valves in the event of loss of communication.
- Client LED status.
- Network parameters.
- Firmware updates...



##### DIAGNOSTIC

- Cycle counters, vacuum and blow-off control, gripped pieces, lost pieces, ASC...
- Power-supply voltage.
- Firmware version.
- Product reference.
- Vacuum cycle acquisition...



##### INPUT DATA

- Vacuum and blow-off control.



##### OUTPUT DATA

- Instant vacuum level (0 to 100%).
- "Gripped Product" signal (ON/OFF).
- Regulation system status.
- Alarms (power-supply voltage, temperature, preventive maintenance).





EtherNet/IP CANopen



#### A Setting for Every Application

The LEMCOM is based on an innovative, efficient product structure:

- The "master" module manages communication on the fieldbus, assures management of the "secondary" modules and is a fully-integrated vacuum pump. Its 2 communication ports enable a continuous fieldbus.
- The "secondary" modules are interconnected with the "master" module via the COVAL bus.


Contact between the "master" module and the "secondary" modules is confirmed by an M8 connecting bridge for island configurations or by a M8/M8 standard cable for configurations based on remote modules.

#### Advantages:

This product structure guarantees flexibility in selection, enabling use of LEMCOMs in stand-alone, island or mixed configurations. As a result, vacuum generators may be placed in close proximity to the application, guaranteeing a reduction:

- in gripping time
- in cycle time
- in energy consumption.

Because setup and diagnosis of the LEMCOM is carried out remotely, it is not necessary to install them in easily accessible zones.



#### Full Remote Access

LECOM parameters can easily be updated remotely and in several ways. Configuration is possible using LEMCOM Manager PC software, the embedded web server (EtherNet/IP and PROFINET) or by sending vacuum parameters directly from the PLC during

use or on initialization. This flexibility enables the LEMCOM user to adapt to all types of applications without direct intervention on the vacuum generator.



- #### EtherNet/IP
- Embedded web server.
  - Implicit (I/O) and explicit messaging (setting) (EtherNet/IP).
  - Synchronous (I/O) and asynchronous data (configuration) (PROFINET)

#### CANopen

- PDO/SDO.
- PDO: Process Data Object (I/O process data).  
SDO: Service Data Object (configuration data).

#### LECOM MANAGER

- Dedicated universal application: LEMCOM Manager.







EtherNet/IP CANopen



### LEMCOM: Versatile Series for all Applications

The opposite page demonstrates the versatility of this series. In addition to a wide range of complete, stand-alone, or island vacuum pumps, LEMCOM has options for protocol, vacuum level, and valve components.

### Venturi Specifications


#### 1- Maximum Vacuum Level

Dependent upon the mixer profile:

- 85% of maximum vacuum is optimal for gripping airtight products.
- 60% of maximum vacuum is optimal for gripping porous products.

#### 2- Nozzle Diameter

Reflects the generated vacuum flow rate, as well as energy consumption. Hence, it must be selected to meet precise requirements without wasting energy.



### Handling of Porous Products: (cardboard, untreated wood, pastries, etc.) → LEMCOM 60% max. vacuum

When porosity and/or surface leaks are expected during gripping, a vacuum level between 35 and 55% is the best economical compromise generated by a maximum **venturi vacuum level of 60%**.

To determine the most effective nozzle diameter, use the table at right and measure the leakage flow rate of the material.

Evacuation time (in seconds) of 1 liter volume				Consumed Air (SCFM)	Vacuum flow (SCFM)
	vacuum reached	35%	45%	55%	
Nozzle Ø					
1.0 mm	0.83	1.31	2.35	1.55	1.34
1.2 mm	0.52	0.83	1.49	2.3	2.54
1.4 mm	0.34	0.54	0.97	3.18	3.25

### Handling of Airtight Products: (glass, plastic, coated wood, sheet metal, etc.) → LEMCOM 85% max. vacuum

Gripping done without major leaks will benefit from a high level of vacuum: Between 55 and 75% generated by a maximum **venturi vacuum level of 85%**.

Depending on the volume to be evacuated and the time available for product gripping, use the table below to select the most effective nozzle diameter and vacuum flow rate.



On airtight products, "ASC" enables you to considerably reduce compressed air consumption. The table below shows:

- A larger nozzle provides a faster grip without consuming more, when using "ASC".
- A smaller nozzle only consumes less when the operation is continued without "ASC".

#### Working without "ASC":

Evacuation time (in seconds) of 1 liter volume				Consumed Air (SCFM)	Vacuum flow (SCFM)
	vacuum reached	55%	65%	75%	
Nozzle Ø					
1.0 mm	1.76	2.38	3.33	1.55	1.02
1.2 mm	1.13	1.53	2.15	2.3	1.59
1.4 mm	0.73	0.99	1.38	3.18	2.47

#### When using "ASC" (evacuation of 1 liter volume):

Ø buse	gripping time (65% vacuum) (s)	Time up to 75% vacuum (s)	Consumed Air (ft³)
1.0 mm	2.38	3.33	0.077
1.2 mm	1.53	2.15	0.077
1.4 mm	0.99	1.38	0.077

### ACCESSORIES

Cat 5 shielded Ethernet cable: M8, straight, female, 4-pin – RJ45, straight, male, 8-pin – suitable for drag chain use

- CDM8RJ45L2: length 2 m.
- CDM8RJ45L5: length 5 m.
- CDM8RJ45L10: length 10 m.

Cat 5 shielded Ethernet cable: M8, straight, female, 4-pin, on both ends – suitable for drag chain use

- 80003053 : longueur 1 m.

M8/M8 "COVAL bus" cable: M8, straight, female, 4-pin – M8, straight, female, 4-pin

- CDM8FFL05: length 0.5 m.
- CDM8FFL1: length 1 m.
- CDM8FFL2: length 2 m.
- CDM8FFL4: length 4 m.

Other lengths on request.

Power supply cable: M8, straight, female, 4-pin – open end

- CDM8: longueur 2 m.
- CDM8N: longueur 0.5 m.

120 Ω "COVAL bus" termination: M8, straight, female, 4-pin – M8, plug, male, 4-pin

- 8000230: longueur 0.2 m.

The COVAL bus is based on a CAN architecture and requires the addition of a bus termination to ensure proper communication between the secondary and master modules. It takes the form of an M8 male/M8 female cable that includes a 120 Ω line termination resistor.

It must be integrated on the last secondary of the COVAL bus, between the module's rear connector and the 24 V DC power supply.

When using a stand-alone master module, this termination is not required.





EtherNet/IP CANopen




	<b>LEMC</b>	<b>90</b>	<b>X</b>	<b>14</b>	<b>S</b>	<b>Y2</b>	<b>G</b>	<b>B2</b>
--	-------------	-----------	----------	-----------	----------	-----------	----------	-----------

VACUUM LEVEL	
60 % max. vacuum is optimal for porous materials	<b>60</b>
85 % max. vacuum is optimal for airtight products	<b>90</b>

NOZZLE DIAMETER	
1 mm Ø nozzle	<b>10</b>
1.2 mm Ø nozzle	<b>12</b>
1.4 mm Ø nozzle	<b>14</b>


### MODULE COMPOSITION

#### NC Vacuum pump with blow-off



- LEMC\_X\_S\_G\_
- NC vacuum control valve:
    - in case of electrical cut-off, vacuum generation stops (see p. 8/32).
  - Blow-off configured on site at choice:
    - Blow-off controlled by specific signal;
    - Automatically delayed blow-off time from 0 to 10 s.
  - Adjustable blow-off flow rate.

#### NO Vacuum pump with blow-off



- LEMC\_X\_V\_G\_
- NO vacuum control valve:
    - In case of electrical cut-off, vacuum continues to be generated (see p. 8/32).
  - Blow-off configured on site, at choice:
    - Blow-off controlled by specific signal;
    - Automatically delayed blow-off time from 0 to 10 s.
  - Adjustable blow-off flow rate.

### PROTOCOL

**Q2**

**PROFIBUS** master  
LEMC\_X\_Q2G\_



- On-board 2-Port Ethernet Switch.
- On-board web server.
- Dedicated configuration software.
- M8/RJ45 standard connectors.
- GSDML file.

**W2**

**CANopen** master  
LEMC\_X\_W2G\_



- Two CAN ports.
- From 20 to 1000 Kbps.
- Dedicated configuration software.
- Configuration by SDO.
- Regulated PDO-TX transmission threshold.

**Y2**

**EtherNet/IP** master  
LEMC\_X\_Y2G\_



- On-board 2-Port Ethernet Switch.
- On-board web server.
- Dedicated configuration software.
- M8/RJ45 standard connectors.
- RSLogix 5000 AOI + EDS file.

**Z2**

secondary module  
LEMC\_X\_Z2G\_



- Universal secondary module, can be used with any fieldbus.
- If necessary, M8/M8 "COVAL Bus" 120 Ω termination, available in accessories.

### CONFIGURATION

1 stand-alone module

#### Island assemblies

**B2**

LEMC\_X\_GB2



Island assembly with 2 modules, with connecting bridges for internal "COVAL Bus" and M8/M8 120 Ω termination:

→ The first module is of the type selected in "PROTOCOL".

→ The following one is a secondary module.

**B3**

LEMC\_X\_GB3



Island assembly with 3 modules, with connecting bridges for internal "COVAL Bus" and M8/M8 120 Ω termination:

→ The first module is of the type selected in "PROTOCOL".

→ The following two are secondary modules.

**B4**

...

NB: LEMC\_X\_Z2GB\_ "Secondary" island modules are delivered without the M8/M8 "COVAL Bus" 120 Ω termination - order separately.

#### Components for island assembly

**B**

LEMC\_X\_GB



Island module, complete with integrated assembly screw.



Island endplates set complete with assembly screw and plug for common pressure inlet.

**Part No.: LEMSETA**



Connecting bridge for internal "COVAL Bus".

**Part No.: 80001231**

NB: If necessary, M8/M8 "COVAL Bus" 120 Ω termination is available in accessories

**OPTION:** Version without non-return valve available on request.

### EXAMPLES OF COMPLETE PART NUMBER:

**LEMC90X14SY2G** LEMCOM vacuum pump, 85% maximum vacuum, 1.4 mm Ø nozzle, controlled by a NC (Normally Closed) solenoid valve, stand-alone EtherNet/IP™ "master" module.

**LEMC90X10SY2GB3** Island assembly of 3 LEMCOM vacuum pumps, 85% maximum vacuum, 1 mm nozzle Ø, controlled by a NC (Normally Closed) solenoid valve, EtherNet/IP™ "master" module, 2 secondary modules, with connecting bridges and the M8/M8 "COVAL Bus" 120 Ω termination.








PROFI  
NET

EtherNet/IP CANopen





#### 1- Stand-alone Modules

##### Mounting from side



##### Mounting from front




To mount from front, in addition to the module, a mounting kit must be ordered:

Kit for mounting from front:  
1 plate + 4 screws

**Part No.: LEMFIXA**

##### Mounting on DIN rail




For static mounting (for example, in a cabinet), a module can be clipped onto a DIN rail. For this purpose, the module must first be equipped with an individual plate for mounting onto a DIN rail


DIN rail mounting kit:  
1 plate/clip + 4 screws

**Part No.: LEMFIXB**


#### 2- Islands



##### Mounting from front



##### Mounting on DIN rail



DIN rail mounting kit:  
2 clips + 2 screws

**Part No.: LEMFIXC**






EtherNet/IP CANopen




### Electrical Connections


#### LECOM master EtherNet/IP PROFINET



#### LECOM master CANopen




#### LECOM secondary module



YE: yellow, WH: white, BU: blue, OG: orange, BR: brown, BK: black

→ bus "COVAL"

→ alimentation



#### M8/M8 "COVAL BUS" 120 Ω TERMINATION

Male M8/Female M8 cable integrating a 120 Ω termination resistor. The termination must be integrated on the last "secondary" module of the COVAL Bus, between the final M8 connector of the product and the 24V DC electric supply. See "Accessories", page 8/35.



### Common Specifications

- Supply: Non-lubricated air 5 microns filtered, according to standard ISO 8573-1:2010 [4:5:4].
- Operating pressure: 4.5 to 7 bar.
- Mini dynamic pressure:
  - stand-alone module: P = 4.5 bar.
  - island modules: 4 bar.
- Blow-off: adjustable flow:
  - stand-alone version: P = 3.5 bar.
  - island version: P network.
- Maximum vacuum: 85%.
- Suction flow rate: From 1.02 to 3.25 SCFM.
- Air consumption: From 1.55 to 3.18 SCFM, when operating "without ASC".
- Integrated non-clogging silencer.
- Noise level: approximately 68 dBA "ASC off". 0 dBA with ASC.
- Electric protection grade: IP65.
- Maximum operating frequency: 4 Hz.
- Service life: 30 million cycles.
- Weight: 150 g.
- Operating temperature: From 32 to 122°F.
- Materials: PA 6-6 15% FG, brass, aluminum, NBR.
- 4-pins M8 male connectors.

#### Self-Adaptation

- Continuous monitoring of the leakage level: Shutoff or automatic return to operation with ASC.

#### Integrated electronics

- 24V DC supply (regulated ± 10 %).
- Electric consumption: "master" < 150 mA, "secondary" < 100 mA, of which 30 mA (0.7W) per vacuum and blow-off pilot.
- Measurement range: 0 to 99% vacuum.
- Measurement accuracy: ±1.5 % of range, temperature compensated.
- Communication ports protected against wiring errors or reversed polarity.

### Service Specifications

#### Settings

- Piece gripping (L1) and regulation (L2) thresholds.
- Automatic blow-off time configurable (0 to 10 seconds).

- Activation/deactivation of ASC regulation system.
- Activation/deactivation of the (DIAG ECO) leakage level monitoring system.
- Adjustable blue LED functioning mode
- Valve functioning mode in the event of loss of communication

#### Diagnosis

- Instantaneous vacuum level (0 to 99%).
- Gripped product, loss of product, regulation in process, regulation default information.
- Cycle counters (vacuum, blow-off, gripped piece, ASC, etc.).
- Supply voltage and internal temperature.
- Product reference and serial number.
- Firmware version.

#### Configuration and diagnosis tools

- LECOM Manager PC software (EtherNet/IP, PROFINET and CANopen universal application).
- Embedded web server (EtherNet/IP and PROFINET module).

#### Communication

##### EtherNet/IP:

- 2-port ethernet switch.
- Static IP address or DHCP.
- EDS file & RSLogix 5000 Add-On Instructions.

##### PROFINET:

- 2-port ethernet switch.
- Static IP address or PROFINET DCP.
- GSDML file

##### CANopen:

- 2 CAN port.
- 10 to 1000 Kbps.
- EDS file.


##### COVAL Bus:

- CAN link between "master" and "secondary" units / 1 Mbps.
- Connection by specific bridge for island assembly or unshielded female M8/female M8 cable.
- Max total length of the COVAL Bus: 20 meters.



# General points

## Self-Regulating Vacuum Pumps Applications



### Description

GVMAX series of pumps are designed for gripping, handling and retaining airtight objects.

The principle is simple: as soon as the required level of vacuum is reached, the compressed air supply is stopped and the vacuum is maintained in the installation thanks to the non-return valve. Thus, the self-regulating system guarantees an optimum level of vacuum.


This approach considerably reduces both compressed air consumption and the noise level.

Moreover, thanks to their intelligent functions, they guarantee safety and optimum vacuum management for the application. COVAL recommends these pumps for applications involving airtight objects.

### The Specific Functions of Vacuum-regulating Vacuum Pumps

They have the following characteristics:

- Vacuum generation by venturi effect (maximum pressure drop - 850 mbar or 85% vacuum).
- Air-saving, vacuum-regulating function.
- Adjustable blow-off.
- Visual and switching output control of vacuum level by digital electronic vacuum switch.
- Positive safety holds objects in case of electrical emergency stop (electrical outlets switched off) via its NO vacuum supply valve, maintenance can be carried out in complete safety.



8


### Operating Principle of a GVMAX Series Vacuum Pump

The cycle shows the three stages of a GVMAX:

Wait - Suction - Blow-off.

Regulation is automatically carried out by the equipment's internal loop. The interest of the GVMAX vacuum pump is based on these three stages:

- Wait: no consumption, no clogging, no noise.
- Suction-regulation: the object is gripped and the vacuum pump automatically stops.
- Blow-off: automatically timed for release and return to neutral position in preparation for the next cycle.






# General points

## Self-Regulating Vacuum Pumps

### General




#### Regulating System in an Air-saving Vacuum Pump

The GVMAX vacuum pump is designed to save compressed air during a gripping cycle. The device stops consuming compressed air when the vacuum threshold pre-set in the vacuum switch is reached in the network. This is known as "regulation".

The diagram below shows the regulating system of a vacuum pump. As soon as optimum vacuum (vacuum threshold 1) is reached, the pumps maintain the vacuum until the level of vacuum descends to the hysteresis value after a period of time "t" due to leakage.

The self-regulating system guarantees that an optimum level of vacuum is maintained and reduces both air consumption and noise level throughout the cycle.

#### Vacuum Level in Relation to Time for a Regulation Cycle



#### GVMAX Vacuum Pump Yield

Volume of air consumed and time to create a vacuum in a 5 liter tank with a 4 bar GVMAX vacuum pump:


vacuum (%)	time to create a vacuum (s)	air consumed (SCFM)
10	0.2	0.03
20	0.3	0.06
30	0.6	0.10
40	0.8	0.15
50	1.1	0.21
60	1.5	0.28
70	2.1	0.38
80	3.0	0.55
85	4.0	0.74



# General points

## Self-Regulating Vacuum Pumps

### Applications




#### HOLDING

During the final phase of manufacture a snowboard must be held in position for several minutes.


Using vacuum pumps with the air-saving function generates significant energy savings.

Also see the **LEMAX** series (p. 8/15) and **LEMAX+** series (p. 8/23).



#### EMPTYING A TANK

The regulation function of the vacuum pumps are used in this type of application. Hysteresis of the switching output regulation is adjustable between 1 and 25% vacuum on electric models.



Attention: For regulation of the vacuum level in tanks of more than 10 liters, consult us for the pneumatic versions.


#### SAFE GRIPPING

##### ■ Electric GVMAX

Grip is maintained on the object (airtight object) if there is a power failure.

##### ■ Pneumatic GVMAX

Grip is maintained on the object (airtight object) if the pneumatic power is interrupted.




Grip is maintained if the electrical power or compressed air supply is interrupted.



# GVMAX V2-2/V2-2R

## Self-Regulating Vacuum Pumps

(Electric Vacuum and Blow-off Control)



Industry-specific applications



With GVMAXV2-2 and GVMAXV2-2R, COVAL offers two types of solutions based on a standard GVMAX electric vacuum pump.

These vacuum pumps provide an "all in one" solution by integrating all necessary functions, controls, valves, vacuum regulation, blow-off, product gripping control from an integrated vacuum switch, and silencer into a single, light and compact module.

The M12 connections dramatically simplify installation and use. They are available in two versions and are compatible with PLC safety:

- GVMAXV2-2: non-adjustable vacuum switch (factory configured)
- GVMAXV2-2R: adjustable vacuum switch

### Characteristics

model	Ø nozzle (mm)	max. vacuum (%)	flow consumed at 4 bar (SCFM)	max. suction power (SCFM)	dynamic supply pressure	operating pressure	⚖ (g)
GVMAX V2-2	2.5	90	10.59	7.06	4.5 bar relative pressure	4.5 to 6 bar	550
GVMAX V2-2R	2.5	90	10.59	7.06	4.5 bar relative pressure	4.5 to 6 bar	550

### Applications

The two solutions, GVMAX V2-2 and GVMAX V2-2R are used for gripping airtight objects in the stamping, sheet-metal/bodywork and mounting industries for handling, transfer and holding operations. The GVMAX V2-2/V2-2R is designed for the Automotive sector.

### Electrical connections


- Automaton input  
5-pole M12 connector
- (1) Inlet connector - brown, 24 V DC  
(3) 0 Volt (or -) - blue  
(4) Vacuum switch threshold 2 outlet - black

- Automaton output  
5-pole M12 connector
- (2) Blow-off control - white, 24 V DC  
(4) Vacuum immobilization in waiting position (neutral position) - black, 24 V DC


- Pneumatic supply maintained on the "compressed air" input of the vacuum pump.
- Electric power supply

**Suction:** 24 V DC NO solenoid valve. From rest to suction (must be powered to stop suction).

**Blow-off:** 24V DC NC solenoid valve



Red LED Green LED



2 digit display in % vacuum  
(e.g. 75 for 75% vacuum)

### Evacuation Time in Seconds per Liter

% vacuum	10	20	30	40	50	60	70	80	85
GVMAX V2-2/V2-2R	0.03	0.07	0.11	0.16	0.22	0.30	0.41	0.60	0.77

### Advantages

In relation to the standard GVMAX the GVMAX V2-2 and GVMAX V2-2R solutions offer the following advantages:

- Safety: vacuum generation in case of power failure by air inlet solenoid valve in normally open operation (24 V DC).
- Powerful, controllable blow-off.
- Data processing circuit (connection cable).
- Connection by 2 male 5 pin M12 connectors, (Input/ Output).
- Non-adjustable vacuum switch (factory-set) with the GVMAX V2-2 and adjustable vacuum switch with the GVMAX V2-2R.
- Compatible with safety PLCs and other safety systems.

### Specifications

Base body	Aluminium (AU 4 PB)
Valve body	POM (black polyacetal)
Silencer	Black PC with felt internal element
Vacuum switch	PA66, PC, brass, NBR seal
Electric wiring	PA66
Screw	Zinc-plated steel
Inside parts	Brass; Aluminum; Desmopan
Seals	NBR
Membrane	NBR with nylon substrate

### Vacuum switch display legibility

The GVMAX is fitted with an indexable vacuum switch (45°, 90°, 180°). This vacuum switch is set to the following values (values used in the automotive industry):

GVMAX V2-2 or V2-2R	Function	Threshold	Hysteresis
Threshold 1: vacuum regulation	NO	H1: 75 %	h1: 10 %
Threshold 2: object detected	NO	H2: 65 %	h2: 10 %


For all orders, please specify: **GVMAX V2-2** (Non-adjustable vacuum switch)  
**GVMAX V2-2R** (Adjustable vacuum switch)




# GVMAX V2-2/V2-2R

## Self-Regulating Vacuum Pumps


### Dimensions, Curves, Options



#### Dimensions



#### Curves



#### Options

##### ■ Manifold mounting

The GVMAX V2-2 and V2-2R can also be manifold-mounted.

Up to 4 vacuum pumps can be installed on one base.

Manifold references (example with GVMAX V2-2)

GVMAX V2-2 B1 (Base + 1 x GVMAX V2-2)

GVMAX V2-2 B2 (Base + 2 x GVMAX V2-2)


GVMAX V2-2 B3 (Base + 3 x GVMAX V2-2)

GVMAX V2-2 B4 (Base + 4 x GVMAX V2-2)

##### ■ Protective housing for GVMAX, Part No. GVOMAXV2

The protective housing for the GVMAX is transparent and removable.

Coval recommends using a protective housing to protect the vacuum pump.




**GVMAX V2-2 B4**



**GVOMAXV2**



## Self-Regulating Vacuum Pumps (Electric Vacuum and Blow-off Control)



The communication between both elements, electronic vacuum switch and gripping valve control, enables the consumption of compressed air to be regulated and in particular significantly reduced. This range of vacuum pumps is strongly recommended for gripping airtight objects, clamping, and for medium or long cycles. Electrically controllable blow-off is integrated for release.

### Materials

PA 6-6 15% FV, POM, PC 15% FV, brass, aluminum, NBR.

Industry-specific applications



### Safety

The GVMAX E1 has a non-return valve installed as standard which enables it to maintain the vacuum within the circuit if there is a power failure. This function guarantees maximum safety conditions for operators during handling.

### Characteristics

model	Ø nozzle (mm)	max. vacuum (%)			air drawn in (SCFM)			L2 (mm)		⚖ (g)
		X	T	N	X	T	N	S	K <sup>(1)</sup>	
GVMAX E1	2.5	50	75	90	12.71	8.48	7.06	60	121	510

(1) delivered as standard on version X.

### Evacuation Time in Seconds per Liter

% vacuum	Ø nozzle	10			20			30			35			40			45			50			60			70			80			85		
versions	(mm)	X	T	N	X	T	N	X	T	N	X	T	N	X	T	N	X	T	N	X	T	N	X	T	N	X	T	N	X	T	N	X	T	N
GVMAX E1	2.5	0.02	0.03	0.03	0.04	0.06	0.07	0.08	0.10	0.11	0.01	0.14	0.14	0.16	0.19	0.21	0.22	0.30	0.30	0.30	0.30	0.30	0.30	0.30	0.30	0.50	0.41	0.60	0.60	0.60	0.60	0.60	0.60	0.77

### Operating Principle


When the selected vacuum level is reached, the compressed air supply stops. This interruption does not have any effect as the non-return valve maintains the vacuum and thus the grip. The vacuum switch continually analyzes the vacuum requirements. As soon as the minimum threshold is reached, it activates the vacuum generation valve to return to the pre-set value.

See page 8/39.


### Specifications

<b>Supply</b>	Non-lubricated filtered air, 2 to 6 bar, optimum at 4 bar
<b>Temperature</b>	32 to 140 °F
<b>Contact output</b>	PNP switching output NO or NC, adjustable hysteresis
<b>Anti-parasite function</b>	Integrated with display LED
<b>Suction rate</b>	Adjusted by flow restrictor

Curves: see page 8/43



### Dimensions



For all orders, please specify:

Model + Characteristic + Silencer + C.A. fitting + Pilot

Example: GVMAXNK14E1

1: Model	2: Characteristic	3: Silencer	4: C.A. fitting	5: Pilot
GVMAX	X 50 % vacuum	- Without silencer	14 G1/4"-F	E1 24 V DC NC
	T 75 % vacuum	S Diffuser		
	N 90 % vacuum	K Through-type		




## Self-Regulating Vacuum Pumps (Pneumatic Vacuum and Blow-off Control)



The communication between both elements, pneumatic vacuum switch and gripping valve control, enables the consumption of compressed air to be regulated and in particular significantly reduced. This range of vacuum pumps is strongly recommended for gripping airtight objects, clamping, and for medium or long cycles in explosive environments. Pneumatically controllable blow-off is integrated for release.

Note: The volume of the piping must not exceed 10 liters. For higher volumes, please consult us.

Industry-specific applications



### Materials

PA 6-6 15% FV, POM, PC 15% FV, brass, aluminum, NBR.

### Safety

The GVMAX P1 has two non-return valve functions installed as standard which enables it to maintain the vacuum within the circuit if the pneumatic power is interrupted. This function guarantees maximum safety conditions for operators during handling.

### Characteristics

model	Ø nozzle (mm)	max. vacuum (%)			air drawn in (SCFM)			L2 (mm)		⚖ (g)
		X	T	N	X	T	N	S	K <sup>(1)</sup>	
GVMAX P1	2.5	50	75	90	12.71	8.48	7.06	60	121	440

(1) delivered as standard on version X.

### Evacuation Time in Seconds per Liter

% vacuum	Ø nozzle	10			20			30			35	40			45	50			60		70		80	85
versions	(mm)	X	T	N	X	T	N	X	T	N	X	X	T	N	X	T	N	T	N	T	N	N	N	
GVMAX P1	2.5	0.02	0.03	0.03	0.04	0.06	0.07	0.08	0.10	0.11	0.01	0.14	0.14	0.16	0.19	0.21	0.22	0.30	0.30	0.50	0.41	0.60	0.77	


### Operating Principle

When the selected vacuum level is reached, the compressed air supply stops. This interruption does not have any effect on the operation in progress as the no-return valve maintains the vacuum and thus the grip. The vacuum switch continually analyzes the vacuum requirements. As soon as the minimum threshold is reached, it activates the vacuum generation valve. The chosen level of vacuum is immediately re-established. See page 8/39.

### Specifications

Supply	Non-lubricated filtered air, 2 to 6 bar, optimum at 4 bar
Temperature	32 to 140 °F
Vacuum switch	PSE100PKNO
Pressure at the vacuum switch	Equal to or greater than vacuum pumps supply pressure
Hysteresis	100 mbar max.


Curves: see page 8/43



Note: to ensure optimum operation, we advise you to ensure the vacuum network is airtight. For this purpose we recommend using NVS vacuum feeders and screwed vacuum fittings with O-rings (RDV, RCOV).

### Dimensions

- (1) 5.5 bar compressed air input
- (2) Fast 2.7x4 blow-off control
- (3) G1/2"-F Gas Exhaust
- (4) Regulation threshold adjustment
- (5) PSE100PKNO vacuum switch
- (6) Hollow shaft for vacuum control vacuum switch pressurization
- (7) G1/4"-F



For all orders, please specify:

Model + Characteristic + Silencer + C.A. fitting + Pilot

Example: GVMAXNK14P1

1: Model	2: Characteristic	3: Silencer	4: C.A. fitting	5: Pilot
GVMAX	X 50 % vacuum	- Without silencer	14 G1/4"-F	P1
	T 75 % vacuum	S Diffuser		
	N 90 % vacuum	K Through-type		



# High Flow Vacuum Generator

## Chapter 9

### CMS



#### Multi-stage Vacuum Pumps

- Multi-stage technology
- 2 vacuum flow rates: 31.8 and 63.6 SCFM
- Optional control valve for vacuum and release cycles
- (M12 connectors)
- Optional vacuum gauge
- For applications requiring a high suction flow rate
- Emptying of large tanks
- Handling porous materials
- Remotely power vacuum chambers
- MVG and CVG Series

P<sub>9/2</sub>

### M--C



#### Air Amplifiers

- Operating principle based on the COANDA effect
- Bore diameter (Ø): 6, 10, 20, 30, 40 mm
- Flow rate: between 7.06 and 177 SCFM depending on the supply pressure (between 1.5 and 6 bar)
- Body material: aluminum
- Recommended for gripping lightweight, porous products: foam, carpet, cakes, leather, etc.
- Transport of powdery materials: powders, granules, etc.
- Transporting small, lightweight objects: paper clips, rice, coffee, etc.
- Smoke evacuation, depressurizing chambers

P<sub>9/4</sub>

### TVM



#### Pipes for Air Amplifiers

- Flexible polyurethane hose with steel spiral reinforcement.
- 4 sizes available: Ø 25, 40, 50 and 60 mm
- Anti-static properties according to DIN 53486
- Commonly used with COVAL air amplifiers (M--C series)
- High resistance to abrasion, cutting lubricant and UV rays

P<sub>9/7</sub>



# CMS

## Multi-stage Vacuum Pumps




With its multi-stage ejectors, CMS series, COVAL proposes an adapted response to all applications which need high suction flow; like emptying of high volume tanks or handling of porous objects.

Thanks to their characteristics, the CMS multi-stage vacuum generators are perfectly suited to feed vacuum grippers at a distance.

- Optional control valve for vacuum and release cycles
- M12 Connector

Industry-specific applications




### Characteristics

Model	Consumption (SCFM)	Suction rate (SCFM)	Maximum vacuum (%)	Supply pressure (bar)	Optimal pressure (bar)	Noise level (dBA)	Weight (Kg)
CMS90X50...	6.71	31.8	85	5-7	6	65	1
CMS90X100...	13.42	63.6	85	5-7	6	65	1

### Performance Curves

Suction flow (SCFM)




### Control Versions

#### Option R

**NC vacuum control, without blow-off :**  
CMS90X\_\_RV\_\_


- 1 control signal.
- NC vacuum control valve.



#### Option S

**NC vacuum control, with controlled blow-off:**  
CMS90X\_\_SV\_\_


- 2 control signals.
- NC vacuum control valve.
- blow-off controlled by external signal (NC control valve).



#### Option V

**NO, vacuum control, with controlled blow-off:**  
CMS90X\_\_VV\_\_

- 2 control signals.
- NO vacuum control valve.
- blow-off controlled by external signal (NC control valve).






# CMS

## Multi-stage Vacuum Pumps



### M12 Electrical Connection



Materials used

**Base body**  
**Valve body**  
**Silencer**

Glass-fiber reinforced PA 6  
Glass-fiber reinforced PA 6  
Aluminum with felt internal  
element  
Brass; Aluminum

### Electrical Characteristics

- Control voltage: 24 VDC (regulated) +/- 10%.
- Current draw: 30 mA (0.7 W) vacuum or blow-off.
- Max. operating frequency: 2 Hz.
- Number of operations: 10 million cycles.

**Screws**

Zinc-plated steel.

**Seals**

NBR.


**Membrane**

NBR.

### Dimensions


#### ■ CMS WITHOUT CONTROL VALVE:

- CMS90X\_\_N V\_\_



#### ■ CMS WITH CONTROL VALVE:

- CMS90X\_\_R V\_\_  
- CMS90X\_\_S V\_\_  
- CMS90X\_\_V V\_\_



#### Needle dial vacuum gauge:

**CMS 90 X --- VF**

- Damping: by silicone movement (patented).
- Measuring: Bourdon tube in CuSn.
- Precision: +/- 2.5% of max. scale value
- Frame: black ABS.



**To place an order, specify:**

**Model + Vacuum level + X + Suction flow + Control + Monitoring**

**Example: CMS90X100RVF**

1: Model	2: Vacuum level	3: Suction rate	4: Control	5: Monitoring
<b>CMS</b>	<b>90</b> 85%	<b>50</b> 31.8 SCFM <b>100</b> 63.6 SCFM	<b>N</b> Without control <b>R</b> NC Vacuum control <b>S</b> NC Vacuum and NC blow-off control <b>V</b> NO Vacuum and NC blow-off control	<b>VO</b> without Vacuum gauge <b>VF</b> Vacuum gauge



# M--C

## Air Amplifiers


### Applications




#### BLOW-OFF, CLEANING, WASTE SUCTION




#### SORTING BY WEIGHT




#### TRANSPORT OF GRANULES (rice, grains of wheat or coffee, etc.)



#### DEGASSING, SMOKE EVACUATION



#### GRIPPING AND / OR UNSTACKING VERY POROUS LOADS





# M-C

## Air Amplifiers



By virtue of the COANDA effect, the motor flux draws in air at room temperature. This physical phenomenon greatly amplifies the flow which results in very high suction produced with low consumption.

- Gripping of very porous, lightweight products: foam, carpet, cakes, leather, etc.
- Transport of powdery materials: powders, granules, etc.
- Transporting small, lightweight objects: paper clips, rice, coffee, etc.
- Smoke evacuation, chamber depressurization, etc.


### Operation requirement

Compressed air filtration at 5 microns for the M6C model and 20 microns for the other models.

### Characteristics

	L	N	M	C.A.	ØD	ØD1	ØD2	(g)
<b>M 6 C</b>	77	27.5	37	G1/8"-F	39	20	6	100
<b>M 10 C</b>	60	20	36	G1/8"-F	40	25	10	100
<b>M 20 C</b>	90	30	55	G1/4"-F	60	40	20	295
<b>M 30 CV</b>	105	35	72	G1/4"-F	77	50	30	495
<b>M 40 CV</b>	112	40	86	G3/8"-F	92	60	40	600

Note: all dimensions are shown in (mm).



- (1) Suction
  - (2) Discharge
  - (3) G1/4"-F
  - (4) Control valve, optional. Note: the valve is incompatible with the M40C model.
- A =
- 77 mm for an AP2 valve + DIN connection (connector supplied)
  - 68 mm for an AP2 valve + M12 connection (connector not supplied)
  - 44 mm for an AP2 + pneumatic connection for 2.7x4 tube

### Specifications

<b>Compressed air</b>	Dry non-lubricated 1.5 to 5 bar
<b>Maximum pressure drop</b>	see table page 9/6
<b>Materials</b>	Aluminum body
<b>Temperature</b>	32 to 176°F

### Additional information

- Stainless steel versions are available on request.
- The 5 products present the best amplification ratio (consumption/suction). COVAL can study smaller amplification ratios (higher consumption) but higher maximum vacuum for transporting heavy objects.



### For all orders, please specify:

Model + bore Ø + C.A. control + C.A. fitting + valve controls

Example : M30CVAP214E1

1: Model	2: Bore Ø	3: C.A. controls	4: Valve controls
<b>M</b>	<b>6 C</b> 6 mm <b>10 C</b> 10 mm <b>20 C</b> 20 mm <b>30 CV</b> 30 mm <b>40 CV</b> 40 mm	<b>-</b> Without control valve <b>AP214</b> C.A. control valve	<b>P1</b> Pneumatic <b>E1</b> 24 V DC DIN









#### Maximum Vacuum / Supply Pressure

	Supply pressure / Maximum vacuum (in Bar)		Supply pressure / Maximum vacuum (in mm CE)	
	2	3	4	5
<b>M 6 C</b>	900	1500	2000	2600
<b>M 10 C</b>	200	500	700	1000
<b>M 20 C</b>	207	310	400	510
<b>M 30 CV</b>	90	130	220	280
<b>M 40 CV</b>	140	200	284	360

#### Maximum Overpressure / Supply Pressure

	Supply pressure / Maximum vacuum (in Bar)		Supply pressure / Maximum vacuum (in mm CE)	
	2	3	4	5
<b>M 6 C</b>	100	550	1300	2000
<b>M 10 C</b>	400	700	1500	2000
<b>M 20 C</b>	220	340	500	600
<b>M 30 CV</b>	45	70	100	160
<b>M 40 CV</b>	96	145	199	290








Flexible polyurethane tube reinforced with a steel spiral covered in PVC.  
Highly resistant to abrasion, cutting fluids and UV light.

■ Anti-static treatment in compliance with standard DIN 53486.

### Specifications

Diameter D (mm)	Ø 25 - Ø 40 - Ø 50 - Ø 60
Bend radius	10 x D
Maximum pressure drop	-250 mbar
Maximum pressure	1 bar
Temperature	-40 to 212°F
Anti-static	R < 108 Ohm



**For all orders, please specify :**

**Model + Diameter + Length**

**Example: TVM4010**

1: Model	2: Diameter	3: Length (m)
TVM	25 Ø 25 mm	- In meters
	40 Ø 40 mm	10 A ring
	50 Ø 50 mm	
	60 Ø 60 mm	



# Vacuum Pump Accessories

## Chapter 10

### SIL GV



#### Diffuser-type Silencers

- Noise reduction of between 30 and 39 dBA
- Passage of air through a soundproof material
- Available in 4 sizes
- 4 types of fitting, M-5F, G1/8", G1/4", G 1/2"

- Very good sound reduction
- Air outlet gently diffused
- Reduced size

**P** 10/3

### SIL K--C



#### Through Type Silencers

- Through type silencer
- Noise reduction of between 30 and 33 dBA
- Noise absorbed laterally by soundproof textile
- Available in 5 sizes
- 3 types of fitting, G1/8", G1/4", G1/2"

- Noise reduction mastered
- No clogging
- No pressure loss
- Ideal for dusty environments
- Possibility of collecting the exhaust

**P** 10/3

### MS



#### Blow-off Devices

- Direct connection on the micro- and mini-ejectors via an M5 fitting
- Pressure connection by push fitting for Ø 4x6 or 2.7x4 tube
- 3.53 SCFM blow-off flow at 5 bar

- Allows direct blow-off on the VR type micro-ejectors or any other M5 fitting
- Reduces cycle times
- Avoids using a vacuum-proof distributor

**P** 10/4

### FVI



#### Vacuum Filters

- A range of 8 different models of vacuum filters for optimum adaptation depending on the source of vacuum generation
- 3 filtration materials: paper, polyester and stainless steel
- 6 types of fitting, depending on the model: G3/8", G1/2", G3/4", G1"1/4, G1"1/4 and G2".

- Ideal vacuum filter for high suction flow rate vacuum sources
- Solution optimized to suit each operating environment thanks to three types of filtering material used in the filter cartridges
- A wide range adapted to your application
- Easy-to-replace cartridges in case of clogging

**P** 10/5

### FVUM FVUG



#### Vacuum Filters

- A range of 4 models
- 2 sizes and 3 types of fittings: G1/4", G3/8" and G1/2"
- Transparent tank

- Transparent tank, visual checking on clogging possible
- Different models mean you can select a solution adapted to your application

**P** 10/7

### FVG



#### Mini Vacuum Filters

- A range of 4 models

- Ideal for mounting with micro and mini in-line ejectors
- Easy-to-replace cartridges in case of clogging

**P** 10/8

### FVL12



#### In-line Filter

- 400 micron stainless steel screen

- Easy to mount in-line on the vacuum network or directly on the vacuum pump

**P** 10/9

### FVL68



#### In-line Vacuum Filter

- Simple push connection for 6x8mm hose

- Quick integration into vacuum network

**P** 10/9



# Vacuum Pump Accessories

## Chapter 10

**FSL**



### Liquid Separator Vacuum Filters

- 2 filtration (60 and 100 microns)
- Transparent tank
- Manual drain
- We particularly recommend using the FSL series liquid separator vacuum filters to retain liquid and particles that may be found in a vacuum network.

**P** 10/10

**CD  
CC**



### Screw-type Electrical Connectors

- M8 and M12
- 4 and 5 poles
- Straight or elbow(90°)

**P** 10/11




# SIL GV. SIL K -- C

## Diffuser Type Silencers, Through-type Silencers




From when it was founded, COVAL has always given particular attention to reducing the noise of vacuum pumps and improving their performance.

Often copied, never equalled, the acoustic performance of COVAL vacuum pumps stems from the inside shape of the venturi system and the innovative design of the hit-tech soundproof materials used for the silencers.



### Diffuser type silencer

- Very good noise reduction
- Air output gently diffused.



### Through-type silencer

- Noise reduction mastered.
- No clogging.
- No pressure loss.

## SIL GV series diffuser-type silencers


Noise reduction by breaking up the air jet in a baffle inside the diffuser.  
Passage of air through a soundproof material.



### Characteristics

Models	ØA	B	ØC	Weight (g)	Medium-level noise reduction (dBA)
SIL GV 10 M5 F	18	36	M5-F	5	30
SIL GV 10	18	36	G1/8"-M	5	30
SIL GV 15	20	46	G1/4"-M	10	35
SIL GV 20	30	62	G1/2"-M	29	39

Note: all dimensions are shown in (mm)



### Specifications

Material	POM (Polyoxymethylene)
Temperature	14 to 122 °F

## SIL K -- C series through-type silencers


- Noise absorbed laterally by soundproof material.
- Free output without pressure loss or clogging.



### Characteristics

Models	ØA	B	ØC	Weight (g)	Medium-level noise reduction (dBA)	Materials
SIL K 18 C	20	68	G1/8"-M	22	33	thread: aluminum
SIL K 14 C	20	68	G1/4"-M	25	31	tube: PA6, 30% GF
SIL K 38 C	30	121	G3/8"-M	90	33	polycarbonate, 30% GF
SIL K 12 C	30	121	G1/2"-M	92	33	
SIL K 12 CS	30	54	G1/2"-M	61	28	

Note: all dimensions are shown in (mm)



### Specifications

Material	Black anodized aluminum or black polycarbonate (according to Ø) interior: Textile soundproof material
Temperature	14 to 122 °F

### Special:

**COVAL** develops tailor-made through-type silencers according to specifications, male or female fitting, length, diameter, characteristics on request.



# MS

## Quick Release Devices



Economical solution developed especially for Coval micro-ejectors to suit applications requiring blow-off combined with very reduced size and weight. This device enables the user to connect the compressed air network directly onto the M5 fitting.

### Advantages


- Allows blow-off on VR or any other M5 fitting
- Reduces cycle times
- Avoids using a vacuum-proof distributor.

### Technical Characteristics

Model	Push fitting	L
MS2M5	Ø 2.7x4	25.8
MS4M5	Ø 4x6	28.10


- Pressure connection by push fitting for Ø 4x6 or 2.7x4 tube
- Connection to the vacuum network by M5 male threaded fitting
- Blow-off flow rate at 5 bar: 3.53 SCFM
- Materials: polyamide PA 6.6 + brass (CuZn) + nitrile (NBR)

### Dimensions



(1) Push fitting

### Pneumatic Diagram



MS

10



For all orders, please specify:  
Model + Push fitting  
e.g. : MS2M5

1: Model	2: Push fitting
MS2M5	Ø 2.7x4
MS4M5	Ø 4x6

Note: all dimensions are shown in (mm)



# FVI

## Vacuum Filters



The FVI range is compatible with pneumatic vacuum generators (venturi) or electric vacuum pumps (the FVI 2 model is suitable for a suction turbine). Each filter is fitted with an interchangeable cartridge treated to guarantee long life expectancy for the whole unit. The filtering element consists of a 5 micron filter (made of paper for version C), which is sufficient to protect pumps and venturi under normal operating conditions.

Note: For filtration leaving large deposits (powder), mount the filter horizontally or upside down.


Important: These filters are designed for vacuum. They cannot withstand pressure greater than atmospheric pressure.

Filter cartridge available in 3 versions: paper, polyester and stainless steel.

### Characteristics


Models	A	H	R	Flow rate (SCFM)	Weight (g)
FVI 38	79	76	G3/8"-F	14.13	270
FVI 12	101	86	G1/2"-F	21.19	600
FVI 34	101	86	G3/4"-F	21.19	600
FVI 114	135	96	G1"1/4-F	49.44/42.38	1050
FVI 114 G	173	156	G1"1/4-F	49.44/42.38	1850
FVI 2	201	258	G2"-F	176.6	3900

Note: all dimensions are shown in (mm)



### Specifications

Body material	Stamped steel sheet
Treatment	Black paint
Filtration	5 microns with a paper cartridge 3 microns with a polyester cartridge 60 microns with a stainless steel cartridge
Pressure loss	2 to 4% vacuum with a new filter 5 to 7% vacuum with average clogging



For all orders, please specify:  
Model + Fitting + Filtering material  
e.g.: FVI34P

1: Model	2: Fitting	3: Filtering material
FVI	38 G3/8" 12 G1/2" 34 G3/4" 114 G1"1/4 114G G1"1/4 2 G2"	C Paper P Polyester I Stainless steel





### Filter

Models	Use
<b>FVI 38</b>	GVP 20
<b>FVI 12</b>	GVP 25 - 30 - PVR 6 (211.88 Cf)
<b>FVI 34</b>	Vacuum pumps: 353/565 Cf
<b>FVI 114</b>	Vacuum pumps: 706/882 Cf
<b>FVI 2</b>	Turbine

### Filtration

COVAL offers three filtration principles:

#### Model C: CE filtration element

- Paper cartridge with 5 micron filtration.
- No damp cleaning process possible.
- Incompatible to very humid conditions

#### Model P: PE filtration element

- Polyester cartridge with 3 micron filtration.
- Damp cleaning possible.

#### Model I: IE filtration element

- Stainless steel cartridge, 60 micron filtration.
- For use in very damp environments (water, liquid)


### Accessories

Models	Replacement cartridge (*)	External Ø	Internal Ø	H2
<b>FVI 38</b>	FVI 38*E	51	23	57
<b>FVI 12</b>	FVI 12*E	64	38	68
<b>FVI 34</b>	FVI 12*E	64	38	68
<b>FVI 114</b>	FVI 114*E	98	60	71
<b>FVI 114 G</b>	FVI 114G*E	125	64	125
<b>FVI 2</b>	FVI 2*E	149	88	221

(\*) Specify the filter material: **C** (paper) ; **P** (polyester) ; **I** (stainless steel).

Note: all dimensions are shown in (mm)

### Replacement cartridge



### Other Models

#### FVG 11-2-3-5-6 series vacuum filters, for micro-ejectors

- Polyester cartridge
- See page 10/8

#### FVUM 14-38 series vacuum filters for GVP 12 and 15 vacuum pumps

- FVUG 38-12 vacuum filters, in-line stainless steel cartridge for GVP 15 and 25 vacuum pumps and small electric vacuum pumps.
- See page 10/7



# FVUM. FVUG

## In-line Filters

The advantage of this range of filters is that they are equipped with a transparent tank so that clogging is visible.

### Characteristics

Models	A	B	C	D	G	Flow rate (SCFM)
FVUM 14	75	60	49.5	49.5	G1/4"-F	5.30
FVUM 38	75	64	49.5	51.5	G3/8"-F	12.36
FVUG 38	90.5	126.5	75	112.5	G3/8"-F	12.36
FVUG 12	90.5	130	75	114.5	G1/2"-F	17.66


Note: all dimensions are shown in (mm)

### Operating range


■ - 1 to 10 bar

### Specifications

Body material	High: nylon 6.6 Tank: transparent polyamide
Filtration	Two options available: 50 micron stainless steel grill or Polyethylene 80 micron
Temperature	32 to 122°F



- (1) Vacuum generator
- (2) Filtering element
- (3) Body
- (4) Tank



For all orders, please specify:  
Model + Size + Fitting + Type of cartridge  
e.g. : FVUG38P

1: Model	2: Size	3: Fitting	4: Cartridge
FVU	M G	Mini Large	14 38 12
			G1/4" for M series G3/8" for M and G series G1/2" for G series
			- P
			Stainless steel Polyethylene



To order a replacement filtering element, please specify:  
e.g. : FVUM12E

Model	Reference of the filtering element
FVUM14 and 38	FVUM12E (Stainless steel)
FVUG12 and 38	FVUG12E (Stainless steel)
FVUM14P and 38P	FVUM12PE (Polyethylene)
FVUG12P and 38P	FVUG12PE (Polyethylene)

### Mounting bracket for vacuum filter


Materials: Polyethylene 20% fiber glass.

#### Model


FVUFIXM	Mounting bracket for filter FVUM
FVUFIXG	Mounting bracket for filter FVUG



FVUFIXM



FVUFIXG



Please specify part n°, eg: FVUFIXM  
Please see table above



# FVG

## Mini Vacuum Filters



FVG series vacuum filters are especially recommended for fine filtration. Their light weight allows easy on-board installation.

### Mini-filters

Models	Vacuum pumps
<b>FVG 3</b>	GVP 10 - VR 07 - VR 09
<b>FVG 5</b>	GVP 12 and 14
<b>FVG 6</b>	GVP 20



### Characteristics

Models	A	B	C	E	F	G	D1	D2
<b>FVG 3</b>	8	16	33	55.5	50.5	18	G1/8"-F	G1/8"-F
<b>FVG 5</b>	12.5	25	42	65	50	23	G1/4"-F	G1/4"-F
<b>FVG 6</b>	15	30	47	70	60	23	G3/8"-F	G3/8"-F

Note: all dimensions are shown in (mm)

### Specifications


<b>Operating pressure</b>	-1 to 5 bar
<b>Temperature</b>	32 to 140 °F
<b>Filtration (μ)</b>	FVG 3-5-6 : 40
<b>Weight (g)</b>	FVG 3/5/6 : 90/150/235
<b>Material</b>	Anodized aluminum



(1) D1 (input)  
(2) DE (Output)

### Accessories

Replacement cartridges: interchangeable filtration element.  
Add E to the filter model reference to order the replacement cartridge.



Filtration angle 300°



For all orders, please specify:  
**Model + Type + Filter or Cartridge**  
e.g.: FVG5

1: Model	2: Type	3: Filter or Cartridge
<b>FVG</b>	<b>3</b> FVG 3	- Filter
	<b>5</b> FVG 5	E Cartridge
	<b>6</b> FVG 6	



# FVL 12

## In-line Filter




The FVL12 in-line filter allows quick integration for vacuum pumps GVP and GEMP.

### Specifications

<b>Material</b>	Body: Nickel-plated brass Grille: 400 micron stainless steel
<b>Weight</b>	50 g

Mounting on option

The FVL 12 series in-line filter can also be mounted as a GVO P option on GVP series vacuum pumps. See page 7/8.



Note: all dimensions are shown in (mm)



For all orders, please specify: FVL12

# FVL 68

## In-line Vacuum Filter




The FVL68 in-line filter ensures quick integration into a vacuum network, thanks to its push fitting for 6 x 8 calibre pipes.

Ideal for protecting a vacuum generator from normal clogging. The FVL is equipped with a 400 micron filtering grille.

### Applications

The FVL68 in-line filter is ideal for protecting LEM mini vacuum pumps. Installation directly onto the vacuum outlet of the pump, using a 6 x 8 push fitting.

Industry-specific applications



### Specifications


<b>Material</b>	Body: POM Grille: 400 micron stainless steel Push fitting Brass – Steel and polymer
<b>Weight</b>	7 g.

Note: all dimensions are shown in (mm)



Specify part n°: FVL68

Dimensions



Example usage





# FSL

## Liquid Separator Vacuum Filters



We particularly recommend using the FSL series liquid separator vacuum filters to retain liquid and particles that may be found in a vacuum network. The filtering element consists of a 60 or 100 micron stainless steel filter and protects the vacuum generator under normal operating conditions.

### Advantages

- Transparent tank that makes clogging visible.
- Manual drain in the bottom of the tank used to remove any liquid and dirt (Note: This operation must only be carried out when the vacuum network is at atmospheric pressure).


### Characteristics

Models	Fitting	Stainless steel filtering	Flow rate <sup>(1)</sup> (SCFM)
FSL38 I 100	G3/8"-F	100 µ	12.25
FSL38 I 60	G3/8"-F	60 µ	12.25

(1) The flow rate may vary according to the viscosity of the liquid drawn in.

### Specifications

<b>Material</b>	Lid: molded aluminium Tank: transparent polyamide Filter cartridge: stainless steel Accessories: brass and nickel-plated brass Seal: nitrile
<b>Filtering</b>	Two options available: 60 and 100 microns
<b>Operating range</b>	-1 to 2 bar
<b>Pressure max.</b>	2 bar
<b>Temperature</b>	32 to 122°F



For all orders, please specify:  
**Model + Filtering**  
e.g.: FSL38I100

1 : Model	2 : Filtering
FSL38 I	100 100 µ
	60 60 µ



To order a replacement filtering element, please specify:  
e.g.: FSL38 I 100 E

Model	Reference of the filtering element	Filtering
FSL38 I 100	FSL38 I 100 E	100 µ
FSL38 I 60	FSL38 I 60 E	60 µ



### Mounting bracket for FSL series liquid separator filter

Material: zinc-plated steel

#### Model

**FSL38FIX** Mounting bracket for FSL filter

Note: Supplied with two M6 screws to mount bracket on filter.



Note: all dimensions are shown in (mm)



Specify part n°: FSL38FIX




## Screw-type Electrical Connectors, M8 and M12




### M8 Connector Characteristics

Models	Connectors	No. of pins	Orientation	Cable length
CDM8	M8	4	Straight	2 m
CDM8N	M8	4	Straight	0.5 m
CCM8	M8	4	Elbow	2 m




1: Brown  
2: White  
3: Blue  
4: Black

### M8




### M12 Connector Characteristics

Models	Connectors	No. of pins	Orientation	Cable length
CDM12N	M12	4	Straight	2 m
CDM12L5	M12	4	Straight	5 m
CCM12	M12	4	Elbow	2 m
CDM125PL2	M12	5	Straight	2 m
CDM125PL5	M12	5	Straight	5 m
CCM125PL2	M12	5	Elbow	2 m




1: Brown  
2: White  
3: Blue  
4: Black



1: Brown  
2: White  
3: Blue  
4: Black  
5: Gray

### M12



### Specifications

Female screw-type connector.

PVC cable

Protection : IP 65



Specify part n°, eg: CDM8N  
Refer to characteristics table above



# Vacuum Switch Range

## Chapter 11

---



# Vacuum Switch Range

## Chapter 11

### PSK



#### Mini Vacuum Switch

- 1 digital output
- Adjustable vacuum threshold
- 3 vacuum port sizes available
- M8 connection

- Ultra-compact and lightweight
- LED visual indicators

**P** 11/3

### PSA 100 C



#### Electronic Vacuum Switch with Display

- 2 configurable digital outputs
- NO or NC outputs
- Adjustable hysteresis
- IP 65

- The PSA100 C electronic vacuum switch is the most efficient vacuum measuring component in the COVAL range.
- It can be easily installed on all machines and robots, etc. thanks to its compact lightweight design.

**P** 11/4

### PSD 100



#### Vacuum Switch with 3-colour Display

- 1 to 5 VDC analog output
- Response time: < 5ms
- 2 vacuum fittings available
- M8 connection

- The compact PSD100 electronic vacuum switch is used to check the exact level of vacuum in the system.
- Analog output

**P** 11/5

### PSP 100



#### Electronic Vacuum Switch

- 1 configurable digital output
- Response time: < 5ms
- 3 vacuum fittings available
- 2 electric fittings available

- The PSP100 electronic switch reduces size while accurately monitoring the vacuum level
- Adjustable digital output and hysteresis.

**P** 11/7

### PSP 100 ANA



#### Electronic Vacuum Switch Analog Output

- 1 Analog output from 1V to 5 VDC
- Response time: < 5ms
- 2 vacuum port sizes available
- M8 connections

- The PSP100 ANA electronic switch reduces size while accurately monitoring the vacuum level
- Analog output

**P** 11/8

### PSE 100 E



#### Electric Vacuum Switch

- Adjustment range -300mb to -850mb
- All voltages
- Cable or M12 connector outputs

- The PSE 100 E vacuum switch with electric output is used to check the vacuum level in the circuit.
- It is adapted to all electrical automated systems.
- The choice between the NO or NC function is made during wiring.

**P** 11/9

### PSE 100 P



#### Pneumatic Vacuum Switch

- 2 versions available (NO or NC)
- Adjustment range: -300mb to -850mb
- The PSE 100 E series vacuum switch with pneumatic output enables the vacuum level in the system to be checked by means of a patented system.

- This vacuum switch exists in two versions:
- NO version, recommended for "air-saving" on the vacuum pump
- N.C. version to cover the "safety" function (object detected, etc.) and "SFC signal" function.

**P** 11/10



# Vacuum Switch Range

## Chapter 11

### PSE 100 PK



#### Pneumatic Vacuum Switch

- 2 versions available (NO or NC)
- Adjustment range:
  - NC: -250 to -830mb
  - NO: -350 to -880mb
- The vacuum switch with pneumatic output is used to check the vacuum level in the circuit. It is recommended for measuring slowly changing vacuum levels such as regulating or checking vacuum levels in networks over 1 liter.
- NO version, recommended for "air-saving" on the vacuum pump.
- NC version to cover the "safety" function (object detected, etc.) and "SFC signal" function.

P<sub>11/11</sub>

### VAF 111



#### Needle Vacuum Gauge

- VAF 111 series vacuum gauges are recommended for viewing the level of vacuum on a network for maintenance, checking and adjustment purposes (Green zone of use: -0.65 to -1 bar)
- 3 diameters available: 40, 50 and 63 mm
- Zone for use printed red and green

P<sub>11/12</sub>



# PSK


## Mini Vacuum Switch



The PSK series adjustable vacuum switches, due to a compact and ultra-light design, enable installation close to the suction cups for reduced response times. PSKs are ideal for applications requiring only a simple "object gripped" signal, and offer an economical and effective solution for applications with one vacuum generator per suction cup.

- Simple installation, plug-in port or thread-in fitting
- Compact size : 26 x 10 x 10.4 mm
- Weight: 8.3 g

Industry-specific applications



### Specifications

<b>Model</b>	<b>PSK 100</b>
<b>Setting pressure range</b>	0 to 100% vacuum (0~-101.3 kPa)
<b>Withstand pressure</b>	0.6 MPa
<b>Fluid</b>	Air, Non-corrosive/Non-flammable gas
<b>Power supply voltage</b>	10.8 to 30 VCC
<b>Load current</b>	80mA max.
<b>Internal voltage drop</b>	≤ 0.8 V
<b>Current consumption</b>	10 mA max.
<b>Sensor type</b>	PNP
<b>Output short circuit protection</b>	Yes
<b>Setting method</b>	Adjusting by VR
<b>Response time</b>	Approx. 1ms
<b>Repeatability</b>	≤ +/-1% F/S/
<b>Hysteresis</b>	3% F.S. max.
<b>Indicator</b>	Red LED turns ON
<b>Enclosure</b>	IP 40
<b>Temperature characteristic</b>	≤ +/-3% F/S/ of detected pressure (77°F) at temp. Range of 32~122°F
<b>Ambient temp. range</b>	Operation: 0 ~ 60°C (32 ~ 140°F), Storage: -20 ~ 70°C (-4 ~ 158°F) (No condensation or freezing)
<b>Ambient humidity range</b>	Operation/Storage: 35 ~ 85% RH (No condensation)
<b>Vibration</b>	Total amplitude 1.5 mm, 10Hz-55Hz-10Hz scan for 1 minute, two hours each direction of X, Y and Z
<b>Shock</b>	980m/s <sup>2</sup> (100G), 3 times each in direction of X, Y and Z
<b>vacuum connection</b>	Push-in tube or thread-in
<b>Electrical connection</b>	M8 connection 3-pin (Cable L:150 mm)
<b>Weight</b>	Approx. 8.3 g (with M8, 3-pin male connector)


### Advantages

- Simple installation:  
Plug-in port for push-to-connect fittings
- Compact size:  
Extremely compact size to fit the most confined areas

### Additional Information

#### Electrical connections

- M8, 3-pin male connector




- 1 = + (Brown)
- 2 = - (Blue)
- 4 = out (Black)


- Ø6mm stem for one-touch push fitting, Male M5 or G1/8"-M.

### Dimensions


PSK 100G18M8



PSK 100M5M8



PSK 100D6M8



For all orders, please specify:  
**Model + Measuring range + Vacuum connection + Connection**  
Example: PSK100G18M8

1: I	2: Measuring range	3: Vacuum connection	4: Connection
PSK	100 0 to 100% vacuum	D6 Ø 6 mm G18 G 1/8"-M, M5-F M5 M5 male	M8 M8, 3-pin male connector



# PSA 100 C

## Electronic Vacuum Switch with Display




The PSA100C series electronic vacuum switch is the most efficient COVAL vacuum measuring component. It can be easily installed on all machines and robots, etc. thanks to its compact lightweight design.

Moreover it has a digital vacuum level display with two independently-adjustable digital outputs. Every aspect has been designed to make it easy to use.

Advantages: front panel programming, simplified adjustment and threshold locking, display inversion, your choice of NO or N.C. outlets (hysteresis can be independently adjusted for each output).

Industry-specific applications




### Specifications

Compatible fluids	All non-corrosive, filtered, non-lubricated gases
Supply	12 to 24 V CC $\pm$ 10%
Current consumed	$\leq$ 60 mA
PNP transistor output	125 mA with 24 V DC, programmable NO or NC
Output viewing	Led
Output 1	Green LED
Output 2	Red LED
Programming	Keyboard
Display	Bar
EMC	Industrial standard Class B
Protection	IP 40
Electrical connection	M8, 4-pin connector
Pneumatic connection	G1/8" or M5-F
Shock resistance	100 G on XYZ
Display resolution	1%
Adjustment resolution	1%
Rating range	0.10 ~ -1.00 bar
Setting range	0.00 ~ -1.00 bar
Maximum overpressure	3 bar
Weight	30 g

### Advantages


- 2 configurable digital outputs
- Adjustable hysteresis
- M8 F connector
- LED display
- PNP



### Additional Information



#### Electrical connections

- M8 connector



- 1 = + 24 V DC
- 2 = Output 2
- 3 = Common
- 4 = Output 1

### Dimensions



### Accessories

- Straight or elbow connector, see page 10/11.
- Mounting on vacuum pump:
  - GVP series: GVO PSA 100 C
  - GEMP series: VA option

Note: all dimensions shown in (mm)



For all orders, please specify: PSA 100 C



# PSD 100

## Vacuum Switch with 3-color Display

The new PSD100 series mini-vacuum switch with display offers easy reading thanks to the size of its screen and its 3-color display.

Its compactness and lightness facilitate its integration on all machines.

Easily adjustable, it is equipped with an extremely precise electronic vacuum level sensor and has an adjustable digital output as well as an analog output. The PSD100 has mounting accessories on option, making it very easy to install.



Industry-specific applications




### Specifications

<b>Pressure rating range</b>		0.0 ~ -101.3 kPa					
<b>Pressure setting range</b>		10.0 ~ -101.3 kPa					
<b>Max. pressure</b>		300 kPa					
<b>Fluid</b>		Air, non-corrosive/non-flammable gas					
<b>Pressure setting resolution</b>	kPa	MPa	kgf/cm <sup>2</sup>	bar	psi	inHg	mmHg
	0.1	/	0.001	0.001	0.01	0.1	1
<b>Power supply voltage</b>		12 to 24 V DC $\pm 10\%$ , ripple (P-P) 10% or less					
<b>Current consumption</b>		$\leq 40$ mA (without load)					
<b>Switch output</b>		1 PNP digital output (2x on PNP2 version) Max. load current: 125 mA Max. supply voltage: 24 VDC Residual voltage: $\leq 1.5$ V					
<b>Repeatability (Switch output)</b>		$\leq \pm 0.2\%$ F.S. $\pm 1$ digit					
<b>Hysteresis</b>	<b>Threshold mode</b>	Adjustable (1 to 8 digits)					
	<b>Hysteresis mode</b>	Adjustable					
	<b>Window comparator mode</b>	Adjustable (1 to 8 digits)					
<b>Response time</b>		$\leq 2.5$ ms (anti-vibration function: 25 ms, 100 ms, 250 ms, 500 ms, 1000 ms and 1500 ms selection)					
<b>Output short circuit protection</b>		Yes					
<b>7 segment LCD display</b>		Two colour (red / green) main display, orange sub-display (refresh rate: 5 times / 1sec.)					
<b>Indicator accuracy</b>		$\leq \pm 2\%$ F.S. $\pm 1$ digit (ambient temperature: $77 \pm 37.4^\circ\text{F}$ )					
<b>Switch ON indicator</b>		Orange OUT 1 / OUT 2 (PNP2 only)					
<b>Analog output (voltage power) (PNP version only)</b>		Output voltage: 1 to 5 V $\leq \pm 2.5\%$ F.S. (within rated pressure range), linearity: $\leq \pm 1\%$ F.S. / Output impedance: approx. 1 k $\Omega$					
<b>Environnement</b>	<b>Enclosure</b>	IP40					
	<b>Ambient temp. range</b>	operation: $32 - 122^\circ\text{F}$ / storage: $14 - 140^\circ\text{F}$ (no condensation or freezing)					
	<b>Ambient humidity</b>	Operation / Storage: 35-85% RH (no condensation)					
	<b>Permissible voltage</b>	1000 V AC in 1-min (between case and lead wire)					
	<b>Insulation resistance</b>	50 M Ohm min. (at 500 V DC, between case and lead wire)					
	<b>Vibrations</b>	Total amplitude 1.5 mm or 10 G, 10 Hz-150 Hz-10 Hz scan for 1 minute, two hours in each direction of X, Y and Z					
	<b>Shocks</b>	100 m/s <sup>2</sup> (10 G), 3 times each in direction of X, Y and Z					
<b>Temperature characteristic</b>		$\leq \pm 2\%$ F.S. of detected pressure ( $77^\circ\text{F}$ ) at temp. range of $32-122^\circ\text{F}$					
<b>Port size</b>		G1/8", M5-F					
<b>Lead wire</b>		Oil-resistance cable (0.15 mm <sup>2</sup> )					
<b>Weight</b>		Approx. 45 g (with M8, 4-pin male connector)					

### Advantages

- 3-colour digital LCD display, easy readability.
- 6 pressure units available (kPa, bar, psi, inHg, mmHg, kgf/cm<sup>2</sup>).
- PNP version:
  - 1 PNP digital output (NO or NC).
  - 1 analog output (1-5V).
- PNP2 version:
  - 2 PNP digital outputs (NO or NC).
- Double display showing the measured value and threshold value at the same time.
- "Key lock function" with indicator light, «Lock» mode with light indicator to prevent an accidental misadjustment.
- "Power-save function" with indicator light.
- 3 mounting solutions.

### Panel Description



- 1 - 2-colour main display
- 2 - Lock indicator
- 3 - Output 1 indicator
- 4 - Button
- 5 - Setting button
- 6 - Button
- 7 - Output 2 indicator (PNP2 version)
- 8 - Setting mode (sub-display section)
- 9 - Pressure unit display section



For all orders, please specify:  
Model + Electrical connection + Outputs.  
Example: PSD100CPNP

1: Model	2: Electrical connection	3: Outputs
PSD100CPNP	M8 connector	1 digital output PNP 1 analog output
PSD100LPNP2	2 m cable	2 digital outputs PNP

### Accessories

- CDM8: M8 Female connector – 4 poles, 2 m.
- PSDFIXA: Vertical attachment bracket.
- PSDFIXB: Horizontal attachment bracket.
- PSDFIXC: Front attachment kit.
- PSDFIXD: Front attachment kit + front protective lid.



## Two digital clocks are shown. The clock on the left displays 5:34 and -65.0. The clock on the right displays 7:85 and -65.0. Both clocks have a small display at the top showing a battery level indicator and a small square icon.

**PSD100LPNP\_**

2xM3

20

20

2000

1 = Brown (+)  
2 = White (OUT2)  
3 = Blue (-)  
4 = Black (OUT 1)

"Vacuum" connection  
G1/8"-M; M5-F

12






# PSP 100

## Electronic Vacuum Switch



PSP series electronic vacuum switches have integrated threshold and hysteresis adjustment as standard. 3 vacuum fittings (G1/8" Male, M5 female or M5 F Base) and 2 electrical connections (2 meter cable and M8 connector) make up the standard range.

Industry-specific applications




### Specifications

Models	PSP 100 L	PSP 100 LM5	PSP 100 C	PSP 100 CM5
Compatible fluids	All non-corrosive, filtered, non-lubricated gases			
Supply	Regulated 18-30 V DC, polarity inversion protection			
Current consumed	< 20 mA			
Transistor output	NO 125 mA with 24 VDC			
Thermal drift	± 3% of the measuring scale between 32 and 122°F			
Output viewing	LED			
Response time	< 5 ms			
Threshold adjustment	By 3/4 turn potentiometer			
Hysteresis adjustment	0 to 30% adjustment by 3/4 turn potentiometer			
EMC	Industrial standard class B			
Materials	PA 66 and brass	PA 66 and Alu.	PA 66 and brass	PA 66 and Alu.
Temperature	Operation: 32 to 122 °F Storage: 14 to 140 °F			
Protection	IP 50			
Electrical connection	PVC cable (length 2m)		M8 connector (4 poles)	
Pneumatic connection	G1/8"-M or M5-F	Base M5-F	G1/8"-M or M5-F	Base M5-F
Weight	62 g	67 g	22 g	27 g
Adjustment range	0 to -1 bar			

### Advantages


- 1 configurable digital output
- Adjustable hysteresis
- Measuring range: 0 / -1 bar
- Overpressure: +3 bar
- PNP




### Additional Information

#### Electrical connections

- PVC cable (length 2m)




- M8 connector




- 1 = + 24 V - Brown
- 2 = -
- 3 = 0 V - Blue
- 4 = Contact - Black

#### Vacuum switch attachment - Clip Part No: PSE.F



### Dimensions



- (1) M8 4 pole connector version
- (2) PVC cable version (2 m)
- (3) Hysteresis adjustment
- (4) Threshold adjustment
- (5) Threshold display LED

Note: all dimensions shown in (mm)

### Accessories

- Straight or angled connector, see page 10/11.
- Mounting on vacuum pump:
  - GVP series: GVO PSP 100 C
  - GVO PSP 100 L
  - GEMP series: VB option




For all orders, please specify:  
Model + Electrical connection + Vacuum connection.  
Example: PSP100C

1: Model	2: Electrical connection	3: Vacuum connection
PSP 100	L 2 m cable C M8 connector	- G1/8"-M or M5-F M5 Base M5-F




# PSP 100 ANA

## Electronic Vacuum Switch Analog Output



The PSP 100 ANA contains an analog output. It is fitted with 2 vacuum connections as standard (G1/8" male or M5 Female) and one M8 electrical connector.

Industry-specific applications



### Specifications


<b>Compatible fluids</b>	All filtered, non-corrosive, non-lubricated gases
<b>Supply</b>	24 V DC (18 V DC min / 30 V DC max)
<b>Current draw</b>	< 20 mA
<b>Analog output</b>	1 to 5 VDC from 0 to -1 bar
<b>Thermal drift</b>	± 3% of the measuring scale between 32 and 122°F
<b>Response time</b>	< 5 ms
<b>EMC</b>	Industrial standard Class B
<b>Materials</b>	PA 66 and brass
<b>Temperature</b>	Operation: 32 to 122 °F Storage: 14 to 140 °F
<b>Protection</b>	IP 50
<b>Electrical connection</b>	M8 connector (4 pins)
<b>Pneumatic connection</b>	G1/8" Male and M5 Female
<b>Weight</b>	22 g

### Advantages

- 1 analog output from 1 to 5 VDC
- Measuring range: 0 / -1 bar
- Overpressure: +3 bar max.
- PNP


### Electrical Diagrams

- M8 connector



- 1 = + 24 V (Brown)
- 2 = analog output from 1 to 5 VDC (white)
- 3 = 0 V common (blue)

### Dimensions



Note: all dimensions shown in (mm)

### Accessories

- Straight or elbow connector, see page 10/11.



For all orders, please specify: PSP 100 ANA



# PSE 100 E






# PSE 100 P

## Pneumatic Vacuum Switch



The PSE 100 P series vacuum switch with pneumatic output allows the vacuum level in the system to be checked by means of a patented system. This vacuum switch exists in two versions: NO version recommended for the "air saving" function on a venturi and NC version for the "safety" function (object detected, etc.) and "SFC signal".


Industry-specific applications




### Specifications

Models	Two versions: NO and NC
Compatible fluids	All non-corrosive gases
Pression d'utilisation	2 to 6 bar
Adjustment range	- 300 mb to -850 mb
Precision	3%
Hysteresis	80 to 100 mb
Repetitivity	< 3% of the whole range
Maximum speed	30 cycles per minute
Permissible overpressure	2 bar (destructive at 5 bar)
Mechanical endurance	5 x 10 <sup>6</sup> operations
Materials	Body: Polyacetal - Vacuum sensor: nitrile membrane
Weight	32 g
Temperature	14 °F to 176 °F
Flow rate at 6 bar	2.47 SCFM

### Dimensions




- (1) Vacuum threshold - Adjustment screw
- (2) Hollow shaft for tube, inside Ø 2.7 mm
- (3) Vacuum
- (4) NO or NC output
- (5) Pressure input




### Additional Information

- Mounting as GVO option in the GVP / GEMP vacuum pump range.

### Pneumatic connection



Vacuum switch attachment - Clip Part No: PSE.F



For all orders, please specify:  
Model + Version.  
Example: PSE100PNO

1: Model	2: Version
PSE 100 P	NO Normally Open (NO)
	NF Normally Closed (NC)

Note: all dimensions shown in (mm)



# PSE 100 PK

## Pneumatic Vacuum Switch




The PSE 100 K vacuum switch with pneumatic output is used to check the vacuum level in the circuit.

It is recommended for measuring slowly changing vacuum levels such as regulating or checking vacuum levels in networks over 1 liter.


This vacuum switch exists in two versions: NO version recommended for the "air saving" function on a venturi and NC version for the "safety" function (object detected, etc.) and "SFC signal".

Industry-specific applications




### Specifications

<b>Models</b>	<b>Two versions: NO and NC</b>
<b>Compatible fluids</b>	All non-corrosive, non-lubricated gases
<b>Operating pressure</b>	2 to 6 bar
<b>Adjustment range</b>	NF: -250 to -830 mb, NO: -350 to -880 mb
<b>Precision</b>	± 10 %
<b>Hysteresis</b>	NF: 10 mb - NO: 200 mb
<b>Repetitivity</b>	< 3% of the whole range
<b>Maximum speed</b>	30 cycles per minute
<b>Permissible overpressure</b>	2 bar (destructive at 5 bar) (on vacuum measuring orifice)
<b>Mechanical endurance</b>	5 x 10 <sup>6</sup> operations
<b>Materials</b>	Body: Polyacetal - Vacuum sensor: nitrile membrane
<b>Weight</b>	32 g
<b>Temperature</b>	14 °F to 176 °F
<b>Flow rate at 6 bar</b>	2.33 SCFM



### Dimensions




- (1) Vacuum threshold adjustment  
(2) Signal output, NC or NO tube

- (3) M5 Vacuum input  
(4) Pressure input Ø4 tube


### Additional Information

- Mounting in GVO option in the GVP / GEMP vacuum pump range.

#### Pneumatic connection



Vacuum switch attachment - Clip Part No: PSE.F



**For all orders, please specify:  
Model + Version.  
Example: PSE100PKNO**

1: Model	2: Version
PSE 100 PK	NO Normally Open (NO)
	NF Normally Closed (NC)

Note: all dimensions shown in (mm)



# VAF 111

## Vacuum Gauge




VAF 111 series vacuum gauges are recommended for visually checking the vacuum level for maintenance, monitoring and adjustment purposes.

They are mounted as options on modular vacuum pumps GVP series, reference GVO VAF11140.

See page 7/7.

Industry-specific applications



### Characteristics


Models	D <sup>(1)</sup>	D1	b1	b2	b3	b4	d
VAF 111 40	40	43	32.5	12	52	4	G1/8"-M
VAF 111 50	50	54	32.5	12	52	4	G1/4"-M
VAF 111 63	63	68	32.5	12	52	4	G1/4"-M

(1) Flush-mounting diameter.  
All dimensions shown in (mm)

### Specifications

Damping	By silicone movement - Patented
Ring	Chrome
Measuring	Bourdon tube in CuSn
Precision	cl.2.5 (± 2.5% of max. scale value)
Housing	Black ABS
Temperature	32 to 140°F
Flush-mounting	Ring included in the delivery
Option	as per quantity, possibility of customized dial.

### Dimensions



For all orders, please specify:  
Model + Version.  
Example: VAF11150

1: Model	2: Version
VAF 111	40 Ø 40 mm
	50 Ø 50 mm
	63 Ø 63 mm







# Peripheral Devices

## Chapter 12

**NVS**  
**NVR**  
**NVA**



### Vacuum Feeders

- Vacuum feeders, 1 input, 4 to 8 outputs
- NVS: Screwed feeder fittings
- NVR: Push fitting feeder fittings
- NVA: Threaded aluminum feeder
- Facilitates optimum vacuum management by improved distribution
- Eliminates air pressure loss
- Simplifies connection
- Less time-consuming installation
- Compact and lightweight

**P** 12/2

**RDV**  
**RCOV**  
**Y**



### Screwed Vacuum Fittings with O-ring

- RDV, RCOV and RY series: Straight, adjustable elbow or Y fitting
- Diameter options: 5/8, and 6/8, 7/10, 8/10, 1 0/12
- Gas fittings options: 1/2", 1/4", 1/8", 3/8"
- 100% vacuum-tight
- Integrated O-ring
- Improved circuit sealing
- Can be removed and reinstalled without requiring preparation of the tubing

**P** 12/3

**RVM**  
**RVF**  
**RVT**  
**TVR**  
**COV**



### Fittings, Vacuum Tubes, Collars

- Rigid tubes allow a vacuum network to be installed with no pressure loss
- Barbed fittings guarantee a rigid connection between the source and the vacuum tube
- Collars used on TVR type pipes to guarantee network sealing

**P** 12/4

**REV 38**



### Vacuum Regulator

- Adjustment precision: 3.4 mbar
- Materials used in the VITON body and lacquered aluminum foundry
- Adjustment by threaded pin
- G3/8" fitting attachment bracket
- Direct connection to a vacuum pump
- Very fine adjustment

**P** 12/5

**AG**



### Vacuum Valves, 3 channels

- Connection to the vacuum network
- Electric control
- Voltage: 12 VDC, 24 VDC or VAC, 110 VAC, 220 VAC
- NO or NC for the vacuum or compressed air supplied servo
- Facilitates vacuum or compressed air network management
- NO or NC option allows adaptation to suit the application

**P** 12/6

**PA**



### Angular Jaw Clamps

- Adjustment of finger speed with compressed air regulator
- 3 models
- For use on all types of manipulators
- Recommended for injection press unloading robots for parts or sprue

**P** 12/7



# NVS, NVR, NVA

## Vacuum Feeders




The NVS and NVR series vacuum feeders enable distribution of the vacuum in 4 to 8 channels by a simple unit. The 8/10 inputs and 4 or 8 6/8 outputs eliminate pressure loss.

### Characteristics

		Screwed vacuum fittings		Push fittings		Threaded
Models		NVS 4	NVS 8	NVR 4	NVR 8	NVA 4
Material	Body	PA 6.6 – 30 % fiber glass, black, ULVO94				Aluminium 2014 A
	fitting	Nickel-plated brass		PA		
For tube		calibrated polyamide or polyurethane (PUR)				4 x G1/4"-F and 1 x G3/8"-F
Vacuum		■ ++	■ ++	■	■	
Pressure (up to 10 bar max.)		-	-	■	■	■


■ ++ Recommended for vacuum networks with regulation

**NVS 4**




Input for Ø 8 x 10 calibrated tube

**NVS 8**



Input for Ø 8 x 10 calibrated tube




4x outputs for Ø 6 x 8 calibrated tube



8x outputs for Ø 6 x 8 calibrated tube





**NVR 4**



Input for Ø 8 x 10 calibrated tube


**NVR 8**




4x outputs for Ø 6 x 8 calibrated tube



8x outputs for Ø 6 x 8 calibrated tube



**NVA 4**



2 clearance holes for CHC M4 screws

4 x G1/4"-F



For all orders, please specify:  
Model + Type + Number of outlets  
e.g.: NVS8

1: Model	2: Type	3: Number of outlets
NV	S screwed fittings	4 4 outputs - 1 input
	R push fittings	8 8 outputs - 1 input
	A threaded	4 4 outputs - 1 input

Note: All dimensions are in mm

Note: for NVA series, one reference only: NVA4



# RDV, RCOV, Y

## Screwed Vacuum Fittings with O-ring



### Characteristics


Range of special vacuum-tight fittings, fitted with O-ring (blue).

- 100% vacuum-tight and improved circuit sealing
- Can be removed and reinstalled without requiring preparation of the tubing
- Adjustable fittings for improved vacuum distribution
- Material: nickel-plated brass

### RDV Series Straight Fitting

Ref.	ØA	F	CH	CH1	P	L
RDV1868	6/8*	G1/8"-M	14	14	6	26
RDV1468	6/8*	G1/4"-M	17	14	8	29
RDV14810	8/10	G1/4"-M	17	16	9	30.5
RDV3868	6/8*	G3/8"-M	19	14	9	30.5
RDV38810	8/10	G3/8"-M	19	16	9	32
RDV38812	8/12	G3/8"-M	19	19	9	32.3
RDV12810	8/10	G1/2"-M	24	16	10	33.5
RDV381012	10/12	G3/8"-M	19	19	9	32.3
RDV12812	8/12	G1/2"-M	24	19	10	34.5
RDV121012	10/12	G1/2"-M	24	19	10	34


\* 6/8 fittings are 5.5/8 compatible.



### RCOV Series Elbow Fitting

Ref.	ØA	F	CH	CH1	CH2	P	L	L1
RCOV1868	6/8*	G1/8"-M	10	14	14	7	24	22
RCOV1468	6/8*	G1/4"-M	13	14	17	9	28.5	27.5
RCOV14810	8/10	G1/4"-M	13	16	17	9	28.5	28
RCOV3868	6/8	G3/8"-M	13	14	22	9	29	27.5
RCOV38810	8/10	G3/8"-M	13	16	22	9	29	28
RCOV12810	8/10	G1/2"-M	17	16	26	10	35	34
RCOV121012	10/12	G1/2"-M	17	19	26	10	35	34

\* 6/8 fittings are 5.5/8 compatible.



### Y Fitting, Y Series

Ref.	ØE	ØS
Y68	6/8*	6/8*
Y810	8/10	8/10
Y81068	8/10	6/8
Y812	8/12	8/12
Y81268	8/12	6/8
Y1012	10/12	10/12
Y1012810	10/12	8/10

\* 6/8 fittings are 5.5/8 compatible.



Note: All dimensions are in mm



# RVM, RVF, RVT, TVR, COV

## Fittings, Vacuum Tubes, Collars


### Fittings RVM, RVF, RVT

Barbed fittings used to connect the vacuum source to the vacuum tube to guarantee a rigid connection.


Material: **brass**

Models	D	D1	D2	d*
RVM 1014	G1/4"-M	-	-	10
RVM 1038	G3/8"-M	-	-	10
RVM 1538	G3/8"-M	-	-	15
RVM 1512	G1/2"-M	-	-	15
RVM 2012	G1/2"-M	-	-	20
RVM 2034	G3/4"-M	-	-	20
RVF 1038	G3/8"-F	-	-	10
RVF 1512	G1/2"-F	-	-	15
RVF 2034	G3/4"-F	-	-	20
RVT 1012	-	G1/2"-F	G3/8"-M	10
RVT 1534	-	G3/4"-F	G1/2"-M	15


(\*) Inside diameter of the suitable pipe



RVM



RVF



RVT

### Vacuum Tubes TVR


Thanks to their rigid design and steel coil, they ensure there is no pressure loss on the vacuum network.

Colour: **Crystal**

Models	inside Ø	outside Ø	r*
TVR 10	10	16	18
TVR 15	15.5	22.5	30
TVR 20	19.5	27.5	37

\*r: minimum curve fitting

TVR vacuum tubes hold a 90% vacuum with an ambient temperature of 86°F.



### Collars COV

Accessory to be used for attaching TVR type pipes to guarantee perfect sealing.

Material: **stainless steel**

Models	Tube réf.	L
COV 10	TVR 10	7
COV 15	TVR 15	7
COV 20	TVR 20	7

Other dimensions and shapes on request.



Note: All dimensions are in mm



# REV 38

## Vacuum Regulator



When connected to an electric vacuum pump, the REV series vacuum regulator ensures a precise, stable vacuum. The user can obtain very fine adjustment thanks to the adjustment knob.

### Characteristics

- Vacuum supply (Max): -1013 mbar
- Adjustment precision: 3.4 mbar
- Through flow: 3 SCFM to -846 mbar
- Operating temperature : 40 to 194°F

### Specifications


Adjustment	By threaded pin
------------	-----------------

Material:


Body: **Aluminum**

Internal system: **brass, zinc-plated steel**

Elastomer: **Nitrile**



### Dimensions



REV 38

12




For all orders, please specify: REV 38







NC vacuum supplied servo  
3: Exhaust  
2: Use  
1: Pump




NC C.A. supplied servo  
3: Exhaust  
2: Use  
1: Pump



NO vacuum supplied servo  
3: Exhaust  
2: Use  
1: Pump





NO C.A. supplied servo  
3: Exhaust  
2: Use  
1: Pump



### Characteristics and Dimensions

Ref. NO C.A. servo	Ref. NC C.A. servo	Ref. NO Vacuum servo	Ref. NC Vacuum servo	Ø R	Diagram	A	B	C	D	E	F	G	H	I	J	K	L	Ø M	Ø N
AG 3002	AG 3001	-	-	G1/8"-F	1	102	48.5	16	5.3	-	15.8	36	28	25	7	17.5	-	M5-F	4.5
AG 3010	AG 3009	AG 3211	AG 3210	G1/4"-F	1	140.5	74	36	24.5	23	35.5	59	40	32	24	22.5	-	G1/8"-F	4.5
AG 3012	AG 3011	AG 3215	AG 3214	G3/8"-F	1	140.5	74	36	24.5	23	35.5	59	40	32	24	22.5	-	G1/8"-F	4.5
AG 3021	AG 3020	AG 3223	AG 3222	G1/2"-F	2	154	100	78.5	75	63	54.5	21	30	50.5	35	41	47	G1/8"-F	6.4
AG 3041	AG 3040	AG 3233	AG 3232	G3/4"-F	2	154	100	78.5	75	63	54.5	21	30	50.5	35	41	47	G1/8"-F	6.4
AG 3051	AG 3050	AG 3243	AG 3242	G1"-F	2	175	115	101	89	76	62.5	25.5	38	64	40	51	55	G1/8"-F	8.4
AG 3063	AG 3062	AG 3257	AG 3256	G1"1/2"-F	2	245.5	150	158	138	113.5	113	34	68	96	59	68	85	G1/8"-F	11



### Specifications

Fluid	Non-lubricated 50 micron filtered air. If lubrication is used it must be uninterrupted		
Maximum vacuum	97 %		
Operating temperature	-4 to 104 °F		
Fluid temperature	max 104 °F		
Dynamic seal	polyurethane		
Static seal	NBR		
Coil power	11 VA	10 VA	
Voltage	12 VDC / 24 VDC	24 VAC / 110 VAC / 220 VAC	
Minimum vacuum for vacuum supplied servo	20 %	-	

### Flow Rate

Fitting	G1/8"	G1/4"	G3/8"	G1/2"	G3/4"	G1"	G1"1/2"
Nominal diameter [mm]	5.5	8	10	15	19	25	39
Flow rate [m³/h]	1.5	4	10	20	35	90	180
Response time (activation) <sup>(1)</sup>	15	18	18	20	20	20	60
Response time (deactivation) <sup>(1)</sup>	25	28	28	40	40	45	40
Minimum control pressure (bar) for C.A. servo	1.5	2.5	2.5	3	3	3	4

(1) with monostable electrical control

Note: All dimensions are in mm

### Voltage code

Code	E1	E2	E3	E4	E5	E6	E7
Voltage	24 VDC	220 VAC	24 VAC	110 VAC	48 VAC	24 VDC NO	12 VDC



For all orders, please specify:  
Model + Voltage  
e.g.: AG3215E1





The PA series angular jaw clamps are used in robotics and the plastics industry and more generally on all types of manipulators. They are particularly recommended for use on injection press unloading robots.

Choose a clamp with a theoretical force  $F_{\text{Coval}}$  to at least twice the effective force required.

The clamping forces in the table above are theoretical forces and are given for a pressure of 6 bar. Gripping force is inversely proportional to the distance between the gripping point and the fulcrum. For example, for a PA 20 clamp with the gripping point 25mm from the fulcrum, the clamping force will be:

$$F = 10.1 \text{ (table below)} \times 15/25 = 6.06 \text{ kg.}$$

The weight of the objects to be handled is added to that of the clamp and must not exceed 1/20th of the force exerted on the gripping point.

The opening and closing speed of the fingers can be adjusted with the compressed air regulator.

- **DE:** double action clamp using compressed air.
- **SEF:** closure by compressed air, opening by return spring (simple closing effect).
- **SEO:** opening by compressed air, closure by return spring (simple opening effect).

### Characteristics

Models	Clamping force(kg)	Min. pressure (bar)	Weight (g)	Magnetic sensor option
PA 16 SEF	4	2.5	120	-
PA 16 SEO	5.2	2.5	120	-
PA 16 DE <sup>(1)</sup>	5.5 to 6.5	1.5	120	-
PA 20 SEF	7.5	2	190	yes
PA 20 SEO	8.5	2	190	yes
PA 20 DE <sup>(1)</sup>	10.1 to 12.2	1.2	190	yes
PA 32 SEF	16.5	1.8	490	yes
PA 32 SEO	19.5	1.8	490	yes
PA 32 DE <sup>(1)</sup>	22 to 24	1	490	yes
PA 50 DE <sup>(1)</sup>	52 to 60	0.8	1660	yes

(1) The clamping force above is given in bar at a distance of 15 mm from the fulcrum for models PA 16 - 20 - 32 and 30 mm from the fulcrum for models PA 50.

### Specifications

Compressed air	Filtered, lubricated or non-lubricated
Maximum pressure	10 bar
Material	Anodized aluminum
Seal	Nitrile (NBR)
Heat treatment	On and fingers
Operating temperature	14 to 158 °F



For all orders, please specify:  
**Model + Action + Magnetic sensor**  
 e.g.: PA20SEOM

1: Model	2: Actions	3: Magnetic sensors
PA 16 to PA 50	SEF Simple closing effect SEO Simple opening effect DE Double action	- Without M For PA 20 - 32 - 50







# Gripping Solutions

## Chapter 13

### MVG



#### Modular Vacuum Grippers

- Custom sizing from 150x150 to 1200x1000 mm
- Ultra-light
- Configurable gripping interface (foam, suction cups, COVAL-flex)
- Multi-zone
- Thanks to their high degree of modularity, The MVGs vacuum grippers provide the optimal handling solution for products of varied sizes, shapes and weight,
- Staggered or multiple grip/release
- External or independant vacuum generation
- Adaptation to all activity field

P 13/2

### CVG



#### Customized Vacuum Grippers

- 3 standard lengths (424, 624, 824 mm)
- light and compact
- Configurable gripping interface (foam or suction cups)
- Configurable following applications
- Random Gripping of various products
- Vacuum generators integrated or separated
- Adaptable to all activity sectors

P 13/10

### CSGS



#### Bags/sacks Gripping System


- 2 suction cups sizes are available
- 2 lifting capacity: 35 and 60 kgs
- 4 suction power
- Robust and compact
- The CSGS is a complete assembly, suction cup + vacuum pump, for paper or plastic sacks handling of 25 to 60 kgs load
- Quick and economical installation

P 13/18




COVAL's MVG series vacuum grippers correspond perfectly to the expectations of integrators and users: thanks to their high degree of modularity, they provide the optimal handling solution for products of varied sizes, shapes and weights.

With a single MVG gripper, easily integrated into the process, the user can carry out single or multiple grips of diverse products, both simply and safely.



Industry-specific



### Standard Customization

The modular design, in standard variations, of the MVG series vacuum grippers gives it a high degree of flexibility with regards to format, gripping interface and vacuum pump, to respond perfectly to application requirements.

Furthermore, to optimize production cycles and palletization planning, MVG grippers can be equipped with several independent gripping zones (multi-zone), ensuring multiple or staggered gripping/release points.

### Advantages

- Customized formats
- Compact and lightweight
- Adaptation to products
- Multi-zone
- Adaptation to installation
- Simple to install and use
- Readily available
- COVAL service



More information



### Applications

MVG series vacuum grippers offer a unique solution for handling products in different industrial sectors:

- Packaging
- Plastics
- Metal
- Glass
- Concrete/stone
- Carbon
- Wood




COVAL-flex



# MVG

## Modular Vacuum Grippers

### General Information



#### Customized Modular Grippers



##### Custom sizing

From (150x150) to (1200x1000) mm




##### Ultra-light

Reduced payload weight



##### Configurable gripping interface

depending on the products to be handled







#### Multi-zone

MVG vacuum grippers can create independent gripping zones, guaranteeing optimization of vacuum management (increased vacuum level, reduced leaks and energy consumption).

- Staggered grip/release points.
- Management of formats to be handled.
- Pallet Layer Optimization.
- Simple or multiple grip/release points.

Examples of configuration:




MVG

13



## Modular Vacuum Grippers Integrated Technologies



With MVG, COVAL gives you a choice of 3 complementary gripping interface technologies: vacuum grippers with foam, suction cup grippers and grippers with our new "COVAL-Flex" interface.

In order to optimize the performance of the MVG series for different applications, the vacuum grippers are available in different gripping patterns, hole diameters, and cup sizes.

→ A broad range which meets all application requirements.

### Choice of Gripping Interface

#### "FOAM" interface


- Handling of rigid products
- Gripping textured or uneven surfaces
- 2 standard hole diameters (Ø 12 and Ø 16 mm)
- 2 standard hole patterns

#### "SUCTION CUP" interface

- Handling of flexible products
- Wide range of options
- 3 types of standard suction cups (Ø 14, Ø 25 and Ø 33 mm)
- 3 standard cup patterns

#### "COVAL-FLEX" interface

- Handling of aluminum cans, canned food, glass containers...
- Flexible interface, extremely tear-resistant
- 2 thicknesses available: 3 and 6 mm
- Hole pattern dependent upon application requirements, completely customizable



**COVAL-flex**

### Standard Hole/Cup Patterns

#### "MINI" type interfaces



- Reduced hole spacing, allowing small, flexible pieces to be gripped
- The multitude of gripping points guarantee a strong grip, even with random positioning of products
- Sizes, see page 13/7.

#### "MEDIUM" type interfaces

- Intermediary gripping point distribution between the mini and maxi interfaces
- Ideal for handling dense loads, where gripping surfaces are reduced
- Sizes, see page 13/7.

#### "MAXI" type interfaces

- Large gripping point surfaces, allowing heavy loads to be gripped
- Ideal for gripping products with rigid gripping surfaces
- Sizes, see page 13/7.




### Flow Management

#### Flow control nozzles

This technology enables calibration of vacuum leakage, and is easily customizable by COVAL. The controlled flow will ensure maximum gripping potential through reduced leakage in the system.

This system guarantees the requisite vacuum level necessary to grip the piece.






# MVG

## Modular Vacuum Grippers

### Integrated Technologies



#### Vacuum Generation



##### Integrated vacuum generator, CMSMVG Series

Integration of a multi-stage vacuum generator on the MVG gripper provides a comprehensive and compact gripping solution, as well as easy integration in your process.

Options: integration of a vacuum and/or blow-off solenoid control valve with M12 connector and a vacuum level display (electronic vacuum switch display or vacuum gauge).

##### Advantages

- A comprehensive solution
- 3 standard sizes
- Option: vacuum and/or blow-off control valve
- Option: visual display of vacuum level




##### External vacuum generator

MVG vacuum grippers can be used with an external vacuum pump. Depending on the application, an independent generator is necessary (a regenerative blower, an electric vacuum pump or a pneumatic generator – see page 9/2). This version of the MVG series is equipped with a G1"-F interface enabling the vacuum source to be easily connected.

Option: integration of a vacuum level display (vacuum switch or vacuum gauge).

##### Advantages:

- Reduced weight
- Adaptation to user environment
- Option: visual display of vacuum level




Integrated generator	Model	Con- sumption (SCFM)	Flow rate (SCFM)	Max. vacuum (%)	Sound level (dBA)
<b>CMSMVG 50</b>	MVG ...E1...	6.71	31.78	85	65
<b>CMSMVG 100</b>	MVG ...E2...	13.42	63.57	85	65
<b>2xCMSMVG 100</b>	MVG ...E3...	26.84	127.13	85	65



#### VACUUM GENERATION AND MULTI-ZONE

COVAL's Multi-zone technology provides independently defined vacuum zones on the same gripper. For this reason, each zone has a separate vacuum pump, either integrated or external.

As each multi-zone application is different, we will work with you to determine the best configuration for your process.




Example:  
MVG gripper,  
860 x 635 mm, with  
2 independent zones,  
each with a vacuum pump  
and vacuum level display.



# MVG

## Modular Vacuum Grippers

### Control and Visualization




#### Vacuum Pump Control

When necessary, the MVG vacuum grippers can be equipped with a vacuum control valve and/or blowoff to optimize product release. This also enables cleaning of the vacuum network and flow restricting nozzles.

A vacuum switch or analog gauge is available as an option for those requiring a visual display of the vacuum level in the system.


#### IMPLEMENTATION



#### ■ Option S - NC vacuum control, with controlled blow-off:

MVG\_X\_\_S\_


- 2 control signals.
- NC vacuum control valve.
- Blow-off controlled by external signal (NC control valve).



#### ■ Option V - NO vacuum control, with controlled blow-off:

MVG\_X\_\_V\_



- 2 control signals.
- NO vacuum control valve.
- Blow-off controlled by external signal (NC control valve).



#### ELECTRICAL CONTROL

- Control voltage: 24VDC (regulated) +/- 10 %.
- Current draw: 30 mA (0.7 W) vacuum or blow-off.
- Maximum usage frequency: 2 Hz.
- Number of operations: 10 million cycles.

#### ELECTRICAL M12 CONNECTIONS



#### Visualization of Vacuum Level

When required, MVG series grippers can incorporate a vacuum level display with an electronic vacuum switch or vacuum gauge :

#### ■ Option VA - electronic vacuum switch with 3-color display (PSD100CPNP):

MVG\_X\_\_VA

- Pressure rating range: 0.0 ~ -101.3 kPa.
- Pressure setting range: 10.0 ~ -101.3 kPa.
- Max. pressure: 300 kPa.
- Fluid: Air, non-corrosive/non-flammable gas.
- Hysteresis: adjustable.
- Response time: ≤ 2.5ms, with anti-vibration function.
- 7 segment LCD display : 2 color (red/green) main display, orange sub-display (refresh rate: 5 times/1sec.)
- Choice of pressure unit display: kPa, MPa, kgf/cm<sup>2</sup>, bar, psi, InHg, mmHg.
- Power supply voltage: 12 to 24 V DC ±10%.
- Current consumption: ≤ 40mA (without load).
- Repeatability (switch output): ≤ ±0.2% F.S. ±1 digit.
- Electrical connection: M8 (4-pin).
- Protection: IP40.
- Ambient temperature range: 32 to 122°F (operation).
- Material (enclosure): PA 6.6 20%GF.




#### ■ Option VF - vacuum gauge


(VAF11140):

MVG\_X\_\_VF

- Vacuum gauge with needle.
- Damping: by silicone movement (patented).
- Measuring: Bourdon tube in CuSn.
- Precision: cl. 2.5 (+/- 2.5% of max. scale value).
- Frame: black ABS









#### MVG Series with Suction Cup Gripping Interface


"mini" type suction cup interface



"medium" type suction cup interface




"maxi" type suction cup interface




#### MVG Series with Foam Gripping Interface


"mini" type foam interface




"maxi" type foam interface



Mounting rail



MVG Series with CMSMVG pump



#### MVG Series with "COVAL-flex" Gripping Interface

3 mm thick "COVAL-flex" interface




**COVAL-flex**

6 mm thick "COVAL-flex" interface







	MVG	1200	X	1000	D	VSA33JK		E3		S	VA
<div> <div> <b>LENGTH</b>  Overall length (mm):  150 to 1200 mm </div> <div> 150 ... 1200 </div> </div> <div> <div> <b>WIDTH</b>  Overall width (mm):  150 to 1000 mm </div> <div> 150 ... 1000 </div> </div> <div> <b>HOLE/CUP PATTERN LAYOUT</b>  Staggered  <b>Q</b>  Straight*  <b>D</b> </div> <p><small>* Only available for "maxi" type gripping interface with suction cup ø mini 26mm.</small></p>											
<div> <b>VACUUM GENERATOR</b>  Without vacuum generator <b>G0</b>  1 x CMSMVG 50 <b>E1</b>  1 x CMSMVG 100 <b>E2</b>  2 x CMSMVG 100 <b>E3</b> </div> <div> <b>VACUUM GENERATOR CONTROL</b>  Without control <b>N</b>  <b>S</b>  <b>V</b> </div>											
<b>GRIPPING INTERFACES</b>											
<div> <b>SUCTION CUP GRIPPING INTERFACE</b>  <div> <b>"mini" type interface:</b>  2.5 bellows suction cups ø 14 mm in silicone 30 Shore with flow control nozzles. </div> <div> <b>"medium" type interface:</b>  1.5 bellows suction cups ø 25 mm in natural rubber with flow control nozzles. </div> <div> <b>"maxi" type interface:</b>  1.5 bellows suction cups ø 33 mm in natural rubber with flow control nozzles. </div> <div> See "COVAL CUSTOMIZATION". </div> </div> <div> <b>VSP14BF</b>  <b>VSA25JI</b>  <b>VSA33JK</b>  ... </div>											
<div> <b>FOAM GRIPPING INTERFACE</b>  <div> Foam "mini" type interface, EPDM. </div> <div> Foam "maxi" type interface, EPDM. </div> </div> <div> <b>FS</b>  <b>FB</b> </div>											
<div> <b>"COVAL-flex" GRIPPING INTERFACE</b>  <b>COVAL-flex</b>  "COVAL-FLEX" gripping interfaces are designed to respond to specific applications. They will be recommended and specified by our sales department if your application can benefit from their special features. </div>											
<div> <b>VACUUM LEVEL DISPLAY</b>  Without display <b>VO</b>  <b>VA</b>  <b>VF</b> </div>											



## Modular Vacuum Grippers

### Examples of Part Numbers & Specifications

#### Examples of Composed Part Numbers

##### MVG200X200QFSGO



MVG vacuum gripper, 200 x 200 mm, staggered rows, "mini" EPDM type foam gripping interface, without integrated vacuum pump.

##### MVG400X200DVSA25JIE2SV0

MVG vacuum gripper, 400 x 200 mm, straight rows, "medium" type gripping interface, 1.5 bellows suction cups Ø 25 mm in natural rubber with flow control nozzles, 1 CMSMVG100 vacuum pump, with NF control and NF blow-off, without vacuum level display.

##### MVG1200X1000DVSA33JKGONVA

MVG vacuum gripper, 1200 x 1000 mm, straight rows, "maxi" type gripping interface, 1.5 bellows suction cups Ø 33 mm in natural rubber with flow control nozzles, without vacuum pump, with visual display by electronic vacuum switch.



#### General Characteristics

- Compressed air supply for MVG vacuum grippers with generator CMSMVG:
  - 5µ filtered, non-lubricated air relevant to standard ISO 8573-1:2010 [4:5:4].
  - 1 supply for generator type E1 and E2 (1/4 G pressure connection).
  - 2 supplies for generator type E3 (1/4 G pressure connection).
  - Optimal working pressure: 6 bar (maximum pressure 8 bar).
- Blow-off: network supply pressure.
- Protection of the valve: IP 65.
- Temperature: 50 to 140°F.
- Material of the gripper: aluminium, PA 6.6 15% GF, brass, stainless steel, neoprene.
- Material of the valve: PA 6.6 15% GF, POM, PC 15% GF, brass, aluminium, NBR.
- Foam gripping interface material: EPDM.
- Suction cup gripping interface materials:
  - "mini" type interface: silicone 30 Shore.
  - "medium" or "maxi" type interfaces: natural rubber 50 Shore.


#### COVAL CUSTOMIZATION



Sometimes, there are instances where the standard MVG configurations available here will not match your application requirements.



COVAL can provide customized solutions, based on your operating specifications, integrating specific functions (e.g. multi-zoning) or by suggesting a gripping interface based on the COVAL range of suction cups (a wide choice of shapes, diameters and materials) to efficiently meet all your requirements.





With the CVG series, COVAL introduces the universal solution of the vacuum gripper: flexible, simple and economic.

The handling of parts with different sizes, shapes and weights is not a complex, expensive and laborious task anymore.

With a single CVG module, easily integrated into the process, the user can make random gripping of different parts in a simple and secure way.

#### Advantages

The CVG series are fitted with standard sub-units which allow offering a customized solution and fit to the applications and requirements of the integrators and users:

- Compact
- Lightweight
- Integrated functions
- Modularity
- Performance
- Ease of use
- Universal mounting
- ...


#### A Complete System

- 1 light and robust aluminium profile
- 1 universal mounting system
- 3 standard lengths (424, 624, 824mm)
- 3 generator sizes
- 2 plate technologies (foam or suction cups)
- 3 gripping point distributions (mini, medium or maxi)
- 2 flow rate control technologies (check valves or flow resistors)
- 2 control versions (vacuum and blow-off)
- 2 solutions for vacuum monitoring



+ The Vacuum Manager experience of COVAL

= YOUR CVG SOLUTION

More  
information




Industry-specific



Foam plate  
"mini" type



Foam plate  
"maxi" type



"suction cup" plate  
"mini" type



"suction cup" plate  
"medium" type



"suction cup" plate  
"maxi" type

#### Applications


The CVG series vacuum grippers offer a single solution for the handling of products in different industrial sectors:

- Packaging.
- Plastics.
- Metal.
- Glass.
- Concrete/stone.
- Carbon.
- Wood...

The adaptability and the flexibility of COVAL vacuum grippers CVG series respond to the multiple robotic applications.







From now on, thanks to the CVG series, COVAL offers 2 complementary technologies for the vacuum handling: the vacuum grippers with foam and the vacuum grippers with cups:

→ A wide range adaptable to all your applications.

#### Technology Regarding the Gripping Plate

The CVG vacuum gripper range offers 2 technologies regarding the gripping plate and meets the requirements of all applications.

##### "FOAM" plate

- Handling of rigid products.
- Gripping on structured and irregular surface conditions.
- Flow resistor or check valve.
- 2 diameters (ø 12 and 16mm) and 2 gripping point distributions.
- 3 standard lengths (424, 624 and 824mm).



##### "SUCTION CUP" plate

- Handling of flexible or deformable products.
- Wide range of variants.
- Flow resistor (different diameters).
- 3 types of suction pads for standard models (Ø 14, Ø 25 and Ø 33mm).
- 3 gripping point distributions.
- 3 standard lengths (424, 624 and 824mm) ... or tailored length.



#### Gripping Point Distribution

In order to optimize the performances of the CVG vacuum grippers according to the applications, spacing and gripping point diameters are optimized for each variant.

##### "MINI" type plate



- Reduced centre distance ensuring the gripping of small parts.
- Multiple gripping points ensuring the gripping even in case of random position of the part.
- Dimensions, refer to page 13/15.

##### "MEDIUM" type plate

- An intermediate distribution of gripping points between the "mini" and "maxi" type of plates.
- Ideal for the handling of dense loads with reduced gripping surface.
- Dimensions, refer to page 13/15.

##### "MAXI" type plate

- Large surface of the gripping points which allows the gripping of heavy loads.
- Ideal for the gripping of parts with rigid gripping surface.
- Dimensions, refer to page 13/15.



#### Gripping Force of the Vacuum Grippers

Part number	Total length of the vacuum gripper (mm)	Force at 85% vacuum (lbf)*	Force at 45% vacuum (lbf)*
CVG 424	424	247.3	134.9
CVG 624	624	370.9	202.3
CVG 824	824	494.6	269.8

\* Indicative force for a vacuum gripper covered at 100% by the load, without safety factor, on rigid and airtight surface.






#### Flow Rate Control Technologies

##### Flow resistors

This simple and energy saving technology, available for the two types of gripping plates, allows calibrating precisely the vacuum leakage.


It is easily adaptable by COVAL, thanks to a precise sizing according to the application. This system ensures the required vacuum level for the part gripping.



##### Check valves (Coval patent)

This technology (only available on the "foam" plates) ensures an instant gripping thanks to a high suction flow rate. The valves transfer the suction flow rate only when the part to handle is present and close automatically if the part is absent.

This system ensures an optimal gripping. It is therefore ideal for applications with short and dynamic cycles.



#### Vacuum Generation



##### Integrated vacuum generator, CMSE Series

Integration of a multi-stage vacuum generator on the CVG gripper provides a comprehensive and compact gripping solution, as well as easy integration in your process.

Options: integration of a vacuum and/or blow-off solenoid control valve with M12 connector and a vacuum level display (electronic vacuum switch display or vacuum gauge).

##### Advantages:

- A comprehensive solution
- 3 standard sizes
- Option: vacuum and/or blow-off control valve
- Option: visual display of vacuum level





##### External vacuum generator

The CVG vacuum grippers may also be used with an independent vacuum generator. According to the application, an external generator may be necessary (a blower, an electrical vacuum pump or a pneumatic generator, see page 9/2). The CVG series vacuum gripper G0 version is fitted with a G3/4"-F flange allowing the simple connection of the vacuum source.

Option: integration of a vacuum level display (vacuum switch or vacuum gauge).

##### Advantages:

- Reduced weight
- Adaptation to user environment
- Option: visual display of vacuum level



#### Technical data of the CMSE series integrated vacuum generators

Integrated vacuum generator	Model	Consumption (SCFM)	Flow rate (SCFM)	Max. vacuum (%)	Sound level (dBA)
CMSE 50	CVG _____ E1	6.71	31.78	85	65
CMSE 100	CVG _____ E2	13.42	63.57	85	65
2xCMSE 100	CVG _____ E3	26.84	127.13	85	65

#### Configuration generators/vacuum gripper length

Vacuum generator	CVG 424	CVG 624	CVG 824
	Possible config.	Possible config.	Possible config.
G0	■	■	■
E1	■	■	■
E2	■	■	■
E3	■	■	■






#### Vacuum Generator Control

According to the need, the CVG series vacuum grippers may be fitted with a vacuum and/or blow-off control valve in order to optimize the release of the gripped parts and to ensure the cleaning of the network, the flow resistors or check valves. They may also have a built-in vacuum level monitoring thanks to the options: vacuum gauge or vacuum switch (see below).


#### IMPLEMENTATION



#### ■ Option S - NC vacuum control, with controlled blow-off:

MVG\_X\_\_S\_


- 2 control signals.
- NC vacuum control valve.
- Blow-off controlled by external signal (NC control valve).



#### ■ Option V - NO vacuum control, with controlled blow-off:

MVG\_X\_\_V\_



- 2 control signals.
- NO vacuum control valve.
- Blow-off controlled by external signal (NC control valve).



#### ELECTRICAL CONTROL

- Control voltage: 24VDC (regulated) +/- 10 %.
- Current draw: 30 mA (0.7 W) vacuum or blow-off.
- Maximum usage frequency: 2Hz.
- Number of operations: 10 million cycles.


#### ELECTRICAL M12 CONNECTION




#### Vacuum Level Display

##### ■ CVG\_\_\_\_\_VA Display type electronic vacuum switch


- Adjusting range: 0 ~ -1.00 bar
- Hysteresis: adjustable
- Maximum overpressure: 3 bar.
- Repeatability: +/-1% of the range.
- Output thresholds: 2 x NO/NF.
- Switching capacity: 125mA transistor PNP.
- Threshold state display: 2 x leds.
- Display unit: bar.
- Electrical connection: M8 (4 pins).
- Power supply: 18 to 24 V DC (regulated).
- Current draw: < 60 mA.
- Protection: IP 40.
- Frame material: PA 6.6 20 % GF.



Mounting of the VA vacuum switch option for a gripper without vacuum generator (G0), or having a minimum space of 125mm depending on the length of the gripper and the choice of the vacuum generator.




Mounting of the VA vacuum switch option for a gripper with vacuum generator (version E1, E2 or E3) and not having sufficient space for the horizontal mounting.



##### ■ CVG\_\_\_\_\_VF Vacuum gauge

- Vacuum gauge with needle.
- Damping: by silicone movement (patented).
- Measuring: Bourdon tube in CuSn.
- Precision: cl. 2.5 (+/- 2.5% of max. scale value).
- Frame: black ABS





#### Dimensions and Connections



	CVG424	CVG624	CVG824
A	424	624	824
B	384	584	784

in mm

#### G0 Versions

(with independent vacuum source).

The Coval vacuum grippers in series CVG are particularly simple to install and operate. Mounting on all types of automated systems or robots thanks to their universal fixing by 4 rectangular nuts sliding in the groove of the aluminum profile (fixation by 4 M8 screws). These nuts are fitted with a spring plate to allow keeping them in position during unscrewing.





#### E1 or E2 Versions

(1 integrated vacuum generator, CMSE series).




The CVG series COVAL vacuum grippers versions E1 and E2 are mounted on all types of automated systems or robots thanks to the 4 x M8 spacers on the groove of the aluminum profile (mounting by 4 x M8 screws).

For the CVG series vacuum grippers version E3, there are 6 x M8 spacers which can be adjusted as per the requirement.




#### E3 Versions

(2 integrated vacuum generators, CMSE series).




G1/4"-F  
blow-off connection G1/8"-F  
vacuum switch connection  
G1/8"-F






## Customized Vacuum Grippers Plates and Technical Data



### CVG Series with Foam Plate




### NUMBER OF GRIPPING APERTURES PER PLATE


	CVG 424	CVG 624	CVG 824
"mini" type plate aperture Ø 12 mm	98	128	198
"maxi" type plate aperture Ø 16 mm	50	75	100

### CVG Series with Suction Cup Plate


#### "Mini" type suction cup plate



#### "Medium" type suction cup plate



#### "Maxi" type suction cup plate



### NUMBER OF SUCTION CUPS PER PLATE

	CVG 424	CVG 624	CVG 824
"Mini" type suction cup plate Ø 14 mm (or Ø 16 mm max.)	150	220	297
"Medium" type suction cup plate Ø 25 mm (or Ø 18 to 25 mm)	53	83	113
"Maxi" type suction cup plate Ø 33 mm (or Ø 36 mm max.)	30	42	57


### General Characteristics

- Supply: 5 $\mu$  filtered, non-lubricated air relevant to standard ISO 8573-1:2010 [4:5:4].
- Compressed air supply for CVG vacuum grippers with integrated generator CMSE:
  - 1 supply for generator type E1 and E2.
  - 2 supplies for generator type E3.
 (see drawings page 13/14: 1/4 G pressure connection).
- Optimal working pressure: 6 bar (maximum pressure 8 bar).
- Blow-off: network supply pressure.
- Protection of the valve: IP 65.
- Temperature: 50 to 140°F.
- Material of the gripper: aluminium, PA 6.6 15% GF, brass, stainless steel, neoprene.
- Material of the valve: PA 6.6 15% GF, POM, PC 15% GF, brass, aluminium, NBR.
- Foam material: EPDM.
- Suction cup material:
  - "mini" type plate: silicone 30 Shore.
  - "medium" or "maxi" type plate: natural rubber 50 Shore.






According to the constraints of your application, we can personalize your vacuum gripper with the COVAL standard cup range. A wide range of shapes, diameters and materials allows meeting all your requirements.







**CVG Series with Foam Plate: one complete part number**


 <b>CVG</b>	<b>424</b>	<b>V</b>	<b>S</b>	<b>F</b>	<b>E2</b>	<b>S</b>	<b>VA</b>
<b>GRIPPER LENGTH</b>							
424 mm	<b>424</b>				<b>G0</b>	Without vacuum generator	<b>VO</b>
624 mm	<b>624</b>				<b>E1</b>	1 x CMSE 50	
824 mm	<b>824</b>				<b>E2</b>	1 x CMSE 100	<b>VA</b>
					<b>E3</b>	2 x CMSE 100	
<b>TECHNOLOGY</b>							
Check valves		<b>V</b>					
Flow resistors		<b>H</b>					
<b>GRIPPING SURFACES DIA.</b>							
mini			<b>S</b>				
maxi			<b>B</b>				
<i>Integrated filter on the CVG series vacuum gripper with foam plate.</i>							
<b>VACUUM GENERATOR *</b>							
<b>G0</b>							
<b>E1</b>							
<b>E2</b>							
<b>E3</b>							
<i>* see page 13/12 table of the possible configurations.</i>							
<b>VACUUM GENERATOR CONTROL *</b>							
Without control						<b>N</b>	
						<b>S</b>	
						<b>V</b>	
<i>* only for E1 and E2</i>							
<b>VACUUM LEVEL DISPLAY</b>							
<b>VO</b>							Without
<b>VA</b>							Electronic display type vacuum switch 
<b>VF</b>							Vacuum gauge 

*Integrated filter on the CVG series vacuum gripper with foam plate.*

#### Example of composed part numbers:






**CVG 424 V S F E2 S VA** CVG vacuum gripper, length 424mm, check valve technology, foam plate "mini" type with filter, 1 integrated vacuum generator CMSE 100, NC vacuum and blow-off control, electronic display type vacuum switch.





#### CVG Series with Suction Cup Plate: 2 individual part numbers

#### 1- PART NUMBER OF THE FRAME

 <b>CVG 424 X E2</b>		<b>S</b>	<b>VA</b>
GRIPPER LENGTH			
424 mm	<b>424</b>	<b>N</b>	<b>V0</b>
624 mm	<b>624</b>	<b>S</b>	<b>VA</b>
824 mm	<b>824</b>		<b>VF</b>
...	<b>...</b>		
VACUUM GENERATOR*			
<b>G0</b>	Without vacuum generator		
<b>E1</b>	1 x CMSE 50		
<b>E2</b>	1 x CMSE 100		
<b>E3</b>	2 x CMSE 100		
* see page 13/12 table of the possible configurations. E1/E2 : mini. length of the gripper 280 mm. E3 : mini. length of the gripper 545 mm.			
VACUUM GENERATOR CONTROL *			
Without control			
	NC vacuum control & NC blow-off control		
	NO vacuum control & NC blow-off control		
VACUUM LEVEL DISPLAY			
Without			
Electronic display type vacuum switch			
Vacuum gauge			

\* only for E1 and E2

#### 2- PART NUMBER OF THE SUCTION CUP PLATE

CP		424	VSP14BF
GRIPPER LENGTH			SUCTION CUP AND FLOW RESISTOR MODELS ACCORDING TO THE PLATE
424 mm	424	VSP14BF	"Mini" type plate 2.5 bellows suction cups Ø 14 mm in silicone 30 Shore with flow resistors Ø 0.7 mm
624 mm	624	VSA25JI	"Medium" type plate 1.5 bellows suction cups Ø 25 mm in natural rubber with flow resistors Ø 0.9 mm
824 mm	824	VSA33JK	"Maxi" type plate 1.5 bellows suction cups Ø 33 mm in natural rubber with flow resistors Ø 1.1 mm
...	...	...	Special version ↓

#### Example of composed part numbers:

**CVG 424 X E2 S VA**

+

**CP 424 VSP14BF**

CVG vacuum gripper length 424 mm without plate, with 1 integrated vacuum generator CMSE 100, NC vacuum and blow-off control, electronic display type vacuum switch.

Suction cup plate for vacuum gripper length 424 mm, fitted out with VSP cups Ø 14 mm Si3 and flow resistors Ø 0.7 mm.

#### SPECIAL VERSIONS

Your job may sometimes bring situations of use for which our standard versions are not fully adapted.

COVAL is able to give you a customized reply following your specifications by integrating specific functions or by offering you tailored vacuum grippers (adjustment of length or selection of suction cup type).



The CSGS system is a comprehensive package that includes a specific suction pad and an optimized vacuum generator and guarantees high reliability for handling plastic or paper bags from 25 to 60 kg, used for packing powder and/or granulated products.


It is particularly recommended for robotic palletizing and de-palletizing applications that require a quick and secure implementation.

#### Gripping capacity:



The CSGS...X35 models are equipped with a 250x150 mm suction pad allowing them handle loads of up to 35 kg, depending on the bag's resilience. The CSGS...X60 models are equipped with a 360x190 mm suction pad and can handle loads of up to 60 kg.

#### Advantages

- The CSGS system is designed to support the load handled by the suction pad and thus allows it to be installed directly onto the robot's arm.
- The CSGS system allows for a quick and cost-effective installation: it is fed by a single small-sized compressed air hose, which avoids the complexity of setting up a vacuum network consisting of large pipes and vacuum valves.
- The suction pad features a foam lip that ensures the maximum flexibility required for gripping a variety of product types.
- The specific vacuum generator has been designed to provide high air intake flow rates thus allowing for shorter response times and the handling of porous products.
- It does not include any membrane and has no internal moving parts. It therefore is clog-free and can be installed without requiring any filter on the vacuum network.
- Very low noise level thanks to external silencers.
- No heat emission, vibration-free.



Industry-specific



More information




#### Specifications

<b>Feed pressure</b>	Non-lubricated filtered air 2 to 6 bar
<b>Optimal pressure</b>	4 bar
<b>Weight</b>	From 7 to 8.3 kg, depending on model
<b>Materials</b>	NR, aluminum, CuZn, steel
<b>Temperature</b>	From 50 to 122 °F





#### Characteristics

Model	Air consumed (SCFM)			Maximum vacuum (%)	Air drawn (SCFM)
	4 bar	5 bar	6 bar		
<b>CSGS4X15X35</b>	14.13	16.95	19.78	75	25.43
<b>CSGS4X20X35</b>	25.73	30.51	35.60	75	35.31
<b>CSGS4X25X60</b>	38.14	45.77	53.40	84	50.85
<b>CSGS4X30X60</b>	56.50	67.80	79.10	84	63.57



Please specify model, e.g.: CSGS4X15X35  
Refer to characteristics table above





Model	L	I	A	Silencer
CSGS4X15X35	250	150	229	SILK12C
CSGS4X20X35	250	150	229	SILK12C
CSGS4X25X60	360	190	318	SILK34C
CSGS4X30X60	360	190	390	SILK34C

All dimensions are in mm.







# Alphabetical index

<b>A</b>		
<b>AG</b>		
Vacuum Valves, 3 channels	12/6	
<b>B</b>		
<b>BM</b>		
Foam Strips	4/13	
<b>C</b>		
<b>C</b>		
High-performance Suction Cups	2/55	
<b>CC</b>		
Screw-type Electrical Connectors M8 and M12	10/11	
<b>CD</b>		
Screw-type Electrical Connectors M8 and M12	10/11	
<b>CIL</b>		
In-line Ejectors	6/2	
<b>CMS</b>		
Multi-stage Vacuum Pumps	9/2	
<b>COV</b>		
Collars	12/4	
<b>CSGS</b>		
Bags/sacks Gripping System	13/18	
<b>CSP</b>		
Piloted Safety Valves	4/12	
<b>CVG</b>		
Vacuum Grippers	13/10	
<b>F</b>		
<b>Flow Control Fittings</b>	4/9	
<b>FPC</b>		
FlowPack Suction Cups	3/6	
<b>FSL</b>		
Liquid Separator Vacuum Filters	10/10	
<b>FVG</b>		
Mini Vacuum Filters	10/8	
<b>FVI</b>		
Vacuum Filters	10/5	
<b>FVL 12</b>		
In-line Filter	10/9	
<b>FVL 68</b>		
In-line Vacuum Filter	10/9	
<b>FVUG</b>		
In-line Filters	10/7	
<b>FVUM</b>		
In-line Filters	10/7	
<b>G</b>		
<b>GEMP</b>		
Simple Vacuum Pumps with ASR	7/9	
<b>GVEC</b>		
"Easy Clean" Vacuum Pumps	7/12	
<b>GVMAX</b>		
Self-regulating Vacuum Pumps	8/44	
<b>GVMAX V2-2/V2-2R</b>		
Self-regulating Vacuum Pumps	8/39	
<b>GVP</b>		
Vacuum Pumps	7/3	
<b>GVR 09, 10, 12, 14</b>		
Micro Ejectors	6/8	
<b>GVRL 10</b>		
Ultra Light In-line Ejector for High Speeds	6/10	
<b>I</b>		
<b>IMU</b>		
Axial Ball-joints	4/11	
<b>L</b>		
<b>L</b>		
Mounting Extensions	4/7	
<b>LEM</b>		
Integrated Mini-Vacuum Pumps with "ASR"	8/3	
<b>LEM+</b>		
Compact, High Flow Vacuum Pumps with "ASR"	8/9	
<b>LEMAX</b>		
Integrated Mini Vacuum Pumps with "ASC"	8/15	
<b>LEMAX+</b>		
Compact, High Flow Vacuum Pumps with "ASC"	8/23	
<b>LEMCOM</b>		
1 <sup>st</sup> Mini Vacuum Pump on Industrial Fieldbus	8/29	
<b>LEMP</b>		
Mini-Vacuum Pumps with ASR	7/15	
<b>M</b>		
<b>M--C</b>		
Air Amplifiers	9/4	
<b>MS</b>		
Quick Release Devices	10/4	
<b>MVG</b>		
Modular Vacuum Grippers	13/2	
<b>MVS</b>		
Soft Suction Cups for High Speed Applications	3/9	
<b>N</b>		
<b>NVA</b>		
Vacuum Feeders	12/2	
<b>NVR</b>		
Vacuum Feeders	12/2	
<b>NVS</b>		
Vacuum Feeders	12/2	
<b>P</b>		
<b>PA</b>		
Angular Jaw Clamps	12/7	



# Alphabetical index

<b>PMG2</b>					
Mechanical Feelers		4/10			
<b>PSA 100 C</b>					
Electronic Vacuum Switch with Display		11/4			
<b>PSD 100</b>					
Vacuum Switch with 3-colour Display		11/5			
<b>PSE 100 E</b>					
Electric Vacuum Switch		11/9			
<b>PSE 100 P</b>					
Pneumatic Vacuum Switch		11/10			
<b>PSE 100 PK</b>					
Pneumatic Vacuum Switch		11/11			
<b>PSK</b>					
Mini Vacuum Switch		11/3			
<b>PSP 100</b>					
Electronic Vacuum Switch		11/7			
<b>PSP 100 ANA</b>					
Electronic Vacuum Switch Analogue Output		11/8			
<b>R</b>					
<b>RCOV</b>					
Screwed Vacuum Fittings with O-ring		12/3			
<b>RDV</b>					
Screwed Vacuum Fittings with O-ring		12/3			
<b>REV 38</b>					
Vacuum Regulator		12/5			
<b>RSC</b>					
Multi-Compensator Systems		4/5			
<b>RVF</b>					
Fittings		12/4			
<b>RVM</b>					
Fittings		12/4			
<b>RVT</b>					
Fittings		12/4			
<b>S</b>					
<b>SIL GV</b>					
Diffuser Type Silencer		10/3			
<b>SIL K--C</b>					
Through-type Silencer		10/3			
<b>SPL</b>					
Heavy Load Suction Cups		3/28			
<b>STEEL</b>					
Steel Suction Cups with Bonded Seal		3/29			
<b>T</b>					
<b>TS</b>					
Level Compensators		4/4, 4/5			
<b>TS 11</b>					
Level Compensators		4/3			
<b>TSOG</b>					
Anti-Rotation Level Compensators		4/6			
<b>TSOP</b>					
Anti-Rotation Level Compensators		4/6			
<b>TVM</b>					
Pipes for Air Amplifiers		9/7			
<b>TVR</b>					
Vacuum Tubes		12/4			
<b>V</b>					
<b>VAF 111</b>					
Vacuum Gauge		11/12			
<b>VBO</b>					
Suction Cup for Bottle Handling via the Punt		3/16			
<b>VP</b>					
Flat Suction Cups Ø 8 to 75 mm		2/3			
<b>VPA</b>					
Suction Cups for Paper Applications		3/21			
<b>VPAG</b>					
Rounded Suction Cups		3/26			
<b>VPAL</b>					
Suction Cups for Labels		3/23			
<b>VPF</b>					
Flat Suction Cups with Cleats Ø 15 to 50 mm		2/19			
<b>VPG</b>					
Extra-Flat Suction Cups Ø 2 to 200 mm		2/9			
<b>VPO</b>					
Oblong Flat Suction Cups		2/21			
<b>VPR</b>					
Suction Cups for Mailing Applications		3/25			
<b>VPSC</b>					
Ultra-Flat, Non-Marking Suction Cups		3/5			
<b>VPU</b>					
Flat Suction Cups Ø 6 to 50 mm		2/17			
<b>VPYR</b>					
Radial Ball-joint Suction Cups		3/27			
<b>VR 05, 07, 09</b>					
Heavy-duty In-line Ejectors		6/4			
<b>VR 10, 12, 14</b>					
Ejector Fittings		6/6			
<b>VS</b>					
Suction Cups with 2.5 Bellows Ø 5 to 88 mm		2/43			
<b>VSA</b>					
Suction Cups with 1.5 Bellows Ø 5 to 78 mm		2/25			
<b>VSAB</b>					
Suction Cups with 1.5 Bellows Ø 5 to 50 mm		2/31			
<b>VSAF</b>					
Suction Cup for Cheese		3/11			
<b>VSAG</b>					
Suction Cups with 1.5 Bellows Ø 10 to 150 mm		2/33			
<b>VSAJ</b>					
Suction Cups with 1.5 Bellows Ø 15 to 30 mm		2/39			



# Alphabetical index

---

## **VSAOF**

Oblong Suction Cup for Cheese	3/12
-------------------------------	------

## **VSA-VS BM**

Suction Cups with Foam Ring Seals	2/59
-----------------------------------	------

## **VSBM**

Foam Rings	2/60
------------	------

## **VSBO**

Suction Cups for Bottle Handling	3/17
----------------------------------	------

## **VSBO+**

Suction Cups for Bottle Handling	3/17
----------------------------------	------

## **VSD**

Long Stroke Suction Cups	2/51
--------------------------	------

Suction Cups for Bakery Applications	3/13
--------------------------------------	------

## **VSE**

Suction Cups for Bakery Applications	3/13
--------------------------------------	------

## **VSG**

Suction Cups with 2.5 Bellows Ø 5 and 7 mm	2/49
--	------

## **VSO**

Suction Cups for Egg-handling	3/15
-------------------------------	------

## **VSP**

Suction Cups for Bakery Applications	3/13
--------------------------------------	------

## **Y**


### **Y**

Screwed Vacuum Fittings with O-ring	12/3
-------------------------------------	------










# COVAL

vacuum managers

## COVAL ALL ALONG THE LINE




### VIRTUAL VACUUM APPLICATIONS

Browse on your tablet, a 4.0 manufacturing line in motion. Augmented reality to showcase vacuum gripping solutions, and the Industry of the Future.

This interactive application makes it possible to discover the entirety of a packaging line, from the initial primary packaging to palletizing at the end.

Augmented reality provides total immersion within the line and discovery of all stages of the process, as well as different applications for vacuum gripping.

**COVAL - Virtual Vacuum Applications** is a free application for tablets and smartphones downloadable from the App Store and Google Play.



# Advanced Vacuum Solutions





**COVAL**  
vacuum managers

## A TECHNOLOGICAL PARTNER ON A GLOBAL SCALE

COVAL, *vacuum managers*, develops, produces and markets vacuum components and systems for the automation industry worldwide.

COVAL is an ISO 9001: V2015 certified company, which offers innovative solutions integrating reliable and optimized components with intelligent functions. Our aim is to provide the most personalized and economic solution to a given application, while assuring significant improvement in productivity and safety for vacuum users around the world.

COVAL has an ambition for technical excellence and innovation. As a specialist in vacuum automation, COVAL is reputed for offering reliable, personalized, cost effective and productive solutions.

Our references can be found in several principal industrial sectors (Packaging, Food Industry, Automotive, Plastics, Aeronautics...) where vacuum handling is crucial for efficiency and productivity.


Our mission, is to go beyond the limits of a simple component supplier and assist our clients at each step of our interaction by :

- Organizing specialized training programs for our clients and partners.
- Proposing efficient, economic and reliable solutions.
- Ensuring timely delivery and proper installation of our solutions.

Always listening to our clients, we support the implementation of our solutions through an ongoing and attentive relationship.



**COVAL S.A.S.**  
Head Office



**COVAL INC.**



**COVAL IBERICA**



**COVAL GERMANY**



**COVAL ITALIA**



**COVAL CHINA**

Distributed by:



certified quality  
management system

**COVAL VACUUM TECHNOLOGY INC.**  
901 Jones Franklin Road  
Suite 100  
Raleigh, NC 27606  
U.S.A.

Phone : (919) 233-4855  
Fax : (919) 233-4854

[www.coval-inc.com](http://www.coval-inc.com)