

Epson® GX10B SCARA Robot



Epson GX10-Series. Taking SCARA robot performance to the next level.

Ultra high performance and flexibility — high throughput with heavy payloads and multiple arm configurations to accomplish the most demanding tasks with leading-edge precision

Unique high-power-density SCARA — innovative, compact design handles heavy workloads at fast speeds, all in a small footprint

Fast cycle times — high acceleration, smooth motion and fast settling times help maximize throughput with proprietary GYROPLUS® vibration reduction system, plus no ringing or overshoot¹

Ultimate ease of use — intuitive and feature-packed Epson RC+® development software helps create powerful solutions with a simple user interface, integrated debugger and advanced 3D simulator

Low total cost of ownership — includes battery-less encoders and Epson RC+ software with no recurring license fee; rich suite of safety features included with RC700E controller

SafeSense™ technology — standard and advanced safety features can allow for increased productivity and worker protection while potentially minimizing machine footprint due to the reduction of physical barriers


Optimized footprint — table, wall- and ceiling-mount options; 650 mm and 850 mm reaches available; longer Z axis available on all models

Built for demanding environments — Standard, Cleanroom (ISO3)² and ESD, and Protected IP65 models available

Advanced integrated options — Vision Guidance, Parts Feeding, Force Guidance, Conveyor Tracking, Fieldbus and API.NET

Industry 4.0 ready — advanced OPC UA for robotics connectivity provides next-level integration and monitoring

Model Name		GX10B SCARA Robot					
Model Number		GX10-B65x			GX10-B85x		
Mounting Type		Tabletop	Ceiling	Wall	Tabletop	Ceiling	Wall
Arm Length		650 mm			850 mm		
Repeatability	Joint #1 Plus Joint #2				±0.025 mm		
	Joints #1 - #2				±0.010 mm		
	Joint #3				±0.005 deg		
	Joint #4						
Payload	Rated				5 kg		
	Max.				10 kg		
Standard Cycle Time ²		0.34 sec			0.37 sec		
Max. Motion Range	Joint #1	±152 deg	±107 deg		±152 deg	±107 deg	
	Joint #2 Std				±152.5 deg		
	Joint #2 Clean & Protected	±152.5 deg	±130 deg		Z: 0--360 mm ± 152.5 deg Z: -360--390 mm ± 151 deg		
	Joint #3 Std				180 mm/420 mm		
	Joint #3 Clean				150 mm/390 mm		
	Joint #4				±360 deg		
Joint #4 Allowable Moment of Inertia ⁴	Rated				0.02 kg·m ²		
	Max.				0.25 kg·m ²		
Joint #3 Downforce					250 N		
User Electric Lines					15-pin (D-sub), 9-pin (D-sub)		
User Pneumatic Lines					ø4 mm x2, ø6 mm x2		
Brakes					Joint #3 and Joint #4		
Power					AC 200 V - 240 V Single Phase		
Power Consumption					2.5 kVa		
Power Cable Length					3 m/5 m/10 m (flexible, straight and angled cable end options)		
Weight (cables not included)		46 kg, 102 lb	51 kg, 112 lb		49 kg, 108 lb	53 kg, 117 lb	
Applicable Controller					RC700E		
Installation Environment					Standard/Cleanroom ISO3 ² & ESD/Protected		
Safety Standards					TUV Certified to meet ISO 10218-1, UL 1740, CSA Z434, ISO 13849		
What's Included					GX10B robot and RC700E controller, Epson RC+ software, E-Stop unit with cable, E-stop unit with flying leads, connector set (I/O, hand I/O and safety circuit connectors)		
Options							
		Vision Guide CV2			Available		
		IntelliFlex™			Available		
		Force Guidance			Available		
		Conveyor Tracking Kit			R12NZ900AA		
		Epson RC+ 7.0 API			R12NZ920AE		
		GUI Builder 7.0			R12NZ920AH		
		Fieldbus Master			Available		
		Fieldbus Slave (EtherNet/IP, EtherCat, Profinet, Profibus, CCLink)			Available		
		External Control Point (ECP) Option			R12NZ920AF		
		TP3 - Teach Pendant			R12NZ00N3		
		Epson QPC UA for Robots			R19NZ901CE		
		Arm Length Calibration			R19NZ901AD		
		Bellows Kit (Standard and Long Z)			Available		
		GX10B ISO Tool Adapter			R12NZ911C2		



Air-Oil Systems, Inc.

AUTOMATION SOLUTIONS

753 WAMBOLD ROAD SOUDERTON, PA 18964-2715

215.721.9595 800.333.5520 FAX 215.721.7666

www.airoil.com