


Epson C12XLC 6-Axis Robot



Innovative features. Remarkable flexibility.

Ultra high performance and flexibility — high throughput with max-rated payloads and multiple arm configurations to accomplish the most demanding assembly needs

Minimize the workcell space requirement with SlimLine design — compact wrist pitch enables access to hard-to-reach areas in confined spaces; tabletop mounting and 1,400 mm reach available

Fast cycle times — high acceleration, smooth motion and fast settling times help maximize throughput with proprietary GYROPLUS™ vibration reduction system, plus no ringing or overshoot¹

Ultimate ease of use — intuitive and feature-packed Epson RC+® development software helps create powerful solutions with a simple user interface, integrated debugger and advanced 3D simulator

Designed for reliability — innovative, compact design handles max-rated workloads at fast speeds and high precision within a small footprint

Low total cost of ownership — includes features that help reduce support and installation costs: batteryless encoders, a built-in Ethernet cable, Epson RC+ software and a rich suite of safety features

Accelerate the development of workcell applications — fully integrated, optional solutions include vision guidance, parts feeding, force guidance, conveyor tracking and fieldbus; Epson RC+ Solutions Platform allows for seamless expansion of third-party solutions, benefiting developers and end users

Increase user interaction without sacrificing productivity — SafeSense™ technology's standard and advanced safety features, with a proper risk assessment, help allow for increased productivity and worker protection while potentially minimizing workcell footprint due to the reduction of physical barriers

Built for demanding environments — Standard, Cleanroom (ISO 4)² and ESD, and Protected IP67 models available

World-class service and support — with four decades of automation experience, Epson provides support for your automation needs through its dedicated application and service teams

Model Name		C12XLC 6-Axis Robot		
Mounting Type		Tabletop		
Arm Length	P Point: Joints #1 - #5 Center	1,400 mm		
	P Point: Joints #1 - #6 Flange Surface	1,480 mm		
Repeatability	Joints #1 - #6	±0.05 mm		
Payload	Rated	3 kg		
	Max.	12 kg		
Standard Cycle Time ³		0.484 sec		
Max. Motion Range	Joint #1	±240 deg		
	Joint #2	-135 deg ~ +55 deg		
	Joint #3	-61 deg ~ +202 deg		
	Joint #4	±200 deg		
	Joint #5	±135 deg		
	Joint #6	±540 deg		
Allowable Moment of Inertia	Joint #4	0.7 kg·m ²		
	Joint #5	0.7 kg·m ²		
	Joint #6	0.2 kg·m ²		
User Electric Lines		15-Pin (D-Sub), 8-Pin (RJ45 Cat5e), 6-Pin (Force Sensor)		
User Pneumatic Lines		ø6 mm x 2		
Brakes		All Axes		
Power		AC 200 V – 240 V (single phase)		
Power Consumption		2.5 kVA		
Power Cable Length		3 m/5 m/10 m		
Weight (Cables Not Included)		63 kg (IP-67 kg)		
Applicable Controller		RC800A		
Installation Environment		Standard/Cleanroom (ISO 4) ² and ESD/Protected IP67		
Safety Standards		TUV-certified to meet ISO 10218-1, UL 1740, CSA Z434, ISO 13849		
What's Included		C12XLC robot and RC800A controller with safety board. Robot power and signal cables. Connector set (I/O, hand I/O and safety circuit connectors).		
Options				
		Vision Guide	Available	
		IntelliFlex™ Feeders	Available	
		Force Guide	Available	
		Conveyor Tracking	Available	
		Epson RC+ API 8.0	R19NZ901JK	
		GUI Builder 8.0	R19NZ901JQ	
		Fieldbus Master	Available	
		Fieldbus Slave (Ethernet/IP, EtherCAT®, PROFINET, PROFIBUS, CC-Link, DeviceNet®)	Available	
		External Control Point (ECP) 8.0	R19NZ901JL	
		Teach Pendant	Available	
		Epson OPC UA for Robotics	R19NZ901JZ	

Contact:



Air-Oil Systems, Inc.

AUTOMATION SOLUTIONS

753 WAMBOLD ROAD SOUDERTON, PA 18964-2715

215.721.9595 800.333.5520 FAX 215.721.7666

www.airoil.com

¹ When operated within specifications. | ² Complies with ISO Class 3 (ISO 14644-1) cleanroom standards. | ³ Cycle time based on round-trip arch motion (300 mm horizontal, 25 mm vertical) at rated payload setting of tabletop model boost mode (path coordinates optimized for maximum speed).

Specifications and terms are subject to change without notice. EPSON and Epson RC+ are registered trademarks and GYROPLUS is a trademark of Seiko Epson Corporation. IntelliFlex and SafeSense are trademarks of Epson America, Inc. All other product and brand names are trademarks and/or registered trademarks of their respective companies. Epson disclaims any and all rights in these marks. Copyright 2025 Epson America, Inc. CPD-66158 7/25